

## 9 FCC §1.1307(B)(1) & §2.1091 - RF Exposure

### 9.1 Applicable Standard

According to §1.1310 and §2.1091 (Mobile Devices) RF exposure is calculated.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
<b>Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

Note: f = frequency in MHz

\* = Plane-wave equivalent power density

### 9.2 MPE Prediction

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

### 9.3 Test Result

Cellular Band UL:

Maximum peak output power at antenna input terminal (dBm):	<u>28.19</u>
Maximum peak output power at antenna input terminal (mW):	<u>659.17</u>
Prediction distance (cm):	<u>35</u>
Prediction frequency (MHz):	<u>836.6</u>
Antenna Gain, typical (dBi):	<u>14</u>
Cable Loss (dB)	<u>3.6</u>
Maximum Antenna Gain+ Cable Loss (numeric):	<u>10.96</u>
Power density at predication frequency and distance (mW/cm <sup>2</sup> ):	<u>0.4695</u>
MPE limit for uncontrolled exposure at predication frequency (mW/cm <sup>2</sup> ):	<u>0.5577</u>

## Cellular Band DL:

Maximum peak output power at antenna input terminal (dBm):	<u>26.6</u>
Maximum peak output power at antenna input terminal (mW):	<u>457.09</u>
Prediction distance (cm):	<u>35</u>
Prediction frequency (MHz):	<u>881.6</u>
Antenna Gain, typical (dBi):	<u>14</u>
Cable Loss (dB)	<u>3.6</u>
Maximum Antenna Gain+ Cable Loss (numeric):	<u>10.96</u>
Power density at predication frequency and distance (mW/cm <sup>2</sup> ):	<u>0.3256</u>
MPE limit for uncontrolled exposure at predication frequency (mW/cm <sup>2</sup> ):	<u>0.5877</u>

## PCS Band UL:

Maximum peak output power at antenna input terminal (dBm):	<u>26.38</u>
Maximum peak output power at antenna input terminal (mW):	<u>434.51</u>
Prediction distance (cm):	<u>35</u>
Prediction frequency (MHz):	<u>1880</u>
Antenna Gain, typical (dBi):	<u>14</u>
Cable Loss (dB)	<u>8.0</u>
Maximum Antenna Gain+ Cable Loss (numeric):	<u>3.98</u>
Power density at predication frequency and distance (mW/cm <sup>2</sup> ):	<u>0.1124</u>
MPE limit for uncontrolled exposure at predication frequency (mW/cm <sup>2</sup> ):	<u>1.0</u>

## PCS Band DL:

Maximum peak output power at antenna input terminal (dBm):	<u>26.89</u>
Maximum peak output power at antenna input terminal (mW):	<u>488.65</u>
Prediction distance (cm):	<u>35</u>
Prediction frequency (MHz):	<u>1960</u>
Antenna Gain, typical (dBi):	<u>14</u>
Cable Loss (dB)	<u>8.0</u>
Maximum Antenna Gain+ Cable Loss (numeric):	<u>3.98</u>
Power density at predication frequency and distance (mW/cm <sup>2</sup> ):	<u>0.1264</u>
MPE limit for uncontrolled exposure at predication frequency (mW/cm <sup>2</sup> ):	<u>1.0</u>

Note: To meet 33 dBm (2 watts) EIRP limit in PCS band, the gain of antenna used with this booster must be offset by coaxial cable loss such that the antenna gain less cable loss does not exceed 6 dBi.

## Lower LTE Band UL:

Maximum peak output power at antenna input terminal (dBm):	<u>23.85</u>
Maximum peak output power at antenna input terminal (mW):	<u>242.66</u>
Prediction distance (cm):	<u>35</u>
Prediction frequency (MHz):	<u>701</u>
Antenna Gain, typical (dBi):	<u>14</u>
Cable Loss (dB)	<u>3.6</u>
Maximum Antenna Gain+ Cable Loss (numeric):	<u>10.96</u>
Power density at predication frequency and distance (mW/cm <sup>2</sup> ):	<u>0.1728</u>
MPE limit for uncontrolled exposure at predication frequency (mW/cm <sup>2</sup> ):	<u>0.4673</u>

## Lower LTE Band DL:

Maximum peak output power at antenna input terminal (dBm):	<u>24.19</u>
Maximum peak output power at antenna input terminal (mW):	<u>262.42</u>
Prediction distance (cm):	<u>35</u>
Prediction frequency (MHz):	<u>744</u>
Antenna Gain, typical (dBi):	<u>14</u>
Cable Loss (dB)	<u>3.6</u>
Maximum Antenna Gain+ Cable Loss (numeric):	<u>10.96</u>
Power density at predication frequency and distance (mW/cm <sup>2</sup> ):	<u>0.1869</u>
MPE limit for uncontrolled exposure at predication frequency (mW/cm <sup>2</sup> ):	<u>0.4960</u>

## Upper LTE Band UL:

Maximum peak output power at antenna input terminal (dBm):	<u>23.96</u>
Maximum peak output power at antenna input terminal (mW):	<u>248.89</u>
Prediction distance (cm):	<u>35</u>
Prediction frequency (MHz):	<u>782</u>
Antenna Gain, typical (dBi):	<u>14</u>
Cable Loss (dB)	<u>3.6</u>
Maximum Antenna Gain+ Cable Loss (numeric):	<u>10.96</u>
Power density at predication frequency and distance (mW/cm <sup>2</sup> ):	<u>0.1773</u>
MPE limit for uncontrolled exposure at predication frequency (mW/cm <sup>2</sup> ):	<u>0.5213</u>

## Upper LTE Band DL:

Maximum peak output power at antenna input terminal (dBm):	<u>24.32</u>
Maximum peak output power at antenna input terminal (mW):	<u>270.40</u>
Prediction distance (cm):	<u>35</u>
Prediction frequency (MHz):	<u>747</u>
Antenna Gain, typical (dBi):	<u>14</u>
Cable Loss (dB)	<u>3.6</u>
Maximum Antenna Gain+ Cable Loss (numeric):	<u>10.96</u>
Power density at predication frequency and distance (mW/cm <sup>2</sup> ):	<u>0.1926</u>
MPE limit for uncontrolled exposure at predication frequency (mW/cm <sup>2</sup> ):	<u>0.4980</u>

## AWS Band UL:

Maximum peak output power at antenna input terminal (dBm):	<u>24.53</u>
Maximum peak output power at antenna input terminal (mW):	<u>283.79</u>
Prediction distance (cm):	<u>35</u>
Prediction frequency (MHz):	<u>1732.4</u>
Antenna Gain, typical (dBi):	<u>14</u>
Cable Loss (dB)	<u>9</u>
Maximum Antenna Gain+ Cable Loss (numeric):	<u>3.16</u>
Power density at predication frequency and distance (mW/cm <sup>2</sup> ):	<u>0.0583</u>
MPE limit for uncontrolled exposure at predication frequency (mW/cm <sup>2</sup> ):	<u>1.0</u>

## AWS Band DL:

Maximum peak output power at antenna input terminal (dBm):	<u>24.49</u>
Maximum peak output power at antenna input terminal (mW):	<u>281.19</u>
Prediction distance (cm):	<u>35</u>
Prediction frequency (MHz):	<u>2112.4</u>
Antenna Gain, typical (dBi):	<u>14</u>
Cable Loss (dB)	<u>9</u>
Maximum Antenna Gain+ Cable Loss (numeric):	<u>3.16</u>
Power density at predication frequency and distance (mW/cm <sup>2</sup> ):	<u>0.0578</u>
MPE limit for uncontrolled exposure at predication frequency (mW/cm <sup>2</sup> ):	<u>1.0</u>

Note: To meet 30 dBm (1watts) EIRP limit in AWS band, the gain of antenna used with this booster must be offset by coaxial cable loss such that the antenna gain less cable loss does not exceed 5 dBi.