

1 FCC § 1.1307 (b) (1) & § 2.1091-RF EXPOSURE

1.1 Applicable Standard

According to § 1.1310 and § 2.1091 (Mobile Devices) RF exposure is calculated.
Limits for General Population/Uncontrolled Exposure

| Frequency Range (MHz) | Power Density (mW/cm ²) |
|---|-------------------------------------|
| Limits for General Population/Uncontrolled Exposure | |
| 0.3-1.34 | *(100) |
| 1.34-30 | *(180/f ²) |
| 30-300 | 0.2 |
| 300 - 1,500 | f/1500 |
| 1,500 - 100,000 | 1 |

Note: f= frequency in MHz

*=Plane-wave equivalent power density

1.2 MPE Prediction

1.2.1 Calculation of MPE at 20 cm distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG / 4 \pi R^2$$

Where: S=power density

P=power input to antenna

G= maximum power gain of the antenna in the direction of interest relative to an isotropic radiator, subtract antenna's cable loss, (result is in numeric form)

R=distance to the center of radiation of the antenna (20cm in the following calculation)

1.2.2 Calculation formula of G (numeric)

$$G(\text{numeric}) = 10^{\frac{\{\text{Maximum Antenna Gain (dBi)} - \text{Cable Loss (dB)}\}}{10}}$$

Where: G (numeric) = Maximum power gain of the antenna in the direction of interest relative to an isotropic radiator, subtract antenna's cable loss, (result is converted from decibel into numeric form with above equation)

1.3 Test Result

| Outdoor Antenna | | |
|-------------------|----------------------|-------------------|
| Outdoor Antenna | Outdoor Antenna Gain | |
| | At 1900MHz(dBi) | At 800MHz(dBi) |
| CM100-S | 5 | 4 |
| CM230W | 10 | 10 |
| CM288W | 4 | 3 |
| CM100-L | 7 | 5 |
| MAX GAIN | 10 | 10 |
| Outdoor Cable | | |
| Outdoor Cable | Outdoor Cable Loss | |
| | At 1900MHz(dB) | At 800MHz(dB) |
| CM240-40FN 40Feet | 6.52 | 3.98 |
| CM400-65NN 65Feet | 5.43 | 3.89 |
| MIN LOSS | 5.43 | 3.89 |

| Indoor Antenna | | |
|-------------------|---------------------|-------------------|
| Indoor Antenna | Indoor Antenna Gain | |
| | At 1900MHz(dBi) | At 800MHz(dBi) |
| CM222W | 6 | 3 |
| CM248W | 10 | 7 |
| MAX GAIN | 10 | 7 |
| Indoor Cable | | |
| Indoor Cable | Indoor Cable Loss | |
| | At 1900MHz(dB) | At 800MHz(dB) |
| CM240-20FN 20Feet | 3.56 | 2.29 |
| CM400-40NN 40Feet | 3.57 | 2.63 |
| MIN LOSS | 3.56 | 2.29 |

| Cellular Band UL: | |
|--|--------|
| Maximum peak output power at antenna input terminal(dBm): | 20.00 |
| Maximum peak output power at antenna input terminal(mW): | 100.00 |
| Prediction distance(cm): | 20 |
| Prediction frequency(MHz): | 830.00 |
| Maximum Antenna Gain (dBi): | 10 |
| Cable Loss(dB): | 3.89 |
| G (numeric) : | 4.08 |
| Power density at predication frequency and distance(mW/cm ²): | 0.0813 |
| MPE limit for uncontrolled exposure at predication frequency(mW/cm ²): | 0.5533 |

| Cellular Band DL: | |
|--|--------|
| Maximum peak output power at antenna input terminal(dBm): | 3.80 |
| Maximum peak output power at antenna input terminal(mW): | 2.40 |
| Prediction distance(cm): | 20 |
| Prediction frequency(MHz): | 881.00 |
| Maximum Antenna Gain (dBi): | 7 |
| Cable Loss(dB): | 2.29 |
| G (numeric) : | 2.96 |
| Power density at predication frequency and distance(mW/cm ²): | 0.0014 |
| MPE limit for uncontrolled exposure at predication frequency(mW/cm ²): | 0.5873 |

| PCS Band UL: | |
|--|---------|
| Maximum peak output power at antenna input terminal(dBm): | 22.40 |
| Maximum peak output power at antenna input terminal(mW): | 173.78 |
| Prediction distance(cm): | 20 |
| Prediction frequency(MHz): | 1865.00 |
| Maximum Antenna Gain (dBi): | 10 |
| Cable Loss(dB): | 5.43 |
| G (numeric) : | 2.86 |
| Power density at predication frequency and distance(mW/cm ²): | 0.0991 |
| MPE limit for uncontrolled exposure at predication frequency(mW/cm ²): | 1.0000 |

| PCS Band DL: | |
|--|---------|
| Maximum peak output power at antenna input terminal(dBm): | -1.20 |
| Maximum peak output power at antenna input terminal(mW): | 0.76 |
| Prediction distance(cm): | 20 |
| Prediction frequency(MHz): | 1956.00 |
| Maximum Antenna Gain (dBi): | 10 |
| Cable Loss(dB): | 3.56 |
| G (numeric) : | 4.41 |
| Power density at predication frequency and distance(mW/cm ²): | 0.0007 |
| MPE limit for uncontrolled exposure at predication frequency(mW/cm ²): | 1.0000 |

