



# TriFlex-2GO-T™

## Tri-Band Mobile Signal Booster

Frequency Band: 824-849 MHz / 869-894 MHz  
1850-1910 MHz / 1930-1990 MHz  
1710-1755 MHz / 2110-2155 MHz

**[T-Mobile AWS  
& Canada LTE]**

Maximum Gain: 50dB [Cellular/ PCS / AWS]

Maximum Output: 1W EIRP

FCC ID: RSNTRIFLEX-2GO-T

[www.surecall.com](http://www.surecall.com) | 1-888-365-6263 | Assembled in China

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

This is a **CONSUMER** device.

**BEFORE USE**, you **MUST REGISTER THIS DEVICE** with your wireless provider and have your provider's consent. Most wireless providers consent to the use of signal boosters. Some providers may not consent to the use of this device on their network. If you are unsure, contact your provider.

You **MUST** operate this device with approved antennas and cables as specified by the manufacturer. Antennas **MUST** be installed at least 20 cm (8 Inches) from any person.

You **MUST** cease operating this device immediately if requested by the FCC or a licensed wireless service provider.

**WARNING.** E911 location information may not be provided or may be inaccurate for calls served by using this device.

75dB Dual Band  
Cellular Signal Amplifier  
Model: RSNTFLEX-2GO-T  
Frequency Bands: 824-849 MHz / 869-894 MHz  
1850-1910 MHz / 1920-1980 MHz  
1710-1755 MHz / 2110-2155 MHz  
Maximum Output: 1W EIRP  
FCC ID: RSNTFLEX-2GO-T  
www.surecall.com | 1-888-365-6283 | Assembled in China

This is a CONSUMER device  
**BEFORE USE, you MUST REGISTER THIS DEVICE** with your wireless provider and have your provider's consent. Most wireless providers consent to the use of signal boosters. Some providers may not consent to the use of this device on their network. If you are unsure, contact your provider.  
You **MUST** operate this device with approved antennas and cables as specified by the manufacturer. Antennas **MUST** be installed at least 20 cm (8 inches) from any person.  
You **MUST** cease operating this device immediately if requested by the FCC or a licensed wireless service provider.  
**WARNING:** 911 location information may not be provided or may be inaccurate for calls received by using this device.

**SureCall** TriFlex-2GO-T™  
Tri-Band Mobile Signal Booster

Frequency Band: 824-849 MHz / 869-894 MHz  
1850-1910 MHz / 1920-1980 MHz  
1710-1755 MHz / 2110-2155 MHz

Maximum Gain: 50dB [Cellular PCS / AWS]  
Maximum Output: 1W EIRP  
FCC ID: RSNTFLEX-2GO-T  
www.surecall.com | 1-888-365-6283 | Assembled in China

**[T-Mobile AWS & Canada LTE]**

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.