



1 FCC § 1.1307 (b) (1) & § 2.1091-RF EXPOSURE

1.1 Applicable Standard

According to § 1.1310 and § 2.1091 (Mobile Devices) RF exposure is calculated. Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Power Density (mW/cm ²)
Limits for General Population/Uncontrolled Exposure	
0.3-1.34	*(100)
1.34-30	*(180/f ²)
30-300	0.2
300 - 1,500	f/1500
1,500 - 100,000	1

Note: f= frequency in MHz

*=Plane-wave equivalent power density

1.2 MPE Prediction

1.2.1 Calculation of MPE at 20 cm distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG / 4 \pi R^2$$

Where: S=power density

P=power input to antenna

G= maximum power gain of the antenna in the direction of interest relative to an isotropic radiator, subtract antenna's cable loss, (result is in numeric form)

R=distance to the center of radiation of the antenna (20cm in the following calculation)

1.2.2 Calculation formula of G (numeric)

$$G(\text{numeric}) = 10^{\frac{\{ \text{Maximum Antenna Gain (dBi)} - \text{Cable Loss (dB)} \}}{10}}$$

Where: G (numeric) = Maximum power gain of the antenna in the direction of interest relative to an isotropic radiator, subtract antenna's cable loss, (result is converted from decibel into numeric form with above equation)

1.3 Test Result

1.3.1 Under the conditions of Vehicle Kit Component(Antenna KIT)

Vehicle Kit Component						
Outdoor Antenna KIT Antenna:CM200 Cable:CM174 -10FT 10Feet	Outdoor Antenna Gain			Outdoor Cable Loss		
	At 1900MHz (dBi)	At 800MHz (dBi)	At LTE-V (dBi)	At 1900MHz (dB)	At 800MHz (dB)	At LTE-V (dB)
	5	3	3	8.8	4.3	3.8

Indoor Patch Antenna KIT Antenna:CM110W Cable: CM174 -10FT 10Feet	Indoor Antenna Gain			Indoor Cable Loss		
	At 1900MHz (dBi)	At 800MHz (dBi)	At LTE-V (dBi)	At 1900MHz (dB)	At 800MHz (dB)	At LTE-V (dB)
	3	1.1	1.1	8.8	4.3	3.8

LTE-V UL:	
Maximum peak output power at antenna input terminal(dBm):	19.3
Maximum peak output power at antenna input terminal(mW):	85.11
Prediction distance(cm):	20
Prediction frequency(MHz):	780.45
Maximum Antenna Gain (dBi):	3
Cable Loss(dB):	3.8
G(numeric):	0.83
Power density at predication frequency and distance(mW/cm ²):	0.0141
MPE limit for uncontrolled exposure at predication frequency(mW/cm ²):	0.5203

LTE-V DL:	
Maximum peak output power at antenna input terminal(dBm):	-6.3
Maximum peak output power at antenna input terminal(mW):	0.23
Prediction distance(cm):	20
Prediction frequency(MHz):	752.2
Maximum Antenna Gain (dBi):	1.1
Cable Loss(dB):	3.8
G(numeric):	0.54
Power density at predication frequency and distance(mW/cm ²):	0.0001
MPE limit for uncontrolled exposure at predication frequency(mW/cm ²):	0.5015

Cellular Band UL:

Maximum peak output power at antenna input terminal(dBm):	20
Maximum peak output power at antenna input terminal(mW):	100
Prediction distance(cm):	20
Prediction frequency(MHz):	829.188
Maximum Antenna Gain (dBi):	3
Cable Loss(dB):	4.3
G(numeric):	0.74
Power density at predication frequency and distance(mW/cm ²):	0.0148
MPE limit for uncontrolled exposure at predication frequency(mW/cm ²):	0.5528

Cellular Band DL:	
Maximum peak output power at antenna input terminal(dBm):	-6.8
Maximum peak output power at antenna input terminal(mW):	0.21
Prediction distance(cm):	20
Prediction frequency(MHz):	879.313
Maximum Antenna Gain (dBi):	1.1
Cable Loss(dB):	4.3
G(numeric):	0.48
Power density at predication frequency and distance(mW/cm ²):	0.0002
MPE limit for uncontrolled exposure at predication frequency(mW/cm ²):	0.5862

PCS Band UL:	
Maximum peak output power at antenna input terminal(dBm):	20.4
Maximum peak output power at antenna input terminal(mW):	109.65
Prediction distance(cm):	20
Prediction frequency(MHz):	1861.15
Maximum Antenna Gain (dBi):	5
Cable Loss(dB):	8.8
G(numeric):	0.42
Power density at predication frequency and distance(mW/cm ²):	0.0091
MPE limit for uncontrolled exposure at predication frequency(mW/cm ²):	1.0000

PCS Band DL:	
Maximum peak output power at antenna input terminal(dBm):	-7.4
Maximum peak output power at antenna input terminal(mW):	0.18
Prediction distance(cm):	20
Prediction frequency(MHz):	1960.98
Maximum Antenna Gain (dBi):	3
Cable Loss(dB):	8.8
G(numeric):	0.26

Power density at predication frequency and distance(mW/cm ²):	0.0002
MPE limit for uncontrolled exposure at predication frequency(mW/cm ²):	1.0000

1.3.2 Under the conditions of Marine Kit Component Component (Antenna KIT)

Marine Kit Component						
Outdoor Antenna KIT	Outdoor Antenna Gain			Outdoor Cable Loss		
	At 1900MHz (dBi)	At 800MHz (dBi)	At LTE-V (dBi)	At 1900MHz (dB)	At 800MHz (dB)	At LTE-V (dB)
Antenna:CM288W or Galaxy 5412-P Cable:CM240 -40FN 40Feet	4	3	3	6.52	3.98	3.52
Indoor Panel Antenna KIT						
Indoor Panel Antenna KIT	Indoor Antenna Gain			Indoor Cable Loss		
	At 1900MHz (dBi)	At 800MHz (dBi)	At LTE-V (dBi)	At 1900MHz (dB)	At 800MHz (dB)	At LTE-V (dB)
Antenna:CM248W Cable:CM240 -20FN 20Feet	10	7	7	3.56	2.29	2.06

LTE-V UL:	
Maximum peak output power at antenna input terminal(dBm):	19.3
Maximum peak output power at antenna input terminal(mW):	85.11
Prediction distance(cm):	20
Prediction frequency(MHz):	780.45
Maximum Antenna Gain (dBi):	3
Cable Loss(dB):	3.52
G(numeric):	0.89
Power density at predication frequency and distance(mW/cm ²):	0.0141
MPE limit for uncontrolled exposure at predication frequency(mW/cm ²):	0.5203

LTE-V DL:	
Maximum peak output power at antenna input terminal(dBm):	-6.3
Maximum peak output power at antenna input terminal(mW):	0.23
Prediction distance(cm):	20
Prediction frequency(MHz):	752.2
Maximum Antenna Gain (dBi):	7
Cable Loss(dB):	2.06
G(numeric):	3.12
Power density at predication frequency and distance(mW/cm ²):	0.0001
MPE limit for uncontrolled exposure at predication frequency(mW/cm ²):	0.5015

Cellular Band UL:	
Maximum peak output power at antenna input terminal(dBm):	20
Maximum peak output power at antenna input terminal(mW):	100
Prediction distance(cm):	20
Prediction frequency(MHz):	829.188
Maximum Antenna Gain (dBi):	3
Cable Loss(dB):	3.98
G(numeric):	0.8
Power density at predication frequency and distance(mW/cm ²):	0.0159
MPE limit for uncontrolled exposure at predication frequency(mW/cm ²):	0.5528

Cellular Band DL:	
Maximum peak output power at antenna input terminal(dBm):	-6.8
Maximum peak output power at antenna input terminal(mW):	0.21
Prediction distance(cm):	20
Prediction frequency(MHz):	879.313
Maximum Antenna Gain (dBi):	7
Cable Loss(dB):	2.29
G(numeric):	2.96
Power density at predication frequency and distance(mW/cm ²):	0.0001
MPE limit for uncontrolled exposure at predication frequency(mW/cm ²):	0.5862

PCS Band UL:	
Maximum peak output power at antenna input terminal(dBm):	20.4
Maximum peak output power at antenna input terminal(mW):	109.65
Prediction distance(cm):	20
Prediction frequency(MHz):	1861.15
Maximum Antenna Gain (dBi):	10
Cable Loss(dB):	3.56
G(numeric):	4.41
Power density at predication frequency and distance(mW/cm ²):	0.0962
MPE limit for uncontrolled exposure at predication frequency(mW/cm ²):	1.0000

PCS Band DL:	
Maximum peak output power at antenna input terminal(dBm):	-7.4
Maximum peak output power at antenna input terminal(mW):	0.18
Prediction distance(cm):	20
Prediction frequency(MHz):	1960.98

Maximum Antenna Gain (dBi):	10
Cable Loss(dB):	3.52
G(numeric):	4.41
Power density at predication frequency and distance(mW/cm ²):	0.0002
MPE limit for uncontrolled exposure at predication frequency(mW/cm ²):	1.0000

1.3.3 Under the conditions of Desk top/RV Kit Component (Antenna KIT)

Desk top/RV Kit Component						
Outdoor Antenna KIT Antenna:CM288W Cable:CM240 -40FN 40Feet	Outdoor Antenna Gain			Outdoor Cable Loss		
	At 1900MHz (dBi)	At 800MHz (dBi)	At LTE-V (dBi)	At 1900MHz (dB)	At 800MHz (dB)	At LTE-V (dB)
	4	3	3	6.52	3.98	3.52
Indoor Right Angle Antenna KIT Antenna:CM120W Cable: NO	Indoor Antenna Gain			Indoor Cable Loss (Connector IL)		
	At 1900MHz(dBi)	At 800MHz(dBi)	At LTE-V (dBi)	At 1900MHz (dB)	At 800MHz (dB)	At LTE-V (dB)
	3	1.2	1.2	0.3	0.3	0.3

LTE-V UL:	
Maximum peak output power at antenna input terminal(dBm):	19.3
Maximum peak output power at antenna input terminal(mW):	85.11
Prediction distance(cm):	20
Prediction frequency(MHz):	780.45
Maximum Antenna Gain (dBi):	3
Cable Loss(dB):	3.52
G(numeric):	0.89
Power density at predication frequency and distance(mW/cm ²):	0.0141
MPE limit for uncontrolled exposure at predication frequency(mW/cm ²):	0.5203

LTE-V UL:	
Maximum peak output power at antenna input terminal(dBm):	-6.3
Maximum peak output power at antenna input terminal(mW):	0.23
Prediction distance(cm):	20
Prediction frequency(MHz):	752.2
Maximum Antenna Gain (dBi):	1.2
Cable Loss(dB):	0.3
G(numeric):	1.23

Power density at predication frequency and distance(mW/cm ²):	0.0001
MPE limit for uncontrolled exposure at predication frequency(mW/cm ²):	0.5015

Cellular Band UL:	
Maximum peak output power at antenna input terminal(dBm):	20
Maximum peak output power at antenna input terminal(mW):	100
Prediction distance(cm):	20
Prediction frequency(MHz):	829.188
Maximum Antenna Gain (dBi):	3
Cable Loss(dB):	3.98
G(numeric):	0.8
Power density at predication frequency and distance(mW/cm ²):	0.0159
MPE limit for uncontrolled exposure at predication frequency(mW/cm ²):	0.5528

Cellular Band DL:	
Maximum peak output power at antenna input terminal(dBm):	-6.8
Maximum peak output power at antenna input terminal(mW):	0.21
Prediction distance(cm):	20
Prediction frequency(MHz):	879.313
Maximum Antenna Gain (dBi):	1.2
Cable Loss(dB):	0.3
G(numeric):	1.23
Power density at predication frequency and distance(mW/cm ²):	0.0001
MPE limit for uncontrolled exposure at predication frequency(mW/cm ²):	0.5862

PCS Band UL:	
Maximum peak output power at antenna input terminal(dBm):	20.4
Maximum peak output power at antenna input terminal(mW):	109.65
Prediction distance(cm):	20
Prediction frequency(MHz):	1861.15
Maximum Antenna Gain (dBi):	4
Cable Loss(dB):	6.52
G(numeric):	1.56
Power density at predication frequency and distance(mW/cm ²):	0.0122
MPE limit for uncontrolled exposure at predication frequency(mW/cm ²):	1.0000

PCS Band DL:	
Maximum peak output power at antenna input terminal(dBm):	-7.4



Maximum peak output power at antenna input terminal(mW):	0.18
Prediction distance(cm):	20
Prediction frequency(MHz):	1960.98
Maximum Antenna Gain (dBi):	3
Cable Loss(dB):	0.3
G(numeric):	1.86
Power density at predication frequency and distance(mW/cm ²):	0.0001
MPE limit for uncontrolled exposure at predication frequency(mW/cm ²):	1.0000