



RF EXPOSURE REPORT

REPORT NO.: SA960907L10

MODEL NO.: QBT400UB

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT: Qcom Technology Inc.

ADDRESS: 7F, NO. 178, MING CHUAN E. RD. SEC 3, TAIPEI
TAIWAN R.O.C.

ISSUED BY: Advance Data Technology Corporation

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang
244, Taipei Hsien, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.



No Evaluation Required if power is below this threshold:

F(GHz)		mW
Low	2.402	24.58
High	2.480	

Maximum measured transmitter power:

For Printed antenna with 1.40dBi gain

	Pout (dBm)	Pout (mW)
Conducted Power	-0.75	0.841
EIRP Power	0.65	1.161

***Note:** The antenna is Printed antenna with 1.40dBi gain

For Inverted F antenna with 2.20dBi gain

	Pout (dBm)	Pout (mW)
Conducted Power	-0.75	0.841
EIRP Power	1.45	1.396

***Note:** The antenna is Inverted F antenna with 2.20dBi gain

Threshold for no SAR evaluation is 24.58mW

Transmitter power is 1.396mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold