

Application for FCC Certification  
On behalf of

Freescale Semiconductor, Inc.

Product Name: A28 Multi-coil wireless charger Transmitter

Model No.: WCT-5WTXMULTI

FCC ID: RUN-WCT-5WTXMULTI

(RF Exposure Report)

Prepared For : Freescale Semiconductor, Inc.  
Corporate Headquarters, 6501 William Cannon Drive  
West Austin, Texas 78735 USA

Prepared By : Audix Technology (Shanghai) Co., Ltd.  
3F 34Bldg 680 Guiping Rd.,  
Caohejing Hi-Tech Park,  
Shanghai 200233, China

Tel: +86-21-64955500  
Fax: +86-21-64955491

Report No. : ACI-F14177A1  
Date of Test : Jul 17, 2015  
Date of Report : Jul 21, 2015

## TABLE OF CONTENTS

	Page
<b>1 SUMMARY OF STANDARDS AND RESULTS.....</b>	<b>4</b>
1.1 Description of Standards and Results.....	4
<b>2 GENERAL INFORMATION.....</b>	<b>5</b>
2.1 Description of Equipment Under Test.....	5
2.2 Description of Test Facility .....	6
<b>3 SUMMARY OF STANDARDS AND RESULTS.....</b>	<b>7</b>
3.1 Test Equipment.....	7
3.2 Test Setup .....	7
3.3 Applicable Standard .....	7
3.4 Specification Limits .....	8
3.5 Operating Condition of EUT.....	8
3.6 Test Result.....	9

## TEST REPORT FOR HUMAN EXPOSURE

Applicant : Freescale Semiconductor, Inc.  
Manufacturer : Freescale Semiconductor (China) Limited Suzhou Branch  
Factory : Trivo (Taicang) Technologies Co., Ltd.

EUT Description : A28 Multi-coil wireless charger Transmitter  
(A) Model No. : WCT-5WTXMULTI  
(B) Power Supply : AC100~240V/50-60Hz  
(C) Test Voltage : AC 120V/60Hz

Test Procedure Used:

*FCC RULES AND REGULATIONS PART 1 SECTION 1.1310 and  
KDB 680106 D01 v02*

The device described above is tested by Audix Technology (Shanghai) Co., Ltd. to determine the RF Exposure levels emanating from the device. The RF Exposure levels are compared to the FCC Part 1.1310.

The test results are contained in this test report and Audix Technology (Shanghai) Co., Ltd. is assumed full responsibility for the accuracy and completeness of these measurements. This report also shows that the EUT (M/N: WCT-5WTXMULTI), which was tested on Jul 17, 2015 is technically compliance with the FCC limits.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of Audix Technology (Shanghai) Co., Ltd.

This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

Date of Test : Jul 17, 2015 Date of Report : Jul 21, 2015

Producer : Alan He  
ALAN HE / Assistant

Review : SAMMY CHEN  
SAMMY CHEN / Manager

**AUDIX**® For and on behalf of  
Audix Technology (Shanghai) Co., Ltd.

•Signatory : BYRON KWO  
Authorized Signature EMC BYRON KWO/Assistant General Manager

## 1 SUMMARY OF STANDARDS AND RESULTS

### 1.1 Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

Description of Test Item	Standard	Limits	Results
RF Exposure	FCC RULES AND REGULATIONS PART 1.1310 AND KDB 680106 D01 V02	1.1310	Pass

## 2 GENERAL INFORMATION

### 2.1 Description of Equipment Under Test

Description : A28 Multi-coil wireless charger Transmitter

Model Number : WCT-5WTXMULTI

Type of EUT :  Production  Pre-product  Pro-type

Note #1 : The modified histories of report are as follows:

Report No.	Model No.	Rev. Summary	Edition No.	Data of Rev.
ACI-F14177	WCT-5WTXMULTI	Original Report	0	Nov 12, 2014
ACI-F14177A1	WCT-5WTXMULTI	1. To change the location of the component	Rev. A1	Jul 17, 2015

Charge Freq. : 115-205 kHz

Applicant : Freescale Semiconductor, Inc.  
Corporate Headquarters, 6501 William Cannon  
Drive West Austin, Texas 78735 USA

Manufacturer : Freescale Semiconductor (China) Limited  
Suzhou Branch  
No. 288 Zhuyuan Road, Suzhou New District

Factory : Trivo (Taicang) Technologies Co., Ltd.  
Building A10, Taicang Foreign Industry Park,  
No.105 East Shanghai Road, Taicang, Jiangsu,  
P.R.China.

## 2.2 Description of Test Facility

Site Description : Sept. 17, 1998 file on  
(Semi-Anechoic Chamber) Jan.15, 2015 Renewed  
Federal Communications Commission  
FCC Engineering Laboratory  
7435 Oakland Mills Road  
Columbia, MD 21046, USA

Name of Firm : Audix Technology (Shanghai) Co., Ltd.

Site Location : 3 F 34 Bldg 680 Guiping Rd.,  
Caohejing Hi-Tech Park,  
Shanghai 200233, China

FCC registration Number : 91789

Accredited by NVLAP, Lab Code : 200371-0


### 3 SUMMARY OF STANDARDS AND RESULTS

#### 3.1 Test Equipment

The following test equipments are used during the conducted emission test in a shielded room:

Item	Type	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1.	Field Monitor	AR	FM2000	19221	NCR	NCR
2.	Field Probe	AR	FP2000	19233	May 22, 2015	May 21, 2016
3.	Magnetic Field Tester	HIOKI	FT3470-50	130503486	May 27, 2015	May 26, 2016

#### 3.2 Test Setup



#### 3.3 Applicable Standard

FCC Part 1.1310 & KDB 680106 D01 v02 (3)(3)

### 3.4 Specification Limits

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time  E <sup>2</sup> ,  H <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/150	30
1500-100,000	--	--	1.0	30

f = frequency in MHz

\*Plane-wave equivalent power density

KDB 680106 D01(3)(3):

For devices designed for typical desktop applications, such as wireless charging pads, RF exposure evaluation should be conducted assuming a user separation distance of 10 cm. E and H field strength measurements or numerical modeling may be used to demonstrate compliance. Measurements should be made from all sides and the top of the primary/client pair, with the 10 cm measured from the center of the probe(s) to the edge of the device. Emissions between 100 kHz to 300 kHz should be assessed versus the limits at 300 kHz in Table 1 of Section 1.1310: 614 V/m and 1.63 A/m.

### 3.5 Operating Condition of EUT

The EUT was setup on the Charging test mode and then test.

### 3.6 Test Result

#### 3.6.1 Electric Field Strength at 10 cm from the edges surrounding the EUT

Test Position	Test distance (cm)	Test result (v/m)	Limit (v/m)
A: Front	10	1.15	614.00
B: Back	10	1.52	614.00
C: Left	10	2.36	614.00
D: Right	10	1.72	614.00
E: Top	10	3.60	614.00
F: Bottom	10	3.42	614.00
Conclusion		Pass	

#### 3.6.2 Magnetic Field Strength at 10 cm from the edges surrounding the EUT

Test Position	Test distance (cm)	Test result (A/m)	Limit (A/m)
A: Front	10	0.3029	1.63
B: Back	10	0.2606	1.63
C: Left	10	0.4625	1.63
D: Right	10	0.1919	1.63
E: Top	10	0.4544	1.63
F: Bottom	10	0.3670	1.63
Conclusion		Pass	