

Test Report Prepared By:

**Electronics Test Centre
MPB Technologies Inc.**
Unit 100
302 Legget Drive
Kanata Ontario K2K 1Y5

**FINAL REPORT
ON**

Reader & Tag B

IN ACCORDANCE WITH

FCC part 15 Subpart C

MPBT Report No.: P37R2952

Customer P.O. No.: SCA-010-0104

Test Personnel: Janusz Lokaj

Prepared for:

Scanpak Inc.
2250 P1. Transcanada
Dorval, QC
H9P 2X5
Canada

Client Acceptance
Authorized Signatory



Dan Zanette
Lab Manager
Electronic Test Centre
Kanata, Ontario
Authorized Signatory

May 5, 2004
Report Composition Pages 1 to 28

Reviewed By




TABLE OF CONTENTS

1.0 INTRODUCTION	3
1.1 SCOPE	3
1.2 APPLICANT	3
1.3 APPLICABILITY	3
1.4 TEST SAMPLE DESCRIPTION	3
1.5 GENERAL TEST CONDITIONS AND ASSUMPTIONS	4
1.6 SCOPE OF TESTING	4
1.6.1 VARIATIONS IN TEST METHODS	4
1.6.2 TEST SAMPLE MODIFICATIONS	4
2.0 TEST CONCLUSION.....	5
2.1 TRANSMIT CARRIER LEVEL	7
2.1.1 TRANSMIT CARRIER LEVEL - DATA.....	8
2.1.1 MEASUREMENT SETUP.....	10
2.2 UNWANTED EMISSIONS - TRANSMIT.....	11
2.2.1 UNWANTED EMISSIONS DATA - TRANSMIT.....	12
2.3 UNWANTED EMISSIONS - RECEIVE.....	16
2.3.1 UNWANTED EMISSIONS DATA - RECEIVE	17
2.4 EMISSION BANDWIDTH	20
2.4.1 EMISSION BANDWIDTH DATA.....	21
3.0 TEST FACILITY	22
3.1 LOCATION	22
3.2 GROUNDING PLAN	22
3.3 POWER.....	22
3.4 TEST CONFIGURATION.....	23
3.4.1 TABLE TOP EQUIPMENT.....	23
4.0 TEST EQUIPMENT.....	24
4.1 RADIATED EMISSIONS.....	24
4.2 EMI SPECTRUM ANALYZER AND RECEIVER	24
4.2.1 SPECTRUM ANALYZER RANGE 1 of 2	24
4.2.2 SPECTRUM ANALYZER RANGE 2 of 2	24
4.2.3 RECEIVER.....	24
APPENDIX A.....	25
APPENDIX B.....	28

1.0 INTRODUCTION

1.1 SCOPE

The purpose of this report is to present the findings and results of compliance testing performed, in accordance with FCC part 15 Subpart C.

1.2 APPLICANT

This test report has been prepared for Scanpak Inc.

1.3 APPLICABILITY

All test procedures, limits, and results defined in this document apply to the Scanpak Inc. Reader B and Tag B which shall be referred to herein as the Equipment Under Test (EUT).

The results contained in this report relate only to the item(s) tested.

This report does not imply product endorsement by NVLAP or the Canadian or US governments.

1.4 TEST SAMPLE DESCRIPTION

The test sample provided for testing were Reader and Tag B

Product Type:	Pre-production Unit - Telecom
Serial Number:	N/A
Model Number:	TTB-434-01(for TTagB Transceiver Tag & TTB-434 (for TTB-434 Active Reader)
Part Number:	N/A
Cables:	None for TTagB Transceiver Tag Ethernet cable for TTB-434 Active Reader
Power Requirements:	TTagB transceiver Tag: Two lithium coin cells (eg CR-2032) TTB-434 Active Reader: 6 to48V DC supplied as POE (Power Over Ethernet)
Peripheral Equipment:	None for TtagB Transceiver Tag PC, POE injector and AC to DC wall adapter fro TTB-434 Active Reader

1.5 GENERAL TEST CONDITIONS AND ASSUMPTIONS

The EUT was setup and exercised using the configurations, modes of operation and arrangements as defined in this report only. All inputs and outputs to and from other equipment associated with the EUT were adequately simulated.

Where relevant, the EUT was only tested using the monitoring methods and test criteria defined in this report.

All testing, unless otherwise noted, was performed under the following environmental conditions:

Temperature: 17 to 23 °C

Humidity: 45 to 75 %

Barometric Pressure: 68 to 106 kPa

1.6 SCOPE OF TESTING

Tests were performed in accordance with ANSI 63.4 1992 and CISPR 16

1.6.1 VARIATIONS IN TEST METHODS

There were no variations from the test procedures outlined above.

1.6.2 TEST SAMPLE MODIFICATIONS

There were no test sample modifications.

2.0 TEST CONCLUSION

The EUT was subjected to the following tests. Compliance is designated by a **PASS**; non-compliance by a **FAIL**.

The following table summarizes the test results and details the tests performed in terms of the specification and class or level applied, the unique test sample identification, and the EUT modification state, the mode of operation, configuration and cable arrangement (if applicable).

Test Case	Test Type	Specification	Class / Level	Mod State	ENG./ QUAL	Criteria	Result
2.1	Carrier level	FCC part 15.231(b), (e)	N/A	Typ.	QUAL	N/A	PASS
2.2	Unwanted Emissions - Transmitter	FCC part 15.231(b), (e)	N/A	Typ.	QUAL	N/A	PASS
2.3	Unwanted Emissions - Receiver	FCC part 15.205 & 15.209	N/A	TX off & standby	QUAL	N/A	PASS
2.4	Emission Bandwidth	FCC part 15.231(c)	N/A	Typ.	QUAL	N/A	PASS

STATEMENT OF COMPLIANCE

The client equipment referred to in this report was found to comply with the requirements as stated above.

ABBREVIATIONS

CE - Conducted Emissions
 CS-Conducted Susceptibility(Immunity)
 ESD - Electrostatic Discharge
 EFT - Electrical Fast Transient Burst
 E-Field - Electric Field

H-Field - Magnetic Field
 N/T - Not Tested
 N/A - Not Applicable
 RE - Radiated Emissions
 RS- Radiated Susceptibility(Immunity)

MEASUREMENT UNCERTAINTY

The following measurement uncertainty with 95% confidence level was calculated using the methods defined in NAMAS document NIS81: May 1994.

For Radiated E-Field Emissions

Frequency = $\pm 1 \times 10^{-3}$ MHz

Amplitude = ± 4.01 dB

For Conducted Emissions

Frequency = $\pm 1 \times 10^{-3}$ MHz

Amplitude = ± 3.25 dB

For Radiated Immunity E-Field

Frequency = $< 5 \times 10^{-12}$ at center frequency < 21.25 MHz
 = < 0.8 MHz at center frequency ≥ 21.25 MHz

Amplitude = $< \pm 1.2$ dB at +13 dBm to -20 dBm (from 50 kHz to 680 MHz)
 = $< \pm 1.7$ dB at +13 dBm to -20 dBm (from 680 kHz to 1360 MHz)
 = $< \pm 1.7$ dB at -20 dBm to -143 dBm (from 50 kHz to 680 MHz)
 = $< \pm 2.2$ dB at -20 dBm to -143 dBm (from 680 kHz to 1360 MHz)

Harmonics = < -65 dB below center frequency

For Electrostatic Discharge Tests

output voltage = 4 kV ± 5 % (measured at the tip)

For Electrical Fast Transient Tests

output voltage = 4 kV - 0.0 + 0.4 kV

For Surge Immunity Tests


output voltage = 4 kV - 0.0 + 0.4 kV

2.1 TRANSMIT CARRIER LEVEL


Test Summary	
Test Personnel: Janusz Lokaj	Test Date: January 12 and April 2, 2004

Test Description															
Objectives/Criteria	Specifications														
<p>The electric fields radiated by a system or sub-system, shall not exceed the limits for the specifications as stated.</p> <p>It is recommended that a margin of 6dB be allowed for manufacturing tolerances.</p> <p>Worst case Emission was 56.3dBμV/m @ 434.014MHz. This is 24.9dB below the FCC Part 15.231(e) limit.</p>	<p align="center">FCC Part 15.231(b) Subpart C (Intermittent Transmission)</p> <table border="0"> <thead> <tr> <th align="left">Frequency</th> <th align="left">Limits @3m</th> </tr> </thead> <tbody> <tr> <td>70 -130 MHz</td> <td>61.9 dBμV</td> </tr> <tr> <td>130-174 MHz</td> <td>61.9 – 71.5 dBμV</td> </tr> <tr> <td>174-260 MHz</td> <td>71.5 dBμV</td> </tr> <tr> <td>260-470 MHz</td> <td>71.5 – 81.9 dBμV *</td> </tr> <tr> <td>Above 470 MHz</td> <td>81.9 dBμV</td> </tr> <tr> <td>at 433.92MHz</td> <td>81.2 dBμV</td> </tr> </tbody> </table>	Frequency	Limits @3m	70 -130 MHz	61.9 dBμV	130-174 MHz	61.9 – 71.5 dBμV	174-260 MHz	71.5 dBμV	260-470 MHz	71.5 – 81.9 dBμV *	Above 470 MHz	81.9 dBμV	at 433.92MHz	81.2 dBμV
Frequency	Limits @3m														
70 -130 MHz	61.9 dBμV														
130-174 MHz	61.9 – 71.5 dBμV														
174-260 MHz	71.5 dBμV														
260-470 MHz	71.5 – 81.9 dBμV *														
Above 470 MHz	81.9 dBμV														
at 433.92MHz	81.2 dBμV														
Test Result: PASS															

2.1.1 TRANSMIT CARRIER LEVEL - DATA



Radiated Emissions, 30 – 1000 MHz vertical peak prescan



Radiated Emissions, 30 – 1000 MHz horizontal peak prescan

Reader					
Polarization	Frequency	Peak Level	Pulse adjusted Level *	Limit	Margin
	[MHz]	[dB μ V/m]	[dB μ V/m]	[dB μ V/m]	[dB]
Vertical	434.014	87.8	56.3	81.2	-24.9
Horizontal	434.014	87.4	55.9	81.2	-25.3

Tag B					
Polarization	Frequency	Peak Level	Pulse adjusted Level *	Limit	Margin
	[MHz]	[dB μ V/m]	[dB μ V/m]	[dB μ V/m]	[dB]
Vertical	433.919	71.1	39.6	81.2	-41.6
Horizontal	433.919	76.5	45.9	81.2	-36.2

Note: Peak reading detector with resolution bandwidth 120kHz used below 1GHz. Readings adjusted for pulse desensitization as per FCC part 15.35 and CISPR16-1 table 3 – Isolated Pulses.

2.1.1 MEASUREMENT SETUP




2.2 UNWANTED EMISSIONS - TRANSMIT


Test Summary	
Test Personnel: Janusz Lokaj	Test Date: January 12, 26-28, 2004

Test Description													
Objectives/Criteria	Specifications												
<p>The electric fields radiated by a system or sub-system, shall not exceed the limits for the specifications as stated.</p> <p>It is recommended that a margin of 6dB be allowed for manufacturing tolerances.</p> <p>Worst case Emission was 50.4dBμV/m @ 1736.026MHz. This is 11.5dB below the FCC Part 15.231(b) limit.</p>	<p align="center">FCC Part 15.231(b) Subpart C (Intermittent Transmission)</p> <table border="1"> <thead> <tr> <th>Frequency</th> <th>Limits @3m</th> </tr> </thead> <tbody> <tr> <td>70 -130 MHz</td> <td>41.9 dBμV</td> </tr> <tr> <td>130-174 MHz</td> <td>41.9 – 51.5 dBμV</td> </tr> <tr> <td>174-260 MHz</td> <td>51.5 dBμV</td> </tr> <tr> <td>260-470 MHz</td> <td>51.5 – 61.9 dBμV *</td> </tr> <tr> <td>Above 470 MHz</td> <td>61.9 dBμV</td> </tr> </tbody> </table>	Frequency	Limits @3m	70 -130 MHz	41.9 dBμV	130-174 MHz	41.9 – 51.5 dBμV	174-260 MHz	51.5 dBμV	260-470 MHz	51.5 – 61.9 dBμV *	Above 470 MHz	61.9 dBμV
Frequency	Limits @3m												
70 -130 MHz	41.9 dBμV												
130-174 MHz	41.9 – 51.5 dBμV												
174-260 MHz	51.5 dBμV												
260-470 MHz	51.5 – 61.9 dBμV *												
Above 470 MHz	61.9 dBμV												
Test Result: PASS													


2.2.1 UNWANTED EMISSIONS DATA - TRANSMIT




Radiated Emissions, 30 – 1000 MHz vertical peak prescan, Reader & Tag B




Radiated Emissions, 30 – 1000 MHz horizontal peak prescan, Reader & Tag B




Radiated Emissions, 1 – 2.5 GHz vertical peak prescan. Reader



Radiated Emissions, 1 – 2.5 GHz horizontal peak prescan. Reader



Radiated Emissions, 1 – 2.5 GHz vertical peak prescan. Tag B



Radiated Emissions, 1 – 2.5 GHz horizontal peak prescan. Tag B

Top Emissions - Reader							
Vertical				Horizontal			
Freq. [MHz]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Freq. [MHz]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]
868.018	30.3	61.2	-30.9	868.018	34.7	61.2	-26.5
1302.024	42.4	61.9	-19.5	1302.024	42.4	61.9	-19.5
1736.026	50.2	61.9	-11.7	1736.026	50.4	61.9	-11.5
2170.031	47.5	61.9	-14.4	2170.031	47.3	61.9	-14.6

1. Peak reading detector with resolution bandwidth 120kHz used below 1GHz. Readings adjusted for pulse desensitization as per FCC part 15.35 and CISPR16-1 table 3 – Isolated pulses.
2. Average reading detector used above 1GHz.

Top Emissions – Tag B							
Vertical				Horizontal			
Freq. [MHz]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Freq. [MHz]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]
867.840	18.7	61.2	-42.5	867.840	21.3	61.2	-39.9
1301.735	34.5	61.9	-27.4	1301.735	36.4	61.9	-25.5
1735.680	46.0	61.9	-15.9	1735.680	45.5	61.9	-16.4
2169.600	47.2	61.9	-14.7	2169.600	30.0	61.9	-31.9


3. Peak reading detector with resolution bandwidth 120kHz used below 1GHz. Readings adjusted for pulse desensitization as per FCC part 15.35 and CISPR16-1 table 3 – Isolated pulses.
4. Average reading detector used above 1GHz.

2.3 UNWANTED EMISSIONS - RECEIVE


Test Summary	
Test Personnel: Janusz Lokaj	Test Date: January 22,23,27, 2004

Test Description											
Objectives/Criteria	Specifications										
<p>The electric fields radiated by a system or sub-system, shall not exceed the limits for the specifications as stated.</p> <p>It is recommended that a margin of 6dB be allowed for manufacturing tolerances.</p> <p>Worst case Emission was 30.0dBμV/m @ 49.982MHz. This is 10.0dB below the FCC Part 15.209 limit.</p> <p>Worst case Emission was 20.0dBμV/m @ 49.982MHz. This is 10.0dB below the limit.</p>	<p>FCC Part 15.209 Subpart C</p> <table> <tr> <td>Frequency</td> <td>@3m</td> </tr> <tr> <td>30-88 MHz</td> <td>40.0 dBμV</td> </tr> <tr> <td>88-216 MHz</td> <td>43.5 dBμV</td> </tr> <tr> <td>216-960 MHz</td> <td>46.0 dBμV</td> </tr> <tr> <td>> 960 MHz</td> <td>54.0 dBμV</td> </tr> </table>	Frequency	@3m	30-88 MHz	40.0 dBμV	88-216 MHz	43.5 dBμV	216-960 MHz	46.0 dBμV	> 960 MHz	54.0 dBμV
Frequency	@3m										
30-88 MHz	40.0 dBμV										
88-216 MHz	43.5 dBμV										
216-960 MHz	46.0 dBμV										
> 960 MHz	54.0 dBμV										
Test Result: PASS											


2.3.1 UNWANTED EMISSIONS DATA - RECEIVE




Radiated Emissions, ambient scan




Radiated Emissions 30-1000MHz, vertical prescan



Radiated Emissions 30-1000MHz, horizontal prescan



Radiated Emissions 1-2.5GHz, vertical prescan



Radiated Emissions 1-2.5GHz, horizontal prescan


Top Six Emissions – FCC Part 15.209							
Vertical				Horizontal			
Freq. [MHz]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Freq. [MHz]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]
49.982	30.0	40.0	-10.0	889.010	29.7	46.0	-16.3
40.070	28.3	40.0	-11.7	128.039	23.3	43.5	-20.2
76.814	27.6	40.0	-12.4	150.027	21.4	43.5	-22.1
567.239	28.7	46.0	-17.3	120.254	19.8	43.5	-23.7
149.516	8.4	43.5	-35.1	113.933	13.2	43.5	-30.3
234.965	9.3	46.0	-36.7	215.667	12.8	43.5	-30.8

2.4 EMISSION BANDWIDTH


Test Summary	
Test Personnel: Janusz Lokaj	Test Date: January 22, 2004

Test Description	
Objectives/Criteria	Specifications
The emission bandwidth occupied by a system or sub-system, shall not exceed the limits for the specifications as stated.	<p align="center">FCC Part 15.231(c)</p> <p>0.25% of the carrier: 1.08MHz at 433.92MHz</p>
Test Result: PASS	

2.4.1 EMISSION BANDWIDTH DATA



Reader, 1MHz span shown



Tag B, 1MHz span shown

3.0 TEST FACILITY

3.1 LOCATION

The EUT was tested for Electromagnetic Compatibility at the Electronics Test Centre, located in Kanata, Ontario, Canada.

3.2 GROUNDING PLAN

The EUT was located in a rack supplied by the client. No grounding was required according to the Clients specifications.


3.3 POWER

The EUT was self-powered.

3.4 TEST CONFIGURATION

3.4.1 TABLE TOP EQUIPMENT

The following diagrams illustrate the configuration of the EUT test and measurement equipment used for CISPR Radiated and Emissions Testing.



4.0 TEST EQUIPMENT

The following equipment was utilized for this procedure. All measurement devices are calibrated annually, traceable to NIST. Please refer to Appendix B for calibration data.

4.1 RADIATED EMISSIONS

- a) Spectrum Analyzer
- b) Receiver with CISPR Quasi-peak Adapter
- c) Power Isolation Transformers
- d) Biconilog antenna (25 MHz to 2 GHz)
- e) DRG Horn (1 GHz to 18 GHz)
- f) Antenna mast positioner, and controller
- f) Flush-mounted turntable, and controller
- e) Personal Computer and EMI/EMC Software

4.2 EMI SPECTRUM ANALYZER AND RECEIVER

4.2.1 SPECTRUM ANALYZER RANGE 1 of 2

Start Frequency	0.15 MHz
Stop Frequency	30 MHz
Transducer	LISN per CISPR 16
CISPR Bandwidths	200 Hz Average/9 kHz
Spectrum Analyzer BW	10 kHz
Video Bandwidth	100 kHz
Reference Level	100 dBµV

4.2.2 SPECTRUM ANALYZER RANGE 2 of 2

Start Frequency	30 MHz
Stop Frequency	1000 MHz
Transducer	Biconilog Antenna
CISPR Bandwidth	120 kHz Quasi-peak
Spectrum Analyzer BW	120 kHz
Video Bandwidth	1 MHz
Reference Level	100 dBµV

4.2.3 RECEIVER

Transducer	Biconilog Antenna
CISPR Bandwidth	120 kHz Quasi-peak
Measurement Window	20 dBµV