

ATTACHMENT O – SAR TEST PLOTS

EZ500

SAM II Phantom; Left Hand [CRP] Section; Position: (90°,180°); Frequency: 1900 MHz

Probe: ET3DV6 - SN1798; ConvF(5.27,5.27,5.27); Crest factor: 8.0; Head 1900 MHz: $\sigma = 1.42 \text{ mho/m}$ $\epsilon_r = 38.6$ $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR (1g): 0.313 mW/g, SAR (10g): 0.191 mW/g

Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Powerdrift: -0.15 dB

Comment :

MODEL : EZ500


Company : Ezze Mobile Tech., Inc.

Test Position: Left Touch / Antenna: Fixed

Mode: GSM1900 / Channel : 512

Liquid Temperature: 21.5°C

Date Tested : October 31, 2005



EZ500

SAM II Phantom; Left Hand [CRP] Section; Position: (90°,180°); Frequency: 1900 MHz

Probe: ET3DV6 - SN1798; ConvF(5.27,5.27,5.27); Crest factor: 8.0; Head 1900 MHz: $\sigma = 1.42 \text{ mho/m}$ $\epsilon_r = 38.6$
 $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR(1g): 0.270 mW/g, SAR(10g): 0.163 mW/g

Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Powerdrift: -0.01 dB

Comment :

MODEL : EZ500


Company : Ezze Mobile Tech., Inc.

Test Position: Left Touch / Antenna: Fixed

Mode: GSM1900 / Channel : 661

Liquid Temperature: 21.5°C

Date Tested : October 31, 2005



EZ500

SAM II Phantom; Left Hand [CRP] Section; Position: (90°,180°); Frequency: 1900 MHz

Probe: ET3DV6 - SN1798; ConvF(5.27,5.27,5.27); Crest factor: 8.0; Head 1900 MHz: $\sigma = 1.42 \text{ mho/m}$ $\epsilon_r = 38.6 \rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR (1g): 0.189 mW/g, SAR (10g): 0.111 mW/g

Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Powerdrift: 0.01 dB

Comment :

MODEL : EZ500


Company : Ezze Mobile Tech., Inc.

Test Position: Left Touch / Antenna: Fixed

Mode: GSM1900 / Channel : 810

Liquid Temperature: 21.5°C

Date Tested : October 31, 2005



EZ500

SAM II Phantom; Right Hand [CRP] Section; Position: (90°,180°); Frequency: 1900 MHz

Probe: ET3DV6 - SN1798; ConvF(5.27,5.27,5.27); Crest factor: 8.0; Head 1900 MHz: $\sigma = 1.42 \text{ mho/m}$, $\epsilon_r = 38.6$ $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR(1g): 0.819 mW/g, SAR(10g): 0.459 mW/g

Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Powerdrift: -0.10 dB

Comment :

MODEL : EZ500


Company : Ezze Mobile Tech., Inc.

Test Position: Right Touch / Antenna: Fixed

Mode: GSM1900 / Channel : 512

Liquid Temperature: 21.5°C

Date Tested : October 31, 2005



EZ500

SAM II Phantom; Right Hand [CRP] Section; Position: (90°,180°); Frequency: 1900 MHz

Probe: ET3DV6 - SN1798; ConvF(5.27,5.27,5.27); Crest factor: 8.0; Head 1900 MHz: $\sigma = 1.42 \text{ mho/m}$ $\epsilon_r = 38.6$ $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR(1g): 0.791 mW/g, SAR(10g): 0.456 mW/g

Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Powerdrift: 0.03 dB

Comment :

MODEL : EZ500


Company : Ezze Mobile Tech., Inc.

Test Position: Right Touch / Antenna: Fixed

Mode: GSM1900 / Channel : 661

Liquid Temperature: 21.5°C

Date Tested : October 31, 2005



EZ500

SAM II Phantom, Right Hand [CRP] Section; Position: (90°,180°); Frequency: 1900 MHz

Probe: ET3DV6 - SN1798; ConvF(5.27,5.27,5.27); Crest factor: 8.0; Head 1900 MHz: $\sigma = 1.42 \text{ mho/m}$, $\epsilon_r = 38.6$
 $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR (1g): 0.591 mW/g, SAR (10g): 0.338 mW/g

Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Powerdrift: -0.08 dB

Comment :

MODEL : EZ500


Company : Ezze Mobile Tech., Inc.

Test Position: Right Touch / Antenna: Fixed

Mode: GSM1900 / Channel : 810

Liquid Temperature: 21.5°C

Date Tested : October 31, 2005



EZ500

SAM II Phantom; Left Hand [CRP] Section; Position: (90°,180°); Frequency: 1900 MHz

Probe: ET3DV6 - SN1798; ConvF(5.27,5.27,5.27); Crest factor: 8.0; Head 1900 MHz: $\sigma = 1.42 \text{ mho/m}$ $\rho = 38.6 \text{ g/cm}^3$
 $= 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR (1g): 0.121 mW/g, SAR (10g): 0.0754 mW/g

Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Powerdrift: 0.02 dB

Comment :

MODEL : EZ500


Company : Ezze Mobile Tech., Inc.

Test Position: Left Tilt / Antenna: Fixed

Mode: GSM1900 / Channel : 512

Liquid Temperature: 21.5°C

Date Tested : October 31, 2005



EZ500

SAM II Phantom, Left Hand [CRP] Section; Position: (90°,180°); Frequency: 1900 MHz

Probe: ET3DV6 - SN1798; ConvF(5.27,5.27,5.27); Crest factor: 8.0; Head 1900 MHz: $\sigma = 1.42 \text{ mho/m}$ $\epsilon_r = 38.6$ $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR (1g): 0.103 mW/g, SAR (10g): 0.0645 mW/g

Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Powerdrift: -0.06 dB

Comment :

MODEL : EZ500


Company : Ezze Mobile Tech., Inc.

Test Position: Left Tilt / Antenna: Fixed

Mode: GSM1900 / Channel : 661

Liquid Temperature: 21.5°C

Date Tested : October 31, 2005



EZ500

SAM II Phantom; Left Hand [CRP] Section; Position: (90°,180°); Frequency: 1900 MHz

Probe: ET3DV6 - SN1798; ConvF(5.27,5.27,5.27); Crest factor: 8.0; Head 1900 MHz: $\sigma = 1.42 \text{ mho/m}$ $\epsilon_r = 38.6$ $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR (1g): 0.0705 mW/g, SAR (10g): 0.0375 mW/g

Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Powerdrift: -0.02 dB

Comment :

MODEL : EZ500


Company : Ezze Mobile Tech., Inc.

Test Position: Left Tilt / Antenna: Fixed

Mode: GSM1900 / Channel : 810

iquid Temperature: 21.5°C

Date Tested : October 31, 2005



EZ500

SAM II Phantom; Right Hand [CRP] Section; Position: (90°,180°); Frequency: 1900 MHz

Probe: ET3DV6 - SN1798; ConvF(5.27,5.27,5.27); Crest factor: 8.0; Head 1900 MHz: $\sigma = 1.42 \text{ mho/m}$ $\epsilon_r = 38.6$ $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR(1g): 0.136 mW/g, SAR(10g): 0.0876 mW/g

Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Powerdrift: 0.15 dB

Comment :

MODEL : EZ500


Company : Ezze Mobile Tech., Inc.

Test Position: Right Tilt / Antenna: Fixed

Mode: GSM1900 / Channel : 512

Liquid Temperature: 21.5°C

Date Tested : October 31, 2005



EZ500

SAM II Phantom; Right Hand [CRP] Section; Position: (90°,180°); Frequency: 1900 MHz

Probe: ET3DV6 - SN1798; ConvF(5.27,5.27,5.27); Crest factor: 8.0; Head 1900 MHz: $\sigma = 1.42 \text{ mho/m}$ $\epsilon_r = 38.6$ $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7; SAR (1g): 0.112 mW/g, SAR (10g): 0.0721 mW/g

Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Powerdrift: 0.02 dB

Comment :

MODEL : EZ500


Company : Ezze Mobile Tech., Inc.

Test Position: Right Tilt / Antenna: Fixed

Mode: GSM1900 / Channel : 661

Liquid Temperature: 21.5°C

Date Tested : October 31, 2005



EZ500

SAM II Phantom; Right Hand [CRP] Section; Position: (90°,180°); Frequency: 1900 MHz

Probe: ET3DV6 - SN1798; ConvF(5.27,5.27,5.27); Crest factor: 8.0; Head 1900 MHz: $\sigma = 1.42 \text{ mho/m}$ $\epsilon_r = 38.6$ $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR (1g): 0.0807 mW/g, SAR (10g): 0.0516 mW/g

Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0

Powerdrift: 0.10 dB

Comment :

MODEL : EZ500


Company : Ezze Mobile Tech., Inc.

Test Position: Right Tilt / Antenna: Fixed

Mode: GSM1900 / Channel : 810

Liquid Temperature: 21.5°C

Date Tested : October 31, 2005



EZ500 (Body)

SAM II Phantom; Flat Section; Position: (90°,90°); Frequency: 1900 MHz

Probe: ET3DV6 - SN1798; ConvF(4.84,4.84,4.84); Crest factor: 8.0; Body 1900 MHz: $\sigma = 1.48 \text{ mho/m}$ $\epsilon_r = 54.5$ $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR(1g): 0.325 mW/g, SAR(10g): 0.169 mW/g

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Powerdrift: 0.00 dB

Comment :

MODEL : EZ500


Company : Ezze Mobile Tech., Inc.

Test Position: Body / Antenna: Fixed

Mode: GSM1900 / Channel : 512

Liquid Temperature: 21.5°C

Date Tested : October 31, 2005



EZ500 (Body)

SAM II Phantom; Flat Section; Position: (90°, 90°); Frequency: 1900 MHz

Probe: ET3DV6 - SN1798; ConvF(4.84,4.84,4.84); Crest factor: 8.0; Body 1900 MHz: $\sigma = 1.48 \text{ mho/m}$ $\epsilon_r = 54.5$ $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR (1g): 0.464 mW/g, SAR (10g): 0.237 mW/g

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Powerdrift: -0.02 dB

Comment :

MODEL : EZ500


Company : Ezze Mobile Tech., Inc.

Test Position: Body / Antenna: Fixed

Mode: GSM1900 / Channel : 661

Liquid Temperature: 21.5°C

Date Tested : October 31, 2005



EZ500 (Body)

SAM II Phantom; Flat Section; Position: (90°, 90°); Frequency: 1900 MHz

Probe: ET3DV6 - SN1798; ConvF(4.84, 4.84, 4.84); Crest factor: 8.0; Body 1900 MHz: $\sigma = 1.48 \text{ mho/m}$ $\epsilon_r = 54.5$ $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR (1g): 0.103 mW/g, SAR (10g): 0.0602 mW/g

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Powerdrift: 0.01 dB

Comment :

MODEL : EZ500(GPRS)


Company : Ezze Mobile Tech., Inc.

Test Position: Body / Antenna: Fixed

Mode: GSM1900 / Channel : 661

Liquid Temperature: 21.5°C

Date Tested : October 31, 2005



EZ500 (Body)

SAM II Phantom; Flat Section; Position: (90°, 90°); Frequency: 1900 MHz

Probe: ET3DV6 - SN1798; ConvF(4.84, 4.84, 4.84); Crest factor: 8.0; Body 1900 MHz: $\sigma = 1.48 \text{ mho/m}$ $\epsilon_r = 54.5$ $\rho = 1.00 \text{ g/cm}^3$

Cube 5x5x7: SAR(1g): 0.456 mW/g, SAR(10g): 0.230 mW/g

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Powerdrift: 0.03 dB

Comment :

MODEL : EZ500


Company : Ezze Mobile Tech., Inc.

Test Position: Body / Antenna: Fixed

Mode: GSM1900 / Channel : 810

Liquid Temperature: 21.5°C

Date Tested : October 31, 2005



EZ500

SAM II Phantom; Section; Position: ; Frequency: 1900 MHz

Probe: ET3DV6 - SN1798; ConvF(5.27,5.27,5.27); Crest factor: 8.0; Head 1900 MHz: $\sigma = 1.42 \text{ mho/m}$ $\epsilon_r = 38.6$ $\rho = 1.00 \text{ g/cm}^3$

:

Z-Axis: Dx = 0.0, Dy = 0.0, Dz = 5.0

Comment :

MODEL : EZ500


Company : Ezze Mobile Tech., Inc.

Test Position: Right Touch / Antenna: Fixed

Mode: GSM1900 / Channel : 512

Liquid Temperature: 21.5°C

Date Tested : October 31, 2005



EZ500 (Body)

SAM II Phantom; Section; Position: ; Frequency: 1900 MHz

Probe: ET3DV6 - SN1798; ConvF(4.84,4.84,4.84); Crest factor: 8.0; Body 1900 MHz: $\sigma = 1.48 \text{ mho/m}$ $\epsilon_r = 54.5$ $\rho = 1.00 \text{ g/cm}^3$

:

Z-Axis: Dx = 0.0, Dy = 0.0, Dz = 5.0

Comment :

MODEL : EZ500

Company : Ezze Mobile Tech., Inc.

Test Position: Body / Antenna: Fixed

Mode: GSM1900 / Channel : 661

Liquid Temperature: 21.5°C

Date Tested : October 31, 2005

