



09 July 2008
Ref: US-000199

To FCC

BABT
Balfour House, Churchfield Road
Walton on Thames
Surrey, KT12 2TD
United Kingdom
Telephone: +44 (0)1932 251200
Fax: +44 (0)1932 251201
Direct Dial: +44 (0)1932 251217
E-mail: allen.ferry@babt.com
Website: www.babt.com

Overall Assessment Letter for Ezze M4E
FCC id: RV2M4E

I have reviewed this composite application and find it compliant. This is an application for a mobile phone supporting GSM/GPRS and Bluetooth. The GSM supports 850 MHz and 1900 MHz frequency range in both GSM and GPRS modes. Since the mobile phone also has a USB port for connection to Computers a filing for a Class B Computer peripheral has also been made. The phone additionally supports DCS 1800, however is not relevant as it is not supported in North America.

Please note the following:

- 1: The highest reported Head SAR for GSM 850 was 0.877 W/kg at 824.2 MHz in left-hand cheek configuration. The highest reported Head SAR for PCS 1900 was 0.679 W/kg at 1880.0 MHz in right-hand cheek configuration. The highest reported Body SAR for GSM 850 was 0.116 W/kg at 824.2 MHz in handset rear facing phantom position with 15mm separation. The highest reported Body SAR for PCS 1900 was 0.27 W/kg at 1850.2 MHz in handset rear facing phantom position with 15mm separation. The worst case Body SAR configuration in each band was used to perform an additional SAR test using a headset which resulted in a maximum Body SAR level of 0.194 W/kg.
The Bluetooth conducted output power is less than 24mW and the maximum 1-gram PCS 1900 SAR is < 1.2 W/kg. Therefore simultaneous transmission SAR assessment was deemed as not being required.

I underwent the FCC RF exposure training at BABT in July 2007.

Yours sincerely

Allen Ferry
Compliance Manager, BABT

