

TEST REPORT

REPORT NUMBER: I08GE4589-FCC-EMC

ON

Type of Equipment: Tri Band GSM 850/1800/1900 PCS handheld cellular phone
Type of Designation: MEGA1
Manufacturer: Ezze Mobile Tech.,Inc

ACCORDING TO

FCC CFR Part 2, FREQUENCY ALLOCATIONS AND RADIO TREATY MATTERS; GENERAL RULES AND REGULATIONS; e-CFR, March 23, 2006
PART 22, PUBLIC MOBILE SERVICES (Oct 1, 02 Edition)
PART 24, PERSONAL COMMUNICATIONS SERVICES (Oct 1, 97 Edition)

China Telecommunication Technology Labs.

Month date, year
Mar, 23, 2008

Signature



He Guili
Director

FCC ID: RV2MEGA1

Report Date: 2008-3-23

Test Firm Name: China Telecommunication Technology Labs

Registration Number: 840587

Statement

The measurements shown in this report were made in accordance with the procedures described on test pages. All reported tests were carried out on a sample equipment to demonstrate limited compliance with FCC CFR 47 Parts 2, 22, and 24. The sample tested was found to comply with the requirements defined in the applied rules.

CONTENTS

1 GENERAL INFORMATION	4
1.1 NOTES	4
1.2 TESTERS	5
1.3 TESTING LABORATORY INFORMATION	6
1.4 DETAILS OF APPLICANT OR MANUFACTURER	7
2 TEST ITEM	8
2.1 GENERAL INFORMATION	8
2.2 OUTLINE OF EUT	8
2.3 MODIFICATIONS INCORPORATED IN EUT	8
2.4 EQUIPMENT CONFIGURATION	8
2.5 OTHER INFORMATION	9
3 SUMMARY OF TEST RESULTS	10
4 TEST RESULTS OF MODE	11
4.1 RADIATED SPURIOUS EMISSION	11
4.2 RADIATED RF POWER OUTPUT AND ERP	23
4.3 OCCUPIED BANDWIDTH	26
4.4 FREQUENCY STABILITY OVER TEMPERATURE VARIATION	34
4.5 FREQUENCY STABILITY OVER VOLTAGE VARIATION	37
4.6 CONDUCTED RF POWER OUTPUT	39
4.7 CONDUCTED SPURIOUS EMISSION	42
ANNEX A EXTERNAL PHOTOS	47
ANNEX B INTERNAL PHOTOS	51
ANNEX C DEVIATIONS FROM PRESCRIBED TEST METHODS	53

1 General Information

1.1 Notes

All reported tests were carried out on a sample equipment to demonstrate limited compliance with FCC CFR 47 Parts 2, 22 and 24.

The test results of this test report relate exclusively to the item(s) tested as specified in section 2.

The following deviation from, additions to, or exclusions from the test specifications have been made. See Annex C.


China Telecommunication Technology Labs.(CTTL) authorizes the applicant or manufacturer (see section 1.4) to reproduce this report provided, and the test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CTTL Mr. He Guili.


Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. CTTL accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

FCC Parts 2, 22, 24
Equipment: MEGA1

REPORT NO.: 108GE4589-FCC-EMC

1.2 Testers

Name: Li Dongjin
Position: Engineer
Department: Department of EMC test
Signature: 

Name: Lv Ke
Position: Engineer
Department: Department of EMC test
Signature: 

Name: Yuan Yuan
Position: Engineer
Department: Department of EMC test
Signature: 

Editor of this test report:

Name: Li Guoqing
Position: Engineer
Department: Department of EMC test
Date: 2008-03-23
Signature: 

Technical responsibility for area of testing:

Name: Zou Dongyi
Position: Manager
Department: Department of EMC test
Date: 2008-03-23
Signature: 

1.3 Testing Laboratory information

1.3.1 Location

Name: China Telecommunication Technology Labs.
Address: No. 11, Yue Tan Nan Jie, Xi Cheng District
BEIJING
P. R. CHINA, 100083
Tel: +86 10 68094053
Fax: +86 10 68011404
Email: emc@chinattl.com

1.3.2 Details of accreditation status

Accredited by: China National Accreditation Service for Conformity
Assessment (CNAS)
Registration number: CNAS Registration No. CNAS L0570
Standard: ISO/IEC 17025:2005

1.3.3 Test location, where different from section 1.3.1

Name: -----
Street: -----
City: -----
Country: -----
Telephone: -----
Fax: -----
Postcode: -----

1.4 Details of applicant or manufacturer

1.4.1 Applicant

Name: Ezze Mobile Tech., Inc
Address: 1F, Bubmusa Bldg., 151-31, Nonhyun-dong,
Kangnam-ku, Seoul
Country: Korea
Telephone: 82-2-519-7809
Fax: 82-2-519-7882
Contact: Derik SEO
Telephone: +82-2-519-7809
Email: jhseo@ezzemobile.com

1.4.2 Manufacturer (if different from applicant in section 1.4.1)

Name: --
Address: --
City: --
Country: --

1.4.3 Manufactory (if different from applicant in section 1.4.1)

Name: --
Address: --

2 Test Item

2.1 General Information

Manufacturer: Ezze Mobile Tech., Inc

Name: Tri Band GSM 850/1800/1900 PCS handheld cellular phone

Model Number: MEGA1

Serial Number: --

Production Status: Product

Receipt date of test item: 2008-3-13

2.2 Outline of EUT

E.U.T. is a Tri Band GSM 850/1800/1900 PCS handheld cellular phone.

2.3 Modifications Incorporated in EUT

The EUT has not been modified from what is described by the brand name and unique type identification stated above.

2.4 Equipment Configuration

Equipment configuration list:

Item	Generic Description	Manufacturer	Type	Serial No.	Remarks
A	handset	Ezze Mobile Tech	MEGA1	--	None
B	adapter	Yu Feng	USB Type charger	--	None
C	battery	ZHIYIN	Lithium Ion Rechargeable Battery	--	None
D	Earphone	Rich star	Wire Type	--	None

Cables:

Item	Cable Type	Manufacturer	Length	Shield	Quantity	Remarks
1	DC cable on Adapter	Unknown	1.0 m	No	1	None

2.5 Other Information

(a) Modulation is GMSK.

(b) Emission Designator is 281KGXW.

(c) Version of hardware and software

HW Version: V 1.0

SW Version: V 1.0

(d) Adaptor information:

Input: 100-240VAC 50-60Hz

Output: 5.0V

(e) Battery information:

3.7VDC 730mAh

3 Summary of Test Results

A brief summary of the tests carried out is shown as following.

GSM mode:		
Specification Clause	Name of Test	Result
2.1051, 24.238, 2.1053,22.917	Radiated Spurious Emission	Pass
2.1046,24.232	Radiated RF Power Output	Pass
22.913(a)	Effective Radiated Power (ERP)	Pass
2.1049,22.917(b), 24.238(b)	Occupied Bandwidth	*Note 1
2.1055,22.355, 24.235	Frequency Stability over Temperature Variation	Pass
2.1055,22.355, 24.235	Frequency Stability over Voltage Variation	Pass
2.1046,22.913(a), 24.232(c)	Conducted RF Power Output	Pass
2.1051,22.917,24. 238	Conducted spurious emissions	Pass
Note 1: No applicable performance criteria.		

GPRS mode:		
2.1051, 24.238, 2.1053,22.917	Radiated Spurious Emission	Pass
2.1046,24.232	Radiated RF Power Output	Pass
22.913(a)	Effective Radiated Power (ERP)	Pass
2.1049,22.917(b), 24.238(b)	Occupied Bandwidth	*Note 2
2.1055,22.355, 24.235	Frequency Stability over Temperature Variation	Pass
2.1055,22.355, 24.235	Frequency Stability over Voltage Variation	Pass
2.1046,22.913(a), 24.232(c)	Conducted RF Power Output	Pass
2.1051,22.917,24. 238	Conducted spurious emissions	Pass
Note 2: No applicable performance criteria.		

4 Test Results of mode

4.1 Radiated Spurious Emission

Specifications:	2.1051, 24.238, 2.1053, 22.917					
Date of Tests	2008-3-18, 2008-3-21					
Test conditions:	Ambient Temperature: 15℃-35℃ Relative Humidity: 30%-60% Air pressure: 86-106kPa					
Operation Mode	TX on, channel 190 and 661 for GSM and GPRS mode					
Test Results:	Pass					
Test equipment Used:						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
7805	EMI Test Receiver	R/S	ESI26	100211	2009-01-03	Normal
7330	Ultra Broadband Antenna	R/S	HL562	100013	2008-07-24	Normal
7330	Double-Ridged Horn Antenna	R/S	HF906	100037	2009-01-14	Normal
713	Fully-Anechoic Chamber	ETS	11.8m×6.5m×6.3 m	--	2010-11-17	Normal
023	Wireless Communications Test Set	Agilent	8960(E5515C)	GB41450323	2008-06-13	Normal
111835	Wireless Communications Test Set	R&S	CMU200	1100000802	--	Normal

Limit Level Construction:

According to Part 24.238 (a), i.e., Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB, so the limit level is:
 $P(\text{dBm}) - (43 + 10 \log(P)) \text{ dB} = -13\text{dBm}$

Limits for Radiated spurious emissions(UE)

Frequency range	Limit Level /Resolution Bandwidth
30 MHz to 20000 MHz	-13dBm/1MHz

Test Setup:

The EUT was placed in an anechoic chamber, see figure SP. The Wireless Communications Test Set was used to set the TX channel and power level and modulate the TX signal with different bit patterns. The test was done using an automated test system, where all test equipments were controlled by a computer.




Figure SP

Test Method:

The measurement was performed accordance with section 2.2.12 of ANSI/TIA-603-B-2002: *Land Mobile FM or PM Communications Equipment Measurement and Performance Standards*.

- 1 The maximum spurious emissions were searched by turning the azimuth of the turntable, shifting the polarization of the measuring antenna and changing the pose of the EUT.
- 2 Levels of EUT's transmitter harmonics and suspicious signals were recorded.
- 3 The recorded levels were corrected in the automated test system with the correction factors given by a substitution calibration made before the measurement. The calibration was made separately for vertical and horizontal polarization and the system uses different correction factors depending on the measuring antenna polarization.
- 4 The corrected values of radiated spurious emissions indicated as EIRP are reported.

Note:

- 1 The investigated ARFCNs are 190 (836.6 MHz) and 661 (1880.0 MHz).
- 2 The investigated frequency range is 30 MHz ~ 18 GHz, including out of band emission and band-edge emission measurements.

Test Results for GSM mode:

Out of band emission			
Frequency [MHz]	SPU emission [dBm]	EUT pose [H/V]	Antenna Polarization [H/V]
2.487374749	-41.74	V	V
7.515831663	-38.23	V	V
16.323847695	-29.08	V	V
16.323847695	-29.52	V	H
1.665731463	-30.96	H	V
7.515831663	-38.61	H	V
9.191983968	-41.58	H	V
16.32847695	-28.58	H	V
7.515831663	-39.25	H	H
15.60080160	-31.11	H	H
16.323847695	-28.82	H	H
14.351302605	-34.58	V	V
1.665731463	-30.96	H	V
1.947995992	-40.57	H	H
4.999599198	-50.83	H	H

Band-edge emission		
EUT Channel	Frequency [MHz]	Level [dBm]
128 Left band edge	824.000	-16.73
251 Right band edge	849.000	-19.11
512 Left band edge	1850.000	-20.52
810 Right band edge	1910.000	-21.57


Test Results for GPRS mode:

Out of band emission			
Frequency [MHz]	SPU emission [dBm]	EUT pose [H/V]	Antenna Polarization [H/V]
16.290981964	-28.29	V	V
16.323847695	-28.73	H	H
3.711823647	-43.40	V	V
7.483166333	-38.20	V	V
7.483166333	-26.91	V	H
9.353507014	-36.94	V	H
13.094188377	-26.88	V	H
3.711823647	-52.11	H	V
13.094188377	-29.59	H	V

FCC Parts 2, 22, 24
Equipment: MEGA1


REPORT NO.: I08GE4589-FCC-EMC

Band-edge emission		
EUT Channel	Frequency [MHz]	Level [dBm]
128 Left band edge	824.000	-17.31
251 Right band edge	849.000	-16.25
512 Left band edge	1850.000	-19.93
810 Right band edge	1910.000	-20.00


Graphical results:**Graphical results of GSM mode:****S190VF for GSM mode**

FCC Parts 2, 22, 24
Equipment: MEGA1

REPORT NO.: I08GE4589-FCC-EMC




S190HF for GSM mode




S190VT for GSM mode

FCC Parts 2, 22, 24
Equipment: MEGA1


REPORT NO.: I08GE4589-FCC-EMC




S190HT for GSM mode




S661VF for GSM mode



S661HF for GSM mode




S661VT for GSM mode




S661HT for GSM mode


Graphical results of GPRS mode:



S190VF for GPRS mode




S190HF for GPRS mode




S190VT for GPRS mode

FCC Parts 2, 22, 24
Equipment: MEGA1

REPORT NO.: I08GE4589-FCC-EMC




S190HT for GPRS mode




S661VF for GPRS mode

FCC Parts 2, 22, 24
Equipment: MEGA1

REPORT NO.: I08GE4589-FCC-EMC




S661HF for GPRS mode



S661VT for GPRS mode

FCC Parts 2, 22, 24
Equipment: MEGA1

REPORT NO.: I08GE4589-FCC-EMC



S661HT for GPRS mode

4.2 Radiated RF Power Output and ERP

Specifications:		2.1046,24.232,22.913(a)				
Date of Tests		2008-3-20				
Test conditions:		Ambient Temperature: 15℃-35℃ Relative Humidity: 30%-60% Air pressure: 86-106kPa				
Operation Mode		TX on, channel 128, 190, 251, 512, 661 and 810				
Test Results:		Pass				
Test equipment Used:						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
7805	EMI Test Receiver	R/S	ESI26	100211	2009-01-04	Normal
7330	Ultra Broadband Antenna	R/S	HL562	100013	2008-07-24	Normal
7330	Double-Ridged Horn Antenna	R/S	HF906	100037	2009-01-14	Normal
713	Fully-Anechoic Chamber	ETS	11.8m×6.5m×6.3m	--	2010-11-17	Normal
023	Wireless Communications Test Set	Agilent	8960(E5515C)	GB41450323	2008-06-13	Normal
111835	Wireless Communications Test Set	R&S	CMU200	1100000802	--	Normal

Limit Level Construction:

(a) Radiated RF Power Output

According to Part 24.232(b), i.e., Mobile/portable stations are limited to 2 watts EIRP peak power and the equipment must employ means to limit the power to the minimum necessary for successful communications, so the limit level is 2 W or 33 dBm.

(b) ERP

According to Part 22.913(a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.

Limits for Radiated RF Power Output

Frequency range	Limit Level (EIRP)/Resolution Bandwidth
TX channel	33dBm/1MHz

Limits for ERP

Frequency range	Limit Level (ERP)
TX channel	7W

Test Setup:

The EUT was set in an anechoic chamber, which is connected to the Wireless Communications Test Set located outside the chamber over the air. The test was done using an automated test system, where all test equipments were controlled by a computer.

Test Method

The measurement was performed accordance with section 2.2.17 of ANSI/TIA-603-B-2002: *Land Mobile FM or PM Communications Equipment Measurement and Performance Standards*.

1 The maximum power was searched by turning the azimuth of the turntable, shifting the polarization of the measuring antenna and changing the pose of the EUT.

2 The measured levels are EIRP values corrected in the automated test system with the correction factors given by a substitution calibration made before the measurement. The calibration is made separately for vertical and horizontal polarization and the system uses different correction factors depending on the measuring antenna polarization.

3 The corrected maximum levels were reported for EIRP values, and ERP values can be calculated from EIRP values.

Note:

ERP dBm = EIRP dBm – 2.15dB.

ERP Value for GSM 850 band mode:

ARFCN	Frequency [MHz]	ERP [dBm]
128	824.128	23.11
190	836.653	22.45
251	848.778	19.94

EIRP Value for GSM 1900 band mode:

ARFCN	Frequency [MHz]	EIRP [dBm]
512	1850.100	24.34
661	1879.920	24.18
810	1909.900	24.38

ERP Value for GPRS 850 band mode:

ARFCN	Frequency [MHz]	ERP [dBm]
128	824.228	21.15
190	836.653	22.45
251	848.878	20.42

EIRP Value for GPRS 1900 band mode:

ARFCN	Frequency [MHz]	EIRP [dBm]
512	1850.100	24.39
661	1879.920	24.73
810	1909.900	24.46

4.3 Occupied bandwidth

Specifications:	2.1049,22.917(b),24.238(b)					
Date of Test	2008-3-18					
Test conditions:	Ambient Temperature: 15℃-35℃ Relative Humidity: 30%-60% Air pressure: 86-106kPa					
Operation Mode	TX on, channel 128, 190, 251, 512, 661 and 810					
Test Results:	--					
Test equipment Used:						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
7805	EMI Test Receiver	R/S	ESI26	100211	2009-01-03	Normal
7330	Ultra Broadband Antenna	R/S	HL562	100013	2008-07-24	Normal
7330	Double-Ridged Horn Antenna	R/S	HF906	100037	2009-01-14	Normal
713	Fully-Anechoic Chamber	ETS	11.8m×6.5m×6.3m	--	2010-11-17	Normal
023	Wireless Communications Test Set	Agilent	8960(E5515C)	GB41450323	2008-06-13	Normal
111835	Wireless Communications Test Set	R&S	CMU200	1100000802	--	Normal

Test Setup

The situation under which maximum EIRP values were found in the measurement of the radiated RF power output was used to determine the 99% occupied bandwidth. The Wireless Communications Test Set was used to set the TX channel, power level and modulation.

Test Method


The 99% occupied bandwidth was calculated from the spectrum analyzer. Markers in the spectrum analyzer were then placed between the calculated frequencies to show the calculated 99% power band.

Note: --

Results data of GSM mode:


EUT channel	99% occupied bandwidth [kHz]
128	281
190	281
251	281
512	281
661	281
810	281

Graphical results for GSM mode:




FCC Parts 2, 22, 24
Equipment: MEGA1

REPORT NO.: I08GE4589-FCC-EMC



Date: 18.MAR.2008 13:48:59

Channel 190




Date: 18.MAR.2008 14:12:11

Channel 251


FCC Parts 2, 22, 24
Equipment: MEGA1

REPORT NO.: I08GE4589-FCC-EMC



Date: 18.MAR.2008 14:29:13

Channel 512




Date: 18.MAR.2008 14:24:05

Channel 661

FCC Parts 2, 22, 24
Equipment: MEGA1

REPORT NO.: I08GE4589-FCC-EMC



Channel 810


Results data of GPRS mode:

EUT channel	99% occupied bandwidth [kHz]
128	253
190	248
251	244
512	257
661	257
810	244

Graphical results for GPRS mode:


FCC Parts 2, 22, 24
Equipment: MEGA1

REPORT NO.: I08GE4589-FCC-EMC



Date: 18.MAR.2008 15:26:23

Channel 128




Date: 18.MAR.2008 15:22:35

Channel 190


FCC Parts 2, 22, 24
Equipment: MEGA1

REPORT NO.: I08GE4589-FCC-EMC



Date: 18.MAR.2008 15:24:19

Channel 251




Date: 18.MAR.2008 15:15:54


Channel 512

FCC Parts 2, 22, 24
Equipment: MEGA1

REPORT NO.: I08GE4589-FCC-EMC



Channel 661



Channel 810

4.4 Frequency Stability over Temperature Variation

Specifications:	2.1055,22.355,24.235					
Date of Test	2008-3-17, 2008-3-18					
Test conditions:	Ambient Temperature: -30℃-50℃ Relative Humidity: 30%-60% Air pressure: 86-106kPa					
Operation Mode	TX on, channel 190 and 661					
Test Results:	Pass					
Test equipment Used:						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
023	Wireless Communication s Test Set	Agilent	8960(E5515C)	GB41450323	2008-06-13	Normal
561	Temperature Chamber	Terchy Environmental Technology LTD.	MHU-800SR	84121202	2008-05-06	Normal
111835	Wireless Communication s Test Set	R&S	CMU200	1100000802	--	Normal
Limit						
Frequency deviation [ppm]		±2.5				

Test Setup

The EUT was placed in a temperature chamber, demonstrated as figure T. The wireless communications test set (test simulator) was used to set the TX channel and power levels, modulate the TX signal with different bit patterns and measure the frequency of TX.




Figure T: setup for measurement of frequency stability over temperature variation

Test Method

1. The EUT was turned off and placed in the temperature chamber.
2. The temperature of the chamber was set to -30°C and allowed to stabilize.
3. The EUT temperature was allowed to stabilize for 45 minutes.
4. The EUT was turned on and set to transmit with 8960.
5. The maximum transmit frequency deviation during one minute period was measured by Wireless Communications Test Set.
6. The steps 3-5 were repeated for -20°C, -10°C, 0°C, 10°C, 20°C, 30°C, 40°C and 50°C.

Test results data for GSM mode:

Table T1: frequency deviation over temperature variation for channel 190

Temperature[°C]	Deviation[Hz]	Deviation[ppm]	Remarks
-30	-22	-0.026	Pass
-20	-20	-0.024	Pass
-10	-19	-0.023	Pass
0	-19	-0.023	Pass
10	-14	-0.017	Pass
20	-17	-0.020	Pass
30	-15	-0.018	Pass
40	-16	-0.019	Pass
50	-19	-0.023	Pass

Table T2: frequency deviation over temperature variation for channel 661

Temperature[°C]	Deviation[Hz]	Deviation[ppm]	Remarks
-30	-26	-0.014	Pass
-20	-24	-0.013	Pass
-10	-23	-0.012	Pass
0	-18	-0.009	Pass
10	-20	-0.011	Pass
20	-20	-0.011	Pass
30	-21	-0.011	Pass
40	-17	-0.009	Pass
50	-20	-0.011	Pass

Test results data for GPRS mode:

Table T3: frequency deviation over temperature variation for channel 190

Temperature[°C]	Deviation[Hz]	Deviation[ppm]	Remarks
-30	-20	-0.024	Pass
-20	-22	-0.026	Pass
-10	-16	-0.019	Pass
0	-13	-0.016	Pass
10	-12	-0.014	Pass
20	-14	-0.017	Pass
30	-15	-0.018	Pass
40	-13	-0.016	Pass
50	-16	-0.019	Pass

Table T4: frequency deviation over temperature variation for channel 661

Temperature[°C]	Deviation[Hz]	Deviation[ppm]	Remarks
-30	-24	-0.013	Pass
-20	-21	-0.011	Pass
-10	-19	-0.010	Pass
0	-18	-0.009	Pass
10	-20	-0.011	Pass
20	-19	-0.010	Pass
30	-17	-0.009	Pass
40	-16	-0.009	Pass
50	-19	-0.010	Pass

4.5 Frequency Stability over Voltage Variation

Specifications:	2.1055,22.355,24.235					
Date of Test	2008-3-18					
Test conditions:	Ambient Temperature: 15℃-35℃ Relative Humidity: 30%-60% Air pressure: 86-106kPa					
Operation Mode	TX on, channel 190 and 661					
Test Results:	Pass					
Test equipment Used:						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
023	Wireless Communication s Test Set	Agilent	8960(E5515C)	GB41450323	2008-06-13	Normal
111835	Wireless Communication s Test Set	R&S	CMU200	1100000802	--	Normal
7982	DC Power Source	4NIC	DH1715A-3	004224	--	Normal
Limit						
Frequency deviation [ppm]		±2.5				

Test Setup

The EUT was placed in a shielding chamber and powered by the dummy battery which is connected to a DC power source, demonstrated as figure V. The wireless communications test set was used to set the TX channel and power level, modulate the TX signal with different bit patterns and measure the frequency of TX.




Figure V: test setup for measurement of frequency stability over voltage variation

Test Results data for GSM mode:

Table V1: frequency deviation over voltage variation for channel 190

Level	Voltage[V]	Deviation[Hz]	Deviation[ppm]	Remarks
Nominal	3.7	-18	-0.022	Pass
Cut-off point	3.3	-12	-0.014	Pass

Table V2: frequency deviation over voltage variation for channel 661

Level	Voltage[V]	Deviation[Hz]	Deviation[ppm]	Remarks
Nominal	3.7	-37	-0.020	Pass
Cut-off point	3.3	-28	-0.015	Pass

Test Results data for GPRS mode:

Table V3: frequency deviation over voltage variation for channel 190

Level	Voltage[V]	Deviation[Hz]	Deviation[ppm]	Remarks
Nominal	3.7	-16	-0.019	Pass
Cut-off point	3.3	-22	-0.012	Pass

Table V4: frequency deviation over voltage variation for channel 661

Level	Voltage[V]	Deviation[Hz]	Deviation[ppm]	Remarks
Nominal	3.7	-28	-0.015	Pass
Cut-off point	3.3	-30	-0.016	Pass


4.6 Conducted RF Power Output

Specifications:	2.1046,22.913(a),24.232(c)					
Date of Tests	2008-3-18					
Test conditions:	Ambient Temperature: 15°C-35°C Relative Humidity: 30%-60% Air pressure: 86-106kPa					
Operation Mode	TX on, channel 128, 190, 251, 512, 661 and 810					
Test Results:	Pass					
Test equipment Used:						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
7805	EMI Test Receiver	R/S	ESI26	100211	2009-01-04	Normal
023	Wireless Communications Test Set	Agilent	8960(E5515C)	GB41450323	2008-06-13	Normal
---	Power splitter	Jie sai	---	1000132	2009-01-04	Normal
111835	Wireless Communications Test Set	R&S	CMU200	1100000802	--	Normal

Limits for Radiated RF Power Output	
Frequency range	Limit Level (EIRP)/Resolution Bandwidth
TX channel	33dBm/1MHz
Limits for ERP	
Frequency range	Limit Level (ERP)
TX channel	7W

Test Setup:

During the process of testing, the EUT was controlled via the Wireless Communications Test Set to ensure max power transmission and proper modulation and measured by Rhode & Schwarz EMI test receiver (ES126).



Test Method

- 1) The EUT was coupled to the EMI test receiver analyzer mode and the base station simulator through a power divider. The radio frequency load attached to the EUT antenna terminal was 50 Ohm. The loss of the cables the test system is calibrated to correct the readings.
- 2) The spectrum analyzer was set to Maxpeak Detector function and Maximum hold mode.
- 3) The resolution bandwidth of the spectrum analyzer was comparable to the emission bandwidth.

Note: --

Test Results for GSM mode:

ERP Value for GSM 850 band:

ARFCN	Peak output power [dBm]
128	30.42
190	30.77
251	29.7596

EIRP Value for GSM 1900 band:

ARFCN	Peak output power [dBm]
512	26.96
661	27.08
810	27.22

Test Results for GPRS mode:

ERP Value for GPRS 850 band:

ARFCN	Peak output power [dBm]
128	21.51
190	22.39
251	21.82

EIRP Value for GPRS 1900 band:

ARFCN	Peak output power [dBm]
512	19.37
661	19.14
810	19.23

4.7 Conducted Spurious Emission

Specifications:	2.1051,22.917,24.238					
Date of Tests	2008-3-19					
Test conditions:	Ambient Temperature: 15℃-35℃ Relative Humidity: 30%-60% Air pressure: 86-106kPa					
Operation Mode	TX on, channel 190 and 661					
Test Results:	Pass					
Test equipment Used:						
Asset Number	Description	Manufacturer	Model Number	Serial Number	Cal Due	State
7805	EMI Test Receiver	R/S	ESI26	100211	2009-01-04	Normal
023	Wireless Communications Test Set	Agilent	8960(E5515C)	GB41450323	2008-06-13	Normal
---	Power splitter	Jie sai	---	1000132	2009-01-04	Normal
111835	Wireless Communications Test Set	R&S	CMU200	1100000802	--	Normal

Limit Level Construction:


According to Part 24.238 (a), i.e., Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB, so the limit level is:
 $P(\text{dBm}) - (43 + 10 \log(P)) \text{ dB} = -13\text{dBm}$

Limits for Radiated spurious emissions(UE)

Frequency range	Limit Level /Resolution Bandwidth
30 MHz to 20000 MHz	-13dBm/1MHz

Test Setup:

During the process of testing, the EUT was controlled via Wireless Communications Test Set to ensure max power transmission and proper modulation and measured by Rhode & Schwarz EMI test receiver (ES126)



Test Method

The measurement was performed accordance with section 2.2.13 of ANSI/TIA-603-B-2002: *Land Mobile FM or PM Communications Equipment Measurement and Performance Standards*.

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment under test, this equates to a frequency range of 30 MHz to 19.1 GHz, data taken from 30 MHz to 20 GHz.
2. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

Note: --


Test Results for GSM mode:

Out of band emission	
Frequency [MHz]	Level (dBm)
3351.66333	-46.68

Graphical results for GSM mode:


FCC Parts 2, 22, 24
Equipment: MEGA1

REPORT NO.: I08GE4589-FCC-EMC



Date: 19.MAR.2008 15:27:48

Channel 190




Date: 19.MAR.2008 15:28:21

Channel 661

Test Results for GPRS mode:

Out of band emission	
Frequency [MHz]	Level (dBm)
6993.48697	-51.99

Graphical results for GPRS mode:




Channel 190



FCC Parts 2, 22, 24
Equipment: MEGA1

REPORT NO.: I08GE4589-FCC-EMC



Date: 19.MAR.2008 15:06:30

Channel 661

Annex A External Photos



Front view with flip colse



Front view with flip open



Back view



Adaptor



Cable




Battery




Earphone

Annex B Internal Photos




Main board (face)



Main board (back)



Adaptor face



Adaptor back

ANNEX C Deviations from Prescribed Test Methods

No deviation from Prescribed Test Methods.

———— The End of this Report ————

CTL Test Report