

ATTACHMENT O – SAR TEST PLOTS -2/2-

Test Laboratory: HCT

Company Ezze Mobile Tech., Inc.

Mode :GSM850(Body)/ Antenna : Fixed / Channel : 190

Liquid Temperature : 21.6℃/Ambient Temperature: 21.8℃

Date Tested : January 31, 2007

DUT: SLT100down; Type: Slide down; Serial: #1

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.99$ mho/m; $\epsilon_r = 53.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 44

DASY4 Configuration:

- Probe: ET3DV6 - SN1798; ConvF(6.71, 6.71, 6.71); Calibrated: 2006-08-25

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn447; Calibrated: 2006-11-17

- Phantom: SAM 835/900 MHz; Type: SAM

GSM850 Body 190/Area Scan (51x91x1): Measurement grid: $\Delta x = 15$ mm, $\Delta y = 15$ mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (interpolated) = 0.414 mW/g

GSM850 Body 190/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $\Delta x = 8$ mm, $\Delta y = 8$ mm, $\Delta z = 5$ mm


Reference Value = 9.43 V/m; Power Drift = -0.026 dB

Peak SAR (extrapolated) = 0.506 W/kg

SAR(1 g) = 0.384 mW/g; SAR(10 g) = 0.267 mW/g

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.412 mW/g



Test Laboratory: HCT

Company Ezze Mobile Tech., Inc.
Mode : GSM850(Body)/ Antenna : Fixed / Channel : 190 (Bluetooth)
Liquid Temperature : 21.6°C/Ambient Temperature: 21.8°C
Date Tested : January 31, 2007

DUT: SLT100down; Type: Slide down; Serial: #1

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.99$ mho/m; $\epsilon_r = 53.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 44

DASY4 Configuration:

- Probe: ET3DV6 - SN1798; ConvF(6.71, 6.71, 6.71); Calibrated: 2006-08-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn447; Calibrated: 2006-11-17
- Phantom: SAM 835/900 MHz; Type: SAM

GSM850 Body 190/Area Scan (51x91x1): Measurement grid: $\Delta x = 15$ mm, $\Delta y = 15$ mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (interpolated) = 0.290 mW/g

GSM850 Body 190/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $\Delta x = 8$ mm, $\Delta y = 8$ mm, $\Delta z = 5$ mm


Reference Value = 9.78 V/m; Power Drift = 0.076 dB

Peak SAR (extrapolated) = 0.354 W/kg

SAR(1 g) = 0.269 mW/g; SAR(10 g) = 0.191 mW/g

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.286 mW/g



Test Laboratory: HCT

Company Ezze Mobile Tech., Inc.

Mode :GSM850(Body)/ Antenna : Fixed / Channel : 190(Front)

Liquid Temperature : 21.6℃/Ambient Temperature: 21.8℃

Date Tested : January 31, 2007

DUT: SLT100 down; Type: Slide down; Serial: #1

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.99$ mho/m; $\epsilon_r = 53.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 44

DASY4 Configuration:

- Probe: ET3DV6 - SN1798; ConvF(6.71, 6.71, 6.71); Calibrated: 2006-08-25

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn447; Calibrated: 2006-11-17

- Phantom: SAM 835/900 MHz; Type: SAM

GSM850 Body 190/Area Scan (51x91x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (interpolated) = 0.158 mW/g

GSM850 Body 190/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm


Reference Value = 8.88 V/m; Power Drift = -0.035 dB

Peak SAR (extrapolated) = 0.188 W/kg

SAR(1 g) = 0.149 mW/g; SAR(10 g) = 0.111 mW/g

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.158 mW/g



Test Laboratory: HCT

Company Ezze Mobile Tech., Inc.

Mode :GSM850(Body)/ Antenna : Fixed / Channel : 190(GPRS)

Liquid Temperature : 21.6°C/Ambient Temperature: 21.8°C

Date Tested : January 31, 2007

DUT: SLT100 down; Type: Slide down; Serial: #1

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.99$ mho/m; $\epsilon_r = 53.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 44

DASY4 Configuration:

- Probe: ET3DV6 - SN1798; ConvF(6.71, 6.71, 6.71); Calibrated: 2006-08-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn447; Calibrated: 2006-11-17
- Phantom: SAM 835/900 MHz; Type: SAM

GSM850 Body 190/Area Scan (51x91x1): Measurement grid: $\Delta x = 15$ mm, $\Delta y = 15$ mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (interpolated) = 0.152 mW/g

GSM850 Body 190/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $\Delta x = 8$ mm, $\Delta y = 8$ mm, $\Delta z = 5$ mm


Reference Value = 8.76 V/m; Power Drift = -0.080 dB

Peak SAR (extrapolated) = 0.179 W/kg

SAR(1 g) = 0.143 mW/g; SAR(10 g) = 0.106 mW/g

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.151 mW/g



Test Laboratory: HCT

Company Ezze Mobile Tech., Inc.

Mode :GSM1900(Body)/ Antenna : Fixed / Channel : 661

Liquid Temperature : 21.6℃/Ambient Temperature: 21.8℃

Date Tested : January 31, 2007

DUT: SLT100 down; Type: Slide down; Serial: #1

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.47$ mho/m; $\epsilon_r = 52.6$; $\rho = 1000$ kg/m³

Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 44

DASY4 Configuration:

- Probe: ET3DV6 - SN1798; ConvF(4.8, 4.8, 4.8); Calibrated: 2006-08-25

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn447; Calibrated: 2006-11-17

- Phantom: SAM 1800/1900 MHz; Type: SAM

GSM1900 Body 661/Area Scan (51x91x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (interpolated) = 0.150 mW/g


GSM1900 Body 661/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 9.78 V/m; Power Drift = -0.026 dB

Peak SAR (extrapolated) = 0.187 W/kg

SAR(1 g) = 0.131 mW/g; SAR(10 g) = 0.084 mW/g

Maximum value of SAR (measured) = 0.142 mW/g



Test Laboratory: HCT

Company Ezze Mobile Tech., Inc.

Mode : GSM1900(Body)/ Antenna : Fixed / Channel : 661(Bluetooth)

Liquid Temperature : 21.6°C/Ambient Temperature: 21.8°C

Date Tested : January 31, 2007

DUT: SLT100 down; Type: Slide down; Serial: #1

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.47$ mho/m; $\epsilon_r = 52.6$; $\rho = 1000$ kg/m³

Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 44

DASY4 Configuration:

- Probe: ET3DV6 - SN1798; ConvF(4.8, 4.8, 4.8); Calibrated: 2006-08-25

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn447; Calibrated: 2006-11-17

- Phantom: SAM 1800/1900 MHz; Type: SAM

GSM1900 Body 661/Area Scan (51x91x1): Measurement grid: $\Delta x = 15$ mm, $\Delta y = 15$ mm

Maximum value of SAR (interpolated) = 0.147 mW/g


GSM1900 Body 661/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $\Delta x = 8$ mm, $\Delta y = 8$ mm, $\Delta z = 5$ mm

Reference Value = 8.18 V/m; Power Drift = -0.079 dB

Peak SAR (extrapolated) = 0.186 W/kg

SAR(1 g) = 0.130 mW/g; SAR(10 g) = 0.082 mW/g

Maximum value of SAR (measured) = 0.141 mW/g



Test Laboratory: HCT

Company Ezze Mobile Tech., Inc.

Mode : GSM1900(Body)/ Antenna : Fixed / Channel : 661(GPRS)

Liquid Temperature : 21.6°C/Ambient Temperature: 21.8°C

Date Tested : January 31, 2007

DUT: SLT100 down; Type: Slide down; Serial: #1

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.47$ mho/m; $\epsilon_r = 52.6$; $\rho = 1000$ kg/m³

Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 44

DASY4 Configuration:

- Probe: ET3DV6 - SN1798; ConvF(4.8, 4.8, 4.8); Calibrated: 2006-08-25

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn447; Calibrated: 2006-11-17

- Phantom: SAM 1800/1900 MHz; Type: SAM

GSM1900 Body 661/Area Scan (51x91x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (interpolated) = 0.090 mW/g


GSM1900 Body 661/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 7.57 V/m; Power Drift = 0.058 dB

Peak SAR (extrapolated) = 0.120 W/kg

SAR(1 g) = 0.079 mW/g; SAR(10 g) = 0.048 mW/g

Maximum value of SAR (measured) = 0.084 mW/g



Test Laboratory: HCT

Company Ezze Mobile Tech., Inc.

Mode : GSM1900(Body)/ Antenna : Fixed / Channel : 661(Front)

Liquid Temperature : 21.6°C/Ambient Temperature: 21.8°C

Date Tested : January 31, 2007

DUT: SLT100 down; Type: Slide down; Serial: #1

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.47$ mho/m; $\epsilon_r = 52.6$; $\rho = 1000$ kg/m³

Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 44

DASY4 Configuration:

- Probe: ET3DV6 - SN1798; ConvF(4.8, 4.8, 4.8); Calibrated: 2006-08-25

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn447; Calibrated: 2006-11-17

- Phantom: SAM 1800/1900 MHz; Type: SAM

GSM1900 Body 661/Area Scan (51x91x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (interpolated) = 0.089 mW/g


GSM1900 Body 661/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 7.73 V/m; Power Drift = -0.102 dB

Peak SAR (extrapolated) = 0.120 W/kg

SAR(1 g) = 0.079 mW/g; SAR(10 g) = 0.048 mW/g

Maximum value of SAR (measured) = 0.085 mW/g



Test Laboratory: HCT

Company Ezze Mobile Tech., Inc.

Mode :GSM850/Antenna : Fixed / Channel : 251

Liquid Temperature : 21.6°C/Ambient Temperature: 21.8°C

Date Tested : January 31, 2007

DUT: SLT100 down; Type: Slide down; Serial: #1

Communication System: GSM 850; Frequency: 849.8 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 850$ MHz; $\sigma = 0.892$ mho/m; $\epsilon_r = 41$; $\rho = 1000$ kg/m³

Phantom section: Right Section ;Measurement SW: DASY4, V4.7 Build 44

DASY4 Configuration:


- Probe: ET3DV6 - SN1798; ConvF(6.73, 6.73, 6.73); Calibrated: 2006-08-25

- Sensor-Surface: 0mm (Fix Surface)

- Electronics: DAE4 Sn447; Calibrated: 2006-11-17

- Phantom: SAM 835/900 MHz; Type: SAM

Right touch 251/Z Scan (1x1x31): Measurement grid: $dx=20$ mm, $dy=20$ mm, $dz=5$ mm
Maximum value of SAR (measured) = 0.829 mW/g



Test Laboratory: HCT

Company Ezze Mobile Tech., Inc.

Mode :GSM1900/ Antenna : Fixed / Channel : 512

Liquid Temperature : 21.6°C/Ambient Temperature: 21.8°C

Date Tested : January 31, 2007

DUT: SLT100 up; Type: Slide up; Serial: #1

Communication System: GSM 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8.3

Medium parameters used (interpolated): $f = 1850.2$ MHz; $\sigma = 1.4$ mho/m; $\epsilon_r = 39.5$; $\rho = 1000$ kg/m³

Phantom section: Right Section ;Measurement SW: DASY4, V4.7 Build 44

DASY4 Configuration:

- Probe: ET3DV6 - SN1798; ConvF(5.6, 5.6, 5.6); Calibrated: 2006-08-25

- Sensor-Surface: 0mm (Fix Surface)


- Electronics: DAE4 Sn447; Calibrated: 2006-11-17

- Phantom: SAM 1800/1900 MHz; Type: SAM

Right touch 512/Z Scan (1x1x31): Measurement grid: $dx=20$ mm, $dy=20$ mm, $dz=5$ mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.709 mW/g



Test Laboratory: HCT

Company Ezze Mobile Tech., Inc.

Mode : GSM850(Body)/ Antenna : Fixed / Channel : 190

Liquid Temperature : 21.6°C / Ambient Temperature: 21.8°C

Date Tested : January 31, 2007

DUT: SLT100 down; Type: Slide down; Serial: #1

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.99$ mho/m; $\epsilon_r = 53.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 44

DASY4 Configuration:

- Probe: ET3DV6 - SN1798; ConvF(6.71, 6.71, 6.71); Calibrated: 2006-08-25

- Sensor-Surface: 0mm (Fix Surface)


- Electronics: DAE4 Sn447; Calibrated: 2006-11-17

- Phantom: SAM 835/900 MHz; Type: SAM

GSM850 Body 190/Z Scan (1x1x31): Measurement grid: $dx=20$ mm, $dy=20$ mm, $dz=5$ mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.398 mW/g



Test Laboratory: HCT

Company Ezze Mobile Tech., Inc.

Mode :GSM1900(Body)/ Antenna : Fixed / Channel : 661

Liquid Temperature : 21.6℃/Ambient Temperature: 21.8℃

Date Tested : January 31, 2007

DUT: SLT100 down; Type: Slide down; Serial: #1

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.47 \text{ mho/m}$; $\epsilon_r = 52.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 44

DASY4 Configuration:

- Probe: ET3DV6 - SN1798; ConvF(4.8, 4.8, 4.8); Calibrated: 2006-08-25

- Sensor-Surface: 0mm (Fix Surface)

- Electronics: DAE4 Sn447; Calibrated: 2006-11-17

- Phantom: SAM 1800/1900 MHz; Type: SAM

GSM1900 Body 661/Z Scan (1x1x31): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$, $dz=5\text{mm}$
Maximum value of SAR (measured) = 0.083 mW/g

