

SkyPilot Inc.					
FCC ID: RV7-GW-SD1000			Calculate mW/cm2 here. Enter frequency in MHz:		
RF Hazard Distance Calculation			Calculation of Limits from 1.1310 Table 1		
mW/cm2 from Table1:	1.00		F(MHz)	Actual F, MHz	Controlled Ave 6 min Occ, mW/c2
			0.3-3	0.5	Uncontrolled Ave 30 min Gen, mW/cm2
Max RF Power	TX Antenna	MPE	3.0 - 30.0	5	100.0 180.0
P, dBm	G, dBi	Safe Distance, cm	30.0-300	55	0.2
			300-1500	555	1.0 1.9
26.7	16.0	38.4	1500-100000	5555	0.37
0.0	0.0	0.3			
0.0	0.0	0.3			
0.0	0.0	0.3			
0.0	0.0	0.3			
0.0	0.0	0.3			
0.0	0.0	0.3			
0.0	0.0	0.3			
0.0	0.0	0.3			
0.0	0.0	0.3			
Enter P(watts)	Equivalent dBm	Enter dBm	Equivalent Watts		
E ² /3770 = S, mW/cm ₂					
E, V/m = (Pwatts*Ggain*30) ^{0.5} /d, meters					
d = ((Pwatts*G*30)/3770*S) ^{0.5}	Pwatts*Ggain = 10^(PdBm-30+GdBi)/10				
NOTE: For mobile or fixed location transmitters, minimum separation distance is 20 cm, even if calculations indicate MPE distance is less					