

# TEST REPORT

of

FCC Part 15 Subpart C §15.249

FCC ID: RVBXP200T

Equipment Under Test : X-Pointer  
Model Name : XPG200  
Serial No. : N/A  
Applicant : Chois Technology Co., Ltd.  
Manufacturer : Chois Technology Co., Ltd.  
Date of Test(s) : 2009-02-18 ~ 2009-02-26  
Date of Issue : 2009-03-04

In the configuration tested, the EUT complied with the standards specified above.

Tested By:



Date

2009-03-04

Feel Jeong

Approved By



Date

2009-03-04

Denny Ham

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

**Table of contents**

<b>1. General information -----</b>	<b>3</b>
<b>2. Fundamental, Spurious emission and edge band radiated emission -----</b>	<b>6</b>

---

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

## 1. General information

### 1.1 Testing laboratory

SGS Testing Korea Co., Ltd.

Wireless Div. 2FL, 18-34, Sanbon-dong, Gunpo-si, Gyeonggi-do, Korea 435-040

[www.electrolab.kr.sgs.com](http://www.electrolab.kr.sgs.com)

Telephone : +82 +31 428 5700

FAX : +82 +31 427 2371

### 1.2 Details of applicant

Applicant : Chois Technology Co., Ltd.

Address : 1102, Incheon IT Tower, 592-5, Dowha-1 dong, Namgu, Korea

Contact Person : Sang-Hwan Nam

Phone No. : +82 +32 246 3409

Fax No. : +82 +32 246 3406

### 1.3 Description of EUT

<b>Kind of Product</b>	X-Pointer
<b>Model Name</b>	XPG200
<b>Serial Number</b>	N/A
<b>Power Supply</b>	DC 3 V( battery type)
<b>Frequency Range</b>	2405 ~ 2480 MHz
<b>Modulation Technique</b>	GFSK
<b>Number of Channels</b>	79
<b>Operating Conditions</b>	10 ~ 40
<b>Antenna Type</b>	Fixed Type

### 1.4 Details of Modification

-N/A

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

### 1.5 Test equipment list

Equipment	Manufacturer	Model	Cal Due.
Signal Generator	Agilent	E4438C	May 09, 2009
Spectrum Analyzer	Agilent	E4440A	May 09, 2009
High Pass Filter	Wainwright Instrument GmbH	WHK3.0/18G-11SS	Dec. 01, 2009
Preamplifier	H.P	8447F	Jul. 03, 2009
Preamplifier	R&S	SCU_F0118_G35_AFS42_SCC(F)	Aug. 25, 2009
Test Receiver	Rohde & Schwarz	ESVS10	Jul. 21, 2009
Test Receiver	Rohde & Schwarz	ESHS10	Jun. 21, 2009
Ultra-Broadband Antenna	Rohde & Schwarz	HL562	Oct. 02, 2009
Horn Antenna	Electro-Metrics	HF906	Nov. 13, 2009
Anechoic Chamber	SY Corporation	L W H (9.6 m 6.4 m 6.6 m)	Jan. 31, 2010

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

### 1.6. Summary of test results

The EUT has been tested according to the following specifications:

Applied Standard : FCC Part15, Subpart C		
Standard Section	Test Item	Result
15.209(a) 15.249(a) 15.249(d) 15.205	Fundamental, Spurious emission and edge band radiated emission	Complied

### 1.7. Test report revision


Revision	Report number	Description
0	F690501/RF-RTL002945	Initial

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*


## 2. Fundamental, Spurious emission and edge band radiated emission

### 2.1. Test setup

The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz Emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 1 GHz to 24 GHz Emissions.



*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

## 2.2. Test procedures

Radiated emissions from the EUT were measured according to the dictates of ANSI C63.4:2003

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic Chamber The table was rotated 360 degrees to determine the position of the highest radiation.
2. During performing radiated emission above 1 GHz, the EUT was set 3 meter away from the interference-receiving antenna.
3. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarization of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Note :

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz for Peak detection and frequency above 1 GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1 GHz.

---

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

### 2.3. Limit

In the section 15.249(a) :

Except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency	Field strength of fundamental (mV/m)	Field strength of harmonics (uV/m)
902 ~ 928 MHz	50	500
2400 ~ 2483.5 MHz	50	500
5725 ~ 5875 MHz	50	500
24.0 ~ 24.25 GHz	250	2500

Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Fundamental frequency (MHz)	Field strength (uV/m)	Measurement distance (m)
30 ~ 88	100*	3
88 ~ 216	150*	3
216 ~960	200*	3
Above 960	500	3

Remark:

Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

In the above emission table, the tighter limit applies at the band edges.

Fundamental frequency (MHz)	Field strength (uV/m at 3 meter)	Field strength (dBuV/m at 3 meter)
30 ~ 88	100	40
88 ~ 216	150	43.5
216 ~960	200	46
Above 960	500	54

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*



## 2.4. Test result

Ambient temperature : 22  
 Relative humidity : 48 % R.H.

### 2.4.1. Below 1 GHz

Radiated Emissions			Ant	Correction Factors		Total	Limit	
Frequency (MHz)	Reading (dBuV)	Detect Mode	Pol.	AF (dB/m)	Amp Gain+CL (dB)	Actual (dBuV/m)	Limit (dBuV/m)	Margin (dB)
71.225	9.64	Peak	V	6.53	0.93	17.10	40.00	22.90
112.450	7.57	Peak	V	9.63	1.20	18.40	43.50	25.10
793.875	4.93	Peak	V	19.57	3.20	27.70	46.00	18.30
Above 800	Not detected							

#### Remark

1. To get a maximum emission level from the EUT, the EUT was moved throughout the XY, XZ and YZ planes.
2. All spurious emission at channels are almost the same below 1 GHz, so that the channel was chosen at representative in final test.

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

### 3.4.2. Above 1 GHz

#### A. Low Channel

Radiated Emissions			Ant	Correction Factors		Total	Limit	
Frequency (MHz)	Reading (dBuV)	Detect Mode	Pol.	AF (dB/m)	Amp Gain+CL (dB)	Actual (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2405.00	83.78	Peak	V	28.07	-34.77	77.08	114.00	36.92
2390.00*	49.45	Peak	V	28.05	-34.80	42.70	74.00	31.30
4810.00	63.45	Peak	V	32.97	-31.72	64.70	74.00	9.30
4810.00	36.45	Average	V	32.97	-31.72	37.70	54.00	16.30
Above 4900.00	Not Detected							

#### B. Middle Channel

Radiated Emissions			Ant	Correction Factors		Total	Limit	
Frequency (MHz)	Reading (dBuV)	Detect Mode	Pol.	AF (dB/m)	Amp Gain+CL (dB)	Actual (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2440.00	86.81	Peak	V	28.12	-34.73	80.20	114.00	33.80
4880.00	61.41	Peak	V	33.16	-31.89	62.68	74.00	11.32
4880.00	35.54	Average	V	33.16	-31.89	36.81	54.00	17.19
Above 4900.00	Not Detected							

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## C. High Channel

Radiated Emissions			Ant	Correction Factors		Total	Limit	
Frequency (MHz)	Reading (dBuV)	Detect Mode	Pol.	AF (dB/m)	Amp Gain+CL (dB)	Actual (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2480.00	84.48	Peak	V	28.17	-34.68	77.97	114.00	36.03
2483.50*	60.15	Peak	V	28.18	-34.67	53.66	74.00	20.34
4960.00	58.87	Peak	V	33.39	-31.68	60.58	74.00	13.42
4960.00	32.28	Average	V	33.39	-31.68	33.99	54.00	20.01
Above 5000.00	Not Detected							

**Remarks ;**

1. “\*” means the restricted band.
2. To get a maximum emission level from the EUT, the EUT was moved throughout the XY, XZ and YZ planes.
3. Measuring frequencies from 1 GHz to the 10<sup>th</sup> harmonic of highest fundamental Frequency.
4. Radiated emissions measured in frequency above 1000 MHz were made with an instrument using peak/average detector mode.
5. Average test would be performed if the peak result were greater than the average limit.
6. Actual = Reading + AF - Amp Gain + CL

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*