

FCC RF EXPOSURE REPORT

FCC ID: RWO-RZ30026901

Project No. : 1807C144
Equipment : Gaming Headset
Test Model : RC30-026901
Series Model : N/A
Applicant : Razer Inc.
**Address : 201 3rd Street, Suite 900, San Francisco, CA
94103,USA**

**According: : FCC Guidelines for Human Exposure IEEE
C95.1 & KDB447498 D01**

B T L I N C .

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan,
Guangdong, China.

TEL: +86-769-8318-3000 FAX: +86-769-8319-6000

1. CERTIFICATION

Equipment : Gaming Headset
 Brand Name : RAZER
 Test Model : RC30-026901
 Series Model : N/A
 Applicant : Razer Inc.
 Manufacturer : Razer (Asia-Pacific) Pte.,Ltd.
 Address : 514 Chai Chee Lane #07-01~06 Singapore 469029
 Factory : RAZER TECHNOLOGY AND DEVELOPMENT (SHENZHEN) CO., LTD
 Address : East Wing, 3rd Floor, Block 2, Phase 1 of Vision Shenzhen Business Park Keji South Road, Hi-Tech Industrial Park, Shenzhen 518057, China
 Date of Test : Jul. 30, 2018 ~ Aug. 08, 2018
 Test Sample : Engineering Sample No.: D180706283 for conducted, D180706282 for radiated.

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. BTL-FCCP-2-1807C144) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of TAF according to the ISO-17025 quality assessment standard and technical standard(s).

Table for Filed Antenna

Ant.	Brand	P/N	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	PIFA	N/A	3.64
2	N/A	N/A	PIFA	N/A	3.64

Note: There are two antennas but only one antenna works at a time.

2. GENERAL CONCLUSION:

According to FCC KDB447498 D01, Appendix A, SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Appendix A - SAR Test Exclusion Thresholds for 100 MHz - 6 GHz and ≤ 50 mm

MHz	5	10	15	20	25	30	35	40	45	50	mm
150	39	77	116	155	194	232	271	310	349	387	SAR Test Exclusion Thresholds (mW)
300	27	55	82	110	137	164	192	219	246	274	
450	22	45	67	89	112	134	157	179	201	224	
835	16	33	49	66	82	98	115	131	148	164	
900	16	32	47	63	79	95	111	126	142	158	
1500	12	24	37	49	61	73	86	98	110	122	
1900	11	22	33	44	54	65	76	87	98	109	
2450	10	19	29	38	48	57	67	77	86	96	
3600	8	16	24	32	40	47	55	63	71	79	
5200	7	13	20	26	33	39	46	53	59	66	
5400	6	13	19	26	32	39	45	52	58	65	
5800	6	12	19	25	31	37	44	50	56	62	

Maximum measured transmitter power:

Max OutputPower (dBm)	Max Output Power (mW)	Limit (mW)
3.15	2.0654	10

The maximum measured output peak power of this EUT is 2.0654 mW, less than 10mW at 5mm distance.

Conclusion: No SAR evaluation required since transmitter power is below FCC threshold.