

|  |  |  |   |   |
|--|--|--|---|---|
| <b>Prüfbericht-Nr.:</b><br><i>Test report no.:</i>   | CN22NAY5(FCC SAR)002   | <b>Auftrags-Nr.:</b><br><i>Order no.:</i>                  | 238549015                                 | Seite 1 von 30<br><i>Page 1 of 30</i>   |
| <b>Kunden-Referenz-Nr.:</b><br><i>Client reference no.:</i>  | N/A  | <b>Auftragsdatum:</b><br><i>Order date:</i>                | 2022-10-21                                |   |
| <b>Auftraggeber:</b><br><i>Client:</i>   | Razer Inc.<br>9 Pasteur, Suite 100, Irvine, CA92618, USA   |  |   |   |
| <b>Prüfgegenstand:</b><br><i>Test item:</i>  | USB WIRELESS TRANSCEIVER   |  |   |   |
| <b>Bezeichnung / Typ-Nr.:</b><br><i>Identification / Type no.:</i>   | RC30-0471<br>RC30-0471XXXX-XXXX(X can be 0-9 or A-Z)   |  |   |   |
| <b>Auftrags-Inhalt:</b><br><i>Order content:</i>   | Test Report for FCC SAR  |  |   |   |
| <b>Prüfgrundlage:</b><br><i>Test specification:</i>  | FCC 47 CFR §2.1093<br>ANSI Std C95.1<br>IEEE Std 1528:2013<br>IEC/IEEE 62209-1528:2020<br>Published RF Exposure KDB Procedures |  |   |   |
| <b>Wareneingangsdatum:</b><br><i>Date of sample receipt:</i>   | 2022-10-13   |  |   |   |
| <b>Prüfmuster-Nr.:</b><br><i>Test sample no.:</i>  | A003355033-001   |  |   |   |
| <b>Prüfzeitraum:</b><br><i>Testing period:</i>   | 2022-10-20 - 2022-10-20  |  |   |   |
| <b>Ort der Prüfung:</b><br><i>Place of testing:</i>  | EMC/RF Taipei Testing Site   |  |   |   |
| <b>Prüflaboratorium:</b><br><i>Testing laboratory:</i>   | Taipei Testing Laboratories  |  |   |   |
| <b>Prüfergebnis*:</b><br><i>Test result*:</i>  | Pass   |  |   |   |
| <b>überprüft von:</b><br><i>compiled by:</i>   |  | <b>genehmigt von:</b><br><i>authorized by:</i>             |   |   |
| <b>Datum:</b><br><i>Date:</i>  | 2022-10-25   | <b>Ausstellungsdatum:</b><br><i>Issue date:</i>            | 2022-10-25                                |   |
| <b>Stellung / Position:</b>  | Project Engineer   | <b>Stellung / Position:</b>                                | Senior Project Manager                    |   |
| <b>Sonstiges / Other:</b>  |  |  |   |   |
| <b>Zustand des Prüfgegenstandes bei Anlieferung:</b><br><i>Condition of the test item at delivery:</i>   | Prüfmuster vollständig und unbeschädigt<br><i>Test item complete and undamaged</i>   |  |   |   |
| * Legende:   | 1 = sehr gut<br>P(ass) = entspricht o.g. Prüfgrundlage(n)  | 2 = gut<br>F(ail) = entspricht nicht o.g. Prüfgrundlage(n) | 3 = befriedigend<br>N/A = nicht anwendbar | 4 = ausreichend<br>N/T = nicht getestet |
| * Legend:  | 1 = very good<br>P(ass) = passed a.m. test specification(s)  | 2 = good<br>F(ail) = failed a.m. test specification(s)     | 3 = satisfactory<br>N/A = not applicable  | 4 = sufficient<br>N/T = not tested      |
| <b>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</b><br><i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i> |  |  |   |   |

## CONTENTS

|   |           |
|---|-----------|
| <b>HISTORY OF THIS TEST REPORT .....</b>                  | <b>4</b>  |
| <b>1. GENERAL INFORMATION .....</b>                       | <b>5</b>  |
| 1.1 STATEMENT OF COMPLIANCE .....                         | 5         |
| 1.2 EQUIPMENT UNDER TEST (EUT) INFORMATION .....          | 6         |
| 1.2.1 GENERAL INFORMATION .....                           | 6         |
| 1.2.2 WIRELESS TECHNOLOGIES .....                         | 6         |
| 1.3 MAXIMUM CONDUCTED POWER .....                         | 6         |
| <b>2. TEST SITES .....</b>                                | <b>7</b>  |
| 2.1 TEST LABORATORY .....                                 | 7         |
| 2.2 TEST FACILITIES .....                                 | 7         |
| 2.3 LIST OF TEST AND MEASUREMENT INSTRUMENTS .....        | 8         |
| <b>3. MEASUREMENT UNCERTAINTY .....</b>                   | <b>9</b>  |
| <b>4. TEST SPECIFICATION, METHODS AND PROCEDURES.....</b> | <b>11</b> |
| <b>5. RF EXPOSURE LIMITS.....</b>                         | <b>12</b> |
| 5.1 UNCONTROLLED ENVIRONMENT.....                         | 12        |
| 5.2 CONTROLLED ENVIRONMENT.....                           | 12        |
| <b>6. SAR MEASUREMENT SYSTEM.....</b>                     | <b>13</b> |
| 6.1 DEFINITION OF SPECIFIC ABSORPTION RATE (SAR).....     | 13        |
| 6.2 SPEAG DASY SYSTEM.....                                | 13        |
| 6.2.1 ROBOT.....  | 14        |
| 6.2.2 PROBES .....  | 15        |
| 6.2.3 DATA ACQUISITION ELECTRONICS (DAE).....             | 15        |
| 6.2.4 PHANTOMS.....                                       | 16        |
| 6.2.5 DEVICE HOLDER .....                                 | 17        |
| 6.2.6 SYSTEM VALIDATION DIPOLES .....                     | 17        |
| 6.2.7 TISSUE SIMULATING LIQUIDS .....                     | 18        |
| <b>7. SAR MEASUREMENT PROCEDURE .....</b>                 | <b>20</b> |
| 7.1 AREA & ZOOM SCAN PROCEDURE .....                      | 20        |
| 7.2 VOLUME SCAN PROCEDURE .....                           | 20        |
| 7.3 POWER DRIFT MONITORING .....                          | 21        |
| 7.4 SPATIAL PEAK SAR EVALUATION.....                      | 21        |
| 7.5 SAR AVERAGED METHODS .....                            | 21        |
| <b>8. SAR MEASUREMENT EVALUATION .....</b>                | <b>22</b> |
| 8.1 EUT CONFIGURATION AND SETTING .....                   | 22        |
| 8.1.1 ANTENNA LOCATION.....                               | 22        |
| 8.1.2 WIFI TEST CONFIGURATION .....                       | 23        |
| 8.2 TISSUE VERIFICATION .....                             | 24        |
| 8.3 SYSTEM VALIDATION.....                                | 25        |

|  |           |
|--|-----------|
| SYSTEM CHECK PROCEDURE.....  | 25        |
| 8.4 SYSTEM VERIFICATION.....   | 26        |
| 8.5 MAXIMUM OUTPUT POWER.....  | 27        |
| 8.5.1 MEASURED CONDUCTED POWER RESULT .....                                      | 27        |
| 8.6 SAR TESTING RESULTS.....   | 28        |
| 8.6.1 SAR TEST REDUCTION CONSIDERATIONS .....                                    | 28        |
| 8.6.2 SAR RESULTS FOR BODY EXPOSURE CONDITION (SEPARATION DISTANCE IS 5MM GAP) . | 28        |
| <b>9. MULTIPLE TRANSMITTER EVALUATION.....</b>                                   | <b>29</b> |
| <b>10. APPENDIXES .....</b>  | <b>30</b> |

**APPENDIX A – SAR PLOTS OF SYSTEM VERIFICATION****APPENDIX B – SAR PLOTS OF SAR MEASUREMENT****APPENDIX C – CALIBRATION CERTIFICATE FOR PROBE AND DIPOLE****APPENDIX D – PHOTOGRAPHS OF THE TEST SET-UP**

### HISTORY OF THIS TEST REPORT

| Report No.           | Description         | Date Issued |
|----------------------|---------------------|-------------|
| CN22NAY5(FCC SAR)001 | Original Release    | 2022-10-21  |
| CN22NAY5(FCC SAR)002 | Revise series model | 2022-10-25  |

## 1. General Information

### 1.1 Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for the EUT are as follows:

| Operating Mode | Highest Body SAR <sub>1g</sub> (W/kg) |
|----------------|---------------------------------------|
| SRD 2.4G       | 0.279                                 |

Note:

The maximum results of Specific Absorption Rate (SAR) found during testing for the EUT are as follows: This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6W/kg as averaged over any 1 gram of tissue; 10-gram SAR for Product Specific 10g SAR, limit: 4.0W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications.

## 1.2 Equipment Under Test (EUT) Information

### 1.2.1 General Information

|                     |   |
|---------------------|---|
| EUT Type            | USB WIRELESS TRANSCEIVER  |
| Brand Name          | RAZER   |
| Model Name          | RC30-0471   |
| FCC ID              | RWO-RC300471  |
| Series Model        | RC30-0471XXXX-XXXX (X can be 0-9 or A-Z)  |
| Model Difference(s) | The system model number is RZ06-0471XXXX-XXXX, this system consists of Gaming Controller (Model: RZ06-0471) and USB Wireless Transceiver (Model: RC30-0471), X can be 0-9 or A-Z. |
| Antenna Gain:       | Gain: 3.55dBi for 2.4GHz SRD  |

### 1.2.2 Wireless Technologies

|                                   |                        |
|-----------------------------------|------------------------|
| Tx Frequency Bands<br>(Unit: MHz) | Bluetooth: 2406 ~ 2474 |
| Uplink Modulations                | SRD2.4G:GFSK           |

## 1.3 Maximum Conducted Power

The maximum conducted average power (Unit: dBm) including tune-up tolerance is shown as below.

| Mode  | 2.4G SRD |
|-------|----------|
| 2Mbps | 10.5     |

## 2. Test Sites

### 2.1 Test Laboratory

Taipei Testing Laboratories

11F., No. 758, Sec. 4, Bade Rd., Songshan Dist., Taipei City 105 Taiwan (R.O.C.)

### 2.2 Test Facilities

Taipei Testing Laboratories

No. 458-18, Sec. 2, Fenliao Rd., Linkou Dist., New Taipei City 244 Taiwan (R.O.C.)

The tests at the test sites have been conducted under the supervision of a TÜV engineer.

**2.3 List of Test and Measurement Instruments**

| <i>Equipment</i>             | <i>Manufacturer</i> | <i>Model</i>  | <i>SN</i>      | <i>Cal. Date</i> | <i>Cal. Interval</i> |
|------------------------------|---------------------|---------------|----------------|------------------|----------------------|
| Data Acquisition Electronics | SPEAG               | DAE4          | 855            | Apr. 21, 2022    | 1 year               |
| E-Field Probe                | SPEAG               | EX3DV4        | 7400           | Apr. 29, 2022    | 1 year               |
| System Validation Dipole     | SPEAG               | D2450V2       | 804            | Mar. 24, 2022    | 1 year               |
| ENA                          | Agilent             | E5080A        | MY55200677     | Jan. 20, 2022    | 1 year               |
| Signal Analyzer              | R&S                 | FSV40         | 101502         | Feb. 24, 2022    | 1 year               |
| Signal Generator             | R&S                 | SMB100A03     | 181334         | Feb. 25, 2022    | 1 year               |
| Power Meter                  | Anritsu             | ML2495A       | 1901008        | Mar. 15, 2022    | 1 year               |
| Power Sensor                 | Anritsu             | MA2411B       | 1725269        | Mar. 15, 2022    | 1 year               |
| Power Sensor                 | R&S                 | SMB100A03     | 181334         | Feb. 25, 2022    | 1 year               |
| Directional coupler          | Fairview microwave  | FMCP1025-20   | A000553136-001 | N/A              | N/A                  |
| Power Amplifier Mini circuit | mini-circuits       | ZHL-42W       | SN002101809    | N/A              | N/A                  |
| Power Amplifier Mini circuit | Emci                | EMC2830P      | 980352         | N/A              | N/A                  |
| Digital Thermometer          | Testo               | 608-H1        | 45197159       | Nov. 26, 2021    | 1 year               |
| Dielectric assessment Kit    | SPEAG               | DAK-3.5       | 1292           | N/A              | N/A                  |
| Phantom                      | SPEAG               | SAM-Twin V5.0 | 1467           | N/A              | N/A                  |



### 3. Measurement Uncertainty

The component of uncertainty may generally be categorized according to the methods used to evaluate them. The evaluation of uncertainty by the statistical analysis of a series of observations is termed a Type A evaluation of uncertainty. The evaluation of uncertainty by means other than the statistical analysis of a series of observation is termed a Type B evaluation of uncertainty. Each component of uncertainty, however evaluated, is represented by an estimated standard deviation, termed standard uncertainty, which is determined by the positive square root of the estimated variance.

A Type A evaluation of standard uncertainty may be based on any valid statistical method for treating data. This includes calculating the standard deviation of the mean of a series of independent observations; using the method of least squares to fit a curve to the data in order to estimate the parameter of the curve and their standard deviations; or carrying out an analysis of variance in order to identify and quantify random effects in certain kinds of measurement.

A type B evaluation of standard uncertainty is typically based on scientific judgment using all of the relevant information available. These may include previous measurement data, experience, and knowledge of the behavior and properties of relevant materials and instruments, manufacture's specification, data provided in calibration reports and uncertainties assigned to reference data taken from handbooks. Broadly speaking, the uncertainty is either obtained from an outdoor source or obtained from an assumed distribution, such as the normal distribution, rectangular or triangular distributions indicated in table below.

| Uncertainty Distributions | Normal | Rectangular | Triangular | U-Shape |
|---------------------------|--------|-------------|------------|---------|
| Multi-plying Factor(a)    | 1/k(b) | 1/√3        | 1/√6       | 1/√2    |

- (a) standard uncertainty is determined as the product of the multiplying factor and the estimated range of variations in the measured quantity
- (b)  $\kappa$  is the coverage factor

#### Standard Uncertainty for Assumed Distribution

The combined standard uncertainty of the measurement result represents the estimated standard deviation of the result. It is obtained by combining the individual standard uncertainties of both Type A and Type B evaluation using the usual "root-sum-squares" (RSS) methods of combining standard deviations by taking the positive square root of the estimated variances.

Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. Typically, the coverage factor ranges from 2 to 3. Using a coverage factor allows the true value of a measured quantity to be specified with a defined probability within the specified uncertainty range. For purpose of this document, a coverage factor two is used, which corresponds to confidence interval of about 95 %. The DASY uncertainty Budget is shown in the following tables.

**Prüfbericht - Nr.:**      **CN22NAY5**<sub>(FCC SAR)002</sub>  
*Test Report No.*

**Seite 10 von 30**  
*Page 10 of 30*

Per KDB865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is  $< 1.5 \text{ W/kg}$ , the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. The equivalent ratio (1.5/1.6) is applied to extremity and occupational exposure conditions.

#### **4. Test Specification, Methods and Procedures**

The tests documented in this report were performed in accordance with FCC 47 CFR §2.1093, IEEE STD 1528-2013, the following FCC Published RF exposure KDB procedures & manufacturer KDB inquiries:

- KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- KDB 248227 D01 802.11 Wi-Fi SAR v02r02
- KDB 447498 D04 Interim General RF Exposure Guidance v01
- KDB 447498 D02 SAR Procedures for Dongle Xmtr v02r01
- KDB 690783 D01 SAR Listings on Grants v01r03

## 5. RF Exposure Limits

### 5.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

### 5.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

#### Limits for Occupational/Controlled Exposure (W/kg)

| Whole-Body | Partial-Body | Hands, Wrists, Feet and Ankles |
|------------|--------------|--------------------------------|
| 0.4        | 8.0          | 20.0                           |

#### Limits for General Population/Uncontrolled Exposure (W/kg)

| Whole-Body | Partial-Body | Hands, Wrists, Feet and Ankles |
|------------|--------------|--------------------------------|
| 0.08       | 1.6          | 4.0                            |

Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is average over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

## 6. SAR Measurement System

### 6.1 Definition of Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density ( $\rho$ ). The equation description is as below:

$$\text{SAR} = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)


SAR measurement can be related to the electrical field in the tissue by

$$\text{SAR} = \frac{\sigma |E|^2}{\rho}$$

Where:  $\sigma$  is the conductivity of the tissue,  $\rho$  is the mass density of the tissue and E is the RMS electrical field strength.

### 6.2 SPEAG DASY System

DASY system consists of high precision robot, probe alignment sensor, phantom, robot controller, controlled measurement server and near-field probe. The robot includes six axes that can move to the precision position of the DASY6 software defined. The DASY software can define the area that is detected by the probe. The robot is connected to controlled box. Controlled measurement server is connected to the controlled robot box. The DAE includes amplifier, signal multiplexing, AD converter, offset measurement and surface detection. It is connected to the Electro-optical coupler (ECO). The ECO performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC.


**DASY System Setup**

### 6.2.1 Robot


The DASY system uses the high precision robots from Stäubli SA (France). For the 6-axis controller system, the robot controller version (DASY6: CS8c) from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability  $\pm 0.035$  mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)



**DASY6**

### 6.2.2 Probes


The SAR measurement is conducted with the dosimetric probe. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency.


|               |  |   |
|---------------|--|---|
| Model         | EX3DV4   |  |
| Construction  | Symmetrical design with triangular core. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE). |   |
| Frequency     | 4 MHz to 10 GHz<br>Linearity: $\pm 0.2$ dB   |   |
| Directivity   | $\pm 0.3$ dB in HSL (rotation around probe axis)<br>$\pm 0.5$ dB in tissue material (rotation normal to probe axis)                                      |   |
| Dynamic Range | 10 $\mu$ W/g to 100 mW/g<br>Linearity: $\pm 0.2$ dB (noise: typically $< 1$ $\mu$ W/g)   |   |
| Dimensions    | Overall length: 337 mm (Tip: 20 mm)<br>Tip diameter: 2.5 mm (Body: 12 mm)<br>Typical distance from probe tip to dipole centers: 1 mm                     |   |

### 6.2.3 Data Acquisition Electronics (DAE)

|                      |   |   |
|----------------------|---|---|
| Model                | DAE4  |  |
| Construction         | Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop. |   |
| Measurement Range    | -100 to +300 mV (16 bit resolution and two range settings: 4mV, 400mV)  |   |
| Input Offset Voltage | $< 5$ $\mu$ V (with auto zero)  |   |
| Input Bias Current   | $< 50$ fA   |   |
| Dimensions           | 60 x 60 x 68 mm   |   |


**6.2.4 Phantoms**


|                 |   |   |
|-----------------|---|---|
| Model           | Twin SAM  |  |
| Construction    | The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEC/IEEE 62209-1528. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot. |   |
| Material        | Vinylester, glass fiber reinforced (VE-GF)  |   |
| Shell Thickness | $2 \pm 0.2$ mm ( $6 \pm 0.2$ mm at ear point)   |   |
| Dimensions      | Length: 1000 mm<br>Width: 500 mm<br>Height: adjustable feet   |   |
| Filling Volume  | approx. 25 liters   |   |

|                 |   |  |
|-----------------|---|--|
| Model           | ELI   |  |
| Construction    | Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 4 MHz to 10 GHz. ELI is fully compatible with the IEC/IEEE 62209-1528 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles. |  |
| Material        | Vinylester, glass fiber reinforced (VE-GF)  |  |
| Shell Thickness | $2.0 \pm 0.2$ mm (bottom plate)   |  |
| Dimensions      | Major axis: 600 mm<br>Minor axis: 400 mm  |  |
| Filling Volume  | approx. 30 liters   |  |




**6.2.5 Device Holder**

|              |   |   |
|--------------|---|---|
| Model        | Mounting Device   |  |
| Construction | In combination with the Twin SAM Phantom or ELI4, the Mounting Device enables the rotation of the mounted transmitter device in spherical coordinates. Rotation point is the ear opening point. Transmitter devices can be easily and accurately positioned according to IEC, IEEE, FCC or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). |   |
| Material     | POM   |   |

|              |   |  |
|--------------|---|--|
| Model        | Laptop Extensions Kit   |  |
| Construction | Simple but effective and easy-to-use extension for Mounting Device that facilitates the testing of larger devices according to IEC/IEEE 62209-1528 (e.g., laptops, cameras, etc.). It is lightweight and fits easily on the upper part of the Mounting Device in place of the phone positioner. |  |
| Material     | POM, Acrylic glass, Foam  |  |

**6.2.6 System Validation Dipoles**

|                  |  |   |
|------------------|--|---|
| Model            | D-Serial   |  |
| Construction     | Symmetrical dipole with 1/4 balun. Enables measurement of feed point impedance with NWA. Matched for use near flat phantoms filled with tissue simulating solutions. |   |
| Frequency        | 300 MHz to 10 GHz  |   |
| Return Loss      | > 20 dB  |   |
| Power Capability | > 100 W (f < 1GHz), > 40 W (f > 1GHz)  |   |

### 6.2.7 Tissue Simulating Liquids

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5% are listed.




Photo of Liquid Height for Head Position

The dielectric properties of the head tissue simulating liquids are defined in IEEE 1528, and KDB 865664 D01 Appendix A. For the body tissue simulating liquids, the dielectric properties are defined in KDB 865664 D01 Appendix A. The dielectric properties of the tissue simulating liquids were verified prior to the SAR evaluation using a dielectric assessment kit and a network analyzer.

**Targets of Tissue Simulating Liquid**

| Frequency (MHz) | Target Permittivity | Range of $\pm 5\%$ | Target Conductivity | Range of $\pm 5\%$ |
|-----------------|---------------------|--------------------|---------------------|--------------------|
| <b>For Head</b> |                     |                    |                     |                    |
| 750             | 41.9                | 39.8 ~ 44.0        | 0.89                | 0.85 ~ 0.93        |
| 835             | 41.5                | 39.4 ~ 43.6        | 0.90                | 0.86 ~ 0.95        |
| 900             | 41.5                | 39.4 ~ 43.6        | 0.97                | 0.92 ~ 1.02        |
| 1450            | 40.5                | 38.5 ~ 42.5        | 1.20                | 1.14 ~ 1.26        |
| 1640            | 40.3                | 38.3 ~ 42.3        | 1.29                | 1.23 ~ 1.35        |
| 1750            | 40.1                | 38.1 ~ 42.1        | 1.37                | 1.30 ~ 1.44        |
| 1800            | 40.0                | 38.0 ~ 42.0        | 1.40                | 1.33 ~ 1.47        |
| 1900            | 40.0                | 38.0 ~ 42.0        | 1.40                | 1.33 ~ 1.47        |
| 2000            | 40.0                | 38.0 ~ 42.0        | 1.40                | 1.33 ~ 1.47        |
| 2300            | 39.5                | 37.5 ~ 41.5        | 1.67                | 1.59 ~ 1.75        |
| 2450            | 39.2                | 37.2 ~ 41.2        | 1.80                | 1.71 ~ 1.89        |
| 2600            | 39.0                | 37.1 ~ 41.0        | 1.96                | 1.86 ~ 2.06        |
| 3500            | 37.9                | 36.0 ~ 39.8        | 2.91                | 2.76 ~ 3.06        |
| 5200            | 36.0                | 34.2 ~ 37.8        | 4.66                | 4.43 ~ 4.89        |
| 5300            | 35.9                | 34.1 ~ 37.7        | 4.76                | 4.52 ~ 5.00        |
| 5500            | 35.6                | 33.8 ~ 37.4        | 4.96                | 4.71 ~ 5.21        |
| 5600            | 35.5                | 33.7 ~ 37.3        | 5.07                | 4.82 ~ 5.32        |
| 5800            | 35.3                | 33.5 ~ 37.1        | 5.27                | 5.01 ~ 5.53        |
| 6500            | 34.5                | 32.8 ~ 36.2        | 6.07                | 6.04 ~ 6.11        |

## 7. SAR Measurement Procedure

According to the SAR test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

The SAR measurement procedures for each of test conditions are as follows:

- (a) Make EUT to transmit maximum output power
- (b) Measure conducted output power through RF cable
- (c) Place the EUT in the specific position of phantom
- (d) Perform SAR testing steps on the DASY system
- (e) Record the SAR value

### 7.1 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. According to KDB 865664 D01, the resolution for Area and Zoom scan is specified in the table below.

| Items                                 | ≤ 2GHz  | 2-3 GHz | 3-4 GHz | 4-5 GHz | 5-6 GHz |
|---------------------------------------|---------|---------|---------|---------|---------|
| Area Scan<br>( $\Delta x, \Delta y$ ) | ≤ 15mm  | ≤ 12 mm | ≤ 12 mm | ≤ 10 mm | ≤ 10 mm |
| Zoom Scan<br>( $\Delta x, \Delta y$ ) | ≤ 8 mm  | ≤ 5 mm  | ≤ 5 mm  | ≤ 4 mm  | ≤ 4 mm  |
| Zoom Scan<br>( $\Delta z$ )           | ≤ 5 mm  | ≤ 5 mm  | ≤ 4 mm  | ≤ 3 mm  | ≤ 2 mm  |
| Zoom Scan<br>Volume                   | ≥ 30 mm | ≥ 30 mm | ≥ 28 mm | ≥ 25 mm | ≥ 22 mm |

Note:

When zoom scan is required and report SAR is  $\leq 1.4$  W/kg, the zoom scan resolution of  $\Delta x / \Delta y$  (2-3 GHz):  $\leq 8$  mm, 3-4 GHz:  $\leq 7$  mm, 4-6 GHz:  $\leq 5$  mm) may be applied.

### 7.2 Volume Scan Procedure

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

### 7.3 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

### 7.4 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

### 7.5 SAR Averaged Methods





In DASY, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.

## 8. SAR Measurement Evaluation


### 8.1 EUT Configuration and Setting

Test all USB orientations [see figure below: (A) Horizontal-Up, (B) Horizontal-Down, (C) Vertical-Front, and (D) Vertical-Back and Tip] with a device-to-phantom separation distance of 5 mm.

|   |   |  |   |
|---|---|--|---|
|  |  |  |  |
| USB Orientation 1<br>(Horizontal-Up)  | USB Orientation 2<br>(Horizontal-Down)  | USB Orientation 3<br>(Vertical-Front)  | USB Orientation 4<br>(Vertical-Back)  |

**Illustration for USB Connector Orientations**


#### 8.1.1 Antenna Location



**8.1.2 WIFI TEST CONFIGURATION**

For , WLAN engineering testing software installed on the DUT can provide continuous transmitting RF signal.

For WiFi SAR testing, a communication link is set up with the test mode software for WiFi mode test. During the test, at the each test frequency channel, the EUT is operated at the RF continuous emission mode. The test procedures in KDB 248227 D01 are applied.



## 8.2 Tissue Verification

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values. The measured conductivity and relative permittivity should be within  $\pm 5\%$  of the target values.

The following materials are used for producing the tissue-equivalent materials.

### Recipes of Tissue Simulating Liquid

| Tissue Type | Oxidized mineral oil | Tween20 | HEC | NaCl | Sucrose | Triton X-100 | Water | Diethylene Glycol Mono-hexylether |
|-------------|----------------------|---------|-----|------|---------|--------------|-------|-----------------------------------|
| H750        | 44                   | -       | 0.2 | -    | 56.0    | -            | 42.1  | -                                 |
| H835        | 44                   | 48.4    | 0.2 | 1.3  | 57.0    | -            | 41.1  | -                                 |
| H900        | 44                   | 48.4    | 0.2 | 1.4  | 58.0    | -            | 40.2  | -                                 |
| H1450       | 44                   | -       | -   | 0.6  | -       | -            | 56.1  | -                                 |
| H1640       | 44                   | -       | -   | 0.5  | -       | -            | 53.7  | -                                 |
| H1750       | 44                   | 45.3    | -   | 0.4  | -       | -            | 52.6  | -                                 |
| H1800       | 44                   | 45.3    | -   | 0.5  | -       | -            | 55.2  | -                                 |
| H1900       | 44                   | 45.3    | -   | 0.2  | -       | -            | 55.3  | -                                 |
| H2000       | 44                   | 45.3    | -   | 0.1  | -       | -            | 55.4  | -                                 |
| H2300       | 44                   | -       | -   | 0.1  | -       | -            | 55.0  | -                                 |
| H2450       | 44                   | -       | -   | 0.1  | -       | -            | 54.9  | -                                 |
| H2600       | 44                   | -       | -   | 0.1  | -       | -            | 54.8  | -                                 |
| H3500       | 44                   | -       | -   | 0.2  | -       | 20.0         | 71.8  | -                                 |
| H4000       | 44                   | -       | -   | -    | -       | -            | 56.0  | -                                 |
| H5G         | 44                   | -       | -   | -    | -       | 17.2         | 65.5  | 17.2                              |
| H6G         | 44                   | -       | -   | -    | -       | -            | 56.0  | -                                 |

Salt: 99+% Pure Sodium Chloride; Sugar: 98+% Pure Sucrose; Water: De-ionized, 16M +resistivity  
 HEC: Hydroxyethyl Cellulose; Sorbitan monolaurate(Tween 20) ;Di(ethylene glycol) butyl ether, [2-(2-butoxyethoxy)ethanol] ;Triton X-100(ultra pure): Polyethylene glycol mono [4-(1,1,3,3-tetramethylbutyl)phenyl]ether.

The measuring results for tissue simulating liquid are shown as below.

| Test Date     | Tissue Type | Frequency (MHz) | Measured Conductivity ( $\sigma$ ) | Measured Permittivity ( $\epsilon_r$ ) | Target Conductivity ( $\sigma$ ) | Target Permittivity ( $\epsilon_r$ ) | Conductivity Deviation (%) | Permittivity Deviation (%) |
|---------------|-------------|-----------------|------------------------------------|--|----------------------------------|--------------------------------------|----------------------------|----------------------------|
| Oct. 20, 2022 | Head        | 2450            | 1.803                              | 40.160                                 | 1.80                             | 39.2                                 | 0.17                       | 2.45                       |

Note:


The dielectric properties of the tissue simulating liquid must be measured within 24 hours before the SAR testing and within  $\pm 5\%$  of the target values. Liquid temperature during the SAR testing must be within  $\pm 2^\circ\text{C}$ .



### 8.3 System Validation

#### System check Procedure

The system check verifies that the system operates within its specifications. It is performed daily or before every SAR measurement. The system check uses normal SAR measurements in the flat section of the phantom with a matched dipole at a specified distance. The system verification setup is shown as below.



The validation dipole is placed beneath the flat phantom with the specific spacer in place. The distance spacer is touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The spectrum analyzer measures the forward power at the location of the system check dipole connector. The signal generator is adjusted for the desired forward power (250 mW is used for 700 MHz to 3 GHz, 100 mW is used for 3.5 GHz to 6 GHz) at the dipole connector and the power meter is read at that level. After connecting the cable to the dipole, the signal generator is readjusted for the same reading at power meter.

After system check testing, the SAR result will be normalized to 1W forward input power and compared with the reference SAR value derived from validation dipole certificate report. The deviation of system check should be within 10 %.

## 8.4 System Verification

The measuring results for system check are shown as below.

| Test Date     | Frequency (MHz) | 1W Target SAR-1g (W/kg) | Measured SAR-1g (W/kg) | Normalized to 1W SAR-1g (W/kg) | Deviation (%) | Dipole S/N | Probe S/N | DAE S/N |
|---------------|-----------------|-------------------------|------------------------|--------------------------------|---------------|------------|-----------|---------|
| Oct. 20, 2022 | 2450            | 51.90                   | 12.90                  | 51.60                          | -0.58         | 804        | 7400      | 855     |

Note:

Comparing to the reference SAR value provided by SPEAG, the validation data should be within its specification of 10 %. The result indicates the system check can meet the variation criterion and the plots can be referred to Appendix A of this report.

## 8.5 Maximum Output Power

### 8.5.1 Measured Conducted Power Result

All Rate have been tested, the Worst average power (Unit: dBm) is shown as below.

#### <SRD2.4G>

##### 1. Conducted power measurements of 2.4G SRD

| Mode    | Frequency (MHz) | Average power (dBm) |
|---------|-----------------|---------------------|
|         |                 | 2Mbps               |
| SRD2.4G | 2406            | 9.68                |
|         | 2440            | 9.55                |
|         | 2474            | 9.62                |
| Tune-up |                 | 10.50               |

Note:

- 1) The Average conducted power of 2.4G SRD is measured with RMS detector.
- 2) The tested channel results are marks in bold.

## 8.6 SAR Testing Results

### 8.6.1 SAR Test Reduction Considerations

#### <KDB 447498 D01, General RF Exposure Guidance>

- 1) Per KDB447498 D04, all measurement SAR results are scaled to the maximum tune-up tolerance limit to demonstrate compliant.
- 2) Per KDB447498 D04, testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid-band or highest output power channel is:  $\leq 0.8 \text{ W/kg}$  or  $2.0 \text{ W/kg}$ , for 1-g or 10-g respectively, when the transmission band is  $\leq 100 \text{ MHz}$ . When the maximum output power variation across the required test channels is  $> \frac{1}{2} \text{ dB}$ , instead of the middle channel, the highest output power channel must be used.
- 3) Per KDB865664 D01, for each frequency band, repeated SAR measurement is required only when the measured SAR is  $\geq 0.8 \text{ W/kg}$ ; if the deviation among the repeated measurement is  $\leq 20\%$ , and the measured SAR  $< 1.45 \text{ W/kg}$ , only one repeated measurement is required.

### 8.6.2 SAR Results for Body Exposure Condition (Separation Distance is 5mm Gap)


| Plot No. | Mode    | Test Position   | Ch. | Frequency (MHz) | Data Rate | Duty Cycle (%) | Measured Conducted Power (dBm) | Max. Tune-up Power (dBm) | Tune-up Scaling Factor | Power Drift (dB) | Measured SAR-1g (W/kg) | Measured SAR-10g (W/kg) | Reported SAR-1g (W/kg) |
|----------|---------|-----------------|-----|-----------------|-----------|----------------|--------------------------------|--------------------------|------------------------|------------------|------------------------|-------------------------|------------------------|
| 1        | SRD2.4G | Horizontal up   | 4   | 2406            | 2M        | 100            | 9.68                           | 10.50                    | 1.208                  | -0.05            | 0.207                  | 0.104                   | 0.250                  |
| 2        | SRD2.4G | Horizontal Down | 4   | 2406            | 2M        | 100            | 9.68                           | 10.50                    | 1.208                  | -0.02            | 0.231                  | 0.113                   | <b>0.279</b>           |
| 3        | SRD2.4G | Vertical Front  | 4   | 2406            | 2M        | 100            | 9.68                           | 10.50                    | 1.208                  | -0.08            | 0.151                  | 0.074                   | 0.182                  |
| 4        | SRD2.4G | Vertical Back   | 4   | 2406            | 2M        | 100            | 9.68                           | 10.50                    | 1.208                  | -0.18            | 0.216                  | 0.105                   | 0.261                  |
| 5        | SRD2.4G | Tip mode        | 4   | 2406            | 2M        | 100            | 9.68                           | 10.50                    | 1.208                  | -0.02            | 0.017                  | 0.0068                  | 0.021                  |
| 6        | SRD2.4G | Horizontal Down | 38  | 2440            | 2M        | 100            | 9.55                           | 10.50                    | 1.245                  | -0.08            | 0.194                  | 0.097                   | 0.241                  |
| 7        | SRD2.4G | Horizontal Down | 72  | 2474            | 2M        | 100            | 9.62                           | 10.50                    | 1.225                  | -0.1             | 0.185                  | 0.091                   | 0.227                  |

Note: The value with boldface is the maximum SAR Value of each test band.

## 9. Multiple Transmitter Evaluation

The following tables list information which is relevant for the decision if a simultaneous transmit evaluation is necessary according to FCC KDB 447498 D04 Interim General RF Exposure Guidance v01.

The location of the antennas inside the EUT is shown as below picture



**Note:** The EUT only has one antenna and does not have synchronous transmission function.

## 10. Appendixes

Appendix A – SAR Plots of System Verification

Appendix B – SAR Plots of SAR Measurement

Appendix C – Calibration Certificate for Probe and Dipole

Appendix D – Photographs of the Test Set-Up

---END---