

Test Laboratory: BTL Inc.

Date: 2024/9/2

W05_2.4G SRD_Frequency 2402MHz_Bottom Side_0mm

DUT: Dongle;

Communication System: UID 0, SRD (0); Frequency: 2402 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 2402$ MHz; $\sigma = 1.756$ S/m; $\epsilon_r = 40.09$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.2 °C; Liquid Temperature : 22.8 °C

DASY Configuration:

- Probe: EX3DV4 - SN3809; ConvF(7.46, 7.04, 6.83) @ 2402 MHz; Calibrated: 2023/12/18
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1717; Calibrated: 2024/4/18
- Phantom: SAM Right v5.0; Type: QD000P40CC; Serial: TP:1469
- DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450)

Area Scan (13x16x1): Measurement grid: $dx=12$ mm, $dy=12$ mm
Maximum value of SAR (measured) = 0.149 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm
Reference Value = 3.895 V/m; Power Drift = -0.17 dB
Peak SAR (extrapolated) = 0.181 W/kg
SAR(1 g) = 0.083 W/kg; SAR(10 g) = 0.038 W/kg
Maximum value of SAR (measured) = 0.144 W/kg

