

# FCC Radio Test Report

## FCC ID: RWO-RZ0502470

This report concerns (check one): Original Grant Class I Change Class II Change

Project No. : 1804C081  
Equipment : 2.1Gaming Speaker  
Test Model : RZ05-02470  
Series Model : N/A  
Applicant : Razer Inc.  
Address : 201 3rd Street, Suite 900, San Francisco, CA  
94103,USA

Date of Receipt : Apr. 19, 2018  
Date of Test : May 04, 2018 ~ May 15, 2018  
Issued Date : May 30, 2018  
Tested by : BTL Inc.

Testing Engineer : Chay Cai  
(Chay Cai)

Technical Manager : Shawn Xiao  
(Shawn Xiao)

Authorized Signatory : David Mao  
(David Mao)

# B T L I N C .

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan,  
Guangdong, China.

TEL: +86-769-8318-3000 FAX: +86-769-8319-6000



### **Declaration**

**BTL** represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

**BTL's** reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

**BTL's** report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **BTL-self**, extracts from the test report shall not be reproduced except in full with **BTL's** authorized written approval.

**BTL's** laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

### **Limitation**

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

<b>Table of Contents</b>	<b>Page</b>
<b>1 . CERTIFICATION</b>	<b>7</b>
<b>2 . SUMMARY OF TEST RESULTS</b>	<b>8</b>
2.1 TEST FACILITY	9
2.2 MEASUREMENT UNCERTAINTY	9
<b>3 . GENERAL INFORMATION</b>	<b>10</b>
3.1 GENERAL DESCRIPTION OF EUT	10
3.2 DESCRIPTION OF TEST MODES	12
3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	12
3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	13
3.5 DESCRIPTION OF SUPPORT UNITS	13
<b>4 . EMC EMISSION TEST</b>	<b>14</b>
4.1 CONDUCTED EMISSION MEASUREMENT	14
4.1.1 POWER LINE CONDUCTED EMISSION LIMITS	14
4.1.2 TEST PROCEDURE	14
4.1.3 DEVIATION FROM TEST STANDARD	14
4.1.4 TEST SETUP	15
4.1.5 EUT OPERATING CONDITIONS	15
4.1.6 EUT TEST CONDITIONS	15
4.1.7 TEST RESULTS	15
4.2 RADIATED EMISSION MEASUREMENT	16
4.2.1 RADIATED EMISSION LIMITS	16
4.2.2 TEST PROCEDURE	17
4.2.3 DEVIATION FROM TEST STANDARD	17
4.2.4 TEST SETUP	18
4.2.5 EUT OPERATING CONDITIONS	19
4.2.6 EUT TEST CONDITIONS	19
4.2.7 TEST RESULTS (9KHZ TO 30MHZ)	19
4.2.8 TEST RESULTS (30MHZ TO 1000MHZ)	19
4.2.9 TEST RESULTS (ABOVE 1000MHZ)	19
<b>5 . NUMBER OF HOPPING CHANNEL</b>	<b>20</b>
5.1 APPLIED PROCEDURES	20
5.1.1 TEST PROCEDURE	20
5.1.2 DEVIATION FROM STANDARD	20
5.1.3 TEST SETUP	20
5.1.4 EUT OPERATION CONDITIONS	20
5.1.5 EUT TEST CONDITIONS	20
5.1.6 TEST RESULTS	20
<b>6 . AVERAGE TIME OF OCCUPANCY</b>	<b>21</b>

<b>Table of Contents</b>	<b>Page</b>
<b>6.1 APPLIED PROCEDURES / LIMIT</b>	<b>21</b>
6.1.1 TEST PROCEDURE	21
6.1.2 DEVIATION FROM STANDARD	21
6.1.3 TEST SETUP	21
6.1.4 EUT OPERATION CONDITIONS	22
6.1.5 EUT TEST CONDITIONS	22
6.1.6 TEST RESULTS	22
<b>7 . HOPPING CHANNEL SEPARATION MEASUREMENT</b>	<b>23</b>
7.1 APPLIED PROCEDURES / LIMIT	23
7.1.1 TEST PROCEDURE	23
7.1.2 DEVIATION FROM STANDARD	23
7.1.3 TEST SETUP	23
7.1.4 EUT TEST CONDITIONS	23
7.1.5 TEST RESULTS	23
<b>8 . BANDWIDTH TEST</b>	<b>24</b>
8.1 APPLIED PROCEDURES	24
8.1.1 TEST PROCEDURE	24
8.1.2 DEVIATION FROM STANDARD	24
8.1.3 TEST SETUP	24
8.1.4 EUT OPERATION CONDITIONS	24
8.1.5 EUT TEST CONDITIONS	24
8.1.6 TEST RESULTS	24
<b>9 . PEAK OUTPUT POWER TEST</b>	<b>25</b>
9.1 APPLIED PROCEDURES / LIMIT	25
9.1.1 TEST PROCEDURE	25
9.1.2 DEVIATION FROM STANDARD	25
9.1.3 TEST SETUP	25
9.1.4 EUT OPERATION CONDITIONS	25
9.1.5 EUT TEST CONDITIONS	25
9.1.6 TEST RESULTS	25
<b>10 . ANTENNA CONDUCTED SPURIOUS EMISSION</b>	<b>26</b>
10.1 APPLIED PROCEDURES / LIMIT	26
10.1.1 TEST PROCEDURE	26
10.1.2 DEVIATION FROM STANDARD	26
10.1.3 TEST SETUP	26
10.1.4 EUT OPERATION CONDITIONS	26
10.1.5 EUT TEST CONDITIONS	26
10.1.6 TEST RESULTS	26
<b>11 . MEASUREMENT INSTRUMENTS LIST</b>	<b>27</b>
<b>APPENDIX A - CONDUCTED EMISSION</b>	<b>29</b>

**Table of Contents****Page**

<b>APPENDIX B - RADIATED EMISSION (9KHZ-30MHZ)</b>	<b>32</b>
<b>APPENDIX C - RADIATED EMISSION (30MHZ TO 1000MHZ)</b>	<b>37</b>
<b>APPENDIX D - RADIATED EMISSION (ABOVE 1000MHZ)</b>	<b>50</b>
<b>APPENDIX E - NUMBER OF HOPPING CHANNEL</b>	<b>75</b>
<b>APPENDIX F - AVERAGE TIME OF OCCUPANCY</b>	<b>77</b>
<b>APPENDIX G - HOPPING CHANNEL SEPARATION MEASUREMENT</b>	<b>90</b>
<b>APPENDIX H - BANDWIDTH</b>	<b>95</b>
<b>APPENDIX I - PEAK OUTPUT POWER</b>	<b>100</b>
<b>APPENDIX J - ANTENNA CONDUCTED SPURIOUS EMISSION</b>	<b>105</b>

### REPORT ISSUED HISTORY

Issued No.	Description	Issued Date
BTL-FCCP-2-1804C081	Original Issue.	May 30, 2018

## 1. CERTIFICATION

Equipment : 2.1Gaming Speaker  
Brand Name : RAZER  
Test Model : RZ05-02470  
Series Model : N/A  
Applicant : Razer Inc.  
Manufacturer : Razer (Asia-Pacific) Pte.,Ltd.  
Address : 514 Chai Chee Lane #07-01 ~ 06 Singapore 469029  
Factory : RAZER TECHNOLOGY AND DEVELOPMENT (SHENZHEN) CO., LTD  
Address : East Wing, 3rd Floor, Block 2, Phase 1 of Vision Shenzhen Business Park Keji South Road, Hi-Tech Industrial Park, Shenzhen 518057, China  
Date of Test : May 04, 2018 ~ May 15, 2018  
Test Sample : Engineering Sample No.for Conducted D180503482 & Radiation D180503481  
Standard(s) : FCC Part15, Subpart C (15.247)  
ANSI C63.10-2013

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. BTL-FCCP-2-1804C081) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of NVLAP according to the ISO-17025 quality assessment standard and technical standard(s).

**Test result included in this report is only for the Bluetooth part.**

## 2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

Applied Standard(s): FCC Part15, Subpart C (15.247)			
Standard(s) Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247(d)	Antenna conducted Spurious Emission	PASS	
15.247 (a)(1)	Hopping Channel Separation	PASS	
15.247(a)(1)	Bandwidth	PASS	
15.247 (b)(1)	Peak Output Power	PASS	
15.247(d) 15.209	Radiated Spurious Emission	PASS	
15.247 (a)(1)(iii)	Number of Hopping Frequency	PASS	
15.247 (a)(1)(iii)	Dwell Time	PASS	
15.205	Restricted Bands	PASS	
15.203	Antenna Requirement	PASS	

Note:

(1) "N/A" denotes test is not applicable in this test report



## 2.1 TEST FACILITY

The test facilities used to collect the test data in this report is at the location of No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, Guangdong, China.

BTL's test firm number for FCC: 854385

BTL's designation number for FCC: CN5020

## 2.2 MEASUREMENT UNCERTAINTY

The measurement uncertainty figures shall be calculated according the methods described in the ETSI TR 100 028 and shall correspond to an expansion factor (coverage factor)  $k=1.96$  or  $k=2$ (which provide confidence levels of respectively 90% and 95.45% in the case where the distributions characterizing the actual measurement uncertainties are normal (Gaussian)). Measurement Uncertainty for a Level of Confidence of 95 %,  $U=2xUc(y)$ .

The BTL measurement uncertainty as below table:

### A. Conducted Measurement :

Test Site	Method	Measurement Frequency Range	U, (dB)
DG-C02	CISPR	150 KHz ~ 30MHz	2.32

### B. Radiated Measurement :

Test Site	Method	Measurement Frequency Range	Ant. H / V	U, (dB)
DG-CB03	CISPR	9KHz~30MHz	V	3.79
		9KHz~30MHz	H	3.57
		30MHz ~ 200MHz	V	3.82
		30MHz ~ 200MHz	H	3.78
		200MHz ~ 1,000MHz	V	4.10
		200MHz ~ 1,000MHz	H	4.06
		1GHz~18GHz	V	3.12
		1GHz~18GHz	H	3.68
		18GHz~40GHz	V	4.15
		18GHz~40GHz	H	4.14

### C. Other Measurement:

Test Item	Uncertainty
Conducted Spurious Emission	2.67dB
Hopping Channel Separation	53.46MHz
Peak Output Power	0.95dB
Number of Hopping Frequency	53.46MHz
Temperature	0.08°C
Humidity	1.5%

Note: Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

### 3. GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

Equipment	2.1Gaming Speaker	
Brand Name	RAZER	
Test Model	RZ05-02470	
Series Model	N/A	
Model Difference	N/A	
Output Power (Max.)	Operation Frequency	2402~2480 MHz
	Modulation Technology	GFSK(1Mbps) $\pi$ /4-DQPSK(2Mbps)
	Bit Rate of Transmitter	8-DPSK(3Mbps)
	Output Power Max.	3.90 dBm(1Mbps) 3.98 dBm(3Mbps)
Power Source	AC Mains.	
Power Rating	AC100-240V~ 50/60Hz 210W	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

2. Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

3 Table for Filed Antenna:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	AB15XX	PCB	N/A	2.3

### 3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX Mode <b>Note (1)</b>

The EUT system operated these modes were found to be the worst case during the pre-scanning test as following:

For Conducted Emission	
Final Test Mode	Description
Mode 1	TX Mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	TX Mode <b>Note (1)</b>

**Note:**


- (1) The measurements are performed at the high, middle, low available channels.
- (2) The measurements for Hopping Channel Separation, Bandwidth and Peak Output Power were tested during 1Mbps, 2Mbps and 3Mbps, the worst case are 1Mbps and 3Mbps, only worst case was documented.

### 3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

Test Software Version	Airoha.AB152x_verC_LabTestTool		
Frequency	2402 MHz	2441 MHz	2480 MHz
Parameters(1Mbps)	48	46	44
Parameters(3Mbps)	40	37	34

### 3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



### 3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.
A	-	-	-	-	-

Item	Shielded Type	Ferrite Core	Length	Note
1	NO	NO	2.5m	Control Cable
2	NO	NO	2.0m	AC Cable

## 4. EMC EMISSION TEST

### 4.1 CONDUCTED EMISSION MEASUREMENT

#### 4.1.1 POWER LINE CONDUCTED EMISSION LIMITS (Frequency Range 150KHz-30MHz)

Frequency of Emission (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15 -0.50	66 to 56*	56 to 46*
0.50 -5.0	56	46
5.0 -30.0	60	50

Note:

- (1) The limit of " \* " decreases with the logarithm of the frequency
- (2) The test result calculated as following:  
 Measurement Value = Reading Level + Correct Factor  
 Correct Factor = Insertion Loss + Cable Loss + Attenuator Factor(if use)  
 Margin Level = Measurement Value - Limit Value

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz


#### 4.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### 4.1.3 DEVIATION FROM TEST STANDARD

No deviation

#### 4.1.4 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
  2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

#### 4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical function (as a customer would normally use it), EUT was programmed to be in continuously transmitting/receiving data or hopping on mode.

#### 4.1.6 EUT TEST CONDITIONS

Temperature: 25°C  
 Relative Humidity: 55%  
 Test Voltage: AC 120V/60Hz

#### 4.1.7 TEST RESULTS

Please refer to the Appendix A.

Remark:

- (1) All readings are QP Mode value unless otherwise stated AVG in column of『Note』. If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform in this case, a "\*" marked in AVG Mode column of Interference Voltage Measured.
- (2) Measuring frequency range from 150KHz to 30MHz.

## 4.2 RADIATED EMISSION MEASUREMENT

### 4.2.1 RADIATED EMISSION LIMITS (Frequency Range 9KHz -1000MHz)

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

Frequency (MHz)	(dBuV/m) (at 3 meters)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).
- (4) The test result calculated as following:  
 Measurement Value = Reading Level + Correct Factor  
 Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain(if use)  
 Margin Level = Measurement Value - Limit Value



Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Spectrum Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9KHz ~90KHz for PK/AVG detector
Start ~ Stop Frequency	90KHz ~110KHz for QP detector
Start ~ Stop Frequency	110KHz ~490KHz for PK/AVG detector
Start ~ Stop Frequency	490KHz ~30MHz for QP detector
Start ~ Stop Frequency	30MHz~1000MHz for QP detector

#### 4.2.2 TEST PROCEDURE


- a. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
- b. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- c. The height of the equipment or of the substitution antenna shall be 0.8m or 1.5m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
- e. The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1GHz.
- f. The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- g. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform. (below 1GHz)
- h. All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform. (above 1GHz)
- i. For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### 4.2.3 DEVIATION FROM TEST STANDARD


No deviation

**4.2.4 TEST SETUP**


(A) Radiated Emission Test Set-Up Frequency Below 1 GHz



(B) Radiated Emission Test Set-Up Frequency Above 1 GHz



(C) For Radiated Emissions Below 30MHz



#### 4.2.5 EUT OPERATING CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

#### 4.2.6 EUT TEST CONDITIONS

Temperature: 25°C

Relative Humidity: 55%

Test Voltage: AC 120V/60Hz

#### 4.2.7 TEST RESULTS (9KHZ TO 30MHZ)

Please refer to the Appendix B

Remark:

- (1) The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.
- (2) Distance extrapolation factor =  $40 \log (\text{specific distance} / \text{test distance})$  (dB).
- (3) Limit line = specific limits (dBuV) + distance extrapolation factor.

#### 4.2.8 TEST RESULTS (30MHZ TO 1000MHZ)

Please refer to the Appendix C.

#### 4.2.9 TEST RESULTS (ABOVE 1000MHZ)

Please refer to the Appendix D.

Remark:

- (1) No limit: This is fundamental signal, the judgment is not applicable.  
For fundamental signal judgment was referred to Peak output test.

## 5. NUMBER OF HOPPING CHANNEL

### 5.1 APPLIED PROCEDURES

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Frequency Range (MHz)	Result
15.247(a)(1)(iii)	Number of Hopping Channel	2400-2483.5	PASS

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> Operating Frequency Range
RBW	100 KHz
VBW	100 KHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

#### 5.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW=100KHz, VBW=100KHz, Sweep time = Auto.

#### 5.1.2 DEVIATION FROM STANDARD

No deviation.

#### 5.1.3 TEST SETUP



#### 5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

#### 5.1.5 EUT TEST CONDITIONS

Temperature: 25°C  
 Relative Humidity: 55%  
 Test Voltage: AC 120V/60Hz

#### 5.1.6 TEST RESULTS

Please refer to the Appendix E

## 6. AVERAGE TIME OF OCCUPANCY

### 6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(1)(iii)	Average Time of Occupancy	0.4sec	2400-2483.5	PASS

#### 6.1.1 TEST PROCEDURE

- a. The transmitter output (antenna port) was connected to the spectrum analyzer
- b. Set RBW of spectrum analyzer to 1MHz and VBW to 1MHz.
- c. Use a video trigger with the trigger level set to enable triggering only on full pulses.
- d. Sweep Time is more than once pulse time.
- e. Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- f. Measure the maximum time duration of one single pulse.
- g. Set the EUT for DH5, DH3 and DH1 packet transmitting.
- h. Measure the maximum time duration of one single pulse.
  - i. DH5 Packet permit maximum  $1600 / 79 / 6 = 3.37$  hops per second in each channel (5 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times  $3.37 \times 31.6 = 106.6$  within 31.6 seconds.
  - j. DH3 Packet permit maximum  $1600 / 79 / 4 = 5.06$  hops per second in each channel (3 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times  $5.06 \times 31.6 = 160$  within 31.6 seconds.
  - k. DH1 Packet permit maximum  $1600 / 79 / 2 = 10.12$  hops per second in each channel (1 time slot TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times  $10.12 \times 31.6 = 320$  within 31.6 seconds.

#### 6.1.2 DEVIATION FROM STANDARD

No deviation.

#### 6.1.3 TEST SETUP



#### **6.1.4 EUT OPERATION CONDITIONS**

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

#### **6.1.5 EUT TEST CONDITIONS**

Temperature: 25°C

Relative Humidity: 55%

Test Voltage: AC 120V/60Hz

#### **6.1.6 TEST RESULTS**

Please refer to the Appendix F

## 7. HOPPING CHANNEL SEPARATION MEASUREMENT

### 7.1 APPLIED PROCEDURES / LIMIT

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 KHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RBW	30 KHz
VBW	100 KHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


#### 7.1.1 TEST PROCEDURE

- a. The EUT must have its hopping function enabled
- b. Span = wide enough to capture the peaks of two adjacent channels
  - Resolution (or IF) Bandwidth (RBW)  $\geq$  1% of the span
  - Video (or Average) Bandwidth (VBW)  $\geq$  RBW
  - Sweep = Auto
  - Detector function = Peak
  - Trace = Max Hold

#### 7.1.2 DEVIATION FROM STANDARD

No deviation.

#### 7.1.3 TEST SETUP



#### 7.1.4 EUT TEST CONDITIONS

Temperature: 25°C  
 Relative Humidity: 55%  
 Test Voltage: AC 120V/60Hz

#### 7.1.5 TEST RESULTS

Please refer to the Appendix G

## 8. BANDWIDTH TEST

### 8.1 APPLIED PROCEDURES

FCC Part15 (15.247) , Subpart C		
Section	Test Item	Frequency Range (MHz)
15.247(a)(2)	Bandwidth	2400-2483.5

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RBW	30 KHz (20dB Bandwidth) / 30 KHz (Channel Separation)
VBW	100 KHz (20dB Bandwidth) / 100 KHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

#### 8.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 30KHz, VBW=100KHz, Sweep Time = Auto.

#### 8.1.2 DEVIATION FROM STANDARD

No deviation.

#### 8.1.3 TEST SETUP



#### 8.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

#### 8.1.5 EUT TEST CONDITIONS

Temperature: 25°C  
 Relative Humidity: 55%  
 Test Voltage: AC 120V/60Hz

#### 8.1.6 TEST RESULTS

Please refer to the Appendix H



## 9. PEAK OUTPUT POWER TEST

### 9.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(1)	Peak Output Power	1 Watt or 30dBm ( hopping channel >75) 0.125Watt or 21dBm (hopping channel <75	2400-2483.5	PASS


#### 9.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 1MHz/3MHz, VBW= 1MHz/3MHz, Sweep time = Auto.

#### 9.1.2 DEVIATION FROM STANDARD

No deviation.

#### 9.1.3 TEST SETUP



#### 9.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

#### 9.1.5 EUT TEST CONDITIONS

Temperature: 25°C  
Relative Humidity: 55%  
Test Voltage: AC 120V/60Hz

#### 9.1.6 TEST RESULTS

Please refer to the Appendix I

## 10. ANTENNA CONDUCTED SPURIOUS EMISSION

### 10.1 APPLIED PROCEDURES / LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits.


#### 10.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 100KHz, VBW=100KHz, Sweep time = Auto.

#### 10.1.2 DEVIATION FROM STANDARD

No deviation.

#### 10.1.3 TEST SETUP



#### 10.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

#### 10.1.5 EUT TEST CONDITIONS

Temperature: 25°C

Relative Humidity: 55%

Test Voltage: AC 120V/60Hz

#### 10.1.6 TEST RESULTS

Please refer to the Appendix J

## 11. MEASUREMENT INSTRUMENTS LIST

Conducted Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	EMI Test Receiver	R&S	ESCI	100382	Mar. 11, 2019
2	LISN	EMCO	3816/2	52765	Mar. 11, 2019
3	50Ω Terminator	SHX	TF2-3G-A	8122901	Mar. 11, 2019
4	TWO-LINE V-NETWORK	R&S	ENV216	101447	Mar. 11, 2019
5	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
6	Cable	N/A	RG223	12m	Oct. 19, 2018

Radiated Emission Measurement - Below 1GHz					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Antenna	Schwarbeck	VULB9160	9160-3232	Mar. 11, 2019
2	Amplifier	HP	8447D	2944A09673	Oct. 19, 2018
3	Receiver	Agilent	N9038A	MY52130039	Aug. 20, 2018
4	Cable	emci	LMR-400(30MHz-1 GHz)(8m+5m)	N/A	Jun. 26, 2018
5	Controller	CT	SC100	N/A	N/A
6	Controller	MF	MF-7802	MF780208416	N/A
7	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
8	Antenna	EM	EM-6876-1	230	Feb. 07, 2019

Radiated Emission Measurement - Above 1GHz					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Double Ridged Guide Antenna	ETS	3115	75789	Mar. 11, 2019
2	Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170319	Jun. 08, 2018
3	Amplifier	Agilent	8449B	3008A02274	Mar. 11, 2019
4	Microwave Preamplifier With Adaptor	EMC INSTRUMENT	EMC2654045	980039 & HA01	Mar. 11, 2019
5	Receiver	Agilent	N9038A	MY52130039	Aug. 20, 2018
6	Controller	CT	SC100	N/A	N/A
7	Controller	MF	MF-7802	MF780208416	N/A
8	Cable	emci	EMC104-SM-SM-1 2000(12m)	N/A	Jun. 26, 2018
9	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A

**Number of Hopping Channel**

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP40	100185	Aug. 20, 2018

**Average Time of Occupancy**

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP40	100185	Aug. 20, 2018

**Hopping Channel Separation Measurement**

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP40	100185	Aug. 20, 2018

**Bandwidth**

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP40	100185	Aug. 20, 2018

**Peak Output Power**

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP40	100185	Aug. 20, 2018

**Antenna Conducted Spurious Emission**


Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP40	100185	Aug. 20, 2018

Remark: "N/A" denotes no model name, serial no. or calibration specified.  
 All calibration period of equipment list is one year.

## APPENDIX A - CONDUCTED EMISSION

Test Mode: TX Mode


Line



No.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	0.1545	45.36	9.82	55.18	65.75	-10.57	Peak	
2	0.1545	33.75	9.82	43.57	55.75	-12.18	AVG	
3 *	0.1725	50.58	9.82	60.40	64.84	-4.44	Peak	
4	0.1725	37.62	9.82	47.44	54.84	-7.40	AVG	
5	0.2265	42.78	9.82	52.60	62.58	-9.98	Peak	
6	0.2265	29.83	9.82	39.65	52.58	-12.93	AVG	
7	0.3030	39.04	9.82	48.86	60.16	-11.30	Peak	
8	0.3030	28.30	9.82	38.12	50.16	-12.04	AVG	
9	0.4335	32.33	9.80	42.13	57.19	-15.06	Peak	
10	0.5730	31.15	9.82	40.97	56.00	-15.03	Peak	

Test Mode: TX Mode

### Neutral




No.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	0.1770	41.79	9.91	51.70	64.63	-12.93	Peak	
2 *	0.2130	46.78	9.91	56.69	63.09	-6.40	Peak	
3	0.2130	31.06	9.91	40.97	53.09	-12.12	AVG	
4	0.2400	43.44	9.92	53.36	62.10	-8.74	Peak	
5	0.2400	30.09	9.92	40.01	52.10	-12.09	AVG	
6	0.2940	39.00	9.93	48.93	60.41	-11.48	Peak	
7	0.2940	25.42	9.93	35.35	50.41	-15.06	AVG	
8	0.5639	32.18	9.97	42.15	56.00	-13.85	Peak	
9	22.5960	25.87	11.48	37.35	60.00	-22.65	Peak	

## APPENDIX B - RADIATED EMISSION (9KHZ-30MHZ)



Test Mode: TX Mode


Ant 0°



No.	Mk.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		0.0245	34.53	19.48	54.01	119.82	-65.81	AVG	
2		0.0390	30.76	19.05	49.81	115.78	-65.97	AVG	
3	*	0.1112	27.32	17.47	44.79	106.69	-61.90	AVG	

Test Mode: TX Mode


Ant 0°



No.	Mk.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		0.1997	30.91	16.80	47.71	101.60	-53.89	AVG	
2	*	0.5128	28.64	16.45	45.09	73.40	-28.31	QP	
3		2.1440	24.53	15.47	40.00	69.54	-29.54	QP	

Test Mode: TX Mode


Ant 90°



No.	Mk.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		0.0173	36.03	19.97	56.00	122.84	-66.84	AVG	
2	*	0.0253	34.45	19.46	53.91	119.54	-65.63	AVG	
3		0.1097	21.34	17.49	38.83	106.80	-67.97	QP	

Test Mode: TX Mode

Ant 90°




No.	Mk.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		0.2162	33.20	16.75	49.95	100.91	-50.96	AVG	
2	*	0.5128	22.90	16.45	39.35	73.40	-34.05	QP	
3		2.3710	17.64	15.41	33.05	69.54	-36.49	QP	

## APPENDIX C - RADIATED EMISSION (30MHZ TO 1000MHZ)

Test Mode: TX 2402MHz \_CH00\_1Mbps


**Vertical**



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	31.9400	41.44	-15.40	26.04	40.00	-13.96	Peak	
2 *	51.3400	47.00	-15.31	31.69	40.00	-8.31	Peak	
3	67.3450	48.98	-17.45	31.53	40.00	-8.47	Peak	
4	126.0300	41.92	-14.55	27.37	43.50	-16.13	Peak	
5	149.7950	41.83	-12.19	29.64	43.50	-13.86	Peak	
6	160.4650	41.21	-11.32	29.89	43.50	-13.61	Peak	

Test Mode: TX 2402MHz \_CH00\_1Mbps


### Horizontal



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	128.4550	39.69	-14.24	25.45	43.50	-18.05	Peak	
2	148.8250	41.79	-12.25	29.54	43.50	-13.96	Peak	
3	175.9850	38.62	-12.87	25.75	43.50	-17.75	Peak	
4	257.9500	40.49	-14.41	26.08	46.00	-19.92	Peak	
5	279.7750	39.93	-12.11	27.82	46.00	-18.18	Peak	
6 *	832.6750	34.77	-2.10	32.67	46.00	-13.33	Peak	

Test Mode: TX 2441MHz \_CH39\_1Mbps

**Vertical**




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	32.9100	40.75	-15.30	25.45	40.00	-14.55	Peak	
2 *	39.7000	47.59	-15.03	32.56	40.00	-7.44	Peak	
3	48.9150	47.10	-15.26	31.84	40.00	-8.16	Peak	
4	66.3750	46.68	-17.28	29.40	40.00	-10.60	Peak	
5	147.8550	40.85	-12.30	28.55	43.50	-14.95	Peak	
6	159.0100	40.56	-11.38	29.18	43.50	-14.32	Peak	



Test Mode: TX 2441MHz \_CH39\_1Mbps

### Horizontal


80 dBuV/m



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	66.8600	34.54	-17.37	17.17	40.00	-22.83	Peak	
2	111.9650	33.71	-16.60	17.11	43.50	-26.39	Peak	
3	128.4550	39.69	-14.24	25.45	43.50	-18.05	Peak	
4 *	148.8250	41.79	-12.25	29.54	43.50	-13.96	Peak	
5	257.9500	40.49	-14.41	26.08	46.00	-19.92	Peak	
6	279.7750	38.70	-12.11	26.59	46.00	-19.41	Peak	

Test Mode: TX 2480MHz \_CH78\_1Mbps

### Vertical




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measurement dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	48.9150	46.97	-15.26	31.71	40.00	-8.29	Peak	
2	65.8900	47.03	-17.20	29.83	40.00	-10.17	Peak	
3	128.4550	41.51	-14.24	27.27	43.50	-16.23	Peak	
4	146.8850	42.41	-12.36	30.05	43.50	-13.45	Peak	
5	159.9800	41.58	-11.30	30.28	43.50	-13.22	Peak	
6	191.9900	37.53	-15.22	22.31	43.50	-21.19	Peak	

Test Mode: TX 2480MHz \_CH78\_1Mbps

### Horizontal


80 dBuV/m



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	81.4100	34.36	-19.29	15.07	40.00	-24.93	Peak	
2	128.4550	38.14	-14.24	23.90	43.50	-19.60	Peak	
3 *	151.7350	42.44	-12.03	30.41	43.50	-13.09	Peak	
4	167.2550	37.70	-11.74	25.96	43.50	-17.54	Peak	
5	257.9500	41.41	-14.41	27.00	46.00	-19.00	Peak	
6	279.7750	40.65	-12.11	28.54	46.00	-17.46	Peak	

Test Mode: TX 2402MHz \_CH00\_3Mbps


### Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	*	48.430	46.23	-15.26	30.97	40.00	-9.03	peak	
2		66.860	47.36	-17.36	30.00	40.00	-10.00	peak	
3		127.000	41.70	-14.43	27.27	43.50	-16.23	peak	
4		150.280	40.60	-12.16	28.44	43.50	-15.06	peak	
5		560.590	31.47	-6.34	25.13	46.00	-20.87	peak	
6		832.675	35.01	-2.10	32.91	46.00	-13.09	peak	

Test Mode: TX 2402MHz \_CH00\_3Mbps


### Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		51.340	30.56	-15.31	15.25	40.00	-24.75	peak	
2		129.425	38.66	-14.12	24.54	43.50	-18.96	peak	
3	*	149.795	43.51	-12.19	31.32	43.50	-12.18	peak	
4		257.950	41.14	-14.41	26.73	46.00	-19.27	peak	
5		285.595	40.31	-11.86	28.45	46.00	-17.55	peak	
6		561.560	29.71	-6.34	23.37	46.00	-22.63	peak	

Test Mode: TX 2441MHz \_CH39\_3Mbps


### Vertical



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	47.945	48.45	-15.26	33.19	40.00	-6.81	peak	
2	67.830	47.82	-17.53	30.29	40.00	-9.71	peak	
3	104.690	42.89	-17.97	24.92	43.50	-18.58	peak	
4	128.455	42.08	-14.24	27.84	43.50	-15.66	peak	
5	151.250	42.06	-12.07	29.99	43.50	-13.51	peak	
6	196.840	37.25	-15.66	21.59	43.50	-21.91	peak	

Test Mode: TX 2441MHz \_CH39\_3Mbps


**Horizontal**



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	67.345	33.08	-17.45	15.63	40.00	-24.37	peak	
2	110.510	36.05	-16.83	19.22	43.50	-24.28	peak	
3	130.880	38.76	-13.93	24.83	43.50	-18.67	peak	
4 *	150.765	42.93	-12.12	30.81	43.50	-12.69	peak	
5	279.775	39.95	-12.11	27.84	46.00	-18.16	peak	
6	832.190	35.20	-2.10	33.10	46.00	-12.90	peak	

Test Mode: TX 2480MHz \_CH78\_3Mbps

### Vertical




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	*	48.915	46.75	-15.26	31.49	40.00	-8.51	peak	
2		68.800	47.55	-17.70	29.85	40.00	-10.15	peak	
3		129.425	41.86	-14.12	27.74	43.50	-15.76	peak	
4		157.070	41.50	-11.55	29.95	43.50	-13.55	peak	
5		271.530	32.63	-13.09	19.54	46.00	-26.46	peak	
6		832.675	33.69	-2.10	31.59	46.00	-14.41	peak	



Test Mode: TX 2480MHz \_CH78\_3Mbps

### Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1		69.285	35.93	-17.78	18.15	40.00	-21.85	peak	
2		126.515	40.61	-14.49	26.12	43.50	-17.38	peak	
3	*	151.250	45.81	-12.07	33.74	43.50	-9.76	peak	
4		257.950	41.40	-14.41	26.99	46.00	-19.01	peak	
5		285.595	41.35	-11.86	29.49	46.00	-16.51	peak	
6		832.675	33.37	-2.10	31.27	46.00	-14.73	peak	

## APPENDIX D - RADIATED EMISSION (ABOVE 1000MHZ)

Test Mode : TX 2402MHz \_CH00\_1Mbps

Vertical




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2390.0000	37.58	9.00	46.58	74.00	-27.42	Peak	
2	2390.0000	29.56	9.00	38.56	54.00	-15.44	AVG	
3 *	2402.0250	86.37	9.00	95.37	54.00	41.37	AVG	No Limit
4	2402.1750	86.69	9.00	95.69	74.00	21.69	Peak	No Limit

Test Mode : TX 2402MHz \_CH00\_1Mbps

**Vertical**


80 dBuV/m



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	4804.0250	42.06	5.73	47.79	54.00	-6.21	AVG	
2	4804.2799	45.80	5.73	51.53	74.00	-22.47	Peak	

Test Mode : TX 2402MHz \_CH00\_1Mbps


Horizontal



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2390.0000	39.66	9.00	48.66	74.00	-25.34	Peak	
2	2390.0000	30.26	9.00	39.26	54.00	-14.74	AVG	
3 *	2402.0000	90.16	9.00	99.16	54.00	45.16	AVG	No Limit
4	2402.1750	90.51	9.00	99.51	74.00	25.51	Peak	No Limit

Test Mode : TX 2402MHz \_CH00\_1Mbps


### Horizontal



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	4803.9750	44.07	5.73	49.80	54.00	-4.20	AVG	
2	4804.3150	47.24	5.73	52.97	74.00	-21.03	Peak	

Test Mode : TX 2441MHz \_CH39\_1Mbps

**Vertical**




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	2441.0250	79.85	8.98	88.83	54.00	34.83	AVG	No Limit
2	2441.1750	80.23	8.98	89.21	74.00	15.21	Peak	No Limit

Test Mode : TX 2441MHz \_CH39\_1Mbps

**Vertical**

80 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	4881.6900	44.39	5.92	50.31	74.00	-23.69	Peak	
2 *	4881.9500	40.28	5.92	46.20	54.00	-7.80	AVG	



Test Mode : TX 2441MHz \_CH39\_1Mbps

**Horizontal**




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	2441.0000	90.08	8.98	99.06	54.00	45.06	AVG	No Limit
2	2441.1750	90.37	8.98	99.35	74.00	25.35	Peak	No Limit

Test Mode : TX 2441MHz \_CH39\_1Mbps

**Horizontal**


80 dBuV/m



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	4882.0550	43.96	5.92	49.88	54.00	-4.12	AVG	
2	4882.2000	46.89	5.93	52.82	74.00	-21.18	Peak	

Test Mode : TX 2480MHz \_CH78\_1Mbps


Vertical



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	2480.0000	83.38	8.97	92.35	54.00	38.35	AVG	No Limit
2	2480.1500	83.70	8.97	92.67	74.00	18.67	Peak	No Limit
3	2483.5000	40.28	8.97	49.25	74.00	-24.75	Peak	
4	2483.5000	30.45	8.97	39.42	54.00	-14.58	AVG	

Test Mode : TX 2480MHz \_CH78\_1Mbps


Vertical



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	4959.6900	43.69	6.12	49.81	74.00	-24.19	Peak	
2 *	4960.0000	39.53	6.12	45.65	54.00	-8.35	AVG	

Test Mode : TX 2480MHz \_CH78\_1Mbps


Horizontal



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	2480.0250	89.67	8.97	98.64	54.00	44.64	AVG	No Limit
2	2480.1500	89.98	8.97	98.95	74.00	24.95	Peak	No Limit
3	2483.5000	44.07	8.97	53.04	74.00	-20.96	Peak	
4	2483.5000	33.80	8.97	42.77	54.00	-11.23	AVG	

Test Mode : TX 2480MHz \_CH78\_1Mbps


**Horizontal**



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	4960.0650	40.20	6.12	46.32	54.00	-7.68	AVG	
2	4960.2350	44.94	6.12	51.06	74.00	-22.94	Peak	

Test Mode : TX 2402MHz \_CH00\_3Mbps

**Vertical**




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2390.0000	38.49	9.00	47.49	74.00	-26.51	Peak	
2	2390.0000	28.84	9.00	37.84	54.00	-16.16	AVG	
3 *	2401.9750	78.60	9.00	87.60	54.00	33.60	AVG	No Limit
4	2402.2250	80.86	9.00	89.86	74.00	15.86	Peak	No Limit

Test Mode : TX 2402MHz \_CH00\_3Mbps

**Vertical**

80 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	4804.0500	43.41	5.73	49.14	54.00	-4.86	AVG	
2	4804.3000	48.23	5.73	53.96	74.00	-20.04	Peak	



Test Mode : TX 2402MHz \_CH00\_3Mbps

### Horizontal




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2377.9250	38.50	9.01	47.51	74.00	-26.49	Peak	
2	2377.9250	29.88	9.01	38.89	54.00	-15.11	AVG	
3	2390.0000	39.24	9.00	48.24	74.00	-25.76	Peak	
4	2390.0000	29.52	9.00	38.52	54.00	-15.48	AVG	
5 *	2402.0000	88.53	9.00	97.53	54.00	43.53	AVG	No Limit
6	2402.2250	90.69	9.00	99.69	74.00	25.69	Peak	No Limit

Test Mode : TX 2402MHz \_CH00\_3Mbps

**Horizontal**


80 dBuV/m



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	4803.9850	44.71	5.73	50.44	54.00	-3.56	AVG	
2	4804.3700	49.26	5.73	54.99	74.00	-19.01	Peak	

Test Mode : TX 2441MHz \_CH39\_3Mbps


**Vertical**



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	2441.0250	79.05	8.98	88.03	54.00	34.03	AVG	No Limit
2	2441.2000	81.22	8.98	90.20	74.00	16.20	Peak	No Limit

Test Mode : TX 2441MHz \_CH39\_3Mbps


**Vertical**



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	4881.9150	39.88	5.92	45.80	54.00	-8.20	AVG	
2	4882.1100	45.21	5.93	51.14	74.00	-22.86	Peak	

Test Mode : TX 2441MHz \_CH39\_3Mbps

**Horizontal**




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	2441.0000	90.11	8.98	99.09	54.00	45.09	AVG	No Limit
2	2441.2000	92.20	8.98	101.18	74.00	27.18	Peak	No Limit

Test Mode : TX 2441MHz \_CH39\_3Mbps

Horizontal

80 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	4882.0150	44.10	5.92	50.02	54.00	-3.98	AVG	
2	4882.3150	48.53	5.93	54.46	74.00	-19.54	Peak	

Test Mode : TX 2480MHz \_CH78\_3Mbps

**Vertical**

130 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	2479.9750	82.12	8.97	91.09	54.00	37.09	AVG	No Limit
2	2480.1500	84.19	8.97	93.16	74.00	19.16	Peak	No Limit
3	2483.5000	47.91	8.97	56.88	74.00	-17.12	Peak	
4	2483.5000	36.15	8.97	45.12	54.00	-8.88	AVG	

Test Mode : TX 2480MHz \_CH78\_3Mbps

Vertical

80 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	4959.8600	44.69	6.12	50.81	74.00	-23.19	Peak	
2 *	4959.9100	39.29	6.12	45.41	54.00	-8.59	AVG	



Test Mode : TX 2480MHz \_CH78\_3Mbps

Horizontal




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	2479.9750	88.46	8.97	97.43	54.00	43.43	AVG	No Limit
2	2480.1750	90.50	8.97	99.47	74.00	25.47	Peak	No Limit
3	2483.5000	54.00	8.97	62.97	74.00	-11.03	Peak	
4	2483.5000	41.44	8.97	50.41	54.00	-3.59	AVG	

Test Mode : TX 2480MHz \_CH78\_3Mbps

### Horizontal

80 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	4959.5950	47.05	6.12	53.17	74.00	-20.83	Peak	
2 *	4960.0350	41.79	6.12	47.91	54.00	-6.09	AVG	

## APPENDIX E - NUMBER OF HOPPING CHANNEL

### Test Mode Hopping Mode\_1Mbps


Number of Hopping Channel 79



Date: 14.MAY.2018 18:06:27

### Test Mode Hopping Mode\_3Mbps

Number of Hopping Channel 79




Date: 14.MAY.2018 20:07:26

## APPENDIX F - AVERAGE TIME OF OCCUPANCY

Test Mode :	TX Mode_1Mbps
-------------	---------------


Data Packet	Frequency (MHz)	Pulse Duration (ms)	Dwell Time (s)	Limits (s)	Test Result
DH5	2402	2.9200	0.3115	0.4000	Pass
DH3	2402	1.6800	0.2688	0.4000	Pass
DH1	2402	0.4250	0.1360	0.4000	Pass
DH5	2441	2.9200	0.3115	0.4000	Pass
DH3	2441	1.6800	0.2688	0.4000	Pass
DH1	2441	0.4250	0.1360	0.4000	Pass
DH5	2480	2.9200	0.3115	0.4000	Pass
DH3	2480	1.6800	0.2688	0.4000	Pass
DH1	2480	0.4250	0.1360	0.4000	Pass

### CH00-DH1




Date: 14.MAY.2018 18:00:51

### CH00-DH3




Date: 14.MAY.2018 19:36:22

### CH00-DH5



Date: 14.MAY.2018 19:37:46


### CH39-DH1



Date: 14.MAY.2018 18:40:31




### CH39-DH3




Date: 14.MAY.2018 19:36:43

### CH39-DH5




Date: 14.MAY.2018 19:37:54

### CH78-DH1




Date: 14.MAY.2018 18:51:10

### CH78-DH3



Date: 14.MAY.2018 19:36:48

### CH78-DH5




Date: 14.MAY.2018 19:39:27

Test Mode :	TX Mode_3Mbps
-------------	---------------


Data Packet	Frequency	Pulse Duration(ms)	Dwell Time(s)	Limits(s)	Test Result
DH5	2402	2.9200	0.3115	0.4000	Pass
DH3	2402	1.6800	0.2688	0.4000	Pass
DH1	2402	0.4300	0.1376	0.4000	Pass
DH5	2441	2.9200	0.3115	0.4000	Pass
DH3	2441	1.7000	0.2720	0.4000	Pass
DH1	2441	0.4300	0.1376	0.4000	Pass
DH5	2480	2.9200	0.3115	0.4000	Pass
DH3	2480	1.6800	0.2688	0.4000	Pass
DH1	2480	0.4350	0.1392	0.4000	Pass

### CH00-DH1




Date: 14.MAY.2018 20:00:31

### CH00-DH3




Date: 14.MAY.2018 20:11:12

### CH00-DH5




Date: 14.MAY.2018 20:13:28

### CH39-DH1




Date: 14.MAY.2018 20:00:52

### CH39-DH3




Date: 14.MAY.2018 20:11:15

### CH39-DH5




Date: 14.MAY.2018 20:17:55

### CH78-DH1



Date: 14.MAY.2018 20:02:14


### CH78-DH3



Date: 14.MAY.2018 20:11:21



### CH78-DH5




Date: 14.MAY.2018 20:13:38

## APPENDIX G - HOPPING CHANNEL SEPARATION MEASUREMENT


Test Mode : Hopping on \_1Mbps

Frequency (MHz)	Channel Separation (MHz)	2/3 of 20dB Bandwidth (MHz)	Test Result
2402	0.992	0.627	Pass
2441	1.008	0.615	Pass
2480	1.000	0.612	Pass




Date: 14.MAY.2018 18:02:27

### CH39



Date: 14.MAY.2018 18:03:30


### CH78



Date: 14.MAY.2018 18:04:39


Test Mode : Hopping on \_3Mbps

Frequency (MHz)	Channel Separation (MHz)	2/3 of 20dB Bandwidth (MHz)	Test Result
2402	1.005	0.833	Pass
2441	1.013	0.845	Pass
2480	0.996	0.827	Pass




Date: 14.MAY.2018 20:03:23

### CH39



Date: 14.MAY.2018 20:04:33

### CH78




Date: 14.MAY.2018 20:05:37

## APPENDIX H - BANDWIDTH

Test Mode : TX Mode \_1Mbps


Frequency (MHz)	20dB Bandwidth (MHz)	99% Occupied BW (MHz)	Test Result
2402	0.940	0.904	Pass
2441	0.922	0.872	Pass
2480	0.918	0.880	Pass



Date: 14.MAY.2018 17:34:30




**CH39**



Date: 14.MAY.2018 17:39:11


**CH78**



Date: 14.MAY.2018 17:41:59


Test Mode : TX Mode \_3Mbps

Frequency (MHz)	20dB Bandwidth (MHz)	99% Occupied BW (MHz)	Test Result
2402	1.249	1.172	Pass
2441	1.267	1.176	Pass
2480	1.241	1.172	Pass




Date: 14.MAY.2018 19:47:54

CH39



Date: 14.MAY.2018 19:50:39

CH78




Date: 14.MAY.2018 19:57:44

## APPENDIX I - PEAK OUTPUT POWER


Test Mode : TX Mode \_1Mbps

Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Max. Limit (dBm)	Max. Limit (W)	Test Result
2402	3.84	0.0024	21.00	0.125	Pass
2441	3.90	0.0025	21.00	0.125	Pass
2480	3.83	0.0024	21.00	0.125	Pass




Date: 14.MAY.2018 17:36:32

### CH39



Date: 14.MAY.2018 17:39:42


### CH78



Date: 14.MAY.2018 17:44:09


Test Mode : TX Mode \_3Mbps

Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Max. Limit (dBm)	Max. Limit (W)	Test Result
2402	3.98	0.0025	21.00	0.125	Pass
2441	3.92	0.0025	21.00	0.125	Pass
2480	3.76	0.0024	21.00	0.125	Pass




Date: 14.MAY.2018 19:47:18

### CH39



Date: 14.MAY.2018 19:52:50

### CH78




Date: 14.MAY.2018 19:57:02




## APPENDIX J - ANTENNA CONDUCTED SPURIOUS EMISSION

### CH00 (Lower)\_1Mbps




Date: 14.MAY.2018 17:33:57

### CH78 (Upper)\_1Mbps




Date: 14.MAY.2018 17:41:18

### CH00 Hopping on mode (Lower)\_1Mbps




Date: 14.MAY.2018 18:07:01

### CH78 Hopping on mode (Upper)\_1Mbps




Date: 14.MAY.2018 18:07:34


### CH00 (10 Harmonic of the frequency) \_1Mbps



Date: 14.MAY.2018 17:34:43




Date: 14.MAY.2018 17:34:50




Date: 14.MAY.2018 17:34:56


### CH39 (10 Harmonic of the frequency) \_1Mbps



Date: 14.MAY.2018 17:38:19




Date: 14.MAY.2018 17:38:26




Date: 14.MAY.2018 17:38:33


### CH78 (10 Harmonic of the frequency) \_1Mbps



Date: 14.MAY.2018 17:42:11




Date: 14.MAY.2018 17:42:18



Date: 14.MAY.2018 17:42:25




### CH00 (Lower) \_3Mbps




Date: 14.MAY.2018 19:47:25

### CH78 (Upper) \_3Mbps




Date: 14.MAY.2018 19:57:10

### CH00 Hopping on mode (Lower)\_3Mbps




Date: 14.MAY.2018 20:08:18

### CH78 Hopping on mode (Upper)\_3Mbps




Date: 14.MAY.2018 20:08:52


### CH00 (10 Harmonic of the frequency) \_3Mbps



Date: 14.MAY.2018 19:48:07




Date: 14.MAY.2018 19:48:15




Date: 14.MAY.2018 19:48:23


### CH39 (10 Harmonic of the frequency) \_3Mbps



Date: 14.MAY.2018 19:49:59




Date: 14.MAY.2018 19:50:07




Date: 14.MAY.2018 19:50:14


### CH78 (10 Harmonic of the frequency) \_3Mbps



Date: 14.MAY.2018 19:58:03



Date: 14.MAY.2018 19:58:11



Date: 14.MAY.2018 19:58:19