



Site no. : 3m Chamber Data no. : 53  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : Notebook  
Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
Test Mode : IEEE802.11n HT20 2412MHz Tx Mode  
M/N : R209-0116




Site no. : 3m Chamber Data no. : 54  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11n HT20 2412MHz Tx Mode  
 M/N : RZ09-0116

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	4824.000	32.88	8.58	35.70	43.27	49.03	74.00	24.97	Peak
2	4824.000	32.88	8.58	35.70	30.46	36.22	54.00	17.78	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 55  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : Notebook  
Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
Test Mode : IEEE802.11n HT20 2412MHz Tx Mode  
M/N : RZ09-0116



Site no. : 3m Chamber Data no. : 56  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11n HT20 2412MHz Tx Mode  
 M/N : RZ09-0116

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	4824.000	32.88	8.58	35.70	43.12	48.88	74.00	25.12	Peak
2	4824.000	32.88	8.58	35.70	30.35	36.11	54.00	17.89	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 58  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11n HT20 2412MHz Tx Mode  
 M/N : RZ09-0116

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2412.000	28.21	5.81	35.70	94.25	92.57	74.00	-18.57	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 57  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11n HT20 2412MHz Tx Mode  
 M/N : RZ09-0116

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2412.000	28.21	5.81	35.70	92.33	90.65	74.00	-16.65	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 64  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11n HT20 2437MHz Tx Mode  
 M/N : RZ09-0116

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2437.000	28.26	5.85	35.70	95.58	93.99	74.00	-19.99	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 63  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11n HT20 2437MHz Tx Mode  
 M/N : RZ09-0116


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2437.000	28.26	5.85	35.70	91.08	89.49	74.00	-15.49	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.






Site no. : 3m Chamber Data no. : 67  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : Notebook  
Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
Test Mode : IEEE802.11n HT20 2437MHz Tx Mode  
M/N : RZ09-0116




Site no. : 3m Chamber Data no. : 68  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11n HT20 2437MHz Tx Mode  
 M/N : RZ09-0116

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4874.000	32.97	8.63	35.70	43.80	49.70	74.00	24.30	Peak
2	4874.000	32.97	8.63	35.70	31.39	37.29	54.00	16.71	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 65  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : Notebook  
Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
Test Mode : IEEE802.11n HT20 2437MHz Tx Mode  
M/N : RZ09-0116




Site no. : 3m Chamber Data no. : 66  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11n HT20 2437MHz Tx Mode  
 M/N : RZ09-0116

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4874.000	32.97	8.63	35.70	43.59	49.49	74.00	24.51	Peak
2	4874.000	32.97	8.63	35.70	31.22	37.12	54.00	16.88	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 69  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : Notebook  
Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
Test Mode : IEEE802.11n HT20 2462MHz Tx Mode  
M/N : RZ09-0116




Site no. : 3m Chamber Data no. : 70  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11n HT20 2462MHz Tx Mode  
 M/N : RZ09-0116

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	4924.000	33.06	8.69	35.70	43.67	49.72	74.00	24.28	Peak
2	4924.000	33.06	8.69	35.70	30.85	36.90	54.00	17.10	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 71  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : Notebook  
Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
Test Mode : IEEE802.11n HT20 2462MHz Tx Mode  
M/N : RZ09-0116




Site no. : 3m Chamber Data no. : 72  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11n HT20 2462MHz Tx Mode  
 M/N : RZ09-0116

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	4924.000	33.06	8.69	35.70	43.89	49.94	74.00	24.06	Peak
2	4924.000	33.06	8.69	35.70	30.99	37.04	54.00	16.96	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.






Site no. : 3m Chamber Data no. : 74  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11n HT20 2462MHz Tx Mode  
 M/N : RZ09-0116

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2462.000	28.32	5.89	35.70	96.09	94.60	74.00	-20.60	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 73  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11n HT20 2462MHz Tx Mode  
 M/N : RZ09-0116

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2462.000	28.32	5.89	35.70	91.11	89.62	74.00	-15.62	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 83  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11n HT40 2422MHz Tx Mode  
 M/N : RZ09-0116

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2422.000	28.23	5.83	35.70	90.58	88.94	74.00	-14.94	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 84  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11n HT40 2422MHz Tx Mode  
 M/N : RZ09-0116

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2422.000	28.23	5.83	35.70	85.67	84.03	74.00	-10.03	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 87  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : Notebook  
Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
Test Mode : IEEE802.11n HT40 2422MHz Tx Mode  
M/N : RZ09-0116




Site no. : 3m Chamber Data no. : 88  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11n HT40 2422MHz Tx Mode  
 M/N : RZ09-0116

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4844.000	32.92	8.60	35.70	43.95	49.77	74.00	24.23	Peak
2	4844.000	32.92	8.60	35.70	31.51	37.33	54.00	16.67	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 85  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : Notebook  
Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
Test Mode : IEEE802.11n HT40 2422MHz Tx Mode  
M/N : RZ09-0116




Site no. : 3m Chamber Data no. : 86  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11n HT40 2422MHz Tx Mode  
 M/N : RZ09-0116


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4844.000	32.92	8.60	35.70	43.82	49.64	74.00	24.36	Peak
2	4844.000	32.92	8.60	35.70	31.29	37.11	54.00	16.89	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.






Site no. : 3m Chamber Data no. : 89  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : Notebook  
Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
Test Mode : IEEE802.11n HT40 2437MHz Tx Mode  
M/N : RZ09-0116




Site no. : 3m Chamber Data no. : 90  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11n HT40 2437MHz Tx Mode  
 M/N : RZ09-0116

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4874.000	32.97	8.63	35.70	43.63	49.53	74.00	24.47	Peak
2	4874.000	32.97	8.63	35.70	31.31	37.21	54.00	16.79	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 91  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : Notebook  
Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
Test Mode : IEEE802.11n HT40 2437MHz Tx Mode  
M/N : RZ09-0116



Site no. : 3m Chamber Data no. : 92  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11n HT40 2437MHz Tx Mode  
 M/N : RZ09-0116

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4874.000	32.97	8.63	35.70	43.20	49.10	74.00	24.90	Peak
2	4874.000	32.97	8.63	35.70	31.07	36.97	54.00	17.03	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 94  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11n HT40 2437MHz Tx Mode  
 M/N : RZ09-0116

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2437.000	28.26	5.85	35.70	91.42	89.83	74.00	-15.83	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 93  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11n HT40 2437MHz Tx Mode  
 M/N : RZ09-0116

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2437.000	28.26	5.85	35.70	90.30	88.71	74.00	-14.71	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 95  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11n HT40 2452MHz Tx Mode  
 M/N : RZ09-0116

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2452.000	28.29	5.87	35.70	94.38	92.84	74.00	-18.84	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 96  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11n HT40 2452MHz Tx Mode  
 M/N : RZ09-0116


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2452.000	28.29	5.87	35.70	90.72	89.18	74.00	-15.18	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.






Site no. : 3m Chamber Data no. : 101  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : Notebook  
Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
Test Mode : IEEE802.11n HT40 2452MHz Tx Mode  
M/N : RZ09-0116




Site no. : 3m Chamber Data no. : 102  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11n HT40 2452MHz Tx Mode  
 M/N : RZ09-0116

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	4904.000	33.03	8.66	35.70	43.69	49.68	74.00	24.32	Peak
2	4904.000	33.03	8.66	35.70	31.74	37.73	54.00	16.27	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 103  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : Notebook  
Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
Test Mode : IEEE802.11n HT40 2452MHz Tx Mode  
M/N : RZ09-0116




Site no. : 3m Chamber Data no. : 104  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11n HT40 2452MHz Tx Mode  
 M/N : RZ09-0116

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	4904.000	33.03	8.66	35.70	42.68	48.67	74.00	25.33	Peak
2	4904.000	33.03	8.66	35.70	31.22	37.21	54.00	16.79	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.


**5.8G:**  
**Frequency: 1GHz~18GHz**



Site no. : 3m Chamber Data no. : 5  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11a CH149 5745MHz Tx  
 M/N : RZ09-0116

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission			Remark
						Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	
1	5745.000	34.10	9.55	35.70	78.73	86.68	74.00	-12.68	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 6  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11a CH149 5745MHz Tx  
 M/N : RZ09-0116

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5745.000	34.10	9.55	35.70	81.66	89.61	74.00	-15.61	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 7  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : Notebook  
Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
Test Mode : IEEE802.11a CH149 5745MHz Tx  
M/N : RZ09-0116




Site no. : 3m Chamber Data no. : 8  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11a CH149 5745MHz Tx  
 M/N : R209-0116


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	11490.000	38.69	13.28	35.28	43.25	59.94	74.00	14.06	Peak
2	11490.000	38.69	13.28	35.28	30.38	47.07	54.00	6.93	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.






Site no. : 3m Chamber Data no. : 9  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : Notebook  
Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
Test Mode : IEEE802.11a CH149 5745MHz Tx  
M/N : RZ09-0116




Site no. : 3m Chamber Data no. : 10  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11a CH149 5745MHz Tx  
 M/N : RZ09-0116

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	11490.000	38.69	13.28	35.28	43.65	60.34	74.00	13.66	Peak
2	11490.000	38.69	13.28	35.28	30.79	47.48	54.00	6.52	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 13  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : Notebook  
Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
Test Mode : IEEE802.11a CH157 5785MHz Tx  
M/N : RZ09-0116




Site no. : 3m Chamber Data no. : 14  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11a CH157 5785MHz Tx  
 M/N : RZ09-0116

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	11570.000	38.80	13.32	35.26	43.58	60.44	74.00	13.56	Peak
2	11570.000	38.80	13.32	35.26	30.14	47.00	54.00	7.00	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 11  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : Notebook  
Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
Test Mode : IEEE802.11a CH157 5785MHz Tx  
M/N : RZ09-0116



Site no. : 3m Chamber Data no. : 12  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11a CH157 5785MHz Tx  
 M/N : RZ09-0116

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	11570.000	38.80	13.32	35.26	43.29	60.15	74.00	13.85	Peak
2	11570.000	38.80	13.32	35.26	30.35	47.21	54.00	6.79	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 15  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11a CH157 5785MHz Tx  
 M/N : RZ09-0116

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5785.000	34.11	9.59	35.70	75.80	83.80	74.00	-9.80	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 16  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11a CH157 5785MHz Tx  
 M/N : RZ09-0116

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5785.000	34.11	9.59	35.70	79.48	87.48	74.00	-13.48	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.






Site no. : 3m Chamber Data no. : 17  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11a CH165 5825MHz Tx  
 M/N : RZ09-0116

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5825.000	34.13	9.63	35.70	76.84	84.90	74.00	-10.90	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 18  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11a CH165 5825MHz Tx  
 M/N : RZ09-0116

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5825.000	34.13	9.63	35.70	82.71	90.77	74.00	-16.77	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 25  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : Notebook  
Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
Test Mode : IEEE802.11a CH165 5825MHz Tx  
M/N : RZ09-0116




Site no. : 3m Chamber Data no. : 26  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11a CH165 5825MHz Tx  
 M/N : RZ09-0116

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	11650.000	38.91	13.37	35.25	43.17	60.20	74.00	13.80	Peak
2	11650.000	38.91	13.37	35.25	30.08	47.11	54.00	6.89	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 23  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : Notebook  
Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
Test Mode : IEEE802.11a CH165 5825MHz Tx  
M/N : RZ09-0116




Site no. : 3m Chamber Data no. : 24  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11a CH165 5825MHz Tx  
 M/N : RZ09-0116

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	11650.000	38.91	13.37	35.25	43.58	60.61	74.00	13.39	Peak
2	11650.000	38.91	13.37	35.25	30.94	47.97	54.00	6.03	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 27  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : Notebook  
Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
Test Mode : IEEE802.11nHT20 CH165 5825MHz Tx  
M/N : RZ09-0116




Site no. : 3m Chamber Data no. : 28  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT20 CH165 5825MHz Tx  
 M/N : RZ09-0116


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	11650.000	38.91	13.37	35.25	43.58	60.61	74.00	13.39	Peak
2	11650.000	38.91	13.37	35.25	30.21	47.24	54.00	6.76	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.






Site no. : 3m Chamber Data no. : 29  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : Notebook  
Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
Test Mode : IEEE802.11nHT20 CH165 5825MHz Tx  
M/N : RZ09-0116



Site no. : 3m Chamber Data no. : 30  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT20 CH165 5825MHz Tx  
 M/N : RZ09-0116

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	11650.000	38.91	13.37	35.25	43.75	60.78	74.00	13.22	Peak
2	11650.000	38.91	13.37	35.25	30.27	47.30	54.00	6.70	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 32  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Notebook  
 Power Rating : DC 19V From Adapter Input AC 120V/60Hz  
 Test Mode : IEEE802.11nHT20 CH165 5825MHz Tx  
 M/N : RZ09-0116

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5825.000	34.13	9.63	35.70	76.99	85.05	74.00	-11.05	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.