

SGS-CSTC Standards Technical Services Co., Ltd. **Guangzhou Branch**

EMC-TRF-03 Rev 1.0 Report No.: GZCR211102143603R1 Page: 1 of 12 FCC ID: RWO-RZ430407

1 **Cover Page**

RF Exposure Report

Application No.:	GZCR2111021436AT					
Applicant:	Razer Inc					
Address of Applicant:	9 Pasteur, Suite 100, Irvine, CA92618, USA					
Manufacturer:	Razer (Asia-Pacific) Pte Ltd					
Address of Manufacturer:	Razer SEA HQ, 1 one-north Crescent, #02-01, Singapore 138538					
Factory:	Razer Technology and Development (Shenzhen) Co., Ltd					
Address of Factory:	East Wing, 3rd Floor, Block 2, Phase 1 of Vision Shenzhen Business Park,					
	Keji South Road, Hi-Tech Industrial Park, Shenzhen 518057, China					
Equipment Under Test (EU	Г):					
EUT Name:	SMART LAMP					
Model No.:	RZ43-0407, RZ43-0407XXXX-XXXX (X can be 0-9 or A-Z)					
*	Please refer to section 2 of this report which indicates which model was					
	actually tested and which were electrically identical.					
Trade Mark:	RAZER					
Standard(s) :	FCC Rules 47 CFR §2.1091					
Standard(S)	KDB 447498 D04 interim General RF Exposure Guidance v01					
Date of Receipt:	2021-12-29					
Date of Test:	2022-01-02 to 2022-01-12					
Date of Issue:	2023-08-16					
Test Result:	Pass*					

* In the configuration tested, the EUT complied with the standards specified above.

This report supersedes our previous report GZCR211102143603, issued on 2022-07-04, which is hereby deemed null and void

Zidey Lin

Ricky Liu Manager



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exconreate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is entervention of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, e: (86-755) 8307 1443 Co.,Ltd. [Na 98 Kazha Raad, Salented Park, Garagzhou Economic & Technology Development District, Guangzhou, China 510663 t (86–20) 82155555 f (86–20) 82075058 www.sgsgroup.com.cn 中国·广州·经济技术开发区科学城科珠路198号

邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sgs.china@sgs.com



Report No.: GZCR211102143603R1 Page: 2 of 12

EMC-TRF-03 Rev 1.0

	Revision Record							
Version	Chapter	Date	Modifier	Remark				
01		2022-07-04		Original				
02		2023-08-16		Updated the data				

Authorized for issue by:		
	CJ Vu	
	Curry Wu/Project Engineer	-
	Ridey Lin	
	Ricky Liu/Reviewer	





Report No.: GZCR211102143603R1 Page: 3 of 12

EMC-TRF-03 Rev 1.0

2 Contents

			Page
1	COV	ER PAGE	1
2	CON	ITENTS	3
3	GEN	IERAL INFORMATION	4
	3.1	GENERAL DESCRIPTION OF E.U.T.	4
	3.2	DETAILS OF E.U.T.	4
	3.3	SEPARATION DISTANCE	6
	3.4	TEST LOCATION	7
	3.5	TEST FACILITY	7
4	FCC	RADIOFREQUENCY RADIATION EXPOSURE LIMITS	8
	4.1	BLANKET 1 MW BLANKET EXEMPTION	8
	4.2	MPE-BASED EXEMPTION	8
	4.3	SAR-BASED EXEMPTION	9
5	MEA	SUREMENT AND CALCULATION	12
	5.1	MAXIMUM TRANSMIT POWER	12
	5.2	RF EXPOSURE CALCULATION	12



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Cilent's instructions, if any. The Company's sole responsibility is to its Cilent and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) lessed and such sample(s) are relatined for 30 days only. Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: (SNDpoccheck@ess.com)

Co.,Ltd Mo.199 Kezhu Rad, Scientech Park, Guargebou Economic & Technology Development District, Guargebou, China 510663 t (86-20) 82155555 f (86-20) 82075058 www.sgs.group.com.cn oratory. 中国・广州・经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sgs.cchina@sgs.com



Report No.: GZCR211102143603R1 Page: 4 of 12

EMC-TRF-03 Rev 1.0

3 General Information

3.1 General Description of E.U.T.

	Portable device
Product Type:	⊠ Mobile device
	Fixed device

3.2 Details of E.U.T.

Power Supply:	AC Adapter:
	Model: A122-0502000ID
	Input: 100-240V 50/60Hz 0.4A
	Output: 5V 2A 10W
Cable(s):	DC cable 146cm unshielded
For BLE:	
Operation Frequency:	2402MHz to 2480MHz
Bluetooth Version:	V4.2 LE
Modulation Type:	GFSK
Data Rate:	1M/bit
Number of Channels:	40
Channel Spacing:	2MHz
Antenna Type:	FPC Antenna
Antenna Gain:	2.24dBi declared by applicant
For 2.4G:	
Operation Frequency:	802.11b/g/n(HT20): 2412MHz to 2462MHz;802.11n(HT40):
Operation requency.	2422MHz to 2452MHz
Modulation Type:	802.11b: DSSS (CCK, DQPSK, DBPSK);802.11g/n: OFDM
would for Type.	(64QAM, 16QAM, QPSK, BPSK)
Number of Channels:	802.11b/g/n(HT20):11;802.11n(HT40):7
Channel Spacing:	5MHz
Antenna Type:	FPC Antenna
Antenna Gain:	2.24dBi declared by applicant



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-enDocument.aspx. Attention is sues defined therein. Any holder of this document is a cleared to the limitation of lability, indemnification and jurisdiction issues defined therein. Any holder of this document is a cleared to the content or the accession of the company is the supervise of the content or transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing illingercling reports. Scotting of the document is unlawed and feedores may be prosecuted to the fullest centent of the authenticity of testing inspection reports & certificate, please contact us at telephone: (86-755) 8307 1443, or enail: CN_Doccheck@ssgs.com. No document is informed hereing inspection contact as telephone: (86-755) 8307 1443, No Method Steetbard and Steetbard Stee

No.198 Kabu Read, Skentech Park, Gaangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075058 www.sgsgroup.com.cn 中国・广州・经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sgs.china@sgs.com



Report No.: GZCR211102143603R1 Page: 5 of 12

EMC-TRF-03 Rev 1.0

Declaration of EUT Family Grouping:

Model No.: RZ43-0407, RZ43-0407XXXX-XXXX (X can be 0-9 or A-Z)

Only the model RZ43-0407 was tested, since according to the declaration from the applicant, the electrical circuit design, PCB layout, components used and internal wiring and functions were identical for the above models, with only difference on model name and /or product customization including and not limited to color and printed design.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Cilent's instructions, if any. The Company's sole responsibility is to its Cilent and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing imsection report actificate, please contact us at telephone: (86-755) 8307 1443,

Win Wink and Statest Park, Gargabu Economic & Technology Development District, Guargabu, China 5,100,663 t (86-20) 82155555 f (86-20) 82075058 www.sgsgroup.com.cn 中国・广州・经济技术开发区科学域科珠路198号 邮编: 5,10663 t (86-20) 82155555 f (86-20) 82075058 sgs.china@sgs.com



Report No.: GZCR211102143603R1 Page: 6 of 12

EMC-TRF-03 Rev 1.0

3.3 Separation Distance

Minimum test separation distance:	20cm					
Remark: This minimum test separation distance is determined by the smallest distance from the antenna and						
radiating structures or outer surface of the device, according to the host form factor, exposure conditions and						
platform requirements, to any part of the	body or extremity of a user or bystander.					



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-end-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without streport refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing (inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

of emint: Crit Occ Precederation Control (1997) Territory (1997) Territo



Report No.: GZCR211102143603R1 Page: 7 of 12

EMC-TRF-03 Rev 1.0

3.4 Test Location

All tests were performed at: SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou Branch EMC Laboratory, 198 Kezhu Road, Scientech Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663 Tel: +86 20 82155555 Fax: +86 20 82075059 No tests were sub-contracted.

3.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• A2LA (Certificate No. 6606.01)

Compliance Certification Services (Kunshan) Inc. Shenzhen branch is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 6606.01.

• FCC – Designation Number: CN1322

Compliance Certification Services (Kunshan) Inc. Shenzhen branch has been recognized as an accredited testing laboratory.

Designation Number: CN1322. Test Firm Registration Number: 718073

• Innovation, Science and Economic Development Canada

Compliance Certification Services (Kunshan) Inc. Shenzhen branch has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0129.

IC#: 28189.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document to Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are relained for 30 days only. Attention: To check the authenticity of testing /inspection report & contificate, please contact us at telephone: (86-75) 8307 1443,

1.1. Mr.188 karuh Road, Sainteich Park, Guargabu Exonomic & Technology Development District, Guargabou Exonomic & Technology Development District, Gua



Report No.: GZCR211102143603R1 Page: 8 of 12

EMC-TRF-03 Rev 1.0

4 FCC Radiofrequency radiation exposure limits

Test exemptions apply for devices used in general population/uncontrolled exposure environments, according to the SAR-based, or MPE-based exemption thresholds.

4.1 Blanket 1 mW Blanket Exemption

The 1 mW Blanket Exemption of §1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

The 1-mW blanket exemption applies at separation distances less than 0.5 cm, including where there is no separation. This exemption shall not be used in conjunction with other exemption criteria other than those for multiple RF sources in paragraph §1.1307(b)(3)(ii)(A).

The 1-mW exemption is independent of service type and covers the full range of 100 kHz to 100 GHz, but it shall not be used in conjunction with other exemption criteria or in devices with higher-power transmitters operating in the same time-averaging period. Exposure from such higher-power transmitters would invalidate the underlying assumption that exposure from the lower-power transmitter is the only contributor to SAR in the relevant volume of tissue.

4.2 MPE-based Exemption

General frequency and separation-distance dependent MPE-based effective radiated power (ERP) thresholds are in Table B.1 [Table 1 of §1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

RF Source Frequency			Minimum Distance			Threshold ERP	
<i>f</i> ∟ MHz		<i>f</i> ⊦ MHz	λ _∟ / 2π		λ _Η / 2π	W	
0.3	—	1.34	159 m	—	35.6 m	1,920 R ²	
1.34	-	30	35.6 m	-	1.6 m	3,450 R²/f ²	
30	-	300	1.6 m	-	159 mm	3.83 R ²	
300	-	1,500	159 mm	-	31.8 mm	0.0128 R ² f	
1,500	-	100,000	31.8 mm	-	0.5 mm	19.2R ²	
Subscripts L and H are low and high; λ is wavelength.							
From §1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.							

The table applies to any RF source (i.e. single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits. These criteria apply at separation distances from any part of the radiating structure of at least $\lambda/2\pi$. The thresholds are



1.4.1% 198 kamu Rad, Saintel Park, Guargabu Exonomic & Technology Development District, Guargabou, China 510663 t (86-20) 82155555 f (86-20) 82075058 www.sgsgroup.com.cn 、 中国・广州・经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sgs.china@sgs.com



EMC-TRF-03 Rev 1.0

Report No.: GZCR211102143603R1 Page: 9 of 12

based on the general population MPE limits with a single perfect reflection, outside of the reactive nearfield, and in the main beam of the radiator.

For mobile devices that are not exempt per Table B.1 [Table 1 of \$1.1307(b)(1)(i)(C)] at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in \$1.1310 is necessary if the ERP of the device is greater than *ERP*_{20cm} in Formula (B.1) [repeated from \$2.1091(c)(1); also in \$1.1307(b)(1)(i)(B)].

 $P_{\rm th} (\rm mW) = ERP_{20 \rm \ cm} (\rm mW) = \begin{cases} 2040f & 0.3 \rm \ GHz \le f < 1.5 \rm \ GHz \\ 3060 & 1.5 \rm \ GHz \le f \le 6 \rm \ GHz \end{cases}$ (B.1)

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole.

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

Limit calculation							
Frequency range	Frequency(MHz)	R(λ/2π)(m)	Threshold ERP(W)				
300~1500MHz	915	0.0522	0.032				
1500~100000MHz	2480	0.0193	0.007				

4.3 SAR-based Exemption

SAR-based thresholds are derived based on frequency, power, and separation distance of the RF source. The formula defines the thresholds in general for either available maximum time-averaged power or maximum time-averaged ERP, whichever is greater.

If the ERP of a device is not easily determined, such as for a portable device with a small form factor, the applicant may use the available maximum time-averaged power exclusively if the device antenna or radiating structure does not exceed an electrical length of $\lambda/4$.

As for devices with antennas of length greater than $\lambda/4$ where the gain is not well defined, but always less than that of a half-wave dipole (length $\lambda/2$), the available maximum time-averaged power generated by the device may be used in place of the maximum time-averaged ERP, where that value is not known.

The separation distance is the smallest distance from any part of the antenna or radiating structure for all persons, during operation at the applicable ERP. In the case of mobile or portable devices, the separation distance is from the outer housing of the device where it is closest to the antenna.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is content of the Content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) test and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN_Doccheck@ags.com

. No.196 Azzul Ada, Scentech Par, Glangzou Ezonomic & lectrology Deletopment Listic, Guargznou, China 510663 f (86-20) 821/55555 f (86-20) 820/5068 sgs.china@sgs.com



EMC-TRF-03 Rev 1.0

Report No.: GZCR211102143603R1 Page: 10 of 12

The SAR-based exemption formula of \$1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW). This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula (B.2).

$$P_{\rm th} \,({\rm mW}) = \begin{cases} ERP_{20\,\,{\rm cm}} (d/20\,\,{\rm cm})^x & d \le 20\,\,{\rm cm} \\ \\ ERP_{20\,\,{\rm cm}} & 20\,\,{\rm cm} < d \le 40\,\,{\rm cm} \end{cases}$$
(B.2)

where

$$x = -\log_{10}\left(\frac{60}{ERP_{20}\,\mathrm{cm}\sqrt{f}}\right)$$

and *f* is in GHz, d is the separation distance (cm), and *ERP*_{20cm} is per Formula (B.1).



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-enD-Countert.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Cilent's instructions, if any. The Company's sole responsibility is to its Cilent and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document end on the reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing /inspection report & contificate, please contact us at telephone: (86-755) 8307 1443, Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, Attention: At testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, Attention: At there and there authenticity of testing /inspection report & cer



Report No.: GZCR211102143603R1 Page: 11 of 12

EMC-TRF-03 Rev 1.0

Example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)										
Frequency					Distand	ce(mm)				
(MHz)	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

Limit calculation							
Frequency range(GHz)	Frequency(GHz)	Х	Distance(cm)	Pth (mW)			
0.3~1.5	0.915	1.474	0.5	8.133			
1.5~6	2.48	1.905	0.5	2.717			



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without report report refer only to the sample(s) tested and such asample(s) tested and such asample(s) are related for 30 days only. Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@ags.com

Co.,Lid M. 188 Karbu Rad, Salentah Park, Guargabou Ecronomic & Technology Development District, Guargabou, China 510663 t (86-20) 82155555 f (86-20) 82075058 www.sgsgroup.com.cn oratory. 中国・广州・经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sgs.china@sgs.com



Report No.: GZCR211102143603R1 Page: 12 of 12

EMC-TRF-03 Rev 1.0

5 Measurement and Calculation

5.1 Maximum transmit power

BLE:

Test Mode	Test Channel	EIRP [dBm]	EIRP (mW)
BLE	2480	8.22	6.64

2.4G WIFI:

Test Mode	Test Channel	EIRP [dBm]	EIRP (mW)
WIFI	2462	23.78	238.78

The Power Data is based on the RF Test report GZCR211102143601R1 & GZCR211102143602R1

5.2 RF Exposure Calculation

The Max. Power is 238.78mW. The best case gain of the antenna is 2.24dBi.

Remark: we used the maximum power between the conducted power and ERP/EIRP to perform RF exposure exemption evaluation.

	Evaluation method	Exempt Limit(mW)	Verdict
	Blanket 1 mW Blanket Exemption	1mW	N/A
	MPE-based Exemption(ERP)	7mW(ERP)	N/A
\boxtimes	SAR-based Exemption(Pth)	3060mW	Yes

So, the device is to qualify for SAR test exemption, the exemption report is in lieu of the SAR report.

--End of the Report--



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's object responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this lest report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing linspection report & contificate, please contact us at telephone: (86-755) 8307 1443,

ul Mo.18Ketzumet Red Docenter Cuz295555 ft (86-20) 82075058 www.sgsgroup.com.cn Mo.18Ketzumet Red Solenich Park, Gaugzbu Economic & Technology Development District, Guargzbu, China 510663 tt (86-20) 82155555 ft (86-20) 82075058 www.sgsgroup.com.cn 中国・广州・经济技术开发区科学域科珠路198号 邮编: 510663 tt (86-20) 82155555 ft (86-20) 82075058 sgs.china@sgs.com