

Certification of Compliance

CFR 47 Part 15 Subpart B

Test Report File No. : 04-IST-0162 **Date of Issue** : April 11, 2004
Model : LS1500
Kind of Product : LCD Monitor
Applicant : Orion Technology Co., Ltd.
Address : 1242, In-Ri, Apo-Eup, Gimcheon-Si, Kyungbuk, 740-862,
Korea
Manufacturer : Orion Technology Co., Ltd.
Address : 1242, In-Ri, Apo-Eup, Gimcheon-Si, Kyungbuk, 740-862,
Korea

Test Result

Positive

Negative

Reviewed By



S. J. Cho / EMC Group Manager

Approved By



Joon H. Lee / Chief

Comment (s)

- Investigations requested : Measurement to the relevant clauses of FCC rules and regulations Part 15 Subpart B - Unintentional Radiators, Class B.
- The test report with appendix consists of 17 pages.
- The test result only responds to the tested sample.
- It is not allowed to copy this report even partly without the allowance of IST EMC Laboratory.
- This equipment as for has been shown to be capable of continued compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4 2003.



TABLE OF CONTENTS

Table of contents			2
Information of test laboratory, Environmental conditions, Power used, Product information			3
Descriptions of test			
Conducted Emission			4
Radiated Emission			5
Equipment Under Test			6
Summary			7
■ Test Conditions and Data - Emissions			
◆ Conducted Emissions	0.15MHz - 30MHz	Applicable	
Test Conditions / Data and Plots			8-10
◆ Radiated Emissions	30MHz - 1GHz	Applicable	
Test Conditions / Data and Plots			11-12
Appendix	A. The Photos of Test Setup		13-14
	B. The Photos of Equipment Under Test		15-17

Note:

INFORMATIONS OF TEST LABORATORY

EMC LABORATORY of IST Co., Ltd. (*FCC Filing Lab.*)
San 21-8, Goan-Ri, Baekam-Myun, Yongin-City
Kyonggi-Do, 449-860, Korea
TEL : +82 31 333 4093 FAX : +82 31 333 4094

ENVIRONMENTAL CONDITIONS

Temperature 17.2 °C
Humidity 48 %
Atmospheric pressure 1012 mbar

POWER SUPPLY SYSTEM USED

Power supply system AC 120Vac, 60Hz
(Refer to the product information)

PRODUCT INFORMATION

LCD Type : Panel Model - LTM150XH-L06 (SAMSUNG)
 15-inch diagonal AM-TFT (Active Matrix)
 Pixel pitch - 0.297(H) x 0.297(V) mm
 Contrast ratio - 400:1 (Typical)
 Brightness - 430cd/m² (Typical)
 Response Time: 25msec (Typical)

Resolution : 1024 x 768, 75Hz (max.)

Synchronization : Horizontal - 30~62 KHz, Vertical - 56~75 KHz

Input Signal : Sync - separate TTL Level
 Video - Analog 0.7 Vp-p / 75 ohm
 S-Video, AV (Composite, Sound L/R)
 PC Stereo Sound

Power Source : 100~240Vac, 50/60Hz (auto switching)

Dimensions(W x H x D) : 429.5 x 355.6 x 160 mm

Weight-net / gross : 4.2 kg / 5.5 kg

Electrical Ratings : AC/DC Adaptor (DTA-XGA03, Display Technology Co.,ltd.)
 Input - 100-240Vac, 50/60Hz, 0.8A
 Output - 12Vdc, 3A

- EMC suppression device is not used during the test.
- Please refer to user's manual.


DESCRIPTIONS OF TEST

Conducted Emissions:

The measurement were performed over the frequency range of 0.15MHz to 30MHz using a 50Ω/50uH LISN as the input transducer to a Spectrum Analyzer or a Field Intensity Meter. The measurements were made with the detector set for "Peak" amplitude within a bandwidth of 10KHz or for "quasi-peak" & "Average" within a bandwidth of 9KHz.

-Procedure of Test

The line-conducted facility is located inside a shielded room No.1. A 1m X 1.5m wooden table 80cm height is placed 40cm away from the vertical wall and 1.5m away from the other wall of the shielded room. The R/S ESH3-Z5 and EMCO 3825/2 LISN are bonded to bottom of the shielded room. The EUT is located on the wooden table with distance more than 80cm from the LISN and powered from the EMCO LISN .The peripheral equipment is powered from the other LISN. Power to the LISNs are filtered by a noise cut power line filters. All electrical cables are shielded by braided tinned steel tubing with inner ϕ 1.2cm. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply lines will be connected to the EMCO LISN. All interconnecting cables more than 1m were shortened by non-inductive bundling to a 1m length. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating conditions. The RF output of the LISN was connected to the R/S receiver to determine the frequency producing the maximum emission from the EUT. The frequency producing the maximum level was reexamined using Quasi-Peak mode by manual measurement, after scanned by automatic Peak mode for frequency range from 0.15 to 30MHz. The bandwidth of the receiver was set to 10kHz. The EUT, peripheral equipment, and interconnecting cables were arranged and manipulated to maximize each EME emission.




DESCRIPTION OF TEST

Radiated Emissions:

The measurement was performed over the frequency range of 30MHz to 1GHz using antenna as the input transducer to a Spectrum analyzer or a Field Intensity Meter. The measurement was made with the detector set for "quasi-peak" within a bandwidth of 120KHz.

-Procedure of Test

Preliminary measurements were made at 3 meter using bi-conical and log-periodic antennas, and spectrum analyzer to determine the frequency producing the max. emission in anechoic chamber. Appropriate precaution was taken to ensure that all emission from the EUT were maximized and investigated. The system configuration, mode of operation, turn-table azimuth and height with respect to the antenna were noted for each frequency found. The spectrum was scanned from 30MHz to 300MHz using S/B bi-conical antenna and 300 to 1000MHz using S/B log-periodic antenna. Above 1GHz, linearly polarized double ridge horn antennas were used. Final measurements were made at open site with 3-meters test distance using S/B bi-log antenna or horn antenna. The OATS have been verified in regular for its normalized site attenuation. The test equipment was placed on a wooden table. Sufficient time for the EUT, peripheral equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. Each frequency found during pre-scan measurements was re-examined by manual. The detector function was set to CISPR quasi-peak mode and the bandwidth of the receiver was set to 120kHz or 1MHz depending on the frequency of type of signal. The EUT, peripheral equipment and interconnecting cables were re-configured to the set-up producing the max. emission for the frequency and were placed on top of a 0.8-meter high nonmetallic 1 x 1.5 meter table. The EUT, peripheral equipment, and interconnecting cables were re-arranged and manipulated to maximize each emission. The turntable containing the system was rotated; the antenna height was varied 1 to 4 meters and stopped at the azimuth or height producing the maximum emission. Each emission was maximized by: varying the mode of operation to the EUT and/or peripheral equipment and changing the polarity of the antenna, whichever determined the worst-case emission.



SUMMARY

Emissions

■ Conducted Emission

The requirements are MET Not MET
Minimum limit margin 7.5 dB at 0.150 MHz
Maximum limit exceeding

Remarks : Limits are kept with more 3dB margin.

Find the test data in following pages 9 to 10.

■ Radiated Emission

The requirements are MET Not MET
Minimum limit margin 3.6 dB at 240.2 MHz
Maximum limit exceeding

Remarks : Limits are kept with more 3dB margin.

Test Mode at 1024x768, 75Hz.

Find the test data in following page 12.

test Date

Begin of testing : April 06, 2005.

End of testing : April 09, 2005.

Note :

- means the test is applicable,
- is not applicable.

Prepared By



S.J. Oh / Research Engineer

TEST CONDITIONS AND DATA

Conducted Emissions

[Applicable]

◆ Test Equipment Used

Model Name	Description	Manufacture	Calibration Date	Serial Number
ESH 3	Test Receiver	Rohde & Schwarz	Jul. 15, 2004	861742/018
3725/2	LISN	EMCO	Jul. 15, 2004	9101-2068
KNW-407	LISN	Hyup-Rip	Jul. 15, 2004	8-883-10
ESH 3-Z2	Pulse Limiter	Rohde & Schwarz	Jul. 15, 2004	357.8810.52

◆ Test Accessories Used

Type	Manufacturer
Aneroid Barometer	Sato
Hygrometer	Sato


◆ Test Program Scrolling "H" Characters Mode

◆ Test Date April 07, 2004

◆ Test Area Shielded room No.1

Note : *The equipment used is calibrated in regular for every year.*


Conducted Emissions



Freq. [MHz]	Measurement [dB µV]		Limit [dB µV]		Insertion Loss [dB]	Cable Loss [dB µV]	Result [dB µV]		Margin [dB]	
	Q-peak	Average	Q-peak	Average			Q-peak	Average	Q-peak	Average
0.150	57.8	34.4	66.0	56.0	0.2	0.5	58.5	35.1	7.5	20.9
0.194	51.2	24.1	63.9	53.9	0.2	0.5	51.9	24.8	12.0	29.1
2.331	36.2	27.0	56.0	46.0	0.1	0.5	36.8	27.6	19.2	18.4
3.555	34.6	27.1	56.0	46.0	0.1	0.4	35.2	27.7	20.8	18.3
5.582	33.9	26.6	60.0	50.0	0.1	0.5	34.5	27.2	25.5	22.8
10.213	32.6	25.1	60.0	50.0	0.1	0.6	33.3	25.8	26.7	24.2

Note :

Conducted Emissions



Freq. [MHz]	Measurement [dB μV]		Limit [dB μV]		Insertion Loss [dB]	Cable Loss [dB μV]	Result [dB μV]		Margin [dB]	
	Q-peak	Average	Q-peak	Average			Q-peak	Average	Q-peak	Average
0.151	54.1	32.1	65.9	55.9	0.1	0.5	54.7	32.7	11.2	23.2
0.199	49.8	27.8	63.7	53.7	0.1	0.5	50.4	28.4	13.2	25.2
2.321	36.8	28.5	56.0	46.0	0.1	0.5	37.4	29.1	18.6	16.9
4.582	35.6	28.2	56.0	46.0	0.1	0.4	36.2	28.8	19.8	17.2
8.633	32.7	25.0	56.0	46.0	0.1	0.6	33.4	25.7	26.6	24.3
20.009	30.9	22.0	56.0	46.0	0.1	0.7	31.7	22.8	28.3	27.2

Note :

TEST CONDITIONS AND DATA

Radiated Emission

[Applicable]

◆ Test Equipment Used

Name	Type	Manufacturer	Calibration. Date	Serial Number
ESVS10	Test Receiver	Rohde & Schwarz	Aug. 17, 2004	839049/004
VULB 9160	Antenna	Schwarzbeck	Jul. 19, 2004	3048

◆ Test Accessories Used

Type	Manufacturer
Aneroid Barometer	Sato
Hygrometer	Sato

◆ Test Program Scrolling "H" characters Mode

◆ Test Date April 08, 2004

◆ Test Area Open site No.1

Note : The equipment used is calibrated in regular for every year.

Radiated Emissions


Mode	Freq. [MHz]	Reading [dBuV]	Antenna Factor [dB/m]	Cable Loss [dB]	Polar. [H/V]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]
640x480, 75Hz	129.5	18.2	10.4	2.1	V	30.7	43.5	12.8
	142.9	23.1	11.7	2.2	H	37.0	43.5	6.5
	207.3	25.9	8.4	2.5	H	36.8	43.5	6.7
	240.2	24.7	10.2	2.9	H	37.8	46.0	8.2
	519.7	19.1	15.3	4.7	V	39.1	46.0	6.9
	715.1	17.3	18.9	5.0	V	41.2	46.0	4.8
800x600, 75Hz	129.2	19.8	10.4	2.1	V	32.3	43.5	11.2
	142.6	22.3	11.7	2.2	H	36.2	43.5	7.3
	207.9	25.3	8.3	2.5	H	36.1	43.5	7.4
	240.0	25.3	10.2	2.9	H	38.4	46.0	7.6
	519.4	18.2	15.3	4.7	V	38.2	46.0	7.8
	714.6	15.3	18.9	5.0	V	39.2	46.0	6.8
1024x768, 75Hz	64.9	14.0	10.5	1.4	V	25.9	40.0	14.1
	129.9	20.1	10.4	2.1	V	32.6	43.5	10.9
	136.3	14.9	11.1	2.1	H	28.1	43.5	15.4
	142.8	23.1	11.7	2.2	H	37.0	43.5	6.5
	149.3	17.8	12.0	2.2	H	32.0	43.5	11.5
	207.8	26.5	8.3	2.5	H	37.3	43.5	6.2
	240.2	29.3	10.2	2.9	H	42.4	46.0	3.6
	246.7	25.2	10.5	2.8	V	38.5	46.0	7.5
	272.7	19.7	11.6	3.0	H	34.3	46.0	11.7
	454.5	22.0	14.0	4.5	H	40.5	46.0	5.5
	519.4	19.3	15.3	4.7	V	39.3	46.0	6.7
	584.3	15.0	16.5	4.7	H	36.2	46.0	9.8
	714.2	18.2	18.9	5.0	V	42.1	46.0	3.9

Note:

Appendix A. The Photos of Test Setup



Conducted Emissions - Front View




Conducted Emissions - Rear View

Appendix A. The Photos of Test Setup



Radiated Emissions - Front View



Radiated Emissions - Rear View

Appendix B. The Photos of Equipment Under Test



Front View



Rear View

Appendix B. The Photos of Equipment Under Test



Adaptor



Adaptor Label

Appendix B. The Photos of Equipment Under Test



LCD Panel Label



EUT Label