

# Certification of Compliance

**CFR 47 Part 15 Subpart B**

<b>Test Report File No. :</b> 05-IST-0207	<b>Date of Issue :</b> June 14, 2005
<b>Model :</b> LS1700V	
<b>Kind of Product :</b> LCD Monitor	
<b>Applicant :</b> Orion Technology Co., Ltd.	
<b>Address :</b> 1242, In-Ri, Apo-Eup, Gimcheon-Si, Kyungbuk, 740-862,	
	Korea
<b>Manufacturer :</b> Orion Technology Co., Ltd.	
<b>Address :</b> 1242, In-Ri, Apo-Eup, Gimcheon-Si, Kyungbuk, 740-862,	
	Korea

## Test Result

**Positive**

**Negative**

Reviewed By

Approved By




S. J. Cho / EMC Group Manager

Joon H. Lee / Chief

### Comment (s)

- Investigations requested : Measurement to the relevant clauses of FCC rules and regulations Part 15 Subpart B - Unintentional Radiators, Class B.
- The test report with appendix consists of 16 pages.
- The test result only responds to the tested sample.
- It is not allowed to copy this report even partly without the allowance of IST EMC Laboratory.
- This equipment as for has been shown to be capable of continued compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4 2003.



## TABLE OF CONTENTS

<b>Table of contents</b>			2
<b>Information of test laboratory, Environmental conditions, Power used, Product information</b>			3
<b>Descriptions of test</b>			
Conducted Emission			4
Radiated Emission			5
<b>Equipment Under Test</b>			6
<b>Summary</b>			7
<b>■ Test Conditions and Data - Emissions</b>			
◆ Conducted Emissions	0.15MHz - 30MHz	Applicable	
Test Conditions / Data and Plots			8-10
◆ Radiated Emissions	30MHz - 1GHz	Applicable	
Test Conditions / Data and Plots			11-12
Appendix	A. The Photos of Test Setup		13-14
	B. The Photos of Equipment Under Test		15-16

Note:

## INFORMATIONS OF TEST LABORATORY

EMC LABORATORY of IST Co., Ltd. *(FCC Filing Lab.)*  
 San 21-8, Goan-Ri, Baekam-Myun, Yongin-City  
 Kyonggi-Do, 449-860, Korea  
 TEL : +82 31 333 4093                      FAX : +82 31 333 4094

## ENVIRONMENTAL CONDITIONS

Temperature	21.3 °C
Humidity	51 %
Atmospheric pressure	1012 mbar

## POWER SUPPLY SYSTEM USED

Power supply system	AC 120Vac, 60Hz (Refer to the product information)
---------------------	---

## PRODUCT INFORMATION

LCD Type :	Panel Model - LTM170E4-L21 (SAMSUNG LCD) 17-inch diagonal AM-TFT (Active Matrix) Pixel pitch - 0.264(H) x 0.264(V) mm Contrast ratio - 500:1 (Typical) Brightness - 300cd/m <sup>2</sup> (Typical) Response Time: 13msec(Typical)
Resolution :	1280 x 1024, 75Hz (max.)
Synchronization :	Horizontal - 30~75 KHz, Vertical - 50~75 KHz
Input Signal :	Sync - separate TTL Level Video - Analog 0.7 Vp-p / 75 ohm S-Video, AV (Composite, Sound L/R) PC Stereo Sound
Power Source :	DSA-60W-12 1 12050 (DVE, Made in China) In-100~240Vac, 50/60Hz 1.5A Out-DC12V, 4.16A
Dimensions(W x H x D) :	18.5 x 16.9 x 7.5 Inch
Weight-net / gross :	6.2 kg / 7.8 kg

- EMC suppression device is not used during the test.
- Please refer to user's manual.


## DESCRIPTIONS OF TEST

### Conducted Emissions:

The measurement were performed over the frequency range of 0.15MHz to 30MHz using a 50Ω/50uH LISN as the input transducer to a Spectrum Analyzer or a Field Intensity Meter. The measurements were made with the detector set for "Peak" amplitude within a bandwidth of 10KHz or for "quasi-peak" & "Average" within a bandwidth of 9KHz.

#### -Procedure of Test

The line-conducted facility is located inside a shielded room No.1. A 1m X 1.5m wooden table 80cm height is placed 40cm away from the vertical wall and 1.5m away from the other wall of the shielded room. The R/S ESH3-Z5 and EMCO 3825/2 LISN are bonded to bottom of the shielded room. The EUT is located on the wooden table with distance more than 80cm from the LISN and powered from the EMCO LISN .The peripheral equipment is powered from the other LISN. Power to the LISNs are filtered by a noise cut power line filters. All electrical cables are shielded by braided tinned steel tubing with inner  $\phi$  1.2cm. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply lines will be connected to the EMCO LISN. All interconnecting cables more than 1m were shortened by non-inductive bundling to a 1m length. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating conditions. The RF output of the LISN was connected to the R/S receiver to determine the frequency producing the maximum emission from the EUT. The frequency producing the maximum level was reexamined using Quasi-Peak mode by manual measurement, after scanned by automatic Peak mode for frequency range from 0.15 to 30MHz. The bandwidth of the receiver was set to 10kHz. The EUT, peripheral equipment, and interconnecting cables were arranged and manipulated to maximize each EME emission.




## DESCRIPTION OF TEST

### Radiated Emissions:

The measurement was performed over the frequency range of 30MHz to 1GHz using antenna as the input transducer to a Spectrum analyzer or a Field Intensity Meter. The measurement was made with the detector set for "quasi-peak" within a bandwidth of 120KHz.

#### -Procedure of Test

Preliminary measurements were made at 3 meter using bi-conical and log-periodic antennas, and spectrum analyzer to determine the frequency producing the max. emission in anechoic chamber. Appropriate precaution was taken to ensure that all emission from the EUT were maximized and investigated. The system configuration, mode of operation, turn-table azimuth and height with respect to the antenna were noted for each frequency found. The spectrum was scanned from 30MHz to 300MHz using S/B bi-conical antenna and 300 to 1000MHz using S/B log-periodic antenna. Above 1GHz, linearly polarized double ridge horn antennas were used. Final measurements were made at open site with 3-meters test distance using S/B bi-log antenna or horn antenna. The OATS have been verified in regular for its normalized site attenuation. The test equipment was placed on a wooden table. Sufficient time for the EUT, peripheral equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. Each frequency found during pre-scan measurements was re-examined by manual. The detector function was set to CISPR quasi-peak mode and the bandwidth of the receiver was set to 120kHz or 1MHz depending on the frequency of type of signal. The EUT, peripheral equipment and interconnecting cables were re-configured to the set-up producing the max. emission for the frequency and were placed on top of a 0.8-meter high nonmetallic 1 x 1.5 meter table. The EUT, peripheral equipment, and interconnecting cables were re-arranged and manipulated to maximize each emission. The turntable containing the system was rotated; the antenna height was varied 1 to 4 meters and stopped at the azimuth or height producing the maximum emission. Each emission was maximized by: varying the mode of operation to the EUT and/or peripheral equipment and changing the polarity of the antenna, whichever determined the worst-case emission.



## Equipment Under Test

### EUT Type :

- Table-Top.  Floor-Standing.  
 Table-Top and Floor-Standing(Combination).

### Operation - mode of the E.U.T. :

The equipment under test was operated during the measurement under following conditions :

- Standby Mode  
 Operational Condition :  640x480, 75Hz  
 800x600, 75Hz  
 1024x768, 75Hz  
 1280x1024, 75Hz

The test results of followings are the representative of worst case emissions for the available resolution can be adjusted.

### Configuration of the equipment under test :

Following peripheral devices and interface cables were connected during the measurement :

Equipment	Type	Brand	Serial No.
PC	T328k	HP	KRJ33800KY
Keyboard	5219	HP	BN32402948
PS/2 Mouse	M042KO	HP	030330777
Serial Mouse	M-M28	Logitech	811308-00
Printer	A0302380	Northern Telecom	2516S60951

### Connecting Interface Cables :

- Unshielded AC power cable : 1.7 m
- Shielded monitor's signal cable (with two ferrite core) : 1.5 m
- Unshielded PC Stereo In cable (with two ferrite core): 1.0 m
- Shielded Printer's signal cable : 1.8 m
- Unshielded BNC cable (terminated at 75 ohm) : 1.0 m
- Unshielded S-Video (terminated at 75  $\Omega$ )
- Unshielded Audio In (terminated at 47 k $\Omega$ )

Note :

## SUMMARY

### Emissions

#### ■ Conducted Emission

The requirements are  MET  Not MET  
Minimum limit margin 22.3 dB at 0.180 MHz  
Maximum limit exceeding

**Remarks : Limits are kept with more 3dB margin.**

Find the test data in following pages 9 to 10.

#### ■ Radiated Emission

The requirements are  MET  Not MET  
Minimum limit margin 4.4 dB at 270.0 MHz  
Maximum limit exceeding

**Remarks : Limits are kept with more 3dB margin.**

Test Mode at 1280x1024, 75Hz.

Find the test data in following page 12.

### test Date

Begin of testing : June 07, 2005.

End of testing : June 11, 2005.

Note :

- means the test is applicable,
- is not applicable.

Prepared By



S.J.OH / Senior Engineer

## TEST CONDITIONS AND DATA

### Conducted Emissions

[Applicable]

◆ Test Equipment Used

Model Name	Description	Manufacture	Calibration Date	Serial Number
ESH 3	Test Receiver	Rohde & Schwarz	Jul. 15, 2004	861742/018
3725/2	LISN	EMCO	Jul. 15, 2004	9101-2068
KNW-407	LISN	Hyup-Rip	Jul. 15, 2004	8-883-10
ESH 3-Z2	Pulse Limiter	Rohde & Schwarz	Jul. 15, 2004	357.8810.52

◆ Test Accessories Used

Type	Manufacturer
Aneroid Barometer	Sato
Hygrometer	Sato

◆ Test Program           Scrolling "H" Characters Mode


◆ Test Date               June 08, 2005

◆ Test Area               Shielded room No.1

Note :                    *The equipment used is calibrated in regular for every year.*




**Conducted Emissions**



Freq. [MHz]	Measurement [dB µV]		Limit [dB µV]		Insertion Loss [dB]	Cable Loss [dB µV]	Result [dB µV]		Margin [dB]	
	Q-peak	Average	Q-peak	Average			Q-peak	Average	Q-peak	Average
0.180	41.5	28.0	64.5	54.5	0.2	0.5	42.2	28.7	22.3	25.8
0.241	35.2	26.5	62.1	52.1	0.2	0.5	35.9	27.2	26.2	24.9
1.385	17.0	9.5	56.0	46.0	0.1	0.4	17.6	10.1	38.4	35.9
5.354	24.3	22.3	60.0	50.0	0.1	0.4	24.9	22.9	35.1	27.1
11.610	21.0	16.5	60.0	50.0	0.1	0.6	21.7	17.2	38.3	32.8

Note :

Conducted Emissions



Freq. [MHz]	Measurement [dB µV]		Limit [dB µV]		Insertion Loss [dB]	Cable Loss [dB µV]	Result [dB µV]		Margin [dB]	
	Q-peak	Average	Q-peak	Average			Q-peak	Average	Q-peak	Average
0.180	38.8	26.2	64.5	54.5	0.1	0.5	39.4	26.8	25.1	27.7
0.300	32.5	24.3	60.2	50.2	0.1	0.5	33.1	24.9	27.2	25.4
2.404	19.3	14.8	56.0	46.0	0.1	0.5	19.9	15.4	36.1	30.6
12.627	20.2	15.7	60.0	50.0	0.2	0.7	21.1	16.6	38.9	33.4

Note :

## TEST CONDITIONS AND DATA

### Radiated Emission

[Applicable]

◆ Test Equipment Used

Name	Type	Manufacturer	Calibration. Date	Serial Number
ESVS10	Test Receiver	Rohde & Schwarz	Aug. 17, 2004	839049/004
VULB 9160	Antenna	Schwarzbeck	Jul. 19, 2004	3048

◆ Test Accessories Used

Type	Manufacturer
Aneroid Barometer	Sato
Hygrometer	Sato

◆ Test Program           Scrolling "H" characters Mode

◆ Test Date               June 10, 2005

◆ Test Area               Open site No.2

Note : The equipment used is calibrated in regular for every year.

**Radiated Emissions**

Mode	Freq. [MHz]	Reading [dBuV]	Antenna Factor [dB/m]	Cable Loss [dB]	Polar. [H/V]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]
640x480, 75Hz	243.7	21.5	10.6	3.9	V	36.0	46.0	10.0
	269.4	26.1	11.4	3.9	V	41.4	46.0	4.6
	284.0	22.6	11.9	4.2	H	38.7	46.0	7.3
	904.1	5.3	22.1	8.7	V	36.1	46.0	9.9
800x600, 75Hz	243.4	22.4	10.6	3.9	V	36.9	46.0	9.1
	269.1	26.0	11.4	3.9	V	41.3	46.0	4.7
	283.1	22.9	11.9	4.2	H	39.0	46.0	7.0
	903.5	5.0	22.1	8.7	V	35.8	46.0	10.2
1024x768, 75Hz	243.1	22.5	10.6	3.9	V	37.0	46.0	9.0
	268.9	26.1	11.4	3.9	V	41.4	46.0	4.6
	283.7	22.5	11.9	4.2	H	38.6	46.0	7.4
	903.8	6.5	22.1	8.7	V	37.3	46.0	8.7
1280x1024, 75Hz	76.4	10.1	8.3	1.9	V	20.3	40.0	19.7
	219.9	11.5	9.5	3.5	V	24.5	46.0	21.5
	229.5	22.2	10.1	3.6	V	35.9	46.0	10.1
	243.0	23.4	10.6	3.9	V	37.9	46.0	8.1
	258.4	16.7	11.1	3.9	V	31.7	46.0	14.3
	270.0	26.3	11.4	3.9	V	41.6	46.0	4.4
	283.5	22.3	11.9	4.2	H	38.4	46.0	7.6
	297.0	20.0	12.3	4.3	V	36.6	46.0	9.4
	387.8	17.6	14.5	5.1	V	37.2	46.0	8.8
	499.5	14.7	16.6	5.9	H	37.2	46.0	8.8
904.5	7.1	22.1	8.7	V	37.9	46.0	8.1	

Note:

Appendix A. The Photos of Test Setup



Conducted Emissions - Front View



Conducted Emissions - Rear View

Appendix A. The Photos of Test Setup



Radiated Emissions - Front View



Radiated Emissions - Rear View

Appendix B. The Photos of Equipment Under Test



Front View



Rear View

Appendix B. The Photos of Equipment Under Test



LCD Panel Label



EUT Label