



No. DAT-P-114/01-10

TEST REPORT

No. SAR2005003

Test name Electromagnetic Field (Specific Absorption Rate)

Product GSM Triple Frequency Mobile Station

Model A6a

Client Amoi Electronics Co., Ltd.

Type of test Entrusted

Telecommunication Metrology Center
of Ministry of Information Industry



GENERAL TERMS

1. The test report is invalid if not marked with “exclusive stamp for the test report” or the stamp of the test center.
2. Any copy of the test report is invalid if not re-marked with the “exclusive stamp for the test report” or the stamp of the test center.
3. The test report is invalid if not marked with the stamps or the signatures of the persons responsible for performing, revising and approving the test report.
4. The test report is invalid if there is any evidence of erasure and/or falsification.
5. If there is any dissidence for the test report, please file objection to the test center within 15 days from the date of receiving the test report.
6. Normally, entrust test is only responsible for the samples that have undergone the test.
7. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permissions of the test center.

Address: No. 52, Huayuanbei Road, Beijing, P. R. China

Post code: 100083

Cable: 04282

Telephone: +86 10 62302041

Fax: +86 10 62304793

**Telecommunication Metrology Center
of Ministry of Information Industry**


No. SAR2005003

Page 3 of 86


GENERAL SUMMARY

Product	GSM Tri-band Mobile Station	Model	A6a
		Trade mark	
Client	Amoi Electronics Co., Ltd.	Manufacturer	Amoi Electronics Co., Ltd.
Type of test	Entrusted	Arrival Date of sample	Mar. 2nd 2005
Place of sampling	(Blank)	Carrier of the samples	Li Cheng
Quantity of the samples	One	Date of product	(Blank)
Base of the samples	(Blank)	Items of test	SAR
Series number	355437000000031		
Standard(s)	<p>EN 50360–2001: Product standard for the measurement of Specific Absorption Rate related to human exposure to electromagnetic fields from mobile phones.</p> <p>EN 50361–2001: Basic standard for the measurement of Specific Absorption Rate related to human exposure to electromagnetic fields from mobile phones.</p> <p>IEC 62209 Draft: Procedure to Determine the Specific Absorption Rate(SAR) for Hand-hold Mobile Phone (Part 2)</p> <p>ANSI C95.1–1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz</p> <p>OET Bulletin 65 (Edition 97-01) and Supplement C(Edition 01-01): Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits.</p> <p>IEEE 1528–2003: Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques.</p>		
Conclusion	<p>Localized Specific Absorption Rate (SAR) of this portable wireless equipment has been measured in all cases requested by the relevant standards cited in Clause 5.2 of this test report. Maximum localized SAR is below exposure limits specified in the relevant standards cited in Clause 5.1 of this test report.</p> <p>General Judgment: Pass</p>		
Comment	<p>TX Freq. Band: 824-849MHz (GSM) 1850-1910 MHz (PCS)</p> <p>Max. Power: 2 Watt (GSM) 1 Watt (PCS)</p> <p>Antenna Character: 21mm</p> <p>The test results relate only to the items tested of the sample(s).</p>		


Approved by


(Lu Bingsong)

Revised by


(Wang Hongbo)

Performed by


(Qi Dianyuan)

(Stamp) Date of issue: March 11th, 2005

TABLE OF CONTENT

1 COMPETENCE AND WARRANTIES	5
2 GENERAL CONDITIONS	5
3 DESCRIPTION OF EUT	5
3.1 ADDRESSING INFORMATION RELATED TO EUT	5
3.2 CONSTITUENTS OF EUT.....	6
3.3 GENERAL DESCRIPTION.....	7
4 OPERATIONAL CONDITIONS DURING TEST.....	7
4.1 SCHEMATIC TEST CONFIGURATION	7
4.2 SAR MEASUREMENT SET-UP	8
4.3 DASY4 E-FIELD PROBE SYSTEM	8
4.4 E-FIELD PROBE CALIBRATION.....	9
4.5 OTHER TEST EQUIPMENT.....	10
4.6 EQUIVALENT TISSUES.....	11
4.7 SYSTEM SPECIFICATIONS	12
5 CHARACTERISTICS OF THE TEST.....	12
5.1 APPLICABLE LIMIT REGULATIONS	12
5.2 APPLICABLE MEASUREMENT STANDARDS	12
6 LABORATORY ENVIRONMENT	13
7 TEST RESULTS	13
7.1 DIELECTRIC PERFORMANCE	13
7.2 SYSTEM VALIDATION.....	13
7.3 SUMMARY OF MEASUREMENT RESULTS(850 MHz BAND).....	14
7.4 SUMMARY OF MEASUREMENT RESULTS (BODY-WORN, GSM 850 MHz BAND).....	15
7.5 SUMMARY OF MEASUREMENT RESULTS (HEAD, PCS 1900 MHz BAND)	16
7.6 SUMMARY OF MEASUREMENT RESULTS (BODY-WORN, PCS 1900 MHz BAND)	17
7.7 CONCLUSION	17
8 MEASUREMENT UNCERTAINTY.....	17
9 MAIN TEST INSTRUMENTS	19
10 TEST PERIOD	19
11 TEST LOCATION.....	19
ANNEX A MEASUREMENT PROCESS.....	20
ANNEX B TEST LAYOUT	21
ANNEX C GRAPH RESULTS.....	25
ANNEX D SYSTEM VALIDATION RESULTS.....	85

1 COMPETENCE AND WARRANTIES

Telecommunication Metrology Center of Ministry of Information Industry is a test laboratory accredited by DAR (DATech) – Deutschen Akkreditierungs Rat (Deutsche Akkreditierungsstelle Technik) for the tests indicated in the Certificate No. **DAT-P-114/01-10**.

Telecommunication Metrology Center of Ministry of Information Industry is a test laboratory competent to carry out the tests described in this test report.

Telecommunication Metrology Center of Ministry of Information Industry guarantees the reliability of the data presented in this test report, which is the results of measurements and tests performed for the items under test on the date and under the conditions stated in this test report and is based on the knowledge and technical facilities available at **Telecommunication Metrology Center of Ministry of Information Industry** at the time of execution of the test.

Telecommunication Metrology Center of Ministry of Information Industry is liable to the client for the maintenance by its personnel of the confidentiality of all information related to the items under test and the results of the test.

2 GENERAL CONDITIONS

- 2.1 This report only refers to the item that has undergone the test.
- 2.2 This report standalone dose not constitute or imply by its own an approval of the product by the certification Bodies or competent Authorities.
- 2.3 This document is only valid if complete; no partial reproduction can be made without written approval of Telecommunication Metrology Center of Ministry of Information Industry.
- 2.4 This report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of Telecommunication Metrology Center of Ministry of Information Industry and the Accreditation Bodies, if it applies.

3 DESCRIPTION OF EUT

3.1 Addressing Information Related to EUT

Table 1: Applicant (The Client)

Name or Company	Amoi Electronics Co., Ltd.
Address/Post	No. 45, Tiyu Road, Xianmen, Fujian, China
City	Fujian
Postal Code	361012
Country	China
Telephone	0592-6516777-3330
Fax	0592-6516007

Table 2: Manufacturer

Name or Company	Amoi Electronics Co., Ltd.
Address/Post	No. 45, Tiyu Road, Xianmen, Fujian, China
City	Fujian
Postal Code	361012
Country	China
Telephone	0592-6516777-3330
Fax	0592-6516007

3.2 Constituents of EUT

Table 3: Constituents of Samples

Description	Model	Serial Number	Manufacturer
Handset	A6a	355437000000031	Amoi Electronics Co., Ltd.
Lithium Battery	UTC03-A	No	Amoi Electronics Co., Ltd.
AC/DC Adapter	A6a	No	Amoi Electronics Co., Ltd.





Figure 1: Constituents of the sample (Lithium Battery is in the Handset)

3.3 General Description

Equipment Under Test (EUT) is a model of GSM Phase II portable Mobile Station (MS) with non-integrated antenna. It consists of Handset and normal options: Lithium Battery and AC/DC Adapter as Table 1 and Fig. 1. It is a Triple-Band MS (GSM/DCS/PCS), upon the request of the client, SAR is tested respectively for two bands.

The sample undergoing test was selected by the Client.

Components list please refer to documents of the manufacturer

4 OPERATIONAL CONDITIONS DURING TEST

4.1 Schematic Test Configuration

During SAR test, EUT is in Traffic Mode (Channel Allocated) at Normal Voltage Condition. A communication link is set up with a System Simulator (SS) by air link, and a call is established. The Absolute Radio Frequency Channel Number (ARFCN) is allocated to 128,190 and 251 respectively in the case of GSM 885 MHz, or to 512, 661 and 810 respectively in the case of PCS 1900 MHz. The EUT is commanded to operate at maximum transmitting power.

The EUT shall use its internal transmitter. The antenna(s), battery and accessories shall be those specified by the manufacturer. The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power output. If a wireless link is used, the antenna connected to the output of the base station simulator shall be placed at least 50 cm away from the handset. The signal transmitted by the simulator to the antenna feeding point shall be lower than the output power

level of the handset by at least 30 dB.

4.2 SAR Measurement Set-up

These measurements were performed with the automated near-field scanning system DASY4 from Schmid & Partner Engineering AG (SPEAG). The system is based on a high precision robot (working range greater than 0.9m) which positions the probes with a positional repeatability of better than $\pm 0.02\text{mm}$. Special E- and H-field probes have been developed for measurements close to material discontinuity, the sensors of which are directly loaded with a Schottky diode and connected via highly resistive lines (length =300mm) to the data acquisition unit.

A cell controller system contains the power supply, robot controller, teaches pendant (Joystick), and remote control, is used to drive the robot motors. The PC consists of the Micron Pentium III 800 MHz computer with Windows 2000 system and SAR Measurement Software DASY4, A/D interface card, monitor, mouse, and keyboard. The Stäubli Robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC plug-in card.




Figure2. SAR Lab Test Measurement Set-up

The DAE3 consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer.

4.3 Dasy4 E-field Probe System

The SAR measurements were conducted with the dosimetric probe ET3DV6 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe has been calibrated according to the standard procedure with an accuracy of better than $\pm 10\%$. The spherical isotropy was evaluated and found to be better than $\pm 0.25\text{dB}$.

ET3DV6 Probe Specification

Construction	Symmetrical design with triangular core Built-in optical fiber for surface detection System(ET3DV6 only) Built-in shielding against static charges PEEK enclosure material(resistant to organic solvents, e.q., glycol)
Calibration	In air from 10 MHz to 2.5 GHz In brain and muscle simulating tissue at frequencies of 450MHz, 900MHz and 1.8GHz (accuracy \pm 8%) Calibration for other liquids and frequencies upon request
Frequency	10 MHz to > 6 GHz; Linearity: \pm 0.2 dB (30 MHz to 3 GHz)
Directivity	\pm 0.2 dB in brain tissue (rotation around probe axis) \pm 0.4 dB in brain tissue (rotation normal probe axis)
Dynamic Range	5u W/g to > 100mW/g; Linearity: \pm 0.2dB
Surface Detection	\pm 0.2 mm repeatability in air and clear liquids over diffuse reflecting surface(ET3DV6 only)
Dimensions	Overall length: 330mm Tip length: 16mm Body diameter: 12mm Tip diarneter: 6.8mm Distance from probe tip to dipole centers: 2.7mm
Application	General dosimetry up to 3GHz Compliance tests of mobile phones Fast automatic scanning in arbitrary phantoms



Figure3. ET3DV6 E-field Probe



Figure4. ET3DV6 E-field probe

4.4 E-field Probe Calibration

Each probe is calibrated according to a dosimetric assessment procedure with accuracy better than \pm 10%. The spherical isotropy was evaluated and found to be better than \pm 0.25dB. The sensitivity parameters (NormX, NormY, NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe are tested.

The free space E-field from amplified probe outputs is determined in a test chamber. This is performed in a TEM cell for frequencies bellow 1 GHz, and in a wave guide above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is then rotated 360 degrees.

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate

simulated brain tissue. The measured free space E-field in the medium correlates to temperature rise in a dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

$$\text{SAR} = C \frac{\Delta T}{\Delta t}$$

Where: Δt = Exposure time (30 seconds),

C = Heat capacity of tissue (brain or muscle),

ΔT = Temperature increase due to RF exposure.

Or

$$\text{SAR} = \frac{|E|^2 \sigma}{\rho}$$

Where:

σ = Simulated tissue conductivity,

ρ = Tissue density (kg/m³).

4.5 Other Test Equipment

4.5.1 Device Holder for Transmitters

In combination with the Generic Twin Phantom V3.0, the Mounting Device (POM) enables the rotation of the mounted transmitter in spherical coordinates whereby the rotation points is the ear opening. The devices can be easily, accurately, and repeat ably positioned according to the FCC and CENELEC specifications. The device holder can be locked at different phantom locations (left head, right head, flat phantom).



Figure5. Device Holder

4.5.2 Phantom

The Generic Twin Phantom is constructed of a fiberglass shell integrated in a wooden table. The shape of the shell is based on data from an anatomical study designed to determine the maximum exposure in at least 90% of all users. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents the evaporation of the liquid. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot.

Shell Thickness 2±0.1 mm

Filling Volume Approx. 20 liters

Dimensions 810 x 1000 x 500 mm (H x L x W)

Available Special



Figure6. Generic Twin Phantom

4.6 Equivalent Tissues

The liquid used for the frequency range of 800-2000 MHz consisted of water, sugar, salt and Cellulose. The liquid has previously been proven to be suited for worst-case. The Table 4 shows the detail solution. It's satisfying the latest tissue dielectric parameters requirements proposed by the IEEE 1528.

Table 4. Composition of the Head Tissue Equivalent Matter

MIXTURE %	FREQUENCY 824-849MHz
Water	41.45
Sugar	56.0
Salt	1.45
Preventol	0.1
Cellulose	1.0
Dielectric Parameters Target Value	$f=850\text{MHz}$ $\epsilon=41.5$ $\sigma=0.90$

MIXTURE %	FREQUENCY 1850-1910MHz
Water	55.242
Glycol monobutyl	44.452
Salt	0.306
Dielectric Parameters Target Value	$f=1900\text{MHz}$ $\epsilon=40.0$ $\sigma=1.40$

Table 5. Composition of the Body Tissue Equivalent Matter

MIXTURE %	FREQUENCY 824-849MHz
Water	52.4
Sugar	45.0
Salt	1.4
Preventol	0.1
Cellulose	1.0
Dielectric Parameters Target Value	$f=850\text{MHz}$ $\epsilon=55.2$ $\sigma=0.97$

MIXTURE %	FREQUENCY 1900MHz
Water	69.91
Glycol monobutyl	29.96
Salt	0.13
Dielectric Parameters Target Value	$f=1900\text{MHz}$ $\epsilon=53.3$ $\sigma=1.52$

4.7 System Specifications

4.7.1 Robotic System Specifications

Specifications

Positioner: Stäubli Unimation Corp. Robot Model: RX90L

Repeatability: ± 0.02 mm

No. of Axis: 6

Data Acquisition Electronic (DAE) System

Cell Controller

Processor: Pentium III

Clock Speed: 800 MHz

Operating System: Windows 2000

Data Converter

Features: Signal Amplifier, multiplexer, A/D converter, and control logic

Software: DASY4 software

Connecting Lines: Optical downlink for data and status info.

Optical uplink for commands and clock

5 CHARACTERISTICS OF THE TEST

5.1 Applicable Limit Regulations

EN 50360–2001: Product standard for the measurement of Specific Absorption Rate related to human exposure to electromagnetic fields from mobile phones.

It specifies the maximum exposure limit of **2.0 W/kg** as averaged over any 10 gram of tissue for portable devices being used within 20 mm of the user in the uncontrolled environment.

ANSI C95.1–1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

It specifies the maximum exposure limit of **1.6 W/kg** as averaged over any 1 gram of tissue for portable devices being used within 20 mm of the user in the uncontrolled environment.

5.2 Applicable Measurement Standards

EN 50361–2001: Basic standard for the measurement of Specific Absorption Rate related to human exposure to electromagnetic fields from mobile phones.

IEEE 1528–2003: Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques.

They specify the measurement method for demonstration of compliance with the SAR limits for such equipments.

6 LABORATORY ENVIRONMENT

Table 6: The Ambient Conditions during EMF Test

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30%, Max. = 70%
Ground system resistance	< 0.5 Ω
Ambient noise is checked and found very low and in compliance with requirement of standards.	
Reflection of surrounding objects is minimized and in compliance with requirement of standards.	

7 TEST RESULTS

7.1 Dielectric Performance

Table 7: Dielectric Performance of Head Tissue Simulating Liquid

Measurement is made at temperature 22 °C and relative humidity 40%.			
/	Frequency	Permittivity ϵ	Conductivity σ (S/m)
Target value	850 MHz	41.5	0.90
	1900 MHz	40.0	1.40
Measurement value (Average of 10 tests)	850 MHz	40.7	0.88
	1900 MHz	40.1	1.41

Table 8: Dielectric Performance of Body Tissue Simulating Liquid

Measurement is made at temperature 22 °C and relative humidity 40%.			
/	Frequency	Permittivity ϵ	Conductivity σ (S/m)
Target value	850 MHz	55.2	0.97
	1900 MHz	53.30	1.52
Measurement value (Average of 10 tests)	850 MHz	54.3	0.97
	1900 MHz	52.9	1.54

7.2 System Validation

Table 9: System Validation

Measurement is made at temperature 23 °C, relative humidity 40%, input power 250 mW.				
Liquid parameters	Frequency	Permittivity ϵ	Conductivity σ (S/m)	
	850 MHz	41.7	0.88	
	1900 MHz	40.1	1.41	
Verification results	Target value (W/kg)		Measurement value (W/kg)	
	10 g Average	1 g Average	10 g Average	1 g Average
	850 MHz	1.55	2.37	1.59
	1900 MHz	5.31	10.1	4.91
			9.8	

7.3 Summary of Measurement Results(850 MHz Band)

Table 10: SAR Values (GSM 850 MHz Band)

Temperature: 22 °C, humidity: 50%.

Liquid temperature during the test: 22.2°C

Limit of SAR (W/kg)	10 g Average	1 g Average	Conducted Power before/after each test (dBm)
	2.0	1.6	
Test Case	Measurement Result (W/kg)		
	10 g Average	1 g Average	
Left hand, Touch cheek, Top frequency	0.715	1.14	29.41/29.52
Left hand, Touch cheek, Mid frequency	0.636	1.01	29.88/29.79
Left hand, Touch cheek, Bottom frequency	0.607	0.959	29.68/29.72
Left hand, Tilt 15 Degree, Top frequency	0.230	0.316	29.42/29.38
Left hand, Tilt 15 Degree, Mid frequency	0.190	0.259	29.79/29.87
Left hand, Tilt 15 Degree, Bottom frequency	0.176	0.239	29.53/29.65
Right hand, Touch cheek, Top frequency	0.826	1.36	29.45/29.41
Right hand, Touch cheek, Mid frequency	0.755	1.24	29.66/29.52
Right hand, Touch cheek, Bottom frequency	0.682	1.11	29.87/29.68
Right hand, Tilt 15 Degree, Top frequency	0.207	0.288	29.54/29.46
Right hand, Tilt 15 Degree, Mid frequency	0.197	0.272	29.90/29.96
Right hand, Tilt 15 Degree, Bottom frequency	0.193	0.266	29.74/29.72

7.4 Summary of Measurement Results (Body-Worn, GSM 850 MHz Band)

Table 11: SAR Values (GSM 850 MHz Band, body-worn)

Temperature: 22 °C, humidity: 50%. Liquid temperature during the test: 22.2°C			
Limit of SAR (W/kg)	10 g Average	1 g Average	Conducted Power before/after each test (dBm)
	2.0	1.6	
Test Case	Measurement Result (W/kg)		
	10 g Average	1 g Average	
Display of EUT towards the phantom, Top Frequency	0.426	0.684	29.31/29.55
Display of EUT towards the phantom, Mid Frequency	0.378	0.613	29.89/29.88
Display of EUT towards the phantom, Bottom Frequency	0.316	0.512	29.47/29.36

7.5 Summary of Measurement Results (Head, PCS 1900 MHz Band)

Table 12: SAR Values (PCS 1900 MHz Band, head)

Temperature: 22 °C, humidity: 50%.

Liquid temperature during the test: 22.2°C

Limit of SAR (W/kg)	10 g Average	1 g Average	Conducted Power before/after each test (dBm)
	2.0	1.6	
Test Case	Measurement Result (W/kg)		
	10 g Average	1 g Average	
Left hand, Touch cheek, Top frequency	0.341	0.615	29.41/29.52
Left hand, Touch cheek, Mid frequency	0.421	0.754	29.88/29.79
Left hand, Touch cheek, Bottom frequency	0.433	0.771	29.68/29.72
Left hand, Tilt 15 Degree, Top frequency	0.086	0.151	29.42/29.38
Left hand, Tilt 15 Degree, Mid frequency	0.078	0.128	29.79/29.87
Left hand, Tilt 15 Degree, Bottom frequency	0.055	0.093	29.53/29.65
Right hand, Touch cheek, Top frequency	0.499	0.951	29.45/29.41
Right hand, Touch cheek, Mid frequency	0.592	1.12	29.66/29.52
Right hand, Touch cheek, Bottom frequency	0.551	1.05	29.87/29.68
Right hand, Tilt 15 Degree, Top frequency	0.119	0.203	29.54/29.46
Right hand, Tilt 15 Degree, Mid frequency	0.158	0.269	29.90/29.96
Right hand, Tilt 15 Degree, Bottom frequency	0.135	0.227	29.74/29.72

7.6 Summary of Measurement Results (Body-Worn, PCS 1900 MHz Band)

Table 13: SAR Values (PCS 1900 MHz Band, body-worn)

Temperature: 22 °C, humidity: 50%.

Liquid temperature during the test: 22.2°C

Limit of SAR (W/kg)	10 g Average	1 g Average	Conducted Power before/after each test (dBm)
	2.0	1.6	
Test Case	Measurement Result (W/kg)		Conducted Power before/after each test (dBm)
	10 g Average	1 g Average	
Display of EUT towards the phantom, Top Frequency	0.331	0.581	29.31/29.55
Display of EUT towards the phantom, Mid Frequency	0.32	0.559	29.89/29.88
Display of EUT towards the phantom, Bottom Frequency	0.258	0.447	29.47/29.36

7.7 Conclusion

Localized Specific Absorption Rate (SAR) of this portable wireless device has been measured in all cases requested by the relevant standards cited in Clause 5.2 of this report. Maximum localized SAR is below exposure limits specified in the relevant standards cited in Clause 5.1 of this test report.

8 Measurement Uncertainty

SN	<i>a</i>	Type	<i>c</i>	<i>d</i>	<i>e</i> = <i>f(d,k)</i>	<i>f</i>	<i>h</i> = <i>c x f / e</i>	<i>k</i>
	Uncertainty Component		Tol. (± %)	Pro b. Dist.	Div.	<i>c_i</i> (1 g)	1 g <i>u_i</i> (±%)	<i>v_i</i>
1	System repetivity	A	0.5	N	1	1	0.5	9
Measurement System								
2	Probe Calibration	B	5	N	2	1	2.5	∞
3	Axial Isotropy	B	4.7	R	$\sqrt{3}$	$\frac{(1-cp)^{1/2}}{2}$	4.3	∞
4	Hemispherical Isotropy	B	9.4	R	$\sqrt{3}$	$\sqrt{c_p}$		∞

**Telecommunication Metrology Center
of Ministry of Information Industry**

No. SAR2005003

Page 18 of 86

5	Boundary Effect	B	0.4	R	$\sqrt{3}$	1	0.23	∞
6	Linearity	B	4.7	R	$\sqrt{3}$	1	2.7	∞
7	System Detection Limits	B	1.0	R	$\sqrt{3}$	1	0.6	∞
8	Readout Electronics	B	1.0	N	1	1	1.0	∞
9	RF Ambient Conditions	B	3.0	R	$\sqrt{3}$	1	1.73	∞
10	Probe Positioner Mechanical Tolerance	B	0.4	R	$\sqrt{3}$	1	0.2	∞
11	Probe Positioning with respect to Phantom Shell	B	2.9	R	$\sqrt{3}$	1	1.7	∞
12	Extrapolation, interpolation and Integration Algorithms for Max. SAR Evaluation	B	3.9	R	$\sqrt{3}$	1	2.3	∞
	Test sample Related							
13	Test Sample Positioning	A	4.9	N	1	1	4.9	$N-1$
14	Device Holder Uncertainty	A	6.1	N	1	1	6.1	$N-1$
15	Output Power Variation - SAR drift measurement	B	5.0	R	$\sqrt{3}$	1	2.9	∞
	Phantom and Tissue Parameters							
16	Phantom Uncertainty (shape and thickness tolerances)	B	1.0	R	$\sqrt{3}$	1	0.6	∞
17	Liquid Conductivity - deviation from target values	B	5.0	R	$\sqrt{3}$	0.64	1.7	∞
18	Liquid Conductivity - measurement uncertainty	B	5.0	N	1	0.64	1.7	M
19	Liquid Permittivity - deviation from target values	B	5.0	R	$\sqrt{3}$	0.6	1.7	∞
20	Liquid Permittivity - measurement uncertainty	B	5.0	N	1	0.6	1.7	M
	Combined Standard Uncertainty							
	Expanded Uncertainty (95% CONFIDENCE INTERVAL)							
				RSS			11.25	
				$K=2$			22.5	

9 MAIN TEST INSTRUMENTS

Table 14: List of Main Instruments

No.	Name	Type	Serial Number	Calibration Date	Valid Period	
01	Network analyzer	Agilent 8753E	US38433212	September 1, 2004	One year	
02	Dielectric Probe Kit	Agilent 85070C	US99360113	No Calibration Requested		
03	Power meter	HP 436A	2101A11858	September 12, 2004	One year	
04	Power sensor	HP 8481H	2349A07289			
05	Signal Generator	MG 3633A	M73386	No Calibration Requested		
06	Amplifier	AT 50S1G4A	26549	No Calibration Requested		
07	Validation Kit835MHz	SPEAG D 835V2	443	September 2, 2003	Two years	
08	Validation Kit 1900MHz	SPEAG D 1900V2	2d010	September 2, 2003	Two years	
09	BTS	CMU 200	100680	September 13, 2004	One year	
10	E-field Probe	SPEAG ET3DV6	1736	November 25, 2004	One year	
11	DAE	SPEAG DAE3	589	October 21, 2004	One year	

10 TEST PERIOD

The test is performed from March 9, 2005 to March 10, 2005

11 TEST LOCATION

The test is performed at Radio Communication & Electromagnetic Compatibility Laboratory of Telecommunication Metrology Center

END OF REPORT BODY

ANNEX A MEASUREMENT PROCESS

The evaluation was performed with the following procedure:

Step 1: Measurement of the SAR value at a fixed location above the ear point was measured and was used as a reference value for assessing the power drop.

Step 2: The SAR distribution at the exposed side of the head was measured at a distance of 3.9 mm from the inner surface of the shell. The area covered the entire dimension of the head and the horizontal grid spacing was 20 mm x 20 mm. Based on this data, the area of the maximum absorption was determined by spline interpolation.

Step 3: Around this point, a volume of 32 mm x 32 mm x 34 mm was assessed by measuring 5 x 5 x 7 points. On this basis of this data set, the spatial peak SAR value was evaluated with the following procedure:

a. The data at the surface were extrapolated, since the center of the dipoles is 2.7 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.2 mm. The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip.

b. The maximum interpolated value was searched with a straightforward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1g or 10g) were computed using the 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot"-condition (in x ~ y and z-directions). The volume was integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were interpolated to calculate the average.

c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.

Step 4: Re-measurement the SAR value at the same location as in Step 1. If the value changed by more than 5%, the evaluation is repeated.




Figure 1 SAR Measurement Points in Area Scan

ANNEX B TEST LAYOUT



Picture 1 Specific Absorption Rate Test Layout



Picture 2 Left Hand Touch Cheek Position




Picture 3 Left Hand Tilt 15° Position



Picture 4 Right Hand Touch Cheek Position



Picture 5 Right Hand Tilt 15° Position



Picture 6 Flat Phantom -- Body-worn Position (toward phantom, the distance from handset to the bottom of the Phantom is 1.5cm)

ANNEX C GRAPH RESULTS

850 Left Cheek Low

Electronics: DAE3 Sn589

Communication System: GSM 850 Frequency: 824.2 MHz Duty Cycle: 1:8.3

Probe: ET3DV6 - SN1736 ConvF(6.53, 6.53, 6.53)

Cheek Low/Area Scan (41x91x1): Measurement grid: dx=10mm, dy=10mm

Reference Value = 10.8 V/m; Power Drift = -0.1 dB

Maximum value of SAR (interpolated) = 0.986 mW/g


Cheek Low/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.8 V/m; Power Drift = -0.1 dB

Maximum value of SAR (measured) = 0.993 mW/g

Peak SAR (extrapolated) = 1.45 W/kg

SAR(1 g) = 0.959 mW/g; SAR(10 g) = 0.607 mW/g



0 dB = 0.993mW/g

Fig. 1 Left Hand Touch Cheek 850MHz CH128




Fig. 2 Z-Scan at power reference point (Left Hand Touch Cheek 850MHz CH128)

850 Left Cheek Middle

Electronics: DAE3 Sn589

Communication System: GSM 850 Frequency: 836.6 MHz Duty Cycle: 1:8.3

Probe: ET3DV6 - SN1736 ConvF(6.53, 6.53, 6.53)

Cheek Middle/Area Scan (41x91x1): Measurement grid: dx=10mm, dy=10mm

Reference Value = 8.91 V/m; Power Drift = -0.2 dB

Maximum value of SAR (interpolated) = 1.04 mW/g


Cheek Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.91 V/m; Power Drift = -0.2 dB

Maximum value of SAR (measured) = 1.04 mW/g

Peak SAR (extrapolated) = 1.54 W/kg

SAR(1 g) = 1.01 mW/g; SAR(10 g) = 0.636 mW/g



0 dB = 1.04mW/g

Fig. 3 Left Hand Touch Cheek 850MHz CH190




Fig. 4 Z-Scan at power reference point (Left Hand Touch Cheek 850MHz CH190)

850 Left Cheek High

Electronics: DAE3 Sn589

Communication System: GSM 850 Frequency: 848.8 MHz Duty Cycle: 1:8.3

Probe: ET3DV6 - SN1736 ConvF(6.53, 6.53, 6.53)

Cheek High/Area Scan (41x91x1): Measurement grid: dx=10mm, dy=10mm

Reference Value = 9.82 V/m; Power Drift = -0.2 dB

Maximum value of SAR (interpolated) = 1.18 mW/g

Cheek High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.82 V/m; Power Drift = -0.2 dB

Maximum value of SAR (measured) = 1.17 mW/g

Peak SAR (extrapolated) = 1.73 W/kg

SAR(1 g) = 1.14 mW/g; SAR(10 g) = 0.715 mW/g




Fig. 5 Left Hand Touch Cheek 850MHz CH251




Fig. 6 Z-Scan at power reference point (Left Hand Touch Cheek 850MHz CH251)

850 Left Tilt Low

Electronics: DAE3 Sn589

Communication System: GSM 850 Frequency: 824.2 MHz Duty Cycle: 1:8.3

Probe: ET3DV6 - SN1736 ConvF(6.53, 6.53, 6.53)

Tilt Low/Area Scan (41x91x1): Measurement grid: dx=10mm, dy=10mm

Reference Value = 10.8 V/m; Power Drift = 0.006 dB

Maximum value of SAR (interpolated) = 0.256 mW/g


Tilt Low/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.8 V/m; Power Drift = 0.006 dB

Maximum value of SAR (measured) = 0.244 mW/g

Peak SAR (extrapolated) = 0.299 W/kg

SAR(1 g) = 0.239 mW/g; SAR(10 g) = 0.176 mW/g



0 dB = 0.244mW/g

Fig. 7 Left Hand Tilt 15° 850MHz CH128




Fig. 8 Z-Scan at power reference point (Left Hand Tilt 15° 850MHz CH128)

850 Left Tilt Middle

Electronics: DAE3 Sn589

Communication System: GSM 850 Frequency: 836.6 MHz Duty Cycle: 1:8.3

Probe: ET3DV6 - SN1736 ConvF(6.53, 6.53, 6.53)

Tilt Middle/Area Scan (41x91x1): Measurement grid: dx=10mm, dy=10mm

Reference Value = 11.3 V/m; Power Drift = -0.0 dB

Maximum value of SAR (interpolated) = 0.276 mW/g


Tilt Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.3 V/m; Power Drift = -0.0 dB

Maximum value of SAR (measured) = 0.263 mW/g

Peak SAR (extrapolated) = 0.326 W/kg

SAR(1 g) = 0.259 mW/g; SAR(10 g) = 0.190 mW/g



0 dB = 0.263mW/g

Fig. 9 Left Hand Tilt 15° 850MHz CH190




Fig. 10 Z-Scan at power reference point (Left Hand Tilt 15° 850MHz CH190)

850 Left Tilt High

Electronics: DAE3 Sn589

Communication System: GSM 850 Frequency: 848.8 MHz Duty Cycle: 1:8.3

Probe: ET3DV6 - SN1736 ConvF(6.53, 6.53, 6.53)

Tilt High/Area Scan (41x91x1): Measurement grid: dx=10mm, dy=10mm

Reference Value = 13 V/m; Power Drift = 0.1dB

Maximum value of SAR (interpolated) = 0.339 mW/g


Tilt High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13 V/m; Power Drift = 0.1 dB

Maximum value of SAR (measured) = 0.327 mW/g

Peak SAR (extrapolated) = 0.410 W/kg

SAR(1 g) = 0.316 mW/g; SAR(10 g) = 0.230 mW/g



0 dB = 0.327mW/g

Fig. 11 Left Hand Tilt 15° 850MHz CH251




Fig. 12 Z-Scan at power reference point (Left Hand Tilt 15° 850MHz CH251)

850 Right Cheek Low

Electronics: DAE3 Sn589

Communication System: GSM 850 Frequency: 824.2 MHz Duty Cycle: 1:8.3

Probe: ET3DV6 - SN1736 ConvF(6.53, 6.53, 6.53)

Cheek Low/Area Scan (41x91x1): Measurement grid: dx=10mm, dy=10mm

Reference Value = 7.32 V/m; Power Drift = -0.2 dB

Maximum value of SAR (interpolated) = 1.1 mW/g


Cheek Low/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.32 V/m; Power Drift = -0.2 dB

Maximum value of SAR (measured) = 1.17 mW/g

Peak SAR (extrapolated) = 1.74 W/kg

SAR(1 g) = 1.11 mW/g; SAR(10 g) = 0.682 mW/g



0 dB = 1.17mW/g

Fig. 13 Right Hand Touch Cheek 850MHz CH128




Fig. 14 Z-Scan at power reference point (Right Hand Touch Cheek 850MHz CH128)

850 Right Cheek Middle

Electronics: DAE3 Sn589

Communication System: GSM 850 Frequency: 836.6 MHz Duty Cycle: 1:8.3

Probe: ET3DV6 - SN1736 ConvF(6.53, 6.53, 6.53)

Cheek Middle/Area Scan (41x91x1): Measurement grid: dx=10mm, dy=10mm

Reference Value = 9.72 V/m; Power Drift = -0.2 dB

Maximum value of SAR (interpolated) = 1.19 mW/g


Cheek Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.72 V/m; Power Drift = -0.2 dB

Maximum value of SAR (measured) = 1.27 mW/g

Peak SAR (extrapolated) = 1.98 W/kg

SAR(1 g) = 1.24 mW/g; SAR(10 g) = 0.755 mW/g



0 dB = 1.27mW/g

Fig.15 Right Hand Touch Cheek 850MHz CH190




Fig. 16 Z-Scan at power reference point (Right Hand Touch Cheek 850MHz CH190)

850 Right Cheek High

Electronics: DAE3 Sn589

Communication System: GSM 850 Frequency: 848.8 MHz Duty Cycle: 1:8.3

Probe: ET3DV6 - SN1736 ConvF(6.53, 6.53, 6.53)

Cheek High/Area Scan (41x91x1): Measurement grid: dx=10mm, dy=10mm

Reference Value = 10 V/m; Power Drift = 0.0 dB

Maximum value of SAR (interpolated) = 1.33 mW/g


Cheek High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10 V/m; Power Drift = 0.0 dB

Maximum value of SAR (measured) = 1.37 mW/g

Peak SAR (extrapolated) = 2.18 W/kg

SAR(1 g) = 1.36 mW/g; SAR(10 g) = 0.826 mW/g



0 dB = 1.37mW/g

Fig. 17 Right Hand Touch Cheek 850MHz CH251




Fig. 18 Z-Scan at power reference point (Right Hand Touch Cheek 850MHz CH251)

850 Right Tilt Low

Electronics: DAE3 Sn589

Communication System: GSM 850 Frequency: 824.2 MHz Duty Cycle: 1:8.3

Probe: ET3DV6 - SN1736 ConvF(6.53, 6.53, 6.53)

Tilt Low/Area Scan (41x91x1): Measurement grid: dx=10mm, dy=10mm

Reference Value = 8.82 V/m; Power Drift = 0.1 dB

Maximum value of SAR (interpolated) = 0.276 mW/g

Tilt Low/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.82 V/m; Power Drift = 0.1 dB

Maximum value of SAR (measured) = 0.274 mW/g

Peak SAR (extrapolated) = 0.350 W/kg

SAR(1 g) = 0.266 mW/g; SAR(10 g) = 0.193 mW/g



0 dB = 0.274mW/g

Fig. 19 Right Hand Tilt 15° 850MHz CH128




Fig. 20 Z-Scan at power reference point (Right Hand Tilt 15° 850MHz CH128)

850 Right Tilt Middle

Electronics: DAE3 Sn589

Communication System: GSM 850 Frequency: 836.6 MHz Duty Cycle: 1:8.3

Probe: ET3DV6 - SN1736 ConvF(6.53, 6.53, 6.53)

Tilt Middle/Area Scan (41x91x1): Measurement grid: dx=10mm, dy=10mm

Reference Value = 8.95 V/m; Power Drift = -0.1 dB

Maximum value of SAR (interpolated) = 0.284 mW/g


Tilt Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.95 V/m; Power Drift = -0.1 dB

Maximum value of SAR (measured) = 0.280 mW/g

Peak SAR (extrapolated) = 0.360 W/kg

SAR(1 g) = 0.272 mW/g; SAR(10 g) = 0.197 mW/g



0 dB = 0.280mW/g

Fig. 21 Right Hand Tilt 15°850MHz CH190




Fig. 22 Z-Scan at power reference point (Right Hand Tilt 15° 850MHz CH190)

850 Right Tilt High

Electronics: DAE3 Sn589

Communication System: GSM 850 Frequency: 848.8 MHz Duty Cycle: 1:8.3

Probe: ET3DV6 - SN1736 ConvF(6.53, 6.53, 6.53)

Tilt High/Area Scan (41x91x1): Measurement grid: dx=10mm, dy=10mm

Reference Value = 8.9 V/m; Power Drift = -0.1 dB

Maximum value of SAR (interpolated) = 0.300 mW/g

Tilt High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.9 V/m; Power Drift = -0.1 dB

Maximum value of SAR (measured) = 0.294 mW/g

Peak SAR (extrapolated) = 0.381 W/kg

SAR(1 g) = 0.288 mW/g; SAR(10 g) = 0.207 mW/g



0 dB = 0.294mW/g

Fig. 23 Right Hand Tilt 15°850MHz CH251




Fig. 24 Z-Scan at power reference point (Right Hand Tilt 15° 850MHz CH251)

1900 Left Cheek Low

Electronics: DAE3 Sn589

Communication System: GSM 1900MHz Frequency: 1850.2 MHz Duty Cycle: 1:8

Probe: ET3DV6 - SN1736 ConvF(5.37, 5.37, 5.37)

Cheek Low/Area Scan (51x91x1): Measurement grid: dx=10mm, dy=10mm

Reference Value = 5.59 V/m; Power Drift = -0.0 dB

Maximum value of SAR (interpolated) = 0.825 mW/g


Cheek Low/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.59 V/m; Power Drift = -0.0 dB

Maximum value of SAR (measured) = 0.850 mW/g

Peak SAR (extrapolated) = 1.27 W/kg

SAR(1 g) = 0.771 mW/g; SAR(10 g) = 0.433 mW/g



0 dB = 0.850mW/g

Fig. 25 Left Hand Touch Cheek PCS1900MHz CH512




Fig. 26 Z-Scan at power reference point (Left Hand Touch Cheek 1900MHz CH512)

1900 Left Cheek Middle

Electronics: DAE3 Sn589

Communication System: PCS 1900MHz Frequency: 1880 MHz Duty Cycle: 1:8

Probe: ET3DV6 - SN1736 ConvF(5.37, 5.37, 5.37)

Cheek Middle/Area Scan (51x91x1): Measurement grid: dx=10mm, dy=10mm

Reference Value = 5.97 V/m; Power Drift = -0.2 dB

Maximum value of SAR (interpolated) = 0.828 mW/g


Cheek Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.97 V/m; Power Drift = -0.2 dB

Maximum value of SAR (measured) = 0.818 mW/g

Peak SAR (extrapolated) = 1.26 W/kg

SAR(1 g) = 0.754 mW/g; SAR(10 g) = 0.421 mW/g



0 dB = 0.818mW/g

Fig. 27 Left Hand Touch Cheek PCS 1900MHz CH661




Fig. 28 Z-Scan at power reference point (Left Hand Touch Cheek 1900MHz CH661)

1900 Left Cheek High

Electronics: DAE3 Sn589

Communication System: GSM 1900MHz Frequency: 1909.8 MHz Duty Cycle: 1:8

Probe: ET3DV6 - SN1736 ConvF(5.37, 5.37, 5.37)

Cheek High/Area Scan (41x91x1): Measurement grid: dx=10mm, dy=10mm

Reference Value = 5.85 V/m; Power Drift = -0.2 dB

Maximum value of SAR (interpolated) = 0.735 mW/g


Cheek High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.85 V/m; Power Drift = -0.2 dB

Maximum value of SAR (measured) = 0.710 mW/g

Peak SAR (extrapolated) = 1.06 W/kg

SAR(1 g) = 0.615 mW/g; SAR(10 g) = 0.341 mW/g



0 dB = 0.710mW/g

Fig. 29 Left Hand Touch Cheek PCS 1900MHz CH810




Fig. 30 Z-Scan at power reference point (Left Hand Touch Cheek 1900MHz CH810)

1900 Left Tilt Low

Electronics: DAE3 Sn589

Communication System: GSM 1900MHz Frequency: 1850.2 MHz Duty Cycle: 1:8

Probe: ET3DV6 - SN1736 ConvF(5.37, 5.37, 5.37)

Tilt Low/Area Scan (51x91x1): Measurement grid: dx=10mm, dy=10mm

Reference Value = 7.26 V/m; Power Drift = -0.0 dB

Maximum value of SAR (interpolated) = 0.119 mW/g


Tilt Low/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.26 V/m; Power Drift = -0.0 dB

Maximum value of SAR (measured) = 0.093 mW/g

Peak SAR (extrapolated) = 0.151 W/kg

SAR(1 g) = 0.093 mW/g; SAR(10 g) = 0.055 mW/g



0 dB = 0.093mW/g

Fig. 31 Left Hand Tilt 15°PCS1900MHz CH512




Fig.32 Z-Scan at power reference point (Left Hand Tilt 15° 1900MHz CH512)

1900 Left Tilt Middle

Electronics: DAE3 Sn589

Communication System: GSM 1900MHz Frequency: 1880 MHz Duty Cycle: 1:8

Probe: ET3DV6 - SN1736 ConvF(5.37, 5.37, 5.37)

Tilt Middle/Area Scan (51x91x1): Measurement grid: dx=10mm, dy=10mm

Reference Value = 7.36 V/m; Power Drift = 0.2 dB

Maximum value of SAR (interpolated) = 0.126 mW/g


Tilt Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.36 V/m; Power Drift = 0.2 dB

Maximum value of SAR (measured) = 0.129 mW/g

Peak SAR (extrapolated) = 0.203 W/kg

SAR(1 g) = 0.128 mW/g; SAR(10 g) = 0.078 mW/g



0 dB = 0.129mW/g

Fig. 33 Left Hand Tilt 15°PCS1900MHz CH661




Fig. 34 Z-Scan at power reference point (Left Hand Tilt 15° 1900MHz CH661)

1900 Left Tilt High

Electronics: DAE3 Sn589

Communication System: GSM 1900MHz Frequency: 1909.8 MHz Duty Cycle: 1:8

Probe: ET3DV6 - SN1736 ConvF(5.37, 5.37, 5.37)

Tilt High/Area Scan (51x91x1): Measurement grid: dx=10mm, dy=10mm

Reference Value = 9.32 V/m; Power Drift = -0.2 dB

Maximum value of SAR (interpolated) = 0.191 mW/g


Tilt High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.32 V/m; Power Drift = -0.2 dB

Maximum value of SAR (measured) = 0.148 mW/g

Peak SAR (extrapolated) = 0.251 W/kg

SAR(1 g) = 0.151 mW/g; SAR(10 g) = 0.086 mW/g



0 dB = 0.148mW/g

Fig. 35 Left Hand Tilt 15°PCS1900MHz CH810




Fig. 36 Z-Scan at power reference point (Left Hand Tilt 15° 1900MHz CH810)

1900 Right Cheek Low

Electronics: DAE3 Sn589

Communication System: GSM 1900MHz Frequency: 1850.2 MHz Duty Cycle: 1:8

Probe: ET3DV6 - SN1736 ConvF(5.37, 5.37, 5.37)

Cheek Low/Area Scan (41x91x1): Measurement grid: dx=10mm, dy=10mm

Reference Value = 6.7 V/m; Power Drift = -0.0 dB

Maximum value of SAR (interpolated) = 1.03 mW/g


Cheek Low/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.7 V/m; Power Drift = -0.0 dB

Maximum value of SAR (measured) = 1.05 mW/g

Peak SAR (extrapolated) = 1.88 W/kg

SAR(1 g) = 1.05 mW/g; SAR(10 g) = 0.551 mW/g



0 dB = 1.05mW/g

Fig. 37 Right Hand Touch Cheek PCS1900MHz CH512




Fig. 38 Z-Scan at power reference point (Right Hand Touch Cheek 1900MHz CH512)

1900 Right Cheek Middle

Electronics: DAE3 Sn589

Communication System: GSM 1900MHz Frequency: 1880 MHz Duty Cycle: 1:8

Probe: ET3DV6 - SN1736 ConvF(5.37, 5.37, 5.37)

Cheek Middle/Area Scan (41x91x1): Measurement grid: dx=10mm, dy=10mm

Reference Value = 7.04 V/m; Power Drift = -0.0 dB

Maximum value of SAR (interpolated) = 1.12 mW/g


Cheek Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.04 V/m; Power Drift = -0.0 dB

Maximum value of SAR (measured) = 1.12 mW/g

Peak SAR (extrapolated) = 2.02 W/kg

SAR(1 g) = 1.12 mW/g; SAR(10 g) = 0.592 mW/g



0 dB = 1.12mW/g

Fig. 39 Right Hand Touch Cheek PCS1900MHz CH661




Fig. 40 Z-Scan at power reference point (Right Hand Touch Cheek 1900MHz CH661)

1900 Right Cheek High

Electronics: DAE3 Sn589

Communication System: GSM 1900MHz Frequency: 1909.8 MHz Duty Cycle: 1:8

Probe: ET3DV6 - SN1736 ConvF(5.37, 5.37, 5.37)

Cheek High/Area Scan (41x91x1): Measurement grid: dx=10mm, dy=10mm

Reference Value = 6.51 V/m; Power Drift = -0.1 dB

Maximum value of SAR (interpolated) = 0.964 mW/g


Cheek High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.51 V/m; Power Drift = -0.1 dB

Maximum value of SAR (measured) = 0.962 mW/g

Peak SAR (extrapolated) = 1.74 W/kg

SAR(1 g) = 0.951 mW/g; SAR(10 g) = 0.499 mW/g



0 dB = 0.962mW/g

Fig. 41 Right Hand Touch Cheek PCS1900MHz CH810




Fig. 42 Z-Scan at power reference point (Right Hand Touch Cheek 1900MHz CH810)

1900 Right Tilt Low

Electronics: DAE3 Sn589

Communication System: GSM 1900MHz Frequency: 1850.2 MHz Duty Cycle: 1:8

Probe: ET3DV6 - SN1736 ConvF(5.37, 5.37, 5.37)

Tilt Low/Area Scan (41x91x1): Measurement grid: dx=10mm, dy=10mm

Reference Value = 11.9 V/m; Power Drift = -0.0 dB

Maximum value of SAR (interpolated) = 0.303 mW/g


Tilt Low/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.9 V/m; Power Drift = -0.0 dB

Maximum value of SAR (measured) = 0.225 mW/g

Peak SAR (extrapolated) = 0.362 W/kg

SAR(1 g) = 0.227 mW/g; SAR(10 g) = 0.135 mW/g



0 dB = 0.225mW/g

Fig. 43 Right Hand Tilt 15°PCS1900MHz CH512




Fig. 44 Z-Scan at power reference point (Right Hand Tilt 15° 1900MHz CH512)

1900 Right Tilt Middle

Electronics: DAE3 Sn589

Communication System: GSM 1900MHz Frequency: 1880 MHz Duty Cycle: 1:8

Probe: ET3DV6 - SN1736 ConvF(5.37, 5.37, 5.37)

Tilt Middle/Area Scan (41x91x1): Measurement grid: dx=10mm, dy=10mm

Reference Value = 12.8 V/m; Power Drift = 0.1 dB

Maximum value of SAR (interpolated) = 0.356 mW/g


Tilt Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.8 V/m; Power Drift = 0.1 dB

Maximum value of SAR (measured) = 0.264 mW/g

Peak SAR (extrapolated) = 0.436 W/kg

SAR(1 g) = 0.269 mW/g; SAR(10 g) = 0.158 mW/g



0 dB = 0.264mW/g

Fig. 45 Right Hand Tilt 15°PCS1900MHz CH661




Fig. 46 Z-Scan at power reference point (Right Hand Tilt 15° 1900MHz CH661)

1900 Right Tilt High

Electronics: DAE3 Sn589

Communication System: GSM 1900MHz Frequency: 1909.8 MHz Duty Cycle: 1:8

Probe: ET3DV6 - SN1736 ConvF(5.37, 5.37, 5.37)

Tilt High/Area Scan (41x91x1): Measurement grid: dx=10mm, dy=10mm

Reference Value = 11.2 V/m; Power Drift = -0.1 dB

Maximum value of SAR (interpolated) = 0.264 mW/g


Tilt High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.2 V/m; Power Drift = -0.1 dB

Maximum value of SAR (measured) = 0.203 mW/g

Peak SAR (extrapolated) = 0.326 W/kg

SAR(1 g) = 0.203 mW/g; SAR(10 g) = 0.119 mW/g



0 dB = 0.203mW/g

Fig. 47 Right Hand Tilt 15°PCS1900MHz CH810




Fig. 48 Z-Scan at power reference point (Right Hand Tilt 15° 1900MHz CH810)

850 Body Toward Phantom Low

Electronics: DAE3 Sn589

Communication System: GSM 850 Frequency: 824.2 MHz Duty Cycle: 1:8.3

Probe: ET3DV6 - SN1736 ConvF(6.53, 6.53, 6.53)

Toward Phantom Low/Area Scan (41x91x1): Measurement grid: dx=10mm, dy=10mm
Reference Value = 11.8 V/m; Power Drift = -0.2 dB
Maximum value of SAR (interpolated) = 0.550 mW/g

Toward Phantom Low/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 11.8 V/m; Power Drift = -0.2 dB
Maximum value of SAR (measured) = 0.534 mW/g
Peak SAR (extrapolated) = 0.813 W/kg
SAR(1 g) = 0.512 mW/g; SAR(10 g) = 0.316 mW/g



0 dB = 0.534mW/g

Fig. 49 Flat Phantom Body-worn Position 850MHz CH128 with the display of the handset towards the phantom




Fig. 50Z-Scan at power reference point (Flat Phantom 850MHz CH128 with the display of the handset towards the phantom)

850 Body Toward Phantom Middle

Electronics: DAE3 Sn589

Communication System: GSM 850 Frequency: 836.6 MHz Duty Cycle: 1:8.3

Probe: ET3DV6 - SN1736 ConvF(6.53, 6.53, 6.53)

Toward Phantom Middle/Area Scan (41x91x1): Measurement grid: dx=10mm, dy=10mm

Reference Value = 11.8 V/m; Power Drift = 0.0 dB

Maximum value of SAR (interpolated) = 0.663 mW/g

Toward Phantom Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.8 V/m; Power Drift = 0.0 dB

Maximum value of SAR (measured) = 0.652 mW/g

Peak SAR (extrapolated) = 0.988 W/kg

SAR(1 g) = 0.613 mW/g; SAR(10 g) = 0.378 mW/g



Fig. 51 Flat Phantom Body-worn Position 850MHz CH190 with the display of the handset towards the phantom




Fig. 52 Z-Scan at power reference point (Flat Phantom 850MHz CH190 with the display of the handset towards the phantom)

850 Body Toward Phantom High


Electronics: DAE3 Sn589

Communication System: GSM 850 Frequency: 848.8 MHz Duty Cycle: 1:8.3

Probe: ET3DV6 - SN1736 ConvF(6.53, 6.53, 6.53)

Toward Phantom High/Area Scan (41x91x1): Measurement grid: dx=10mm, dy=10mm
Reference Value = 12.5 V/m; Power Drift = -0.2 dB
Maximum value of SAR (interpolated) = 0.753 mW/g

Toward Phantom High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 12.5 V/m; Power Drift = -0.2 dB
Maximum value of SAR (measured) = 0.716 mW/g
Peak SAR (extrapolated) = 1.08 W/kg
SAR(1 g) = 0.684 mW/g; SAR(10 g) = 0.426 mW/g



0 dB = 0.716mW/g

**Fig. 53 Flat Phantom Body-worn Position 850MHz CH251 with the display of the handset
towards the phantom**




Fig. 54 Z-Scan at power reference point (Flat Phantom 850MHz CH251 with the display of the handset towards the phantom)

1900 Body Toward Phantom Low

Electronics: DAE3 Sn589

Communication System: GSM 1900MHz Frequency: 1850.2 MHz Duty Cycle: 1:8

Probe: ET3DV6 - SN1736 ConvF(5.37, 5.37, 5.37)

Toward Phantom Low/Area Scan (41x91x1): Measurement grid: dx=10mm, dy=10mm

Reference Value = 4.35 V/m; Power Drift = -0.2 dB

Maximum value of SAR (interpolated) = 0.468 mW/g

Toward Phantom Low/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.35 V/m; Power Drift = -0.2 dB

Maximum value of SAR (measured) = 0.496 mW/g

Peak SAR (extrapolated) = 0.776 W/kg

SAR(1 g) = 0.447 mW/g; SAR(10 g) = 0.258 mW/g



Fig. 55 Flat Phantom Body-worn Position 1900MHz CH512 with the display of the handset towards the phantom




Fig.56 Z-Scan at power reference point (Flat Phantom 1900MHz CH512 with the display of the handset towards the phantom)

1900 Body Toward Phantom Middle

Electronics: DAE3 Sn589

Communication System: GSM 1900MHz Frequency: 1880 MHz Duty Cycle: 1:8

Probe: ET3DV6 - SN1736 ConvF(5.37, 5.37, 5.37)

Toward Phantom Middle/Area Scan (51x91x1): Measurement grid: dx=10mm, dy=10mm

Reference Value = 4.24 V/m; Power Drift = -0.0 dB

Maximum value of SAR (interpolated) = 0.611 mW/g

Toward Phantom Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.24 V/m; Power Drift = -0.0 dB

Maximum value of SAR (measured) = 0.543 mW/g

Peak SAR (extrapolated) = 1.01 W/kg

SAR(1 g) = 0.559 mW/g; SAR(10 g) = 0.320 mW/g



Fig. 57 Flat Phantom Body-worn Position 1900MHz CH661 with the display of the handset towards the phantom



Fig. 58 Z-Scan at power reference point (Flat Phantom 1900MHz CH661 with the display of the handset towards the phantom)

1900 Body Toward Phantom

Electronics: DAE3 Sn589

Communication System: GSM 1900MHz Frequency: 1909.8 MHz Duty Cycle: 1:8

Probe: ET3DV6 - SN1736 ConvF(5.37, 5.37, 5.37)

Toward Phantom High/Area Scan (41x91x1): Measurement grid: dx=10mm, dy=10mm

Reference Value = 3.85 V/m; Power Drift = 0.2 dB

Maximum value of SAR (interpolated) = 0.603 mW/g

Toward Phantom High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.85 V/m; Power Drift = 0.2 dB

Maximum value of SAR (measured) = 0.636 mW/g

Peak SAR (extrapolated) = 1.03 W/kg

SAR(1 g) = 0.581 mW/g; SAR(10 g) = 0.331 mW/g




Fig. 59 Flat Phantom Body-worn Position 1900MHz CH810 with the display of the handset towards the phantom




Fig. 60 Z-Scan at power reference point (Flat Phantom 1900MHz CH810 with the display of the handset towards the phantom)

ANNEX D SYSTEM VALIDATION RESULTS

Test Laboratory: TMC
File Name: 835MHz.da4

DUT: Dipole 835 MHz Type & Serial Number: D835V2 - SN:443

Program: System Performance Check; Dipole 835MHz,Pin=250mW,d=15mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm

Reference Value = 54.7 V/m

Peak SAR = 3.47 mW/g

SAR(1 g) = 2.35 mW/g; SAR(10 g) = 1.52 mW/g

Power Drift = -0.01 dB

Area Scan (101x101x1): Measurement grid: dx=10mm, dy=10mm




Fig.61 validation 850MHz 250mW

Test Laboratory: TMC
File Name: D1900_SystemCheck_040403.da4

DUT: Dipole 1900 MHz Type & Serial Number: D1900V2 - SN:541
Program: Unnamed Program; Dipole 1900MHz

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1
Medium: Head 1900 MHz ($\sigma = 1.46 \text{ mho/m}$, $\epsilon = 39.66$, $\rho = 1000 \text{ kg/m}^3$)
Phantom section: FlatSection

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm

Reference Value = 90.9 V/m

Peak SAR = 18.3 mW/g

SAR(1 g) = 9.8 mW/g; SAR(10 g) = 4.91 mW/g

Power Drift = 0.004 dB

Area Scan (101x101x1): Measurement grid: dx=10mm, dy=10mm




Fig.62 validation 1900MHz 250mW