

ISED CABid: ES1909  
 Lab. Company Number: 4621A

Test Report No:  
 75163RRF.006A1

## Partial Test Report

USA FCC Part 15.31(h), 15.247, 15.407, 15.209  
 CANADA RSS-247, RSS-Gen

(*) Identification of item tested	HUAIDP20BY
(*) Trademark	Marelli
(*) Model and /or type reference	HUAIDP20BY
Other identification of the product	FCC ID: RX2HUAIDP20BY IC: 4983A-HUAIDP20BY
(*) Features	HUAIDP20BY HW version: PRS2.1 SW version: PI26.50
Applicant	Marelli Europe S.p.A. Viale A. Borletti 61/63 - 20011 Corbetta (MI) - ITALY
Test method requested, standard	USA FCC Part 15.31(h) (10-1-21 Edition): Measurement standards. USA FCC Part 15.407 (10-1-21) Edition: Unlicensed National Information Infrastructure (U-NII) Devices. General technical requirements. USA FCC Part 15.247 (10-1-21) Edition: Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and 5725 - 5850 MHz. USA FCC Part 15.209 (10-1-21) Edition: Radiated emission limits; general requirements. CANADA RSS-247 Issue 3 (February 2023). CANADA RSS-Gen Issue 5 amendment 2 (February 2021). Guidance for Performing Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid Systems Devices Operating Under Section 15.247 of the FCC Rules. 558074 D01 Meas Guidance v05r02 dated April 2, 2019. Guidance for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices 789033 D02 General U-NII Test Procedures New Rules v02r01 dated Dec 14, 2017. ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices. - Transmitter out of band radiated emissions with simultaneous transmissions.
Approved by (name / position & signature)	Antonio José Jurado Industrial & Automotive EMC Lab. Manager
Date of issue	2024-04-05
Report template No.	FDT08_24 (*) "Data provided by the client"

# Index

Competences and guarantees .....	3
General conditions .....	3
Uncertainty .....	3
Data provided by the client.....	4
Usage of samples .....	4
Test sample description .....	4
Identification of the client.....	5
Testing period and place.....	5
Document history .....	5
Environmental conditions .....	6
Remarks and comments .....	6
Testing verdicts.....	7
Summary .....	7
Appendix A: Test results. ....	8

## Competences and guarantees

---

DEKRA Testing and Certification S.A.U. is a testing laboratory accredited by the National Accreditation Body (ENAC - Entidad Nacional de Acreditación) to perform the tests indicated in the Certificate No. 51/LE 147.

DEKRA Testing and Certification is an FCC-recognized accredited testing laboratory with appropriate scope of accreditation that covers the performed tests in this report.

DEKRA Testing and Certification is an ISED-recognized accredited testing laboratory, CABid: ES1909, Company Number: 4621A, with the appropriate scope of accreditation that covers the performed tests in this report.

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification S.A.U. has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification S.A.U. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and it is based on the knowledge and technical facilities available at DEKRA Testing and Certification S.A.U. at the time of performance of the test.

DEKRA Testing and Certification S.A.U. is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

**IMPORTANT:** No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Testing and Certification S.A.U.

## General conditions

---

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification S.A.U.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification S.A.U. and the Accreditation Bodies.

## Uncertainty

---

Uncertainty (factor  $k=2$ ) was calculated according to the DEKRA Testing and Certification S.A.U. internal document PODT000.

The total uncertainty of the measurement system for the radiated emissions of EUT from 30 MHz to 1 GHz is:  
Measurement uncertainty  $\leq \pm 5.15$  dB (with factor  $k = 2$ ).

The total uncertainty of the measurement system for the radiated emissions of EUT from 1 GHz to 17 GHz is:  
Measurement uncertainty  $\leq \pm 4.28$  dB (with factor  $k = 2$ ).

The total uncertainty of the measurement system for the radiated emissions of EUT from 17 GHz to 26.5 GHz is:  
Measurement uncertainty  $\leq \pm 4.89$  dB (with factor  $k = 2$ ).

The total uncertainty of the measurement system for the radiated emissions of EUT from 26.5 GHz to 40 GHz is:  
Measurement uncertainty  $\leq \pm 5.02$  dB (with factor  $k = 2$ ).

## Data provided by the client

The following data has been provided by the client:

1. Information relating to the description of the sample ("Identification of the item tested", "Trademark", "Model and/or type reference tested").
2. The sample of the model HUAIDP20BY is an Infotainment Head Unit, with Bluetooth and Wi-Fi.

DEKRA Testing and Certification S.A.U. declines any responsibility with respect to the information provided by the client and that may affect the validity of result.

## Usage of samples

Samples undergoing test have been selected by: The client.

- Sample S/01 is composed of the following elements:

Control No.	Description	Model	Serial No.	Date of reception
75163/003	Harness	-	-	25-09-2023
75163/005	Cable FAKRA	-	-	25-09-2023
75163/006	Cable FAKRA	-	-	25-09-2023
75163/008	Cable FAKRA	-	-	25-09-2023
75163/009	Cable FAKRA	-	-	25-09-2023
75163/010	Cable FAKRA	-	-	25-09-2023
75163/011	Cable FAKRA	-	-	25-09-2023
75163/012	Cable FAKRA	-	-	25-09-2023
75163/013	Cable FAKRA	-	-	25-09-2023
75163/014	Cable FAKRA	-	-	25-09-2023
75163/016	Infotainment Head Unit	HUAIDP20BY	19083B0PM47D	25-09-2023

Auxiliary elements used with the Sample S/01:

Control No.	Description	Model	Serial No.	Date of reception
75163/001	Module	-	-	25-09-2023
75163/041	AIDA CANBOX	-	-	25-09-2023

Sample S/01 has undergone the following test(s): The Radiated tests indicated in the Appendix A.

## Test sample description

Ports.....:	Port name and description	Cable			
		Specified max length [m]	Attached during test	Shielded	Coupled to patient <sup>(3)</sup>
	MB connector (black)	>3	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
	SB connector (blue)	>3	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
	shielded cables	>3	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Supplementary information to the ports.....:	-				

Rated power supply .....	<b>Voltage and Frequency</b>		
	<input checked="" type="checkbox"/>	DC: MB and SB cables: 13.5 Vdc nominal voltage	
	<input checked="" type="checkbox"/>	DC: shielded cables: 13.5 Vdc nominal voltage	
Rated Power.....	-		
Clock frequencies.....	-		
Other parameters .....	-		
Software version.....	PI26.50		
Hardware version .....	PRS2.1		
Dimensions in cm (W x H x D) ...	220 x 160 x 52 mm		
Mounting position .....	<input type="checkbox"/>	Table top equipment	
	<input type="checkbox"/>	Wall/Ceiling mounted equipment	
	<input type="checkbox"/>	Floor standing equipment	
	<input type="checkbox"/>	Hand-held equipment	
	<input checked="" type="checkbox"/>	Other: HUAIDP20BY is installed in vehicle dashboard (automotive environment)	
Modules/parts.....	<b>Module/parts of test item</b>	<b>Type</b>	<b>Manufacturer</b>
	-	-	-
Accessories (not part of the test item) .....	<b>Description</b>	<b>Type</b>	<b>Manufacturer</b>
	-	-	-
Documents as provided by the applicant.....	<b>Description</b>	<b>File name</b>	<b>Issue date</b>
	-	-	-

<sup>(3)</sup> Only for Medical Equipment

## Identification of the client

Marelli Europe S.p.A.  
 Viale A. Borletti 61/63 - 20011 Corbetta (MI) - ITALY

## Testing period and place

<b>Test Location</b>	DEKRA Testing and Certification S.A.U.
<b>Date (start)</b>	2023-10-20
<b>Date (finish)</b>	2023-10-20

## Document history

Report number	Date	Description
75163RRF.006	2024-01-24	First release.
75163RRF.006A1	2024-04-05	First modification. Some typos in the main page, apartment "Test method requested, standard" are corrected. The standard "CANADA RSS-247 Issue 2 (February 2017)" is corrected to "CANADA RSS-247 Issue 3 (February 2023)".

## Environmental conditions

In the control chamber, the following limits were not exceeded during the test:

<b>Temperature</b>	Min. = 15 °C Max. = 35 °C
<b>Relative humidity</b>	Min. = 20 % Max. = 75 %

In the semianechoic chamber, the following limits were not exceeded during the test.

<b>Temperature</b>	Min. = 15 °C Max. = 35 °C
<b>Relative humidity</b>	Min. = 20 % Max. = 75 %

## Remarks and comments

The tests have been performed by the technical personnel: Victoria Olmedo.

Used instrumentation:

Control No.	Equipment	Model	Manufacturer	Next Calibration
8130	Semianechoic Absorber Lined Chamber	P29419	ALBATROSS PROJECTS GMBH	2026-01
8134	Shielded Room	P29419	ALBATROSS PROJECTS GMBH	N/A
7763	Horn Antenna 1-18 GHz	BBHA 9120 D	SCHWARZBECK MESS-ELEKTRONIK	2026-01
6495	Horn Antenna 18-40 GHz	BBHA 9170	SCHWARZBECK MESS-ELEKTRONIK	2024-03
7769	Preamplifier 30 dB 500MHz-18GHz	BBV 9718 C	SCHWARZBECK MESS-ELEKTRONIK	2024-02
7862	Preamplifier G>30 dB 17-40GHz	BLMA 1840-3G	BONN ELEKTRONIK	2024-03
6158	Signal and Spectrum Analyzer 10 Hz - 40 GHz	FSV40	ROHDE AND SCHWARZ	2023-10
9193	Power Supply DC 30 V / 3 A	ALR3003	ELC	N/A
7755	Digital Multimeter	175	FLUKE	2024-11
4848	SOFTWARE FOR EMC/RF TESTING	EMC32	ROHDE AND SCHWARZ	N/A

## Testing verdicts

Not applicable:	N/A
Pass:	P
Fail:	F
Not measured:	N/M

## Summary

FCC PART 15 PARAGRAPH / RSS-247		
Requirement – Test case	Verdict	Remark
FCC 15.31 (h), 15.209 (a), 15.247 (d), 15.407 (b) / RSS-Gen 8.9, RSS-247 5.5, 6.2.1.2, 6.2.4.2: - Emission limitations radiated (Transmitter)	P	(1)
<u>Supplementary information and remarks:</u> (1) Only Co-Location radiated spurious emission test was requested.		

## Appendix A: Test results



## INDEX

TEST CONDITIONS .....	10
FCC 15.31 (h), 15.209 (a), 15.247 (d), 15.407 (b) / RSS-Gen 8.9, RSS-247 5.5, 6.2.1.2 & 6.2.4.2	
Emission limitations radiated (Transmitter).....	14

## TEST CONDITIONS

(\*): Declared by the Applicant.

### POWER SUPPLY (\*):

Vnominal: 13.5 Vdc  
 Type of Power Supply: External DC (vehicle battery).

### ANTENNA (\*):

#### Bluetooth EDR:

Type of Antenna: Integral (PCB).  
 Maximum Declared Antenna Gain: 0 dBi.

#### 802.11 a20 / n2040 / ac2040 / ac80 SISO:

Type of Antenna: Integral.  
 Maximum Declared Antenna Gain: 0 dBi.

### RADIOS AND CHANNELS TESTED:

Bluetooth EDR / FHSS		
Mode:	Basic Rate (GFSK - 1DH5)	
Channel Spacing:	1 MHz	
Frequency Range:	2402 MHz to 2480 MHz	
Transmit Channels	Channel	Channel Frequency (MHz)
	High: 39	2480

WLAN 5 GHz (IEEE 802.11 a20/n2040/ac204080) / U-NII-3		
Mode:	802.11 n20: index MSC0.	
Frequency Range:	5725 MHz to 5850 MHz	
Channel Spacing:	20 MHz	
Transmit Channels	Channel	Channel Frequency (MHz)
	Low: 149	5745

The modulations and channels configured for each technology are the worst-case combinations in terms of spurious emissions, based on preliminary testing.

The test set-up was made in accordance to the general provisions of FCC DTS Measurement 558074 D01 DTS Meas Guidance v05r2 dated April 2, 2019 and FCC Unlicensed National Information Infrastructure (U-NII) Devices 789033 D02 General U-NII Test Procedures New Rules v02r01 dated Dec 14, 2017.

The EUT was tested in the following operating mode:

- Continuous transmission with a modulated carrier at maximum power in all required channels selecting the supported data rates/modulations types.

During transmitter test the EUT was being controlled by the SW tool to operate in a continuous transmit mode on the test channel as required and in each of the different modulation modes.

### **Selected Transmission Mode for each Radio:**

The following configurations were selected based on preliminary testing that identified those corresponding to the worst-cases:

\* Bluetooth Basic Rate: Transmitter radiated spurious emissions tests were performed with the EUT transmitting in Basic Rate mode because its power is higher than the other modes.

\* WLAN 5 GHz band U-NII-3: Transmitter radiated spurious emissions tests were performed with the EUT transmitting in 802.11 n / 20 / MCS0 mode configuration as this mode was found as the worst-case for spurious emissions than all the other WLAN 5 GHz band U-NII-3 SISO modes.

### **TESTED SIMULTANEOUS TRANSMISSION MODES:**

\* **Co-location Bluetooth EDR, WLAN 5 GHz band U-NII-3**, with the EUT configured to simultaneously transmit two signals at maximum output power:  
Bluetooth Basic Rate in GFSK 1-DH5 mode, WLAN 5 GHz band U-NII-3 in 802.11 n / 20 / MCS0.

**RADIATED MEASUREMENTS:**


All radiated tests were performed in a semi-anechoic chamber. The measurement antenna (Bilog antenna for the range between 30 MHz to 1 GHz and 1 GHz-17 GHz Double ridge horn antenna) is situated at a distance of 3 m and at a distance of 1.5 m for the frequency range 17 GHz-40 GHz (17 GHz-40 GHz horn antenna).

For radiated emissions in the range 17 GHz-40 GHz that is performed at a distance closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.


The equipment under test was set up on a non-conductive platform above the ground plane and the situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height (Bilog antenna and Double ridge horn antenna) was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.


Radiated measurements setup from 30 MHz to 1 GHz:



Radiated measurements setup from 1 GHz to 17 GHz:



Radiated measurements setup  $f > 17$  GHz:



## FCC 15.31 (h), 15.209 (a), 15.247 (d), 15.407 (b) / RSS-Gen 8.9, RSS-247 5.5, 6.2.1.2 & 6.2.4.2 Emission limitations radiated (Transmitter)

### SPECIFICATION:

Radiated emissions which fall in the restricted bands, as defined in §15.205(a), appearing outside of the band 13.110 MHz - 14.010 MHz band must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c) / RSS-Gen):

Frequency Range (MHz)	Field strength ( $\mu\text{V}/\text{m}$ )	Field strength ( $\text{dB}\mu\text{V}/\text{m}$ )	Measurement distance (m)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	30
1.705 - 30.0	30	29.54	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
960 - 40000	500	54	3

The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

For average radiated emission measurements above 1000 MHz, there is also a limit corresponding to 20 dB above the indicated values in the table is specified when measuring with peak detector function.

RSS-247. Attenuation below the general field strength limits specified in RSS-Gen is not required.

### RESULTS:

The situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

All tests were performed in a semi-anechoic chamber at a distance of 3 m for the frequency range 30 MHz-17 GHz and at distance of 1 m for the frequency range 17 GHz-40GHz.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyzer. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

Test performed on the following worst-cases in all relevant tests channels:

• **Co-location mode Bluetooth EDR, WLAN 5 GHz U-NII-3:**

Bluetooth EDR: High Channel (2480 MHz). Basic Rate. GFSK.  
 WLAN 5 GHz U-NII-3 802.11 n20: Low Channel (5745 MHz). BW: 20 MHz. MCS0.

LIMIT: The spurious frequencies were measured at 3 meter. The limit of the test is determined by:

Frequency Range	Detector	Limit at 3m (dBµV/m)
30 MHz to 88 MHz	Quasi-peak	40 dBµV/m
88 MHz to 216 MHz	Quasi-peak	43.5 dBµV/m
216 MHz to 960 MHz	Quasi-peak	46 dBµV/m
960 MHz to 1 GHz	Quasi-peak	54 dBµV/m
1 GHz to 26 GHz	Peak	74 dBµV/m
26 to 40 GHz	Peak	68.23 dBµV/m (*) OR 74 dBµV/m (**)
1 to 40 GHz	Average	54 dBµV/m (**)

(\*) Radiated emissions which fall in the non-restricted bands.

(\*\*) Radiated emissions which fall in the restricted bands, as defined in §15.205(a).

**Frequency range 30 MHz - 1 GHz:**

The spurious emissions below 1 GHz do not depend on either the operating channel or the modulation mode selected in the EUT.

No spurious frequencies at less than 20 dB below the limit.

Measurement Uncertainty (dB):  $<\pm 5.15$

**Frequency range 1 - 40 GHz:**

Spurious frequencies at less than 20 dB below the limit:


Spurious frequency (GHz)	Emission Level (dBµV/m)	Limit (dBµV/m)	Polarization	Detector
11.484090625	66.06	68.23	V	Peak
	51.20	54.00		Average

Measurement Uncertainty (dB):  
 1 - 17 GHz  $<\pm 4.28$   
 17 - 26.5 GHz  $<\pm 4.89$   
 26.5 - 40 GHz  $<\pm 5.02$

Verdict: PASS

Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
30 MHz - 1 GHz	48.5 kHz	PK+	100 kHz	1 s	0 dB
1 GHz - 7 GHz	187.5 kHz	PK+ ; AVG	1 MHz	1 s	0 dB
7 GHz - 17 GHz	312.5 kHz	PK+ ; AVG	1 MHz	1 s	0 dB
17 GHz - 40 GHz	718.75 kHz	PK+ ; AVG	1 MHz	1 s	0 dB


**FREQUENCY RANGE 30 MHz - 1 GHz:**





**FREQUENCY RANGE 1 - 7 GHz:**


Full Spectrum



- Preview Result 2H-AVG      — Preview Result 1H-PK+      — Preview Result 2V-AVG
- Preview Result 1V-PK+      — FCC 15.31 (h) AVG      — FCC 15.31 (h) PK
- ◆ Final\_Result PK+              ◆ Final\_Result AVG


The peak above the limit on the left is the BT EDR carrier frequency.  
 The peak above the limit on the right is the WLAN 5 GHz band U-NII-3 carrier frequency.

**FREQUENCY RANGE 7 - 17 GHz:**



- Preview Result 2H-AVG
- Preview Result 1V-PK+
- Preview Result 1H-PK+ AVG
- Preview Result 2V-AVG
- Final\_Result AVG
- FCC 15.31 (h) AVG
- Final\_Result PK+
- FCC 15.31 (h) PK

**FREQUENCY RANGE 17 - 40 GHz:**



- Preview Result 2H-AVG
- Preview Result 1V-PK+
- Preview Result 1H-PK+ AVG
- Preview Result 2V-AVG
- Final\_Result PK+
- Final\_Result AVG
- FCC 15.31 (h) AVG
- FCC 15.31 (h) PK