

# Radio Exposure Evaluation Report

**FCC ID** : RX3-WBU058VZ

**Equipment** : IEEE 802.11 a/b/g/n/ac/ax 2x2+Bluetooth v5.2 Wireless Adapter

**Brand Name** : Foxconn

**Model Name** : WBU058-VZ

**Applicant** : Hon Hai Precision Industry Co., Ltd.  
No.151, Sec. 1, Nankan Rd., Lujhu Dist., Taoyuan City 33859,  
Taiwan

**Manufacturer** : Hon Hai Precision Industry Co., Ltd.  
No.151, Sec. 1, Nankan Rd., Lujhu Dist., Taoyuan City 33859,  
Taiwan

**Standard** : 47 CFR FCC Part 2 Subpart J, section 2.1091

The product was received on Jan. 10, 2022, and testing was started from Jan. 18, 2022 and completed on Jan. 19, 2022. We, SPORTON INTERNATIONAL INC. Hsinhua Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR FCC Part 2 Subpart J, section 2.1091 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Hsinhua Laboratory, the test report shall not be reproduced except in full.



Approved by: Jackson Tsai

**SPORTON INTERNATIONAL INC. Hsinhua Laboratory**  
No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)



## Table of Contents

<b>HISTORY OF THIS TEST REPORT .....</b>	<b>3</b>
<b>1 GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1 Information.....	5
1.2 Testing Location .....	6
<b>2 MAXIMUM PERMISSIBLE EXPOSURE .....</b>	<b>7</b>
2.1 Limit of Maximum Permissible Exposure .....	7
2.2 MPE Calculation Method.....	8
2.3 Calculated Result and Limit.....	8
<b>Photographs of EUT V01</b>	





### Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

<b>Declaration of Conformity:</b>
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
<b>Comments and Explanations:</b>
None

Reviewed by: Ben Tseng  
Report Producer: Jenny Yang

# 1 General Description

## 1.1 Information

### 1.1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
5GHz WLAN	5150-5250 5250-5350 5470-5725 5725-5850	5180-5240 5260-5320 5500-5700 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
6GHz WLAN	5925 ~ 7125	5955 ~ 7115 5965 ~ 7085 5985 ~ 7025	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
Bluetooth	2400-2483.5	2402-2480	BR / EDR: FHSS (GFSK / $\pi/4$ -DQPSK / 8DPSK) LE: DSSS (GFSK)

### 1.1.2 Antenna Information

Ant.	Brand	Model Name	Antenna Type	Connector
1	Foxconn	-	PCB	N/A
2	Foxconn	-	PCB	N/A
3	Foxconn	-	PCB	N/A
4	Foxconn	-	PCB	N/A

Ant.	Port	Gain (dBi)									BT
		2.4G	5G				6G				
			U-NII-1	U-NII-2A	U-NII-2C	U-NII-3	U-NII-5	U-NII-6	U-NII-7	U-NII-8	
1	1	1.00	2.50	2.68	3.07	2.75	4.35	4.35	4.43	4.02	-
2	2	0.77	0.89	1.68	3.67	3.67	3.37	3.85	5.77	5.78	-
3	2	-	-	-	-	-	-	-	-	-	2.83
4	1	-	-	-	-	-	-	-	-	-	2.97

Note 1: The EUT has four antennas.



**For 2.4GHz function:**

For IEEE 802.11 b/g/n/ax mode (2TX/2RX)  
Ant. 1 (port 1) and Ant. 2 (port 2) could transmit/receive simultaneously.

**For BT function:**

For IEEE 802.15.1 Bluetooth mode (1TX/1RX)  
Support diversity function and pre-tested on each single chain, the worst case was Ant. 4(port 1) and it was recorded in this test report.

**For 5GHz function:**

For IEEE 802.11 a/n/ac/ax mode (2TX/2RX)  
Ant. 1 (port 1) and Ant. 2 (port 2) could transmit/receive simultaneously.

## 1.2 Testing Location

Test Lab. : Sporton International Inc. Hsinhua Laboratory		
<input checked="" type="checkbox"/>	Hsinhua (TAF: 3785)	ADD: No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.) TEL: 886-3-327-3456      FAX: 886-3-327-0973
Test site Designation No. TW3785 with FCC.		
<input type="checkbox"/>	Wen 33rd.St. (TAF: 3785)	ADD: No.14-1, Ln. 19, Wen 33rd St., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: 886-3-318-0787      FAX: 886-3-318-0287
Test site Designation No. TW0008 with FCC.		

## 2 Maximum Permissible Exposure

### 2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f <sup>2</sup> )*	6
30-300	61.4	0.163	1.0	6
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F/1500	30
1500-100,000	-	-	1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

#### Multiple Transmitters Condition

Co-location as simultaneously transmitting (co-transmitting) and the evaluation shall be consider that simultaneous transmissions from co-located devices the individual transmitters are evaluated separately. After sum of the individual value (basic restriction / reference level) are measured/calculated also have to under basic restriction / reference level.

Co-transmitting mode:

1. Bluetooth+WLAN 2.4GHz
2. Bluetooth+WLAN 5GHz
3. Bluetooth+WLAN 6GHz

## 2.2 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit. The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = RF output power (W)

**G** = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

## 2.3 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

### Bluetooth+WLAN 2.4GHz

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm2)	Limit	Ratio
									(mW/cm2)	(S/Limit)
2.4G;BT-EDR	2.97	12.89	15.86	0.50	16.36	0.04325	20	0.0086	1.00000	0.0086
2.4G;G1D	1.00	17.96	18.96	0.50	19.46	0.08831	20	0.01757	1.00000	0.01757
									Sum Ratio	0.02617
									Ratio Limit	1

### Bluetooth+WLAN 5GHz

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm2)	Limit	Ratio
									(mW/cm2)	(S/Limit)
2.4G;BT-EDR	2.97	12.89	15.86	0.50	16.36	0.04325	20	0.0086	1.00000	0.0086
5.8G;D1D	3.67	15.99	19.66	0.50	20.16	0.10375	20	0.02064	1.00000	0.02064
									Sum Ratio	0.02924
									Ratio Limit	1

### Bluetooth+WLAN 6GHz

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm2)	Limit	Ratio
									(mW/cm2)	(S/Limit)
2.4G;BT-EDR	2.97	12.89	15.86	0.50	16.36	0.04325	20	0.00860	1.00000	0.00860
6.7G;D1D	5.77	10.93	16.70	0.50	17.20	0.05248	20	0.01044	1.00000	0.01044
									Sum Ratio	0.01904
									Ratio Limit	1

—————THE END—————