

1 MAXIMUM PERMISSIBLE EXPOSURE (MPE)

1.1 Standard Applicable

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

This is a Mobile device, the MPE is required.

According to §1.1310 and §2.1093 RF exposure is calculated.

Limits for Maximum Permissive Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-15000	/	/	1.0	30

F = frequency in MHz

* = Plane-wave equipment power density

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = Power density

P = Power input to antenna

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

802.11a Max. output power

802.11a Main

CH	Frequency (MHz)	Data Rate	TOTAL POWER (dBm)	TOTAL POWER (mW)	REQUIRED LIMIT (dBm)	RESULT
36	5180	MCS0	13.98	25.003	23.98	PASS
44	5220	MCS0	13.96	24.889	23.98	PASS
48	5240	MCS0	13.92	24.660	23.98	PASS
52	5260	MCS0	13.76	23.768	23.98 or $11+10\log(B) = 24.54$	PASS
60	5300	MCS0	13.78	23.878	23.98 or $11+10\log(B) = 23.92$	PASS
64	5320	MCS0	13.70	23.442	23.98 or $11+10\log(B) = 24.01$	PASS
100	5500	MCS0	11.49	14.093	23.98 or $11+10\log(B) = 23.84$	PASS
116	5580	MCS0	13.71	23.496	23.98 or $11+10\log(B) = 23.89$	PASS
140	5700	MCS0	12.33	17.100	23.98 or $11+10\log(B) = 23.79$	PASS
149	5745	MCS0	13.94	24.774	30	PASS
157	5785	MCS0	13.98	25.003	30	PASS
165	5825	MCS0	13.86	24.322	30	PASS

MPE Prediction (802.11a 5150~5250)

Average output power at antenna input terminal:	13.98	(dBm)
Average output power at antenna input terminal:	25.003454	(mW)
Duty cycle:	95.2	(%)
Maximum Pav :	23.803288	(mW)
Peak Antenna gain (Maximum):	5.35	(dBi)
Peak Antenna gain (linear):	3.4276779	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5180	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm ²)
Power density at predication frequency at 20 (cm)	0.016	(mW/cm ²)
Measurement Result		
The predicted power density level at 20 cm is 0.016 mW/cm ² .		
This is below the uncontrolled exposure limit of 1 mW/cm ² at 5180MHz.		

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

MPE Prediction (802.11a 5250~5350)

Average output power at antenna input terminal:	13.78	(dBm)
Average output power at antenna input terminal:	23.878113	(mW)
Duty cycle:	95.2	(%)
Maximum Pav :	22.731963	(mW)
Peak Antenna gain (Maximum):	5.35	(dBi)
Peak Antenna gain (linear):	3.4276779	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5300	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm ²)
Power density at predication frequency at 20 (cm)	0.016	(mW/cm ²)
Measurement Result		
The predicted power density level at 20 cm is 0.016 mW/cm ² .		
This is below the uncontrolled exposure limit of 1 mW/cm ² at 5300MHz.		

MPE Prediction (802.11a 5470~5725)

Average output power at antenna input terminal:	13.71	(dBm)
Average output power at antenna input terminal:	23.496328	(mW)
Duty cycle:	95.2	(%)
Maximum Pav :	22.368504	(mW)
Peak Antenna gain (Maximum):	4.05	(dBi)
Peak Antenna gain (linear):	2.5409727	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5580	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm ²)
Power density at predication frequency at 20 (cm)	0.011	(mW/cm ²)
Measurement Result		
The predicted power density level at 20 cm is 0.011 mW/cm ² .		
This is below the uncontrolled exposure limit of 1 mW/cm ² at 5580MHz.		

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

MPE Prediction (802.11a 5725~5850)

Average output power at antenna input terminal:	13.98	(dBm)
Average output power at antenna input terminal:	25.003454	(mW)
Duty cycle:	95.2	(%)
Maximum Pav :	23.803288	(mW)
Peak Antenna gain (Maximum):	4.57	(dBi)
Peak Antenna gain (linear):	2.864178	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5785	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm ²)
Power density at predication frequency at 20 (cm)	0.014	(mW/cm ²)
Measurement Result		
The predicted power density level at 20 cm is 0.014 mW/cm ² .		
This is below the uncontrolled exposure limit of 1 mW/cm ² at 5785MHz.		

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

802.11n_HT20M Max. output power

802.11n_HT20_MIMO

CH	Frequency (MHz)	Data Rate	RAGE POWER (dBm)		TOTAL POWER (dBm)	TOTAL POWER (mW)	REQUIRED LIMIT (dBm)		RESULT
			CH 0	CH 1					
36	5180	MCS8	9.72	9.65	12.70	18.601	21.62		PASS
44	5220	MCS8	9.69	9.62	12.67	18.473	21.62		PASS
48	5240	MCS8	9.98	9.91	12.96	19.749	21.62		PASS
52	5260	MCS8	9.99	9.89	12.95	19.727	21.62	or 11+10log(B) = 23.94	PASS
60	5300	MCS8	10.04	9.88	12.97	19.820	21.62	or 11+10log(B) = 23.93	PASS
64	5320	MCS8	9.98	9.77	12.89	19.438	21.62	or 11+10log(B) = 23.95	PASS
100	5500	MCS8	9.94	9.65	12.81	19.089	22.92	or 11+10log(B) = 23.99	PASS
116	5580	MCS8	10.28	9.61	12.97	19.807	22.92	or 11+10log(B) = 23.95	PASS
140	5700	MCS8	10.27	9.34	12.84	19.232	22.92	or 11+10log(B) = 23.95	PASS
149	5745	MCS8	10.23	9.27	12.79	18.997	28.42		PASS
157	5785	MCS8	10.22	9.21	12.75	18.856	28.42		PASS
165	5825	MCS8	10.14	9.23	12.72	18.703	28.42		PASS

MPE Prediction (802.11n_HT20 5150~5250)

MIMO gain= $G+(10 \log N)= 5.35+3.01=8.36\text{dBm}$

Average output power at antenna input terminal:	12.96	(dBm)
Average output power at antenna input terminal:	19.769696	(mW)
Duty cycle:	94.9	(%)
Maximum Pav :	18.761442	(mW)
Peak Antenna gain (Maximum):	8.36	(dBi)
Peak Antenna gain (linear):	6.8548823	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5240	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm ²)
Power density at predication frequency at 20 (cm)	0.026	(mW/cm ²)
Measurement Result		
The predicted power density level at 20 cm is 0.026 mW/cm ² .		
This is below the uncontrolled exposure limit of 1 mW/cm ² at 5240MHz.		

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

MPE Prediction (802.11n_HT20 5250~5350)
MIMO gain= $G+(10 \log N)= 5.35+3.01= 8.36\text{dBm}$

Average output power at antenna input terminal:	12.97	(dBm)
Average output power at antenna input terminal:	19.81527	(mW)
Duty cycle:	94.9	(%)
Maximum Pav :	18.804691	(mW)
Peak Antenna gain (Maximum):	8.36	(dBi)
Peak Antenna gain (linear):	6.8548823	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5300	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm ²)
Power density at predication frequency at 20 (cm)	0.026	(mW/cm ²)

Measurement Result

 The predicted power density level at 20 cm is 0.026 mW/cm².

 This is below the uncontrolled exposure limit of 1 mW/cm² at 5300MHz.

MPE Prediction (802.11n_HT20 5470~5725)
MIMO gain= $G+(10 \log N)= 4.05+3.01= 7.06\text{dBm}$

Average output power at antenna input terminal:	12.97	(dBm)
Average output power at antenna input terminal:	19.81527	(mW)
Duty cycle:	94.9	(%)
Maximum Pav :	18.804691	(mW)
Peak Antenna gain (Maximum):	7.06	(dBi)
Peak Antenna gain (linear):	5.0815944	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5580	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm ²)
Power density at predication frequency at 20 (cm)	0.019	(mW/cm ²)

Measurement Result

 The predicted power density level at 20 cm is 0.019 mW/cm².

 This is below the uncontrolled exposure limit of 1 mW/cm² at 5580MHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

MPE Prediction (802.11n_HT20 5725~5850)

MIMO gain= $G+(10 \log N)= 4.57+3.01= 7.58\text{dBm}$

Average output power at antenna input terminal:	12.79	(dBm)
Average output power at antenna input terminal:	19.010783	(mW)
Duty cycle:	94.9	(%)
Maximum Pav :	18.041233	(mW)
Peak Antenna gain (Maximum):	7.58	(dBi)
Peak Antenna gain (linear):	5.7279603	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5745	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm ²)
Power density at predication frequency at 20 (cm)	0.021	(mW/cm ²)

Measurement Result

The predicted power density level at 20 cm is 0.021 mW/cm².

This is below the uncontrolled exposure limit of 1 mW/cm² at 5745MHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

802.11n_HT40M Max. output power

802.11n_HT40_MIMO

CH	Frequency (MHz)	Data Rate	RAGE POWER (dBm)		TOTAL POWER (dBm)	TOTAL POWER (mW)	REQUIRED LIMIT (dBm)		RESULT
			CH 0	CH 1					
38	5190	MCS8	8.61	8.59	11.61	14.489	21.62		PASS
46	5230	MCS8	8.66	8.58	11.63	14.556	21.62		PASS
54	5270	MCS8	8.61	8.53	11.58	14.390	21.62	or 11+10log(B) = 27.02	PASS
62	5310	MCS8	8.93	8.88	11.92	15.543	21.62	or 11+10log(B) = 27.17	PASS
102	5510	MCS8	9.17	8.66	11.93	15.606	22.92	or 11+10log(B) = 27.16	PASS
110	5550	MCS8	9.32	8.59	11.98	15.778	22.92	or 11+10log(B) = 27.03	PASS
134	5670	MCS8	9.22	8.38	11.83	15.243	22.92	or 11+10log(B) = 27.20	PASS
151	5755	MCS8	9.19	8.36	11.81	15.153		28.42	PASS
159	5795	MCS8	9.08	8.33	11.73	14.899		28.42	PASS

MPE Prediction (802.11n_HT40 5150~5250)

MIMO gain= $G+(10 \log N)= 5.35+3.01= 8.36\text{dBm}$

Average output power at antenna input terminal:	11.63	(dBm)
Average output power at antenna input terminal:	14.554591	(mW)
Duty cycle:	90.44	(%)
Maximum Pav :	13.163172	(mW)
Peak Antenna gain (Maximum):	8.36	(dBi)
Peak Antenna gain (linear):	6.8548823	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5230	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm ²)
Power density at predication frequency at 20 (cm)	0.018	(mW/cm ²)
Measurement Result		
The predicted power density level at 20 cm is 0.018 mW/cm ² .		
This is below the uncontrolled exposure limit of 1 mW/cm ² at 5230MHz.		

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

MPE Prediction (802.11n_HT40 5250~5350)

MIMO gain= $G+(10 \log N)= 5.35+3.01= 8.36\text{dBm}$

Average output power at antenna input terminal:	11.92	(dBm)
Average output power at antenna input terminal:	15.559656	(mW)
Duty cycle:	90.44	(%)
Maximum Pav :	14.072153	(mW)
Peak Antenna gain (Maximum):	8.36	(dBi)
Peak Antenna gain (linear):	6.8548823	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5310	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm ²)
Power density at predication frequency at 20 (cm)	0.019	(mW/cm ²)
Measurement Result		
The predicted power density level at 20 cm is 0.019 mW/cm ² .		
This is below the uncontrolled exposure limit of 1 mW/cm ² at 5310MHz.		

MPE Prediction (802.11n_HT40 5470~5725)

MIMO gain= $G+(10 \log N)= 4.05+3.01= 7.06\text{dBm}$

Average output power at antenna input terminal:	11.98	(dBm)
Average output power at antenna input terminal:	15.776113	(mW)
Duty cycle:	90.44	(%)
Maximum Pav :	14.267916	(mW)
Peak Antenna gain (Maximum):	7.06	(dBi)
Peak Antenna gain (linear):	5.0815944	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5550	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm ²)
Power density at predication frequency at 20 (cm)	0.014	(mW/cm ²)
Measurement Result		
The predicted power density level at 20 cm is 0.014 mW/cm ² .		
This is below the uncontrolled exposure limit of 1 mW/cm ² at 5550MHz.		

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

MPE Prediction (802.11n_HT40 5725~5850)

MIMO gain= $G+(10 \log N)= 4.57+3.01= 7.58\text{dBm}$

Average output power at antenna input terminal:	11.81	(dBm)
Average output power at antenna input terminal:	15.170504	(mW)
Duty cycle:	90.44	(%)
Maximum Pav :	13.720204	(mW)
Peak Antenna gain (Maximum):	7.58	(dBi)
Peak Antenna gain (linear):	5.7279603	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5755	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm ²)
Power density at predication frequency at 20 (cm)	0.016	(mW/cm ²)

Measurement Result

The predicted power density level at 20 cm is 0.016 mW/cm².

This is below the uncontrolled exposure limit of 1 mW/cm² at 5755MHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

802.11ac VHT80M Max. output power

802.11ac VHT80 MIMO

CH	Frequency (MHz)	Data Rate	RAGE POWER (dBm)		TOTAL POWER (dBm)	TOTAL POWER (mW)	REQUIRED LIMIT (dBm)	RESULT
			CH 0	CH 1				
42	5210	MCS8	5.94	5.63	8.80	7.582	21.62	PASS
58	5290	MCS8	5.94	5.63	8.80	7.582	21.62 or 11+10log(B) = 30.08	PASS
106	5530	MCS8	6.02	5.3	8.69	7.388	22.92 or 11+10log(B) = 30.07	PASS
122	5610	MCS8	6.41	5.28	8.89	7.748	22.92 or 11+10log(B) = 30.12	PASS
155	5775	MCS8	6.21	5.28	8.78	7.551	28.42	PASS

MPE Prediction (802.11ac_VHT80 5150~5250)

MIMO gain= $G+(10 \log N)= 5.35+3.01= 8.36\text{dBm}$

Average output power at antenna input terminal:	8.80	(dBm)
Average output power at antenna input terminal:	7.5857758	(mW)
Duty cycle:	82.93	(%)
Maximum Pav :	6.2908838	(mW)
Peak Antenna gain (Maximum):	8.36	(dBi)
Peak Antenna gain (linear):	6.8548823	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5210	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm ²)
Power density at predication frequency at 20 (cm)	0.009	(mW/cm ²)
Measurement Result		
The predicted power density level at 20 cm is 0.009 mW/cm ² .		
This is below the uncontrolled exposure limit of 1 mW/cm ² at 5210MHz.		

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

MPE Prediction (802.11ac_VHT80 5250~5350)
MIMO gain= $G+(10 \log N)= 5.35+3.01= 8.36\text{dBm}$

Average output power at antenna input terminal:	8.80	(dBm)
Average output power at antenna input terminal:	7.5857758	(mW)
Duty cycle:	82.93	(%)
Maximum Pav :	6.2908838	(mW)
Peak Antenna gain (Maximum):	8.36	(dBi)
Peak Antenna gain (linear):	6.8548823	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5290	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm ²)
Power density at predication frequency at 20 (cm)	0.009	(mW/cm ²)
Measurement Result		
The predicted power density level at 20 cm is 0.009 mW/cm ² .		
This is below the uncontrolled exposure limit of 1 mW/cm ² at 5290MHz.		

MPE Prediction (802.11ac_VHT80 5470~5725)
MIMO gain= $G+(10 \log N)= 4.05+3.01= 7.06\text{dBm}$

Average output power at antenna input terminal:	8.89	(dBm)
Average output power at antenna input terminal:	7.744618	(mW)
Duty cycle:	82.93	(%)
Maximum Pav :	6.4226117	(mW)
Peak Antenna gain (Maximum):	7.06	(dBi)
Peak Antenna gain (linear):	5.0815944	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5610	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm ²)
Power density at predication frequency at 20 (cm)	0.006	(mW/cm ²)
Measurement Result		
The predicted power density level at 20 cm is 0.006 mW/cm ² .		
This is below the uncontrolled exposure limit of 1 mW/cm ² at 5610MHz.		

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

MPE Prediction (802.11ac_VHT80 5725~5850)
MIMO gain= $G+(10 \log N)= 4.57+3.01= 7.58\text{dBm}$

Average output power at antenna input terminal:	8.78	(dBm)
Average output power at antenna input terminal:	7.5509223	(mW)
Duty cycle:	82.93	(%)
Maximum Pav :	6.2619798	(mW)
Peak Antenna gain (Maximum):	7.58	(dBi)
Peak Antenna gain (linear):	5.7279603	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5775	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm ²)
Power density at predication frequency at 20 (cm)	0.007	(mW/cm ²)

Measurement Result

 The predicted power density level at 20 cm is 0.007 mW/cm².

 This is below the uncontrolled exposure limit of 1 mW/cm² at 5775MHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group