

FCC PART 15 SUBPART C TEST REPORT

for

Wireless PCI Card

Model No.: WP82RL

FCC ID: RXZ-WP82RL

of

Applicant: Pro-Nets Technology Corporation
Address: 7F, No. 95, Lide St., Chung Ho City 235 Taipei
Taiwan R.O.C.

Tested and Prepared

by

Worldwide Testing Services (Taiwan) Co., Ltd.

FCC Registration No.: 930600

Industry Canada filed test laboratory Reg. No. IC 5679A-1

A2LA Accredited No.: 2732.01



Report No.: W6M21010-10941-C-1

6F, NO. 58, LANE 188, RUEY-KUANG RD., NEIHU TAIPEI 114, TAIWAN, R.O.C.
TEL: 886-2-66068877 FAX: 886-2-66068879 E-mail: wts@wts-lab.com



TABLE OF CONTENTS

1	GENERAL INFORMATION.....	2
1.1	NOTES.....	2
1.2	TESTING LABORATORY	3
1.2.1	Location	3
1.2.2	Details of accreditation status	3
1.3	DETAILS OF APPROVAL HOLDER.....	3
1.4	APPLICATION DETAILS	4
1.5	GENERAL INFORMATION OF TEST ITEM.....	4
1.6	TEST STANDARDS.....	5
2	TECHNICAL TEST	6
2.1	SUMMARY OF TEST RESULTS	6
2.2	TEST ENVIRONMENT	6
2.3	TEST EQUIPMENT LIST.....	7
2.4	GENERAL TEST PROCEDURE	9
3	TEST RESULTS (ENCLOSURE)	11
3.1	PEAK OUTPUT POWER (TRANSMITTER).....	12
3.2	EQUIVALENT ISOTROPIC RADIATED POWER.....	14
3.3	RF EXPOSURE COMPLIANCE REQUIREMENTS	14
3.4	TRANSMITTER RADIATED EMISSIONS IN RESTRICTED BANDS.....	15
3.5	SPURIOUS EMISSIONS (TX).....	16
3.6	RADIATED EMISSION ON THE BAND EDGE	27
3.7	MINIMUM 6 dB BANDWIDTH.....	28
3.8	PEAK POWER SPECTRAL DENSITY	29
3.9	RADIATED EMISSION FROM DIGITAL PART	30
3.10	POWER LINE CONDUCTED EMISSION	31

APPENDIX



Registration number: W6M21010-10941-C-1
FCC ID: RXZ-WP82RL

1 General Information

1.1 Notes

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has passed all the relevant tests conforms to a specification.

Neither is there any guarantee that such a test sample will interwork with other genuinely open systems. The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that its performance generally conforms to representative cases of communications equipment.

The test results of this test report relate exclusively to the item tested as specified in 1.5.

The test report may only be reproduced or published in full.

Reproduction or publication of extracts from the report requires the prior written approval of the Worldwide Testing Services(Taiwan) Co., Ltd.


Specific Conditions:

Usage of the hereunder tested device in combination with other integrated or external antennas requires at least additional output power measurements, spurious emission measurements, conducted emission measurements (AC supply lines) and radio frequency exposure evaluations for each individual configuration performed, for certification by FCC.


The test sample is able to work according IEEE 802.11 b/g/n.

This report is related to FCC Part 15 C (DSSS and OFDM device).

Tester:

October 15, 2010	Robert Ren	
Date	WTS-Lab. Name	Signature

Technical responsibility for area of testing:

October 15, 2010	Chang Tse-Ming	
Date	WTS Name	Signature



Registration number: W6M21010-10941-C-1
FCC ID: RXZ-WP82RL

1.2 Testing laboratory

1.2.1 Location

OATS
No.5-1, Shuang Sing Village,
LiShuei Rd., Wanli Township,
Taipei County 207, Taiwan (R.O.C.)
Company
Worldwide Testing Services(Taiwan) Co., Ltd.
6F, NO. 58, LANE 188, RUEY-KUANG RD.
NEIHU, TAIPEI 114, TAIWAN R.O.C.
Tel : 886-2-66068877
Fax : 886-2-66068879

1.2.2 Details of accreditation status

Accredited testing laboratory

A2LA accredited number: 2732.01

FCC filed test laboratory Reg. No. 930600

Industry Canada filed test laboratory Reg. No. IC 5679A-1



Test location, where different from Worldwide Testing Services (Taiwan) Co., Ltd. :

Name: ./.
Accredited number: ./.
Street: ./.
Town: ./.
Country: ./.
Telephone: ./.
Fax: ./.

1.3 Details of approval holder

Name: Pro-Nets Technology Corporation
Street: 7F, No.95, Lide St., Chung Ho City
Town: 235 Taipei
Country: Taiwan R.O.C.
Telephone: +886-2-8221-8385
Fax: +886-2-8221-7009



Registration number: W6M21010-10941-C-1
FCC ID: RXZ-WP82RL

1.4 Application details

Date of receipt of test item: October 06, 2010
Date of test: from October 06, 2010 to October 14, 2010

1.5 General information of Test item

Type of test item: Wireless PCI Card
Model Number: WP82RL
Brand Name: PRO-NETS
Multi-listing model number: without
Photos: see Appendix

Technical data

Frequency band: 2.4 GHz – 2.4835 GHz

11b, 11g, 11n 20MHz

Frequency (ch 1 or A): 2.412 GHz
Frequency (ch 6 or B): 2.437 GHz
Frequency (ch 11 or C): 2.462 GHz

11n 40MHz

Frequency (ch 1 or A): 2.422 GHz
Frequency (ch 4 or B): 2.437 GHz
Frequency (ch 7 or C): 2.452 GHz

Number of Channels: 11b, 11g, 11n 20MHz: 11
11n 40MHz: 7

Operation modes: duplex

Modulation Type: DSSS / OFDM

Fixed point-to-point operation: Yes / No

Type of Antenna: Dipole Antenna

Antenna gain: 2.08 dBi

Power supply: 120VAC / 3.3V(from PC)

Emission designator: 11b: DSSS: 14M0G1D
11g: OFDM: 18M2W7D
11n 20MHz: OFDM: 18M4W7D
11n 40MHz: OFDM: 36M6W7D

Host device: none



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21010-10941-C-1
FCC ID: RXZ-WP82RL

Classification :

Fixed Device	<input checked="" type="checkbox"/>
Mobile Device (Human Body distance > 20cm)	<input type="checkbox"/>
Portable Device (Human Body distance < 20cm)	<input type="checkbox"/>
Modular Radio Device	<input type="checkbox"/>

Transmitter

Unom

Mode A (802.11b)

Power (ch 1 or A):	Conducted: 22.01 dBm
Power (ch 6 or B):	Conducted: 22.63 dBm
Power (ch 11 or C):	Conducted: 22.91 dBm

Mode B (802.11g)

Power (ch 1 or A):	Conducted: 17.30 dBm
Power (ch 6 or B):	Conducted: 17.98 dBm
Power (ch 11 or C):	Conducted: 18.33 dBm

Mode C (802.11n20MHz)

Power (ch 1 or A):	Conducted: 17.45 dBm
Power (ch 6 or B):	Conducted: 18.03 dBm
Power (ch 11 or C):	Conducted: 18.24 dBm

Mode D (802.11n40MHz)

Power (ch 1 or A):	Conducted: 17.79 dBm
Power (ch 4 or B):	Conducted: 18.00 dBm
Power (ch 7 or C):	Conducted: 18.29 dBm

Manufacturer: (if applicable)

Name:	./.
Street:	./.
Town:	./.
Country:	./.

1.6 Test standards

Technical standard : FCC RULES PART 15 SUBPART C § 15.247 (2009-10)



Registration number: W6M21010-10941-C-1
FCC ID: RXZ-WP82RL

2 Technical test

2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests performed.

or

The deviations as specified in 2.5 were ascertained in the course of the tests performed.

2.2 Test environment

Temperature: 23 °C
Relative humidity content: 20 ... 75 %
Air pressure: 86 ... 103 kPa
Power supply: 120VAC / 3.3Vdc (from PC)
Extreme conditions parameters: ./.



Registration number: W6M21010-10941-C-1
 FCC ID: RXZ-WP82RL

2.3 Test Equipment List

No.	Test equipment	Type	Serial No.	Manufacturer	Cal. Date	Next Cal. Date
ETSTW-CE 001	EMI TEST RECEIVER	ESHS10	842121/013	R&S	2010/9/2	2011/9/1
ETSTW-CE 004	ZWEILEITER-V- NETZNACHBILDUNG TWO- LINE V-NETWORK	ESH3-Z5	840731/011	R&S	2010/3/2	2011/3/1
ETSTW-CE 005	Line-Impedance Stabilisation Network	NNBM 8126D	137	Schwarzbeck	2010/9/8	2011/9/7
ETSTW-CE 006	IMPULSBEGRENZER PULSE LIMITER	ESH3-Z2	100226	R&S	2010/5/8	2011/5/7
ETSTW-CE 007	SPECTRUM ANALYZER 5GHz	FSB	849670/001	R&S	Pre-test Use NCR	
ETSTW-CE 008	HF-EICHLITUNG RF STEP ATTENUATOR 139dB DPSP	334.6010.02	844581/024	R&S	Function Test	
ETSTW-CE 009	TEMP.&HUMIDITY CHAMBER	GTH-225-40-1P-U	MAA0305-009	GIANT FORCE	2010/7/21	2011/7/19
ETSTW-CE 015	CISPR 22 TWO BALANCED TELECOM PAIRS IMPEDANCE STABILIZATION NETWORK	FCC-TLISN-T8-02	20307	FCC	2010/9/6	2011/9/5
ETSTW-RE 002	Function Generator	33220A	MY43004982	Agilent	Function Test	
ETSTW-RE 003	EMI TEST RECEIVER	ESI 26	831438/001	R&S	2010/8/10	2011/8/9
ETSTW-RE 004	EMI TEST RECEIVER	ESI 40	832427/004	R&S	2010/9/14	2011/9/13
ETSTW-RE 005	EMI TEST RECEIVER	ESVS10	843207/020	R&S	2010/9/2	2011/9/1
ETSTW-RE 006	Attenuator 10dB	50HF-010-5N-1	None	STEP	2010/3/5	2011/3/4
ETSTW-RE 010	ABSORBING CLAMP	MDS 21	3469	Schwarzbeck	2010/9/6	2011/9/5
ETSTW-RE 012	TUNABLE BANDREJECT FILTER	D.C 0309	146	K&L	Function Test	
ETSTW-RE 013	TUNABLE BANDREJECT FILTER	D.C 0336	397	K&L	Function Test	
ETSTW-RE 018	MICROWAVE HORN ANTENNA	AT4560	27212	AR	2010/9/8	2011/9/7
ETSTW-RE 020	MICROWAVE HORN ANTENNA	AT4002A	306915	AR	Function Test	
ETSTW-RE 021	SWEEP GENERATOR	SWM05	835130/010	R&S	2010/8/20	2011/8/19
ETSTW-RE 027	Passive Loop Antenna	6512	00034563	EMCO	2010/7/22	2011/7/21
ETSTW-RE 028	Log-Periodic Dipole Array Antenna	3148	34429	EMCO	2010/4/14	2011/4/13
ETSTW-RE 029	Biconical Antenna	3109	33524	EMCO	2010/4/14	2011/4/13
ETSTW-RE 030	Double-Ridged Guide Horn Antenna	3117	00035224	EMCO	2010/3/2	2011/3/1
ETSTW-RE 032	Millivoltmeter	URV 55	849086/013	R&S	2010/8/17	2011/8/16
ETSTW-RE 033	WaveRunner 6000A Serie Oscilloscope	WAVERUNNER 6100A	LCRY0604P14508	LeCroy	Function Test	
ETSTW-RE 034	Power Sensor	URV5-Z4	839313/006	R&S	2010/8/17	2011/8/16
ETSTW-RE 044	Log-Periodic Antenna	HL050	100094	R&S	2010/5/11	2011/5/10
ETSTW-RE 047	PSA SERIES SPECTRUM ANALYZER	E4445A	MY46181369	Agilent	Pre-test Use NCR	
ETSTW-RE 048	Triple Loop Antenna	HXYZ 9170	HXYZ 9170-134	Schwarzbeck	2010/8/30	2011/8/29
ETSTW-RE 049	TRILOG Super Broadband test Antenna	VULB 9160	9160-3185	Schwarzbeck	2010/4/13	2011/4/12
ETSTW-RE 051	Attenuator 6dB	50HF-006-1	None	JFW	2010/3/5	2011/3/4
ETSTW-RE 053	Attenuator 3dB	50HF-003-1	None	JFW	2010/3/5	2011/3/4
ETSTW-RE 055	SPECTRUM ANALYZER	FSU 26	200074	R&S	2010/6/3	2011/6/2



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21010-10941-C-1
 FCC ID: RXZ-WP82RL

ETSTW-RE 060	Attenuator 30dB	5015-30	F651012z-01	ATM	Pre-test Use NCR	
ETSTW-RE 061	Amplifier Module	CHC 1	None	ETS	2010/9/27	2011/9/26
ETSTW-RE 062	Amplifier Module	CHC 2	None	KMIC	2009/11/12	2010/11/11
ETSTW-RE 064	Bluetooth Test Set	MT8852B-042	6K00005709	Anritsu	Function Test	
ETSTW-RE 065	Amplifier	AMF-6F-18002650-25-10P	941608	MITEQ	2010/4/13	2011/4/12
ETSTW-RE 066	Highpass Filter	H1G013G1	206015	MICROWAVE CIRCUITS, INC.	2010/3/5	2011/3/4
ETSTW-RE 072	CELL SITE TEST SET	8921A	3339A00375	HP	2010/9/30	2011/9/29
ETSTW-RE 073	Power Meter	N1911A	MY45100769	Agilent	2010/1/7	2011/1/6
ETSTW-RE 074	Power Sensor	N1921A	MY45241198	Agilent	2010/1/7	2011/1/6
ETSTW-RE 081	Highpass Filter	H03G13G1	4260-02 DC0428	MICROWAVE CIRCUITS, INC.	2010/3/5	2011/3/4
ETSTW-RE 096	SIGNAL GENERATOR	SMIQ 03B	102274	R&S	2010/5/31	2011/5/30
ETSTW-RE 099	DC Block	50DB-007-1	None	JFW	2010/3/5	2011/3/4
ETSTW-RE 105	2.4GHz Notch Filter	NO124411	39555	MICROWAVE CIRCUITS, INC.	2010/3/25	2011/3/24
ETSTW-RE 106	Humidity Temperature Meter	TES-1366	091011113	TES	2010/3/25	2011/3/24
ETSTW-GSM 002	Universal Radio Communication Tester	CMU 200	109439	R&S	2010/9/8	2011/9/7
ETSTW-GSM 019	Band Reject Filter	WRCTF824/849-822/851-40/12+9SS	3	WI	Function Test	
ETSTW-GSM 020	Band Reject Filter	WRCD1747/1748-1743/1752-32/5SS	1	WI	Function Test	
ETSTW-GSM 021	Band Reject Filter	WRCD1879.5/1880.5-1875.5/1884.5-32/5SS	3	WI	Function Test	
ETSTW-GSM 022	Band Reject Filter	WRCT901.9/903.1-904.25-50/8SS	1	WI	Function Test	
ETSTW-GSM 023	Power Divider	4901.19.A	None	SUHNER	2010/9/20	2011/9/19
ETSTW-Cable 002	Microwave Cable	SUCOFLEX 104 (S Cable 7)	238093	HUBER+SUHNER	2010/9/27	2011/9/26
ETSTW-Cable 003	Microwave Cable	SUCOFLEX 104 (S Cable 11)	209953	HUBER+SUHNER	2010/9/27	2011/9/26
ETSTW-Cable 006	Microwave Cable	SUCOFLEX 104 (S Cable 8)	238095	HUBER+SUHNER	2010/3/5	2011/3/4
ETSTW-Cable 010	BNC Cable	5 M BNC Cable	None	JYE BAO CO.,LTD.	2010/3/5	2011/3/4
ETSTW-Cable 011	BNC Cable	BNC Cable 1	None	JYE BAO CO.,LTD.	2010/8/19	2011/8/18
ETSTW-Cable 012	BNC Cable	BNC Cable 2	None	JYE BAO CO.,LTD.	2010/8/19	2011/8/18
ETSTW-Cable 013	Microwave Cable	SUCOFLEX 104 (S Cable 5)	232345	HUBER+SUHNER	2010/3/5	2011/3/4
ETSTW-Cable 022	N TYPE Cable	OATS Cable 3	0002	JYE BAO CO.,LTD.	2010/3/5	2011/3/4
ETSTW-Cable 028	Microwave Cable	FA147A0015M2020	30064-2	UTIFLEX	2010/9/13	2011/9/12
ETSTW-Cable 029	Microwave Cable	FA147A0015M2020	30064-3	UTIFLEX	2010/9/13	2011/9/12
ETSTW-Cable 039	Microwave Cable	SUCOFLEX 104 (S Cable 19)	316739	HUBER+SUHNER	2010/3/5	2011/3/4
WTSTW-SW 001	EMI TEST SOFTWARE	Harmonics-1000	None	EMC PARTNER	HARCS Version 4.16 Firmware Version 2.18	
WTSTW-SW 002	EMI TEST SOFTWARE	EZ_EMG	None	Farad	Version ETS-03A1	
WTSTW-SW 003	EMS TEST SOFTWARE	i2	None	AUDIX	Version 3.2007-8-17b	
WTSTW-SW 005	GSM Fading Level Correction	GSMFadLevCor	None	R&S	Version 1.66	



Registration number: W6M21010-10941-C-1
FCC ID: RXZ-WP82RL

2.4 General Test Procedure

POWER LINE CONDUCTED INTERFERENCE: The procedure used was ANSI STANDARD C63.4-2003 using a 50 μ H LISN (if necessary). Both lines were observed. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed.

RADIATION INTERFERENCE: The test procedure used was according to ANSI STANDARD C63.4-2003 employing a spectrum analyzer. For investigated frequency is equal to or below 1GHz, the RBW and VBW of the spectrum analyzer was 100 kHz and 100kHz respectively with an appropriate sweep speed. For investigated frequency is above 1GHz, both of RBW and VBW of the spectrum analyzer were 1 MHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dB μ V) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB.

Example:

Freq (MHz) METER READING + ACF + CABLE LOSS (to the receiver) = FS
33 20 dB μ V + 10.36 dB + 6 dB = 36.36 dB μ V/m @3m

The EUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m (non metallic table) and arranged according to ANSI C63.4-2003 Section 13.1.2. The table used for radiated measurements is capable of continuous rotation. The spectrum was scanned from 30 MHz to the frequency specified as follows:

- (1) If the intentional radiator operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
- (2) If the intentional radiator operates at or above 10 GHz and below 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.
- (3) If the intentional radiator operates at or above 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 200 GHz, whichever is lower, unless specified otherwise elsewhere in the rules.
- (4) If the intentional radiator contains a digital device, regardless of whether this digital device controls the functions of the intentional radiator or the digital device is used for additional control or function purposes other than to enable the operation of the intentional radiator, the frequency range shall be investigated up to the range specified in paragraphs (a)(1)-(a)(3) of this section or the range applicable to the digital device, as shown in paragraph (b)(1) of this Section, whichever is the higher frequency range of investigation.

For hand-held devices, a exploratory test was performed with three (3) orthogonal planes to determine the highest emissions.

Measurements were made by Worldwide Testing Services(Taiwan) Co., Ltd. at the registered open field test site located at No.5-1, Shuang Sing Village, LiShuei Rd., Wanli Township, Taipei County 207, Taiwan (R.O.C.) The Registration Number: 930600.



Registration number: W6M21010-10941-C-1

FCC ID: RXZ-WP82RL

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

When the radiated emission limits are expressed in terms of the average value of the emission, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.

The formula is as follows:

Average = Peak + Duty Factor

Duty Factor = $20 \log(\text{dwell time}/T)$

T = 100ms when the pulse train period is over 100 ms or the period of the pulse train.

Modified Limits for peak according to 15.35 (b) = Max Permitted average Limits + 20dB



Registration number: W6M21010-10941-C-1
 FCC ID: RXZ-WP82RL

3 Test results (enclosure)

TEST CASE	Para. Number	Required	Test passed	Test failed
Peak Output Power	15.247(b)(3)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Equivalent radiated Power	15.247(b)(3)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Spurious Emissions radiated – Transmitter operating	15.247(c): 15.209	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Band Edge Measurement	15.247(c)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Minimum 6 dB Bandwidth	15.247(a)(2)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Peak Power Spectral Density	15.247(d)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Radiated Emission from Digital Part	15.109	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Power Line Conducted Emission	15.207	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>

Note:

1. This EUT incorporates a MIMO function with IEEE 802.11b, 802.11g, and 802.11n draft 2.0. Physically, this EUT includes two transmitters and two receivers with two incoherent streams. This device uses multiplexing and also employ cyclic delay diversity to improve range and throughput, and this device simultaneously operates on two adjacent channels.
2. This EUT is 2*2 spatial MIMO (2Tx&2Rx) without beam forming function. That operates dual chain configuration. The Pre-test was performed to determine the worst case mode from all possible combinations between all available modulations, data rates, bandwidths, and spatial stream modes.
3. The worst case mode was base on the investigations by measuring the peak and average power according to the description above. The detail of chosen mode for full testing are as below:

Mode	Available channel	Chosen Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	1,6,11	DSSS	DBPSK	1
802.11g	1 to 11	1,6,11	OFDM	BPSK	6
Draft 802.11n (20MHz)	1 to 11	1,6,11	OFDM	BPSK	6.5
Draft 802.11n (40MHz)	1 to 7	1,4,7	OFDM	BPSK	13.5

4. Because both antennas operate simultaneously, when performed the relevant conducted measurement(ex. RF output power, peak power spectral density....and so on), we basically use a splitter to combine each antenna port in order to get the total measuring results.



Registration number: W6M21010-10941-C-1
 FCC ID: RXZ-WP82RL

3.1 Peak Output Power (transmitter)

FCC Rule: 15.247(b)(3)

This measurement applies to equipment with an integral antenna and to equipment with an antenna connector and equipped with an antenna as declared by the applicant.

The power was measured with modulation (declared by the applicant).

Mode 802.11b

Test condition		Conducted Power		
		Channel A	Channel B	Channel C
$T_{nom} = 23^{\circ}C$	$V_{nom} = 120\ V$	[dBm]	[dBm]	[dBm]
		22.01	22.63	22.91

Mode 802.11g

Test condition		Conducted Power		
		Channel A	Channel B	Channel C
$T_{nom} = 23^{\circ}C$	$V_{nom} = 120\ V$	[dBm]	[dBm]	[dBm]
		17.30	17.98	18.33

Mode 802.11n 20MHz

Test condition		Conducted Power		
		Channel A	Channel B	Channel C
$T_{nom} = 23^{\circ}C$	$V_{nom} = 120\ V$	[dBm]	[dBm]	[dBm]
		17.45	18.03	18.24

Mode 802.11n 40MHz

Test condition		Conducted Power		
		Channel A	Channel B	Channel C
$T_{nom} = 23^{\circ}C$	$V_{nom} = 120\ V$	[dBm]	[dBm]	[dBm]
		17.79	18.00	18.29



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21010-10941-C-1
 FCC ID: RXZ-WP82RL

Mode 802.11b

Test condition $T_{nom} = \text{--}^{\circ}\text{C}, V_{nom} = \text{--} \text{ V}$	Signal Field strength TX highest power mode dB μ V/m
Frequency [MHz]	--
--	

Mode 802.11g

Test condition $T_{nom} = \text{--}^{\circ}\text{C}, V_{nom} = \text{--} \text{ V}$	Signal Field strength TX highest power mode dB μ V/m
Frequency [MHz]	--
--	

Mode 802.11n 20MHz

Test condition $T_{nom} = \text{--}^{\circ}\text{C}, V_{nom} = \text{--} \text{ V}$	Signal Field strength TX highest power mode dB μ V/m
Frequency [MHz]	--
--	

Mode 802.11n 40MHz

Test condition $T_{nom} = \text{--}^{\circ}\text{C}, V_{nom} = \text{--} \text{ V}$	Signal Field strength TX highest power mode dB μ V/m
Frequency [MHz]	--
--	

Limits:

Frequency MHz	Power dBm
902 - 928	30
2400 – 2483.5	30
5725 – 5850	30

In case of employing transmitter antennas having antenna gain > 6 dBi and using fixed point-to point operation consider §15.247 (b)(4)

Test equipment used: ETSTW-RE 055

Explanation: The diagrams for the peak output power measurements are included in Appendix.



Registration number: W6M21010-10941-C-1
 FCC ID: RXZ-WP82RL

3.2 Equivalent isotropic radiated power

FCC Rule: 15.247(b)(3)

EIRP = max. conducted output power + antenna gain
 EIRP = 22.91 dBm + 2.08dBi
 = 24.99 dBm

Limit: EIRP = +36 dBm for Antenna gain <2.08dBi

Test equipment used: ETSTW-RE 055

3.3 RF Exposure Compliance Requirements

FCC OET Bulletin 65 Edition 97.01 determines the equations for predicting RF fields and applicable limits.

The prediction for power density in the far-field but will over-predict power density in the near field, where it could be used for walking a “worst case” or conservative prediction.

$$S = \frac{PG}{4 \pi R^2}$$

- S – Power Density
- P – Output power ERP
- R – Distance
- D – Cable Loss
- AG – Antenna Gain

Item	Unit	Value	Remarks
P	mW	195.4339	Peak value
D	dB		
AG	dBi	2.08	
G		1.6	Calculated Value
R	cm	20	Assumed value
S	mW/cm ²	0.0622	Calculated value

Limits:

Limit for General Population / Uncontrolled Exposure	
Frequency (MHz)	Power Density (mW/cm ²)
1500 – 100.000	1.0



Registration number: W6M21010-10941-C-1
FCC ID: RXZ-WP82RL

3.4 Transmitter Radiated Emissions in Restricted Bands

FCC Rules: 15.247 (c), 15.205, 15.209, 15.35

Radiated emission measurements were performed from 30 MHz to 26500 MHz.

For radiated emission tests, the analyzer setting was as followings:

Frequency \leq 1 GHz, RBW:100 kHz, VBW: 100 kHz (Peak measurements)

Frequency $>$ 1 GHz, RBW: 1 MHz, VBW: 1 MHz (Peak measurements)

Frequency $>$ 1 GHz , RBW:1 MHz , VBW: 10 Hz (Average measurements)

Limits.

For frequencies below 1GHz:

Frequency of Emission (MHz)	Field strength (microvolts/meter)	Field Strength (dB microvolts/meter)
30 - 88	100	40.0
88 - 216	150	43.5
216 - 960	200	46.0
Above	500	54.0

For frequencies above 1GHz (Average measurements).

Guidance on Measurement of Digit Transmission Systems:

“If the emission is pulsed, modify the unit for continuous operation, use the setting shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation.”

The correction factor, based on the total channel dwell time in a 100 ms period, may be mathematically applied to a measurement made with an average detector, to further reduce the value.

Duty cycle correction = $20 \log (\text{dwell time} / 100\text{ms})$

Note: No duty cycle correction was added to the reading of this EUT.

Explanation: see attached diagrams in Appendix.



Registration number: W6M21010-10941-C-1

FCC ID: RXZ-WP82RL

3.5 Spurious Emissions (tx)

Spurious emission was measured with modulation (declared by manufacturer).

In any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c))

FCC Rule: 15.247(c), 15.35

For out of band emissions that are close to or that exceed the 20 dB attenuation requirement described in the specification, radiated measurements were performed at a 3 m separation distance to determine whether these emissions complied with the general radiated emission requirement.

Limits:

For frequencies above 1GHz (Peak measurements).

Modified Limit for peak according to 15.35 (b) = Max Permitted average Limits + 20dB

For frequencies above 1GHz (Average measurements).

Max. reading – 20dB

Max. reading – 20 dB

Guidance on Measurement of Digit Transmission Systems:

“If the emission is pulsed, modify the unit for continuous operation, use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation.”

The correction factor, based on the total channel dwell time in a 100 ms period, may be mathematically applied to a measurement made with an average detector, to further reduce the value.

Duty Cycle correction = $20 \log (\text{dwell time}/100\text{ms})$

Test equipment used: ETSTW-RE 003, ETSTW-RE 004, ETSTW-RE 018, ETSTW-RE 028,
ETSTW-RE 029, ETSTW-RE 030, ETSTW-RE 044

Note: No duty cycle correction was added to the reading of EUT.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21010-10941-C-1
 FCC ID: RXZ-WP82RL

SAMPLE CALCULATION OF LIMIT. All results will be updated by an automatic measuring system in accordance with point 2.3.

Calculation of test results:

Such factors like antenna correction, cable loss, external attenuation etc. are already included in the provided measurement results. This is done by using validated test software and calibrated test system according the accreditation requirements.

The peak and average spurious emission plots was measured with the average limits.

In the Table being listed the critical peak and average value and exhibit the compliance with the above calculated Limits.

If in the column's correction factor states a value then the max. Field strength in the same row is corrected by a value gained from the "Correction Factor".

Model: WP82RL Date: 2010/10/8
 Mode: 802.11b CH1 Temperature: 27.9 °C Engineer: Robert
 Polarization: Horizontal Humidity: 58 %

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
280.5210	17.00	peak	15.74	32.74	46.00	-13.26	60	150
610.0200	6.96	peak	23.67	30.63	46.00	-15.37	160	150
988.7776	7.40	peak	29.07	36.47	54.00	-17.53	290	150

Polarization: Horizontal

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
3000.0000	48.88	---	-4.56	44.32	---	74.00	54.00	-29.68	280	150
4820.5130	48.40	---	-4.95	43.45	---	74.00	54.00	-30.55	160	150
7236.0000	47.24	---	-2.37	44.87	---	74.00	54.00	-29.13	180	150

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
280.5210	16.60	peak	15.74	32.34	46.00	-13.66	300	150
610.0200	6.29	peak	23.67	29.96	46.00	-16.04	160	150
970.5411	7.96	peak	28.84	36.80	54.00	-17.20	220	150

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
2814.1030	54.65	---	-6.26	48.39	---	74.00	54.00	-25.61	290	150
4824.0000	45.22	---	-4.94	40.28	---	74.00	54.00	-33.72	120	150
7236.0000	47.15	---	-2.37	44.78	---	74.00	54.00	-29.22	290	150



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21010-10941-C-1
 FCC ID: RXZ-WP82RL

Mode: 802.11b CH6
 Polarization: Horizontal

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
278.3566	13.88	peak	15.65	29.53	46.00	-16.47	230	150
611.4230	6.57	peak	23.69	30.26	46.00	-15.74	160	150
994.3887	8.15	peak	29.15	37.30	54.00	-16.70	290	150

Polarization: Horizontal

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
3002.0040	51.01	---	-4.56	46.45	---	74.00	54.00	-27.55	130	150
4873.7480	50.80	---	-4.86	45.94	---	74.00	54.00	-28.06	180	150
7311.0000	48.48	---	-2.76	45.72	---	74.00	54.00	-28.28	160	150

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
280.5210	16.50	peak	15.74	32.24	46.00	-13.76	160	150
611.4230	6.78	peak	23.69	30.47	46.00	-15.53	160	150
994.3887	7.57	peak	29.15	36.72	54.00	-17.28	180	150

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
3002.0040	47.32	---	-4.56	42.76	---	74.00	54.00	-31.24	290	150
4874.0000	46.73	---	-4.86	41.87	---	74.00	54.00	-32.13	280	150
7311.0000	48.56	---	-2.76	45.80	---	74.00	54.00	-28.20	160	150

Mode: 802.11b CH11
 Polarization: Horizontal

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
279.4388	12.81	peak	15.70	28.51	46.00	-17.49	100	150
610.0200	7.72	peak	23.67	31.39	46.00	-14.61	130	150
984.5691	7.34	peak	29.02	36.36	54.00	-17.64	190	150



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21010-10941-C-1
 FCC ID: RXZ-WP82RL

Polarization: Horizontal

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
3000.0000	49.32	---	-4.56	44.76	---	74.00	54.00	-29.24	160	150
4923.0770	49.78	---	-4.89	44.89	---	74.00	54.00	-29.11	140	150
7386.0000	47.42	---	-3.09	44.33	---	74.00	54.00	-29.67	160	150

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
280.5210	13.07	peak	15.74	28.81	46.00	-17.19	230	150
610.0200	7.65	peak	23.67	31.32	46.00	-14.68	260	150
981.7635	7.97	peak	28.98	36.95	54.00	-17.05	130	150

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
3000.0000	49.17	---	-4.56	44.61	---	74.00	54.00	-29.39	160	150
4924.0000	46.78	---	-4.89	41.89	---	74.00	54.00	-32.11	290	150
7386.0000	47.06	---	-3.09	43.97	---	74.00	54.00	-30.03	180	150

Mode: 802.11g CH1

Polarization: Horizontal

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
283.2264	14.94	peak	15.81	30.75	46.00	-15.25	130	150
611.4230	6.76	peak	23.69	30.45	46.00	-15.55	160	150
1000.0000	7.22	peak	29.22	36.44	54.00	-17.56	210	150

Polarization: Horizontal

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
3000.0000	48.29	---	-4.56	43.73	---	74.00	54.00	-30.27	130	150
4824.0000	46.66	---	-4.94	41.72	---	74.00	54.00	-32.28	290	150
7236.0000	46.86	---	-2.37	44.49	---	74.00	54.00	-29.51	130	150



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21010-10941-C-1
 FCC ID: RXZ-WP82RL

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
280.5210	17.09	peak	15.74	32.83	46.00	-13.17	100	150
610.0200	7.29	peak	23.67	30.96	46.00	-15.04	100	150
983.1662	7.76	peak	29.00	36.76	54.00	-17.24	290	150

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
3000.0000	50.00	---	-4.56	45.44	---	74.00	54.00	-28.56	160	150
4824.0000	45.03	---	-4.94	40.09	---	74.00	54.00	-33.91	250	150
7236.0000	46.34	---	-2.37	43.97	---	74.00	54.00	-30.03	160	150

Mode: 802.11g CH6

Polarization: Horizontal

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
280.5210	13.96	peak	15.74	29.70	46.00	-16.30	310	150
610.0200	7.02	peak	23.67	30.69	46.00	-15.31	130	150
976.1522	7.73	peak	28.91	36.64	54.00	-17.36	190	150

Polarization: Horizontal

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
2997.9960	50.93	---	-4.58	46.35	---	74.00	54.00	-27.65	260	150
4873.7480	50.31	---	-4.86	45.45	---	74.00	54.00	-28.55	260	150
7311.0000	50.39	---	-2.76	47.63	---	74.00	54.00	-26.37	100	150

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
280.5210	17.31	peak	15.74	33.05	46.00	-12.95	130	150
610.0200	7.00	peak	23.67	30.67	46.00	-15.33	130	150
981.7635	8.36	peak	28.98	37.34	54.00	-16.66	290	150



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21010-10941-C-1
 FCC ID: RXZ-WP82RL

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
3250.5010	47.60	---	-4.53	43.07	---	74.00	54.00	-30.93	290	150
4873.7480	49.69	---	-4.86	44.83	---	74.00	54.00	-29.17	140	150
7311.0000	49.52	---	-2.76	46.76	---	74.00	54.00	-27.24	290	150

Mode: 802.11g CH11

Polarization: Horizontal

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
274.5690	14.58	peak	15.45	30.03	46.00	-15.97	130	150
610.0200	6.69	peak	23.67	30.36	46.00	-15.64	130	150
983.1662	7.28	peak	29.00	36.28	54.00	-17.72	280	150

Polarization: Horizontal

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
3000.0000	50.48	---	-4.56	45.92	---	74.00	54.00	-28.08	300	150
4923.0770	53.12	---	-4.89	48.23	---	74.00	54.00	-25.77	180	150
7391.0260	51.60	---	-3.11	48.49	---	74.00	54.00	-25.51	160	150

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
280.5210	16.93	peak	15.74	32.67	46.00	-13.33	130	150
610.0200	8.17	peak	23.67	31.84	46.00	-14.16	200	150
983.1662	7.51	peak	29.00	36.51	54.00	-17.49	190	150

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
3000.0000	51.49	---	-4.56	46.93	---	74.00	54.00	-27.07	180	150
4923.0770	51.34	---	-4.89	46.45	---	74.00	54.00	-27.55	280	150
7386.0000	48.22	---	-3.09	45.13	---	74.00	54.00	-28.87	140	150



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21010-10941-C-1
 FCC ID: RXZ-WP82RL

Mode: 802.11n 20M CH1
 Polarization: Horizontal

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
282.1442	13.73	peak	15.78	29.51	46.00	-16.49	130	150
610.0200	7.63	peak	23.67	31.30	46.00	-14.70	160	150
991.5832	7.50	peak	29.11	36.61	54.00	-17.39	190	150

Polarization: Horizontal

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
3000.0000	50.73	---	-4.56	46.17	---	74.00	54.00	-27.83	230	150
4820.5130	48.70	---	-4.95	43.75	---	74.00	54.00	-30.25	290	150
7236.0000	46.70	---	-2.37	44.33	---	74.00	54.00	-29.67	130	150

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
280.5210	16.80	peak	15.74	32.54	46.00	-13.46	130	150
610.0200	7.04	peak	23.67	30.71	46.00	-15.29	130	150
980.3606	7.84	peak	28.96	36.80	54.00	-17.20	160	150

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
3000.0000	51.13	---	-4.56	46.57	---	74.00	54.00	-27.43	230	150
4824.0000	46.43	---	-4.94	41.49	---	74.00	54.00	-32.51	290	150
7236.0000	47.52	---	-2.37	45.15	---	74.00	54.00	-28.85	50	150

Mode: 802.11n 20M CH6
 Polarization: Horizontal

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
274.0280	14.05	peak	15.42	29.47	46.00	-16.53	130	150
610.0200	7.97	peak	23.67	31.64	46.00	-14.36	130	150
991.5832	7.58	peak	29.11	36.69	54.00	-17.31	290	150



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21010-10941-C-1
 FCC ID: RXZ-WP82RL

Polarization: Horizontal

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
2997.9960	50.34	---	-4.58	45.76	---	74.00	54.00	-28.24	200	150
4874.0000	48.69	---	-4.86	43.83	---	74.00	54.00	-30.17	100	150
7311.0000	48.09	---	-2.76	45.33	---	74.00	54.00	-28.67	260	150

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
280.5210	16.50	peak	15.74	32.24	46.00	-13.76	130	150
611.4230	6.58	peak	23.69	30.27	46.00	-15.73	130	150
977.5551	7.64	peak	28.93	36.57	54.00	-17.43	190	150

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
2997.9960	47.49	---	-4.58	42.91	---	74.00	54.00	-31.09	160	150
4874.0000	47.41	---	-4.86	42.55	---	74.00	54.00	-31.45	280	150
7311.0000	48.39	---	-2.76	45.63	---	74.00	54.00	-28.37	160	150

Mode: 802.11n 20M CH11

Polarization: Horizontal

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
280.5210	13.29	peak	15.74	29.03	46.00	-16.97	110	150
610.0200	6.47	peak	23.67	30.14	46.00	-15.86	130	150
970.5411	9.01	peak	28.84	37.85	54.00	-16.15	160	150

Polarization: Horizontal

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
3000.0000	50.25	---	-4.56	45.69	---	74.00	54.00	-28.31	130	150
4923.0770	51.69	---	-4.89	46.80	---	74.00	54.00	-27.20	180	150
7391.0260	55.37	41.26	-3.11	52.26	38.15	74.00	54.00	-15.85	160	150



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21010-10941-C-1
 FCC ID: RXZ-WP82RL

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
280.5210	16.80	peak	15.74	32.54	46.00	-13.46	130	150
612.8256	6.58	peak	23.70	30.28	46.00	-15.72	130	150
983.1662	7.53	peak	29.00	36.53	54.00	-17.47	290	150

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
3000.0000	51.03	---	-4.56	46.47	---	74.00	54.00	-27.53	190	150
4923.0770	49.02	---	-4.89	44.13	---	74.00	54.00	-29.87	150	150
7386.0580	60.13	51.10	-3.09	57.04	48.01	74.00	54.00	-5.99	359	150

Mode: 802.11n 40M CH1

Polarization: Horizontal

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
265.9118	12.12	peak	15.05	27.17	46.00	-18.83	200	150
611.4230	7.48	peak	23.69	31.17	46.00	-14.83	100	150
995.7916	7.97	peak	29.17	37.14	54.00	-16.86	200	150

Polarization: Horizontal

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
3000.0000	49.11	---	-4.56	44.55	---	74.00	54.00	-29.45	300	150
4820.5130	48.49	---	-4.95	43.54	---	74.00	54.00	-30.46	140	150
7250.0000	53.96	---	-2.44	51.52	---	74.00	54.00	-22.48	290	150

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
280.5210	17.81	peak	15.74	33.55	46.00	-12.45	300	150
611.4230	6.90	peak	23.69	30.59	46.00	-15.41	130	150
997.1943	7.78	peak	29.18	36.96	54.00	-17.04	160	150



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21010-10941-C-1
 FCC ID: RXZ-WP82RL

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
3000.0000	50.48	---	-4.56	45.92	---	74.00	54.00	-28.08	160	150
4844.0000	45.12	---	-4.91	40.21	---	74.00	54.00	-33.79	160	150
7243.5900	53.36	---	-2.41	50.95	---	74.00	54.00	-23.05	210	150

Mode: 802.11n 40M CH4

Polarization: Horizontal

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
283.2264	14.71	peak	15.81	30.52	46.00	-15.48	300	150
611.4230	7.11	peak	23.69	30.80	46.00	-15.20	130	150
974.7495	7.68	peak	28.89	36.57	54.00	-17.43	100	150

Polarization: Horizontal

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
3002.0040	51.09	---	-4.56	46.53	---	74.00	54.00	-27.47	230	150
4874.0000	46.85	---	-4.86	41.99	---	74.00	54.00	-32.01	250	150
7311.0000	48.53	---	-2.76	45.77	---	74.00	54.00	-28.23	160	150

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
279.9800	16.46	peak	15.73	32.19	46.00	-13.81	130	150
610.0200	9.27	peak	23.67	32.94	46.00	-13.06	300	150
991.5832	7.86	peak	29.11	36.97	54.00	-17.03	190	150

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
2997.9960	47.93	---	-4.58	43.35	---	74.00	54.00	-30.65	190	150
4874.0000	46.55	---	-4.86	41.69	---	74.00	54.00	-32.31	280	150
7311.0000	47.89	---	-2.76	45.13	---	74.00	54.00	-28.87	160	150



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21010-10941-C-1
 FCC ID: RXZ-WP82RL

Mode: 802.11n 40M CH7
 Polarization: Horizontal

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
279.4388	13.98	peak	15.70	29.68	46.00	-16.32	130	150
610.0200	7.11	peak	23.67	30.78	46.00	-15.22	130	150
974.7495	7.22	peak	28.89	36.11	54.00	-17.89	190	150

Polarization: Horizontal

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
3000.0000	49.77	---	-4.56	45.21	---	74.00	54.00	-28.79	160	150
4904.0000	45.99	---	-4.83	41.16	---	74.00	54.00	-32.84	160	150
7326.9230	50.87	---	-2.83	48.04	---	74.00	54.00	-25.96	180	150

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
280.5210	17.12	peak	15.74	32.86	46.00	-13.14	130	150
611.4230	7.48	peak	23.69	31.17	46.00	-14.83	130	150
995.7916	7.99	peak	29.17	37.16	54.00	-16.84	290	150

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
3000.0000	50.44	---	-4.56	45.88	---	74.00	54.00	-28.12	290	150
4904.0000	46.08	---	-4.83	41.25	---	74.00	54.00	-32.75	290	150
7320.5130	52.52	---	-2.80	49.72	---	74.00	54.00	-24.28	140	150

- Note**
1. Correction Factor = Antenna factor + Cable loss - Preamplifier
 2. The formula of measured value as: Test Result = Reading + Correction Factor
 3. Detector function in the form : PK = Peak, QP = Quasi Peak, AV = Average
 4. All not in the table noted test results are more than 20 dB below the relevant limits.
 5. See the attached diagram as appendix.

TEST RESULT (Transmitter): The unit DOES meet the FCC requirements.

Test equipment used: ETSTW-RE 003, ETSTW-RE 004, ETSTW-RE 018, ETSTW-RE 028, ETSTW-RE 029, ETSTW-RE 030, ETSTW-RE 044



Registration number: W6M21010-10941-C-1
 FCC ID: RXZ-WP82RL

3.6 Radiated Emission on the band edge

According to FCC rules part 15 subpart C §15.247(c) in any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required.

In addition radiated emission which fall in the restricted bands, as defined in section 15.205(a), must also with the radiated emission limits.

Mode 802.11b

Test conditions		Attenuation at or outside band-edges	
		Lower Band-edge	Upper Band-edge
$T_{nom} = 23^{\circ}C$	$V_{nom} = 120 V$	55 dB	56.48 dB

Mode 802.11g

Test conditions		Attenuation at or outside band-edges	
		Lower Band-edge	Upper Band-edge
$T_{nom} = 23^{\circ}C$	$V_{nom} = 120 V$	39.69 dB	50.62 dB

Mode 802.11n 20MHz

Test conditions		Attenuation at or outside band-edges	
		Lower Band-edge	Upper Band-edge
$T_{nom} = 23^{\circ}C$	$V_{nom} = 120 V$	39.72 dB	52.28 dB

Mode 802.11n 40MHz

Test conditions		Attenuation at or outside band-edges	
		Lower Band-edge	Upper Band-edge
$T_{nom} = 23^{\circ}C$	$V_{nom} = 120 V$	42.65 dB	46.55 dB

Limit:

Frequency Range / MHz	Limit
902 – 928	- 20 dB
2400 – 2483.5	
5725 - 5850	

Test equipment used: ETSTW-RE 055
 Explanation: Please see attached diagram as appendix.



Registration number: W6M21010-10941-C-1
 FCC ID: RXZ-WP82RL

3.7 Minimum 6 dB Bandwidth

The analyzer ResBW was set to 100 kHz. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK reading was taken, two markers were set 6 dB below the maximum level on the right and the left side of the emission. The 6 dB bandwidth is the frequency difference between the two markers.

Mode 802.11b

Test conditions		6 dB Bandwidth		
		Channel 1	Channel 6	Channel 11
T _{nom} = 23°C	V _{nom} = 120 V	9.006410257MHz	9.006410256MHz	8.910256410 MHz

Mode 802.11g

Test conditions		6 dB Bandwidth		
		Channel 1	Channel 6	Channel 11
T _{nom} = 23°C	V _{nom} = 120 V	17.692307692MHz	17.628205128MHz	17.596153846MHz

Mode 802.11n 20MHz

Test conditions		6 dB Bandwidth		
		Channel 1	Channel 6	Channel 11
T _{nom} = 23°C	V _{nom} = 120 V	17.371794872MHz	17.371794872 MHz	17.628205128 MHz

Mode 802.11n 40MHz

Test conditions		6 dB Bandwidth		
		Channel 1	Channel 4	Channel 7
T _{nom} = 23°C	V _{nom} = 120 V	35.705128205MHz	35.705128205 MHz	35.833333333 MHz

Limits:

Frequency Range MHz	Limits
902-928	min 500 kHz
2400-2483.5	min 500 kHz
5725-5850	min 500 kHz

Test equipment used: ETSTW-RE 055

Explanation: see attached diagrams in Appendix.



Registration number: W6M21010-10941-C-1
 FCC ID: RXZ-WP82RL

3.8 Peak Power Spectral Density

Peak Power Spectral density is a measured at low, middle and high channel.
 The peak output power is measured with a measurement bandwidth of 10 MHz and displayed on diagram together with Peak Power Spectral Density result which was measured with a bandwidth of 3 kHz, appreciate frequency span and sweep time.

Mode 802.11b

Test conditions		Peak Power Spectral Density (3 kHz)		
		Channel 1 [dBm]	Channel 6 [dBm]	Channel 11 [dBm]
$T_{nom} = 23^{\circ}C$	$V_{nom} = 120 V$	-8.61	-7.13	-6.78

Mode 802.11g

Test conditions		Peak Power Spectral Density (3 kHz)		
		Channel 1 [dBm]	Channel 6 [dBm]	Channel 11 [dBm]
$T_{nom} = 23^{\circ}C$	$V_{nom} = 120 V$	-15.44	-14.73	-13.68

Mode 802.11n 20MHz

Test conditions		Peak Power Spectral Density (3 kHz)		
		Channel 1 [dBm]	Channel 6 [dBm]	Channel 11 [dBm]
$T_{nom} = 23^{\circ}C$	$V_{nom} = 120 V$	-15.48	-14.69	-14.34

Mode 802.11n 40MHz

Test conditions		Peak Power Spectral Density (3 kHz)		
		Channel 1 [dBm]	Channel 4 [dBm]	Channel 7 [dBm]
$T_{nom} = 23^{\circ}C$	$V_{nom} = 120 V$	-15.29	-15.12	-14.69

Limits:

Frequency Range MHz	dBm
902-928	8
2400-2483.5	8
5725-5850	8

Test equipment used: ETSTW-RE 055

Explanation: see attached diagrams in Appendix.



Registration number: W6M21010-10941-C-1
FCC ID: RXZ-WP82RL

3.9 Radiated Emission from Digital Part

FCC Rule: 15.109

Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency of Emission (MHz)	Field Strength (microvolts/meter)	Field Strength (dBmicrovolts/meter)
30 – 88	100	40.0
88 – 216	150	43.5
216 – 960	200	46.0
Above 960	500	54.0

Test equipment used: ETSTW-RE 003, ETSTW-RE 004, ETSTW-RE 018, ETSTW-RE 028,
ETSTW-RE 029, ETSTW-RE 030, ETSTW-RE 044

Explanation: The test results are listed in the separated test report no. W6M21010-10941-P-15B.



Registration number: W6M21010-10941-C-1
 FCC ID: RXZ-WP82RL

3.9 Power Line Conducted Emission

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the table bellows with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals.

This measurement was transact first with instrumentation using an average and peak detector and a 10 kHz bandwidth. If the peak detector achieves a calculated level, the measurement is repeated by an instrumentation using a quasi-peak detector.

Frequency	Level (dBμV)	
	quasi-peak	average
150 kHz	lower limit line	Lower limit line

Model: WP82RL Date: 2010/10/11
 Mode: Temperature: 24 °C Engineer: Robert
 Polarization: N Humidity: 60 %

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result (dBuV)		Limit (dBuV)		Margin (dB)
	QP	Ave.		QP	Ave.	QP	Ave.	
0.1500	38.90	12.58	10.74	49.64	23.32	66.00	56.00	-16.36
0.1748	33.72	29.28	10.75	44.47	40.03	64.73	54.73	-14.70
0.2492	24.03	20.39	10.72	34.75	31.11	61.78	51.78	-20.67
0.6320	5.98	1.40	10.59	16.57	11.99	56.00	46.00	-34.01
1.1861	27.67	27.09	10.32	37.99	37.41	56.00	46.00	-8.59
6.8160	23.36	21.32	10.23	33.59	31.55	60.00	50.00	-18.45

Polarization: L1

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result (dBuV)		Limit (dBuV)		Margin (dB)
	QP	Ave.		QP	Ave.	QP	Ave.	
0.1525	37.76	10.55	10.75	48.51	21.30	65.86	55.86	-17.35
0.1742	33.38	29.12	10.76	44.14	39.88	64.76	54.76	-14.88
0.2778	12.61	-0.47	10.72	23.33	10.25	60.88	50.88	-37.55
0.4917	12.32	10.29	10.66	22.98	20.95	56.14	46.14	-25.19
2.0097	13.50	11.06	10.09	23.59	21.15	56.00	46.00	-24.85
6.2200	22.52	21.23	10.26	32.78	31.49	60.00	50.00	-18.51

- Note:**
1. The formula of measured value as: Test Result = Reading + Correction Factor
 2. The Correction Factor = Cable Loss + LISN Insertion Loss + Pulse Limit Loss
 3. Detector function in the form : PK = Peak, QP = Quasi Peak, AV = Average
 4. All not in the table noted test results are more than 20 dB below the relevant limits.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21010-10941-C-1
FCC ID: RXZ-WP82RL

Limits:

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi Peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

Test equipment used: ETSTW-CE 001, ETSTW-CE 004, ETSTW-CE 006

Explanation: see attached diagrams in Appendix.



Registration number: W6M21010-10941-C-1
FCC ID: RXZ-WP82RL

Appendix


Measurement diagrams

1. Peak Output Power
2. Spurious Emissions radiated
3. Band Edge Measurement
4. Minimum 6dB Bandwidth
5. Peak Power Spectral Density
6. Power Line Conducted Emission




Registration number: W6M21010-10941-C-1
 FCC ID: RXZ-WP82RL

Peak Output Power 802.11b Channel 1



MAX OUTPUT POWER 802.11b CH1
 Date: 12.OCT.2010 09:25:31

802.11b Channel 6




MAX OUTPUT POWER 802.11b CH6
 Date: 12.OCT.2010 09:25:57




Registration number: W6M21010-10941-C-1
 FCC ID: RXZ-WP82RL

802.11b Channel 11



MAX OUTPUT POWER 802.11b CH11
 Date: 12.OCT.2010 09:26:18

802.11g Channel 1




MAX OUTPUT POWER 802.11g CH1
 Date: 12.OCT.2010 09:29:08




Registration number: W6M21010-10941-C-1
 FCC ID: RXZ-WP82RL

Channel 6



MAX OUTPUT POWER 802.11g CH6
 Date: 12.OCT.2010 09:28:47

Channel 11




MAX OUTPUT POWER 802.11g CH11
 Date: 12.OCT.2010 09:28:26




Registration number: W6M21010-10941-C-1
 FCC ID: RXZ-WP82RL

802.11n 20MHz Channel 1



MAX OUTPUT POWER 802.11n 20MHz CH1
 Date: 12.OCT.2010 09:30:08

Channel 6




MAX OUTPUT POWER 802.11n 20MHz CH6
 Date: 12.OCT.2010 09:30:37




Registration number: W6M21010-10941-C-1
 FCC ID: RXZ-WP82RL

Channel 11



MAX OUTPUT POWER 802.11n 20MHz CH11
 Date: 12.OCT.2010 09:30:56

802.11n 40MHz Channel 1




MAX OUTPUT POWER 802.11n 40MHz CH1
 Date: 12.OCT.2010 09:32:48




Registration number: W6M21010-10941-C-1
 FCC ID: RXZ-WP82RL

Channel 4



MAX OUTPUT POWER 802.11n 40MHz CH4
 Date: 12.OCT.2010 09:33:17

Channel 7





MAX OUTPUT POWER 802.11n 40MHz CH7
 Date: 12.OCT.2010 09:34:10



Registration number: W6M21010-10941-C-1
FCC ID: RXZ-WP82RL

Spurious Emissions radiated 802.11b Channel 1 Antenna Polarization H

82.0 dBuV/m




Note:

Up Line: Peak Limit Line, Down Line: Ave Limit Line

- 1 The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
- 2 The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
- 3 For corrected test results are listed in the relevant table of radiated test data of this test report.



Registration number: W6M21010-10941-C-1
FCC ID: RXZ-WP82RL





Note:

Up Line: Peak Limit Line, Down Line: Ave Limit Line

- 1 The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
- 2 The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
- 3 For corrected test results are listed in the relevant table of radiated test data of this test report.



Registration number: W6M21010-10941-C-1
FCC ID: RXZ-WP82RL



Note:



Up Line: Peak Limit Line, Down Line: Ave Limit Line

- 1 The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
- 2 The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
- 3 For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21010-10941-C-1
FCC ID: RXZ-WP82RL



Note:



Up Line: Peak Limit Line, Down Line: Ave Limit Line

- 1 The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
- 2 The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
- 3 For corrected test results are listed in the relevant table of radiated test data of this test report.



Registration number: W6M21010-10941-C-1
FCC ID: RXZ-WP82RL

Antenna Polarization V





Note:

Up Line: Peak Limit Line, Down Line: Ave Limit Line

- 1 The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
- 2 The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
- 3 For corrected test results are listed in the relevant table of radiated test data of this test report.



Registration number: W6M21010-10941-C-1
FCC ID: RXZ-WP82RL





Note:

Up Line: Peak Limit Line, Down Line: Ave Limit Line

- 1 The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
- 2 The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
- 3 For corrected test results are listed in the relevant table of radiated test data of this test report.



Registration number: W6M21010-10941-C-1
FCC ID: RXZ-WP82RL



Note:



Up Line: Peak Limit Line, Down Line: Ave Limit Line

- 1 The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
- 2 The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
- 3 For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21010-10941-C-1
FCC ID: RXZ-WP82RL



Note:

Up Line: Peak Limit Line, Down Line: Ave Limit Line


- 1 The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
- 2 The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
- 3 For corrected test results are listed in the relevant table of radiated test data of this test report.



Registration number: W6M21010-10941-C-1
FCC ID: RXZ-WP82RL

Channel 6

Antenna Polarization H




Note:

Up Line: Peak Limit Line, Down Line: Ave Limit Line

- 1 The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
- 2 The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
- 3 For corrected test results are listed in the relevant table of radiated test data of this test report.



Registration number: W6M21010-10941-C-1
FCC ID: RXZ-WP82RL





Note:

Up Line: Peak Limit Line, Down Line: Ave Limit Line

- 1 The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
- 2 The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
- 3 For corrected test results are listed in the relevant table of radiated test data of this test report.



Registration number: W6M21010-10941-C-1
FCC ID: RXZ-WP82RL





Note:

Up Line: Peak Limit Line, Down Line: Ave Limit Line

- 1 The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
- 2 The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
- 3 For corrected test results are listed in the relevant table of radiated test data of this test report.



Registration number: W6M21010-10941-C-1
FCC ID: RXZ-WP82RL



Note:



Up Line: Peak Limit Line, Down Line: Ave Limit Line

- 1 The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
- 2 The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
- 3 For corrected test results are listed in the relevant table of radiated test data of this test report.



Registration number: W6M21010-10941-C-1
FCC ID: RXZ-WP82RL

Antenna Polarization V



Note:


Up Line: Peak Limit Line, Down Line: Ave Limit Line

- 1 The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
- 2 The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
- 3 For corrected test results are listed in the relevant table of radiated test data of this test report.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21010-10941-C-1
FCC ID: RXZ-WP82RL





Note:

Up Line: Peak Limit Line, Down Line: Ave Limit Line

- 1 The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
- 2 The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
- 3 For corrected test results are listed in the relevant table of radiated test data of this test report.



Registration number: W6M21010-10941-C-1
FCC ID: RXZ-WP82RL





Note:

Up Line: Peak Limit Line, Down Line: Ave Limit Line

- 1 The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
- 2 The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
- 3 For corrected test results are listed in the relevant table of radiated test data of this test report.



Registration number: W6M21010-10941-C-1
FCC ID: RXZ-WP82RL



Note:

Up Line: Peak Limit Line, Down Line: Ave Limit Line

- 1 The attached measurement plots are preliminarily pre-scanned with peak detector for determining the final checking frequencies and are for reference only.
- 2 The some frequencies may exceed the limit line without the specified detectors, but that cannot present the results are failed to the specification of test standard.
- 3 For corrected test results are listed in the relevant table of radiated test data of this test report.