

FCC Test Report

FCC ID : RYK-WPEQ353ACNI
Equipment : 802.11ac/b/g/n Mini PCIe Module
Model No. : WPEQ-353ACNI
Brand Name : SparkLAN
Applicant : SparkLAN Communications, Inc.
Address : 8F., No.257, Sec. 2, Tiding Blvd., Neihu
District, Taipei City 11493, Taiwan.
Standard : 47 CFR FCC Part 15.247
Received Date : Dec. 01, 2015
Tested Date : Dec. 01, 2015 ~ Jan. 14, 2016

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:



Gary Chang / Manager



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Local Support Equipment List	7
1.3	Test Setup Chart	7
1.4	The Equipment List	8
1.5	Test Standards	9
1.6	Measurement Uncertainty	9
2	TEST CONFIGURATION	10
2.1	Testing Condition	10
2.2	The Worst Test Modes and Channel Details	10
3	TRANSMITTER TEST RESULTS.....	11
3.1	Conducted Emissions.....	11
3.2	6dB and Occupied Bandwidth	14
3.3	RF Output Power	17
3.4	Power Spectral Density	19
3.5	Unwanted Emissions into Restricted Frequency Bands	21
3.6	Emissions in Non-Restricted Frequency Bands	49
4	TEST LABORATORY INFORMATION	62

Release Record

Report No.	Version	Description	Issued Date
FR610402AC	Rev. 01	Initial issue	Mar. 15, 2016
FR610402AC	Rev. 02	Revised model name of antenna (page 5.)	Mar. 25, 2016

Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	Conducted Emissions	[dBuV]: 0.476MHz 41.45 (Margin -14.96dB) - QP	Pass
15.247(d) 15.209	Radiated Emissions	[dBuV/m at 3m]: 7311.00MHz 53.24 (Margin -0.76dB) - AV	Pass
15.247(b)(3)	Maximum Output Power	Max Power [dBm]: 27.40	Pass
15.247(a)(2)	6dB Bandwidth	Meet the requirement of limit	Pass
15.247(e)	Power Spectral Density	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

RF General Information					
Frequency Range (MHz)	IEEE Std. 802.11	Ch. Freq. (MHz)	Channel Number	Transmit Chains (N _{TX})	Data Rate / MCS
2400-2483.5	b	2412-2462	1-11 [11]	3	1-11 Mbps
2400-2483.5	g	2412-2462	1-11 [11]	3	6-54 Mbps
2400-2483.5	n (HT20)	2412-2462	1-11 [11]	3	MCS 0-23
2400-2483.5	n (HT40)	2422-2452	3-9 [7]	3	MCS 0-23

Note 1: RF output power specifies that Maximum Peak Conducted Output Power.
 Note 2: 802.11b uses a combination of DSSS-DBPSK, DQPSK, CCK modulation.
 Note 3: 802.11g/n uses a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.

1.1.2 Antenna Details

Ant. No.	Brand	Model	Type	Connector	Operating Frequencies (MHz) / Antenna Gain (dBi)		
					2400~2483.5MHz	5150~5250MHz	5725~5850MHz
1	Long Cheng Tech. Int'l Co., Ltd.	DB B-SMA THIN PADDLE Ant. GEC6200	Dipole	RP-SMA	3	5	5
2	Wanshih Electronic Co., Ltd.	WSS003	Dipole	RP-SMA	2	2	2
3	Long Cheng Tech. Int'l Co., Ltd.	FDBX_F41150-I3B	Dipole	IPEX	2	2.5	2.5

Note: Antenna 1 with highest gain was chosen for final test

1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	3.3Vdc from host
--------------------------	------------------

1.1.4 Channel List

Frequency band (MHz)		2400~2483.5	
802.11 b / g / n HT20		802.11n HT40	
Channel	Frequency(MHz)	Channel	Frequency(MHz)
1	2412	3	2422
2	2417	4	2427
3	2422	5	2432
4	2427	6	2437
5	2432	7	2442
6	2437	8	2447
7	2442	9	2452
8	2447	---	---
9	2452	---	---
10	2457	---	---
11	2462	---	---

1.1.5 Test Tool and Duty Cycle

Test Tool	ART2 GUI, V2.3		
Duty Cycle and Duty Factor	Mode	Duty cycle (%)	Duty factor (dB)
	11b	100.00%	0.00
	11g	100.00%	0.00
	HT20	100.00%	0.00
	HT40	100.00%	0.00

1.1.6 Power Setting


Modulation Mode	Test Frequency (MHz)	Power Set
11b	2412	23
11b	2437	23
11b	2462	22
11g	2412	17.5
11g	2437	23
11g	2462	17.5
HT20	2412	17
HT20	2437	23
HT20	2462	16
HT40	2422	15
HT40	2437	18
HT40	2452	14

1.2 Local Support Equipment List

Support Equipment List					
No.	Equipment	Brand	Model	FCC ID	Signal cable / Length (m)
1	Notebook	DELL	Latitude E6430	DoC	---
2	Fixture	---	---	---	---

Note: Fixture was provided by applicant.

1.3 Test Setup Chart



1.4 The Equipment List

Test Item	Conducted Emission				
Test Site	Conduction room 1 / (CO01-WS)				
Tested Date	Jan. 14, 2016				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
EMC Receiver	R&S	ESCS 30	100169	Oct. 21, 2015	Oct. 20, 2016
LISN	SCHWARZBECK	Schwarzbeck 8127	8127-667	Nov. 13, 2015	Nov. 12, 2016
LISN (Support Unit)	SCHWARZBECK	Schwarzbeck 8127	8127-666	Nov. 26, 2015	Nov. 25, 2016
RF Cable-CON	EMC	EMCCFD300-BM-BM-6000	50821	Dec. 21, 2015	Dec. 20, 2016
50 ohm terminal (Support Unit)	NA	50	04	Apr. 15, 2015	Apr. 14, 2016
Measurement Software	AUDIX	e3	6.120210k	NA	NA

Note: Calibration Interval of instruments listed above is one year.

Test Item	Radiated Emission				
Test Site	966 chamber1 / (03CH01-WS)				
Tested Date	Dec. 01 ~ Dec. 08, 2015				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101498	Dec. 09, 2014	Dec. 08, 2015
Receiver	R&S	ESR3	101658	Nov. 04, 2015	Nov. 03, 2016
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Aug. 20, 2015	Aug. 19, 2016
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Dec. 11, 2014	Dec. 10, 2015
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 04, 2015	Nov. 03, 2016
Loop Antenna	R&S	HFH2-Z2	11900	Nov. 16, 2015	Nov. 15, 2016
Preamplifier	Burgeon	BPA-530	SN:100219	Sep. 10, 2015	Sep. 09, 2016
Preamplifier	Agilent	83017A	MY39501308	Oct. 02, 2015	Oct. 01, 2016
Preamplifier	EMC	EMC184045B	980192	Sep. 01, 2015	Aug. 31, 2016
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16014/4	Dec. 15, 2014	Dec. 14, 2015
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Dec. 15, 2014	Dec. 14, 2015
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16139/4	Dec. 15, 2014	Dec. 14, 2015
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Dec. 15, 2014	Dec. 14, 2015
LF cable 10M	Woken	CFD400NL-LW	CFD400NL-002	Dec. 15, 2014	Dec. 14, 2015
Measurement Software	AUDIX	e3	6.120210g	NA	NA

Note: Calibration Interval of instruments listed above is one year.

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Tested Date	Jan. 13, 2016				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101063	Feb. 03, 2015	Feb. 02, 2016
Power Meter	Anritsu	ML2495A	1241002	Sep. 21, 2015	Sep. 20, 2016
Power Sensor	Anritsu	MA2411B	1207366	Sep. 21, 2015	Sep. 20, 2016
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247

ANSI C63.10-2013

FCC KDB 558074 D01 DTS Meas Guidance v03r04

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor ($k=2$))

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	± 34.134 Hz
Conducted power	± 0.808 dB
Power density	± 0.463 dB
Conducted emission	± 2.670 dB
AC conducted emission	± 2.90 dB
Radiated emission ≤ 1 GHz	± 3.66 dB
Radiated emission > 1 GHz	± 5.63 dB

2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	17°C / 61%	Sky Huang
Radiated Emissions	03CH01-WS	21-24°C / 61-65%	Anderson Hong Vincent Yeh
RF Conducted	TH01-WS	21°C / 64%	Alex Huang

➤ FCC site registration No.: 657002

➤ IC site registration No.: 10807A-1

2.2 The Worst Test Modes and Channel Details

Test item	Modulation Mode	Test Frequency (MHz)	Data Rate	Test Configuration
Conducted Emissions	11g	2437	6 Mbps	---
Radiated Emissions ≤1GHz	11g	2437	6 Mbps	---
Radiated Emissions >1GHz	11b	2412 / 2437 / 2462	1 Mbps	---
Maximum Output Power	11g	2412 / 2437 / 2462	6 Mbps	
6dB bandwidth	HT20	2412 / 2437 / 2462	MCS 0	
Power spectral density	HT40	2422 / 2437 / 2452	MCS 0	

3 Transmitter Test Results

3.1 Conducted Emissions

3.1.1 Limit of Conducted Emissions


Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.

3.1.2 Test Procedures


1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
4. This measurement was performed with AC 120V / 60Hz.

3.1.3 Test Setup




- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.4 Test Result of Conducted Emissions



Modulation	11g	Test Freq. (MHz)	2437
Power Phase	Neutral		



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.150	34.92	56.00	-21.08	34.77	0.13	0.02	Average
2	0.150	48.57	66.00	-17.43	48.42	0.13	0.02	QP
3	0.159	33.08	55.52	-22.44	32.94	0.12	0.02	Average
4	0.159	47.90	65.52	-17.62	47.76	0.12	0.02	QP
5	0.204	25.90	53.45	-27.55	25.78	0.10	0.02	Average
6	0.204	39.44	63.45	-24.01	39.32	0.10	0.02	QP
7	0.486	26.11	46.23	-20.12	25.93	0.14	0.04	Average
8	0.486	38.60	56.23	-17.63	38.42	0.14	0.04	QP
9	1.762	21.49	46.00	-24.51	21.25	0.16	0.08	Average
10	1.762	30.85	56.00	-25.15	30.61	0.16	0.08	QP
11	9.302	26.66	50.00	-23.34	26.24	0.26	0.16	Average
12	9.302	34.10	60.00	-25.90	33.68	0.26	0.16	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

3.2 6dB and Occupied Bandwidth

3.2.1 Limit of 6dB Bandwidth

The minimum 6dB bandwidth shall be at least 500 kHz.

3.2.2 Test Procedures


6dB Bandwidth

1. Set resolution bandwidth (RBW) = 100 kHz, Video bandwidth = 300 kHz.
2. Detector = Peak, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

Occupied Bandwidth


1. Set resolution bandwidth (RBW) = 1 MHz, Video bandwidth = 3 MHz.
2. Detector = Sample, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Use the OBW measurement function of spectrum analyzer to measure the occupied bandwidth.

3.2.3 Test Setup




3.2.4 Test Result of 6dB and Occupied Bandwidth

Modulation Mode	N _{TX}	Freq. (MHz)	6dB Bandwidth (MHz)				Limit (kHz)
			Chain 0	Chain 1	Chain 2	Chain 3	
11b	3	2412	7.54	7.01	7.07	---	500
11b	3	2437	7.07	7.07	6.55	---	500
11b	3	2462	7.07	6.61	7.07	---	500
11g	3	2412	16.35	16.35	16.35	---	500
11g	3	2437	16.29	16.35	16.35	---	500
11g	3	2462	16.35	16.35	16.35	---	500
HT20	3	2412	17.33	17.62	17.62	---	500
HT20	3	2437	17.16	17.62	17.57	---	500
HT20	3	2462	17.57	17.57	17.57	---	500
HT40	3	2422	35.94	35.13	35.48	---	500
HT40	3	2437	35.59	35.48	35.59	---	500
HT40	3	2452	36.41	35.83	36.29	---	500



Modulation Mode	N _{TX}	Freq. (MHz)	99% Occupied Bandwidth (MHz)			
			Chain 0	Chain 1	Chain 2	Chain 3
11b	3	2412	13.54	12.84	13.35	---
11b	3	2437	13.48	13.07	13.05	---
11b	3	2462	12.50	12.47	12.34	---
11g	3	2412	16.73	16.65	16.64	---
11g	3	2437	21.70	19.79	19.71	---
11g	3	2462	16.68	16.64	16.61	---
HT20	3	2412	17.82	17.77	17.77	---
HT20	3	2437	21.71	19.84	20.06	---
HT20	3	2462	17.80	17.76	17.73	---
HT40	3	2422	36.52	36.54	36.50	---
HT40	3	2437	36.56	36.60	36.56	---
HT40	3	2452	36.54	36.74	36.56	---



3.3 RF Output Power

3.3.1 Limit of RF Output Power

Conducted power shall not exceed 1Watt.


- Antenna gain \leq 6dBi, no any corresponding reduction is in output power limit.
- Antenna gain $>$ 6dBi
 - Non Fixed, point to point operations.
The conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dB
 - Fixed, point to point operations
Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point Operations, maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Systems operating in the 5725–5850 MHz band that are used exclusively for fixed, point-to-point operations ,no any corresponding reduction is in transmitter peak output power

3.3.2 Test Procedures

- Maximum Peak Conducted Output Power
 - Spectrum analyzer**
 1. Set RBW = 1MHz, VBW = 3MHz, Detector = Peak.
 2. Sweep time = auto, Trace mode = max hold, Allow trace to fully stabilize.
 3. Use the spectrum analyzer channel power measurement function with the band limits set equal to the DTS bandwidth edges.
 - Power meter**
 1. A broadband Peak RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.
- Maximum Conducted Output Power (For reference only)
 - Power meter**
 1. A broadband Average RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.

3.3.3 Test Setup



3.3.4 Test Result of Maximum Output Power

Modulation Mode	N _{TX}	Freq. (MHz)	Peak conducted Output Power (dBm)							Ant. Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)
			Chain 0	Chain 1	Chain 2	Chain 3	Total Power (mW)	Total Power (dBm)	Limit (dBm)			
11b	3	2412	22.42	22.07	22.09	---	497.455	26.97	30.00	3.00	29.97	36.00
11b	3	2437	22.41	22.34	22.23	---	512.685	27.10	30.00	3.00	30.10	36.00
11b	3	2462	22.19	21.96	21.78	---	473.274	26.75	30.00	3.00	29.75	36.00
11g	3	2412	21.51	21.56	21.22	---	417.232	26.20	30.00	3.00	29.20	36.00
11g	3	2437	22.71	22.64	22.54	---	549.765	27.40	30.00	3.00	30.40	36.00
11g	3	2462	21.39	21.04	20.77	---	384.177	25.85	30.00	3.00	28.85	36.00
HT20	3	2412	21.24	20.51	20.67	---	362.187	25.59	30.00	3.00	28.59	36.00
HT20	3	2437	22.57	22.61	22.51	---	541.345	27.33	30.00	3.00	30.33	36.00
HT20	3	2462	20.09	19.76	19.46	---	285.026	24.55	30.00	3.00	27.55	36.00
HT40	3	2422	18.86	18.23	18.64	---	216.554	23.36	30.00	3.00	26.36	36.00
HT40	3	2437	21.34	21.16	21.06	---	394.405	25.96	30.00	3.00	28.96	36.00
HT40	3	2452	17.76	17.34	17.13	---	165.545	22.19	30.00	3.00	25.19	36.00

Modulation Mode	N _{TX}	Freq. (MHz)	Conducted (Average) Output Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)
			Chain 0	Chain 1	Chain 2	Chain 3			
11b	3	2412	20.06	19.56	19.68	---	284.653	24.54	---
11b	3	2437	20.07	19.81	19.72	---	291.100	24.64	---
11b	3	2462	19.49	19.16	19.14	---	253.369	24.04	---
11g	3	2412	15.81	14.82	15.31	---	102.408	20.10	---
11g	3	2437	19.82	19.52	19.36	---	271.774	24.34	---
11g	3	2462	15.34	15.11	14.89	---	97.464	19.89	---
HT20	3	2412	15.31	14.26	14.68	---	90.008	19.54	---
HT20	3	2437	19.84	19.46	19.41	---	271.988	24.35	---
HT20	3	2462	13.82	13.57	13.37	---	68.577	18.36	---
HT40	3	2422	12.12	11.85	12.1	---	47.822	16.80	---
HT40	3	2437	15.44	15.02	15.01	---	98.459	19.93	---
HT40	3	2452	11.52	11.08	11.02	---	39.661	15.98	---

Note: Conducted average output power is for reference only.

3.4 Power Spectral Density


3.4.1 Limit of Power Spectral Density

Power spectral density shall not be greater than 8 dBm in any 3 kHz band.

3.4.2 Test Procedures

- Maximum peak conducted output power was used to demonstrate compliance to the fundamental output power limit.
 1. Set the RBW = 3kHz, VBW = 10kHz.
 2. Detector = Peak, Sweep time = auto couple.
 3. Trace mode = max hold, allow trace to fully stabilize.
 4. Use the peak marker function to determine the maximum amplitude level.
- Maximum (average) conducted output power was used to demonstrate compliance to the fundamental output power limit.
 1. Set the RBW = 100kHz, VBW = 300 kHz.
 2. Detector = RMS, Sweep time = auto couple.
 3. Set the sweep time to: $\geq 10 \times (\text{number of measurement points in sweep}) \times (\text{maximum data rate per stream})$.
 4. Perform the measurement over a single sweep.
 5. Use the peak marker function to determine the maximum amplitude level.


3.4.3 Test Setup



3.4.4 Test Result of Power Spectral Density

Modulation Mode	N _{TX}	Freq. (MHz)	Total Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
11b	3	2412	2.42	8.00
11b	3	2437	1.72	8.00
11b	3	2462	1.48	8.00
11g	3	2412	-5.93	8.00
11g	3	2437	-1.26	8.00
11g	3	2462	-5.54	8.00
HT20	3	2412	-5.86	8.00
HT20	3	2437	-2.09	8.00
HT20	3	2462	-7.53	8.00
HT40	3	2422	-12.21	8.00
HT40	3	2437	-8.54	8.00
HT40	3	2452	-12.63	8.00

Note: Test result is bin-by-bin summing measured value of each TX port.



3.5 Unwanted Emissions into Restricted Frequency Bands

3.5.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Quasi-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.


3.5.2 Test Procedures

1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.


Note:

1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

3.5.3 Test Setup




3.5.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	11g	Test Freq. (MHz)	2437						
Polarization	Horizontal								
 <p>The graph plots Level (dBuV/m) on the y-axis (0 to 90) against Frequency (MHz) on the x-axis (30 to 1000). A red line represents the FCC CLASS-B limit, which is 40 dBuV/m from 30 to 100 MHz, 45 dBuV/m from 100 to 300 MHz, and 50 dBuV/m from 300 to 1000 MHz. Six blue vertical lines represent emission peaks labeled 1 through 6, with their respective frequencies and levels indicated in the table below.</p>									
Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High cm	Turn Table deg	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB				
1	165.80	31.92	43.50	-11.58	48.90	-16.98	Peak	---	---
2	232.73	36.29	46.00	-9.71	54.77	-18.48	Peak	---	---
3	298.69	40.17	46.00	-5.83	56.06	-15.89	Peak	---	---
4	498.51	29.11	46.00	-16.89	40.36	-11.25	Peak	---	---
5	698.33	39.67	46.00	-6.33	47.86	-8.19	Peak	---	---
6	898.15	34.04	46.00	-11.96	39.40	-5.36	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	11g	Test Freq. (MHz)	2437
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	232.73	29.69	46.00	-16.31	48.11	-18.42	Peak	---	---
2	299.66	30.86	46.00	-15.14	46.65	-15.79	Peak	---	---
3	698.33	35.99	46.00	-10.01	44.08	-8.09	Peak	---	---
4	774.96	32.25	46.00	-13.75	38.98	-6.73	Peak	---	---
5	896.21	33.73	46.00	-12.27	39.01	-5.28	Peak	---	---
6	957.32	35.17	46.00	-10.83	39.60	-4.43	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)


*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

3.5.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 11b


Modulation	11b	Test Freq. (MHz)	2412
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	46.50	54.00	-7.50	49.77	-3.27	Average	303	127
2	2390.00	55.59	74.00	-18.41	58.86	-3.27	Peak	303	127
3	4824.00	41.17	54.00	-12.83	36.24	4.93	Average	128	292
4	4824.00	48.21	74.00	-25.79	43.28	4.93	Peak	128	292
5	12060.00	41.89	54.00	-12.11	27.21	14.68	Average	100	121
6	12060.00	54.95	74.00	-19.05	40.27	14.68	Peak	100	121

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11b	Test Freq. (MHz)	2412
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	51.95	54.00	-2.05	55.22	-3.27	Average	381	248
2	2390.00	68.24	74.00	-5.76	71.51	-3.27	Peak	381	248
3	4824.00	49.50	54.00	-4.50	44.57	4.93	Average	100	376
4	4824.00	52.89	74.00	-21.11	47.96	4.93	Peak	100	376
5	12060.00	41.57	54.00	-12.43	26.89	14.68	Average	100	163
6	12060.00	54.47	74.00	-19.53	39.79	14.68	Peak	100	163

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11b	Test Freq. (MHz)	2437
Polarization	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	36.88	54.00	-17.12	40.15	-3.27	Average	189	96
2	2390.00	49.53	74.00	-24.47	52.80	-3.27	Peak	189	96
3	2483.50	37.56	54.00	-16.44	40.38	-2.82	Average	189	96
4	2483.50	50.49	74.00	-23.51	53.31	-2.82	Peak	189	96
5	4874.00	39.23	54.00	-14.77	34.17	5.06	Average	100	288
6	4874.00	48.01	74.00	-25.99	42.95	5.06	Peak	100	288
7	7311.00	51.16	54.00	-2.84	41.68	9.48	Average	100	155
8	7311.00	57.32	74.00	-16.68	47.84	9.48	Peak	100	155
9	12185.00	42.15	54.00	-11.85	27.42	14.73	Average	100	185
10	12185.00	54.92	74.00	-19.08	40.19	14.73	Peak	100	185

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11b	Test Freq. (MHz)	2437
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	41.48	54.00	-12.52	44.75	-3.27	Average	100	92
2	2390.00	54.45	74.00	-19.55	57.72	-3.27	Peak	100	92
3	2483.50	42.10	54.00	-11.90	44.92	-2.82	Average	100	92
4	2483.50	55.80	74.00	-18.20	58.62	-2.82	Peak	100	92
5	4874.00	48.89	54.00	-5.11	43.83	5.06	Average	100	93
6	4874.00	52.64	74.00	-21.36	47.58	5.06	Peak	100	93
7	7311.00	53.24	54.00	-0.76	43.76	9.48	Average	100	93
8	7311.00	58.63	74.00	-15.37	49.15	9.48	Peak	100	93
9	12185.00	42.34	54.00	-11.66	27.61	14.73	Average	100	134
10	12185.00	55.37	74.00	-18.63	40.64	14.73	Peak	100	134

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11b	Test Freq. (MHz)	2462
Polarization	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	47.51	54.00	-6.49	50.33	-2.82	Average	284	293
2	2483.50	55.25	74.00	-18.75	58.07	-2.82	Peak	284	293
3	4924.00	36.71	54.00	-17.29	31.53	5.18	Average	100	304
4	4924.00	46.25	74.00	-27.75	41.07	5.18	Peak	100	304
5	7386.00	47.80	54.00	-6.20	38.18	9.62	Average	100	173
6	7386.00	54.51	74.00	-19.49	44.89	9.62	Peak	100	173

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11b	Test Freq. (MHz)	2462
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	52.50	54.00	-1.50	55.32	-2.82	Average	100	191
2	2483.50	61.84	74.00	-12.16	64.66	-2.82	Peak	100	191
3	4924.00	47.38	54.00	-6.62	42.20	5.18	Average	197	259
4	4924.00	51.79	74.00	-22.21	46.61	5.18	Peak	197	259
5	7386.00	48.63	54.00	-5.37	39.01	9.62	Average	100	261
6	7386.00	55.37	74.00	-18.63	45.75	9.62	Peak	100	261

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)


*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.5.6 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 11g

Modulation	11g	Test Freq. (MHz)	2412						
Polarization	Horizontal								
									
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2390.00	47.87	54.00	-6.13	51.14	-3.27	Average	100	57
2	2390.00	68.21	74.00	-5.79	71.48	-3.27	Peak	100	57
3	4824.00	31.54	54.00	-22.46	26.61	4.93	Average	100	173
4	4824.00	44.46	74.00	-29.54	39.53	4.93	Peak	100	173
5	12060.00	41.18	54.00	-12.82	26.50	14.68	Average	100	63
6	12060.00	54.30	74.00	-19.70	39.62	14.68	Peak	100	63
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).</p>									

Modulation	11g	Test Freq. (MHz)	2412
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	51.90	54.00	-2.10	55.17	-3.27	Average	383	280
2	2390.00	72.51	74.00	-1.49	75.78	-3.27	Peak	383	280
3	4824.00	34.63	54.00	-19.37	29.70	4.93	Average	194	262
4	4824.00	48.15	74.00	-25.85	43.22	4.93	Peak	194	262
5	12060.00	41.24	54.00	-12.76	26.56	14.68	Average	100	274
6	12060.00	54.24	74.00	-19.76	39.56	14.68	Peak	100	274

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11g	Test Freq. (MHz)	2437
Polarization	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	43.34	54.00	-10.66	46.61	-3.27	Average	176	289
2	2390.00	60.27	74.00	-13.73	63.54	-3.27	Peak	176	289
3	2483.50	49.41	54.00	-4.59	52.23	-2.82	Average	100	76
4	2483.50	70.95	74.00	-3.05	73.77	-2.82	Peak	100	76
5	4874.00	32.67	54.00	-21.33	27.61	5.06	Average	100	165
6	4874.00	45.54	74.00	-28.46	40.48	5.06	Peak	100	165
7	7311.00	43.76	54.00	-10.24	34.28	9.48	Average	100	166
8	7311.00	58.68	74.00	-15.32	49.20	9.48	Peak	100	166

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11g	Test Freq. (MHz)	2437
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	50.38	54.00	-3.62	53.65	-3.27	Average	380	249
2	2390.00	72.10	74.00	-1.90	75.37	-3.27	Peak	380	249
3	2483.50	51.68	54.00	-2.32	54.50	-2.82	Average	100	155
4	2483.50	72.77	74.00	-1.23	75.59	-2.82	Peak	100	155
5	4874.00	35.89	54.00	-18.11	30.83	5.06	Average	193	253
6	4874.00	49.99	74.00	-24.01	44.93	5.06	Peak	193	253
7	7311.00	44.08	54.00	-9.92	34.60	9.48	Average	103	154
8	7311.00	59.85	74.00	-14.15	50.37	9.48	Peak	103	154

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11g	Test Freq. (MHz)	2462
Polarization	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	52.49	54.00	-1.51	55.31	-2.82	Average	386	111
2	2483.50	71.85	74.00	-2.15	74.67	-2.82	Peak	386	111
3	4924.00	31.66	54.00	-22.34	26.48	5.18	Average	100	117
4	4924.00	45.12	74.00	-28.88	39.94	5.18	Peak	100	117
5	7386.00	37.82	54.00	-16.18	28.20	9.62	Average	100	166
6	7386.00	50.81	74.00	-23.19	41.19	9.62	Peak	100	166

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11g	Test Freq. (MHz)	2462
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	52.81	54.00	-1.19	55.63	-2.82	Average	105	103
2	2483.50	72.98	74.00	-1.02	75.80	-2.82	Peak	105	103
3	4824.00	32.59	54.00	-21.41	27.66	4.93	Average	100	95
4	4824.00	45.98	74.00	-28.02	41.05	4.93	Peak	100	95
5	7386.00	37.51	54.00	-16.49	27.89	9.62	Average	100	72
6	7386.00	50.38	74.00	-23.62	40.76	9.62	Peak	100	72

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)


*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.5.7 Transmitter Radiated Unwanted Emissions (Above 1GHz) for HT20

Modulation	HT20	Test Freq. (MHz)	2412						
Polarization	Horizontal								
									
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2390.00	48.33	54.00	-5.67	51.60	-3.27	Average	100	62
2	2390.00	68.54	74.00	-5.46	71.81	-3.27	Peak	100	62
3	4824.00	31.23	54.00	-22.77	26.30	4.93	Average	100	165
4	4824.00	44.23	74.00	-29.77	39.30	4.93	Peak	100	165
5	12060.00	41.08	54.00	-12.92	26.40	14.68	Average	106	69
6	12060.00	54.70	74.00	-19.30	40.02	14.68	Peak	106	69
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).</p>									

Modulation	HT20	Test Freq. (MHz)	2412
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	52.44	54.00	-1.56	55.71	-3.27	Average	378	124
2	2390.00	72.00	74.00	-2.00	75.27	-3.27	Peak	378	124
3	4824.00	34.24	54.00	-19.76	29.31	4.93	Average	188	264
4	4824.00	47.87	74.00	-26.13	42.94	4.93	Peak	188	264
5	12060.00	41.37	54.00	-12.63	26.69	14.68	Average	108	281
6	12060.00	54.50	74.00	-19.50	39.82	14.68	Peak	108	281

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT20	Test Freq. (MHz)	2437
Polarization	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	44.36	54.00	-9.64	47.63	-3.27	Average	100	103
2	2390.00	63.90	74.00	-10.10	67.17	-3.27	Peak	100	103
3	2483.50	50.80	54.00	-3.20	53.62	-2.82	Average	240	85
4	2483.50	71.44	74.00	-2.56	74.26	-2.82	Peak	240	85
5	4874.00	32.14	54.00	-21.86	27.08	5.06	Average	100	218
6	4874.00	45.22	74.00	-28.78	40.16	5.06	Peak	100	218
7	7311.00	43.45	54.00	-10.55	33.97	9.48	Average	111	24
8	7311.00	58.76	74.00	-15.24	49.28	9.48	Peak	111	24

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT20	Test Freq. (MHz)	2437
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	49.37	54.00	-4.63	52.64	-3.27	Average	380	259
2	2390.00	67.43	74.00	-6.57	70.70	-3.27	Peak	100	106
3	2483.50	51.01	54.00	-2.99	53.83	-2.82	Average	100	155
4	2483.50	71.73	74.00	-2.27	74.55	-2.82	Peak	100	155
5	4874.00	36.04	54.00	-17.96	30.98	5.06	Average	190	263
6	4874.00	51.48	74.00	-22.52	46.42	5.06	Peak	190	263
7	7311.00	45.00	54.00	-9.00	35.52	9.48	Average	120	260
8	7311.00	62.31	74.00	-11.69	52.83	9.48	Peak	120	260

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT20	Test Freq. (MHz)	2462
Polarization	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	46.51	54.00	-7.49	49.33	-2.82	Average	103	228
2	2483.50	64.61	74.00	-9.39	67.43	-2.82	Peak	103	228
3	4924.00	31.72	54.00	-22.28	26.54	5.18	Average	100	94
4	4924.00	45.01	74.00	-28.99	39.83	5.18	Peak	100	94
5	7386.00	35.95	54.00	-18.05	26.33	9.62	Average	100	285
6	7386.00	49.09	74.00	-24.91	39.47	9.62	Peak	100	285

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT20	Test Freq. (MHz)	2462
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	53.23	54.00	-0.77	56.05	-2.82	Average	138	295
2	2483.50	72.51	74.00	-1.49	75.33	-2.82	Peak	138	295
3	4924.00	32.49	54.00	-21.51	27.31	5.18	Average	100	3
4	4924.00	45.39	74.00	-28.61	40.21	5.18	Peak	100	3
5	7386.00	36.21	54.00	-17.79	26.59	9.62	Average	100	152
6	7386.00	48.99	74.00	-25.01	39.37	9.62	Peak	100	152


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.5.8 Transmitter Radiated Unwanted Emissions (Above 1GHz) for HT40


Modulation	HT40	Test Freq. (MHz)	2422
Polarization	Horizontal		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	48.19	54.00	-5.81	51.46	-3.27	Average	341	9
2	2390.00	62.50	74.00	-11.50	65.77	-3.27	Peak	341	9
3	4844.00	31.84	54.00	-22.16	26.85	4.99	Average	280	244
4	4844.00	44.66	74.00	-29.34	39.67	4.99	Peak	280	244
5	12110.00	41.09	54.00	-12.91	26.40	14.69	Average	233	269
6	12110.00	53.58	74.00	-20.42	38.89	14.69	Peak	233	269

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT40	Test Freq. (MHz)	2422
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	52.49	54.00	-1.51	55.76	-3.27	Average	373	124
2	2390.00	68.95	74.00	-5.05	72.22	-3.27	Peak	373	124
3	4844.00	32.97	54.00	-21.03	27.98	4.99	Average	164	41
4	4844.00	45.61	74.00	-28.39	40.62	4.99	Peak	164	41
5	12110.00	41.18	54.00	-12.82	26.49	14.69	Average	212	118
6	12110.00	54.33	74.00	-19.67	39.64	14.69	Peak	212	118

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT40	Test Freq. (MHz)	2437
Polarization	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	49.04	54.00	-4.96	52.31	-3.27	Average	100	6
2	2390.00	63.83	74.00	-10.17	67.10	-3.27	Peak	100	6
3	2483.50	51.00	54.00	-3.00	53.82	-2.82	Average	100	148
4	2483.50	67.70	74.00	-6.30	70.52	-2.82	Peak	100	148
5	4874.00	31.60	54.00	-22.40	26.54	5.06	Average	287	246
6	4874.00	44.51	74.00	-29.49	39.45	5.06	Peak	287	246
7	7311.00	35.51	54.00	-18.49	26.03	9.48	Average	157	122
8	7311.00	48.12	74.00	-25.88	38.64	9.48	Peak	157	122

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT40	Test Freq. (MHz)	2437
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	52.28	54.00	-1.72	55.55	-3.27	Average	102	340
2	2390.00	69.45	74.00	-4.55	72.72	-3.27	Peak	102	340
3	2483.50	52.18	54.00	-1.82	55.00	-2.82	Average	108	193
4	2483.50	69.08	74.00	-4.92	71.90	-2.82	Peak	108	193
5	4874.00	32.79	54.00	-21.21	27.73	5.06	Average	163	48
6	4874.00	45.58	74.00	-28.42	40.52	5.06	Peak	163	48
7	7311.00	35.27	54.00	-18.73	25.79	9.48	Average	188	124
8	7311.00	48.51	74.00	-25.49	39.03	9.48	Peak	188	124

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT40	Test Freq. (MHz)	2452
Polarization	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	48.88	54.00	-5.12	51.70	-2.82	Average	100	145
2	2483.50	64.77	74.00	-9.23	67.59	-2.82	Peak	100	145
3	4904.00	31.82	54.00	-22.18	26.68	5.14	Average	281	244
4	4904.00	44.67	74.00	-29.33	39.53	5.14	Peak	281	244
5	7356.00	35.69	54.00	-18.31	26.14	9.55	Average	152	129
6	7356.00	48.36	74.00	-25.64	38.81	9.55	Peak	152	129

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT40	Test Freq. (MHz)	2452
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	52.41	54.00	-1.59	55.23	-2.82	Average	115	110
2	2483.50	66.32	74.00	-7.68	69.14	-2.82	Peak	115	110
3	4904.00	33.02	54.00	-20.98	27.88	5.14	Average	155	53
4	4904.00	45.91	74.00	-28.09	40.77	5.14	Peak	155	53
5	7356.00	35.43	54.00	-18.57	25.88	9.55	Average	182	117
6	7356.00	48.26	74.00	-25.74	38.71	9.55	Peak	182	117

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.6 Emissions in Non-Restricted Frequency Bands

3.6.1 Emissions in Non-Restricted Frequency Bands Limit

Peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz

3.6.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.6.3 Test Procedures


Reference level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Use the peak marker function to determine the maximum PSD level

Emission level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Scan Frequency range is up to 25GHz
4. Use the peak marker function to determine the maximum amplitude level

3.6.4 Test Setup





3.6.5 Test Result of Emissions in non-restricted frequency bands


This test item is performed on each TX output individually without summing or adding $10 \log(N_{ANT})$ since measurements are made relative to the in-band emissions on the individual outputs. Only worst test result of each operating mode is presented.

3.6.6 Unwanted Emissions into Non-Restricted Frequency Bands


802.11b










802.11g










802.11n HT20









802.11n HT40







4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp, it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan Hsiang. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin Kou
District, New Taipei City, Taiwan,
R.O.C.

Kwei Shan

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd
St., Kwei Shan Hsiang, Tao Yuan
Hsien 333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd
St., Kwei Shan Hsiang, Tao Yuan
Hsien 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==