



## APPENDIX I RADIO FREQUENCY EXPOSURE

### LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

### EUT Specification

<b>EUT</b>	802.11 b/g/n USB Half Mini Card
<b>Frequency band (Operating)</b>	<input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5.825GHz <input type="checkbox"/> Others
<b>Device category</b>	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others
<b>Exposure classification</b>	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm <sup>2</sup> ) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm <sup>2</sup> )
<b>Antenna diversity</b>	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input checked="" type="checkbox"/> Tx/Rx diversity
<b>Max. output power</b>	IEEE 802.11b mode: 16.66 dBm (46.3446 mW) IEEE 802.11g mode: 17.58 dBm (57.27 mW) draft 802.11n Standard-20 MHz Channel mode: 16.35 dBm ( 43.15 mW) draft 802.11n Wide-40 MHz Channel mode: 14.29 dBm ( 26.85 mW)
<b>Antenna gain (Max)</b>	2dBi (Numeric gain: 1.58)
<b>Evaluation applied</b>	<input checked="" type="checkbox"/> MPE Evaluation* <input type="checkbox"/> SAR Evaluation <input type="checkbox"/> N/A

### **Remark:**

1. The maximum output power is 17.58dBm (57.27mW) at 2412MHz (with 1.58 numeric antenna gain.)
2. DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance.
3. For mobile or fixed location transmitters, no SAR consideration applied. The maximum power density is 1.0 mW/cm<sup>2</sup> even if the calculation indicates that the power density would be larger.

### TEST RESULTS

No non-compliance noted.



**Calculation**

Given  $E = \frac{\sqrt{30 \times P \times G}}{d}$  &  $S = \frac{E^2}{3770}$

Where  $E =$  Field strength in Volts / meter  
 $P =$  Power in Watts  
 $G =$  Numeric antenna gain  
 $d =$  Distance in meters  
 $S =$  Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770d^2}$$

Changing to units of mW and cm, using:

$P (mW) = P (W) / 1000$  and  
 $d (cm) = d(m) / 100$

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where  $d =$  Distance in cm  
 $P =$  Power in mW  
 $G =$  Numeric antenna gain  
 $S =$  Power density in mW / cm<sup>2</sup>

**Maximum Permissible Exposure**

Substituting the MPE safe distance using  $d = 20$  cm into Equation 1:

Yields

$$S = 0.000199 \times P \times G$$

Where  $P =$  Power in mW  
 $G =$  Numeric antenna gain  
 $S =$  Power density in mW / cm<sup>2</sup>



**IEEE 802.11b mode:**

EUT output power = 46.34mW

Numeric Antenna gain = 1.58

→ Power density = 0.013911 mW / cm<sup>2</sup>

**IEEE 802.11g mode:**

EUT output power = 57.27 mW

Numeric Antenna gain = 1.58

→ Power density = 0.017192 mW / cm<sup>2</sup>

**draft 802.11n Standard-20 MHz Channel mode:**

EUT output power =43.15 mW

Numeric Antenna gain = 1.58

→ Power density = 0.012954mW / cm<sup>2</sup>

**draft 802.11n Wide-40 MHz Channel mode:**

EUT output power = 26.85 mW

Numeric Antenna gain = 1.58

→ Power density = 0.00806 mW / cm<sup>2</sup>

*(For mobile or fixed location transmitters, the maximum power density is 1.0 mW/cm<sup>2</sup> even if the calculation indicates that the power density would be larger.)*