

# FCC RADIO TEST REPORT

according to

47 CFR FCC Part 15 Subpart C § 15.247

**Equipment** : 802.11abgn Wireless USB Module  
**Brand Name** : SparkLAN  
**Model No.** : WUBR-507N(LFG)  
**Filing Type** : New Application  
**Applicant** : SparkLAN Communications, Inc.  
8F., No.257, Sec. 2, Tiding Blvd., Neihu District,  
Taipei City 11493, Taiwan  
**FCC ID** : RYK-WUBR507NLFG  
**Manufacturer** : SparkLAN Communications, Inc.  
8F., No.257, Sec. 2, Tiding Blvd., Neihu District,  
Taipei City 11493, Taiwan  
**Received Date** : Nov. 08, 2010  
**Final Test Date** : Jan. 30, 2012

## Statement

**Test result included is only for the printed antenna 802.11n (5725~5850 MHz / 2400~2483.5MHz) of the product.**

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



**SPORTON International Inc.**

No. 52 Hwa Ya 1<sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

**Table of Contents**

**1 SUMMARY OF THE TEST RESULT ..... 2**

**2 GENERAL INFORMATION..... 3**

    2.1 Product Details ..... 3

    2.2 Table for Filed Antenna ..... 4

    2.3 Table for Carrier Frequencies ..... 5

    2.4 Table for Test Modes ..... 6

    2.5 Table for Testing Locations ..... 6

    2.6 Table for Supporting Units ..... 6

    2.7 Table for Parameters of Test Software Setting ..... 7

    2.8 EUT Operation during Test ..... 7

    2.9 Test Configuration ..... 8

**3 TEST RESULT ..... 10**

    3.1 AC Power Line Conducted Emissions Measurement ..... 10

    3.2 Peak Output Power Measurement ..... 14

    3.3 Power Spectral Density Measurement ..... 19

    3.4 6dB Spectrum Bandwidth Measurement ..... 36

    3.5 Radiated Emissions Measurement ..... 67

    3.6 Band Edge and Fundamental Emissions Measurement ..... 95

    3.7 Antenna Requirements ..... 108

**4 LIST OF MEASURING EQUIPMENTS ..... 109**

**5 TEST LOCATION ..... 111**

**6 TAF CERTIFICATE OF ACCREDITATION ..... 112**

**APPENDIX A. MAXIMUM PERMISSIBLE EXPOSURE ..... A1 ~ A3**

**APPENDIX B. TEST PHOTOS ..... B1 ~ B7**

**APPENDIX C. PHOTOGRAPHS OF EUT ..... C1 ~ C10**



# CERTIFICATE OF COMPLIANCE

according to

47 CFR FCC Part 15 Subpart C § 15.247

Equipment : 802.11abgn Wireless USB Module


Model No. : WUBR-507N(LFG)

Brand Name : SparkLAN

Applicant : SparkLAN Communications, Inc.

8F., No.257, Sec. 2, Tiding Blvd., Neihu District,  
Taipei City 11493, Taiwan

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Nov. 08, 2010 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



Wayne Hsu / Assistant Manager

## **SPORTON International Inc.**

No. 52 Hwa Ya 1<sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

**1 SUMMARY OF THE TEST RESULT**

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
3.1	15.207	AC Power Line Conducted Emissions	Complies	3.54 dB
3.2	15.247(b)(3)	Peak Output Power	Complies	10.38 dB
3.3	15.247(e)	Power Spectral Density	Complies	21.37 dB
3.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
3.5	15.247(d)	Radiated Emissions	Complies	3.03 dB
3.6	15.247(d)	Band Edge and Fundamental Emissions	Complies	1.03 dB
3.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Peak Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5×10 <sup>-8</sup>	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

## 2 GENERAL INFORMATION

### 2.1 Product Details

Only the radio detail of IEEE 802.11n is shown in this report. For more detailed features description, please refer to the manufacturer's specifications or user's manual.

Items	Description
Power Type	Power from host
Modulation Data Rate (Mbps)	See the below table for IEEE 802.11n
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Frequency Range	5725 ~ 5850MHz / 2400 ~ 2483.5MHz
Channel Number	5G- 5 for 20MHz bandwidth ; 2 for 40MHz bandwidth 2.4G- 11 for 20MHz bandwidth ; 7 for 40MHz bandwidth
Channel Band Width (99%)	5G- 2TX- MCS 8 (20MHz) : 17.48 MHz ; MCS 8 (40MHz) : 36.08 MHz 2.4G- 2TX- MCS 8 (20MHz) : 17.48 MHz ; MCS 8 (40MHz) : 36.00 MHz
Conducted Output Power	5G- 2TX- MCS 8 (20MHz) : 11.83 dBm ; MCS 8 (40MHz) : 11.40 dBm 2.4G- 2TX- MCS 8 (20MHz) : 19.62 dBm ; MCS 8 (40MHz) : 19.40 dBm

#### IEEE 802.11n Modulation Scheme

MCS Index	Nss	Modulation	R	NBPSC	NCBPS		NDBPS		Data rate(Mbps)	
					20MHz	40MHz	20MHz	40MHz	800nsGI	
									20MHz	40MHz
0	1	BPSK	1/2	1	52	108	26	54	6.5	13.5
1	1	QPSK	1/2	2	104	216	52	108	13.0	27.0
2	1	QPSK	3/4	2	104	216	78	162	19.5	40.5
3	1	16-QAM	1/2	4	208	432	104	216	26.0	54.0
4	1	16-QAM	3/4	4	208	432	156	324	39.0	81.0
5	1	64-QAM	2/3	6	312	648	208	432	52.0	108.0
6	1	64-QAM	3/4	6	312	648	234	486	58.5	121.5
7	1	64-QAM	5/6	6	312	648	260	540	65.0	135.0
8	2	BPSK	1/2	1	104	216	52	108	13.0	27.0
9	2	QPSK	1/2	2	208	432	104	216	26.0	54.0
10	2	QPSK	3/4	2	208	432	156	324	39.0	81.0
11	2	16-QAM	1/2	4	416	864	208	432	52.0	108.0
12	2	16-QAM	3/4	4	416	864	312	648	78.0	162.0
13	2	64-QAM	2/3	6	624	1296	416	864	104.0	216.0
14	2	64-QAM	3/4	6	624	1296	468	972	117.0	243.0
15	2	64-QAM	5/6	6	624	1296	520	1080	130.0	270.0

Symbol	Explanation
NSS	Number of spatial streams
R	Code rate
NBPSC	Number of coded bits per single carrier
NCBPS	Number of coded bits per symbol
NDBPS	Number of data bits per symbol
GI	guard interval

2.2 Table for Filed Antenna

Antenna Category Information	
<input type="checkbox"/>	Equipment placed on the market without antennas
<input checked="" type="checkbox"/>	Integral antenna (antenna permanently attached)
<input checked="" type="checkbox"/>	Temporary RF connector provided
<input type="checkbox"/>	No temporary RF connector provided
<input type="checkbox"/>	External antenna (dedicated antennas)
<input type="checkbox"/>	Single power level with corresponding antenna(s)
<input type="checkbox"/>	Multiple power settings and corresponding antenna(s)
<input type="checkbox"/>	Professional Install
<input type="checkbox"/>	Unique antenna connector
<input type="checkbox"/>	BIOS lock.

Antenna General Information						
Ant. No.	Category	Type	Brand	Model	Gain (dBi)	
					2.4G	5G
1	Internal	Printed	--	--	1.78	3.33
	Internal	Printed	--	--	1.78	3.33
<input type="checkbox"/> EUT is consist of single model antenna assembly for spatial multiplexing MIMO configuration. <input checked="" type="checkbox"/> EUT is consist of multiple model antennas assembly (secondary source multiple model antennas regardless of spatial multiplexing MIMO configuration), the test (except DFS test) should be performed with highest antenna gain of each antenna type. Then Ant. No. 1 shall be performed the test. <input type="checkbox"/> EUT is consist of multiple model antennas assembly for spatial multiplexing MIMO configuration (e.g. model A shall be installed in Port A and model B shall be installed in Port B...).						

Transmitter Outputs & Receiver Inputs Information				
Modulation	Transmitter Outputs	Receiver Inputs	Transmitter Output Signals	Co-location
802.11n HT20 / HT40	2 (SM)	2	Uncorrelated	No
Note 1: CDD - Cyclic Delay Diversity (CDD) modes (e.g., legacy modes in 802.11n devices). In CDD modes, the same digital data is carried by each transmit antenna, but with different cyclic delays. Note 2: STBC - Space Time Block Codes (STBC) for which different digital data is carried by each transmit antenna during any symbol period. Note 3: SM - Spatial Multiplexing MIMO (SM-MIMO), for which independent data streams are sent to each transmit antenna. Note 4: Co-location, Co-location is generally defined as simultaneously transmitting (co-transmitting) antennas within 20 cm of each other.				

Antenna Directional Gain							
Port. No.	Modulaton	Transmitter Outputs Signals Correlated	Transmitter Outputs (N)	Antenna Gain Combination (dBi)		Directional Gain (dBi)	
				2.4G	5G	2.4G	5G
1+2	802.11n HT20 / HT40	Uncorrelated	2	1.78, 1.78	3.33, 3.33	1.78	3.33
<input checked="" type="checkbox"/> For all transmitter outputs with equal antenna gains, directional gain is to be computed as follows ♦ Any transmit signals are correlated, Directional Gain = GANT + 10 log(N) dBi ♦ All transmit signals are completely uncorrelated, Directional Gain = GANT <input type="checkbox"/> For all transmitter outputs with unequal antenna gains, directional gain is to be computed as follows: ♦ Any transmit signals are correlated, Directional Gain = 10 log <sub>10</sub> [(10 <sup>G<sub>1</sub>/20</sup> + 10 <sup>G<sub>2</sub>/20</sup> + ... + 10 <sup>G<sub>N</sub>/20</sup> ) <sup>2</sup> / N] dBi ♦ All transmit signals are completely uncorrelated, Directional Gain = 10 log <sub>10</sub> [(10 <sup>G<sub>1</sub>/10</sup> + 10 <sup>G<sub>2</sub>/10</sup> + ... + 10 <sup>G<sub>N</sub>/10</sup> ) / N] dBi							

**2.3 Table for Carrier Frequencies**

Frequency Band	Channel No.	Frequency (20MHz)	Channel No.	Frequency (40MHz)
5725~5850 MHz	149	5745 MHz	151	5755 MHz
	153	5765 MHz	159	5795 MHz
	157	5785 MHz	-	-
	161	5805 MHz	-	-
	165	5825 MHz	-	-

Frequency Band	Channel No.	Frequency (20MHz)	Channel No.	Frequency (20MHz)
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz	-	-

Frequency Band	Channel No.	Frequency (40MHz)
2400~2483.5MHz	3	2422 MHz
	4	2427 MHz
	5	2432 MHz
	6	2437 MHz
	7	2442 MHz
	8	2447 MHz
	9	2452 MHz



**2.4 Table for Test Modes**

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on the entire possible configuration for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Port. No.
AC Power Line Conducted Emissions	Normal Mode	Auto	-	-
Peak Output Power	MCS 8 (20MHz)	13 Mbps	5G-149/157/165 2.4G-1/6/11	1/2 1+2
	MCS 8 (40MHz)	27 Mbps	5G-151/159 2.4G-3/6/9	1/2 1+2
Power Spectral Density 6dB Spectrum Bandwidth	MCS 8 (20MHz)	13 Mbps	5G-149/157/165 2.4G-1/6/11	1/2 1+2
	MCS 8 (40MHz)	27 Mbps	5G-151/159 2.4G-3/6/9	1/2 1+2
Radiated Emissions Below 1GHz	Normal Mode	Auto	-	-
Radiated Emissions Above 1GHz	MCS 8 (20MHz)	13 Mbps	5G-149/157/165 2.4G-1/6/11	1+2
	MCS 8 (40MHz)	27 Mbps	5G-151/159 2.4G-3/6/9	1+2
Band Edge Emissions	MCS 8 (20MHz)	13 Mbps	5G-149/165 2.4G-1/11	1+2
	MCS 8 (40MHz)	27 Mbps	5G-151/159 2.4G-3/6/9	1+2

**2.5 Table for Testing Locations**

Test Site No.	Site Category	Location
CO04-HY	Conduction	Hwa Ya
TH01-HY	OVEN Room	Hwa Ya
03CH02-HY	SAC	Hwa Ya

Semi Anechoic Chamber (SAC).

**2.6 Table for Supporting Units**

Support Unit	Brand	Model	FCC ID	Remark
Notebook	DELL	PP20L	N/A	Conducted Emissions
(USB) Mouse	Microsoft	1004	N/A	
iPod Nano	Apple	A1119	N/A	
Wireless AP (Remote Workstation)	EDIMAX	BR-6204WG	NDD9562040507	
Mouse	Microsoft	1004	R31264	Radiated Emissions
Notebook	DELL	E5520	DoC	
iPod	APPLE	A1199	DoC	

**2.7 Table for Parameters of Test Software Setting**

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

**Power Parameters of IEEE 802.11n-5G**

Test Software Version	Ralink RT3x7xQA		
Frequency	5745 MHz	5785 MHz	5825 MHz
IEEE 802.11n(20MHz)	04 / 04	05 / 04	06 / 05
Frequency	5755 MHz	5795 MHz	-
IEEE 802.11n(40MHz)	06 / 04	06 / 04	-

**Power Parameters of IEEE 802.11n-2.4G**

Test Software Version	Ralink RT3x7xQA		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11n(20MHz)	06 / 08	08 / 0A	09 / 0B
Frequency	2422 MHz	2437 MHz	2452 MHz
IEEE 802.11n(40MHz)	07 / 08	08 / 0A	08 / 0B

**2.8 EUT Operation during Test**

An executive program, "EMCTEST.EXE" under WIN XP, which generates a complete line of continuously repeating "H" pattern was used as the test software.

The program was executed as follows :

- a. Turn on the power of all equipment.
- b. The NB reads the test program "Winthrax.exe" was executed to read and write data from EUT.
- c. The NB sends "H" messages to the panel and displays "H" patterns on the screen.
- d. Repeat the steps from b to c.

At the same time, the following programs were executed:


- Executed "Winthrax.exe" to read and write data from iPod.
- Executed "ping.exe" to link with the remote workstation to receive and transmit data by WLAN.

Only Radiated used:


- Executed "Ralink RT3x7xQA" to keep transmitting signals at fixed frequency.

**2.9 Test Configuration**


**For conducted emissions**



For radiated emissions 9kHz~1GHz



For radiated emissions above 1GHz



**3 TEST RESULT**

**3.1 AC Power Line Conducted Emissions Measurement**

**3.1.1 Limit**

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

**Class B**

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

**3.1.2 Measuring Instruments and Setting**


Please refer to section 4 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

**3.1.3 Test Procedures**

1. The EUT warm up about 15 minutes then start test.
2. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
3. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
4. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
5. The frequency range from 150 KHz to 30 MHz was searched.
6. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
7. The measurement has to be done between each power line and ground at the power terminal.

3.1.4 Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω. LISN can be placed on top of, or immediately beneath, reference ground plane.
  - (3.1) All other equipment powered from additional LISN(s).
  - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
  - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

3.1.5 Test Deviation

There is no deviation with the original standard.


3.1.6 EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.

3.1.7 Results of AC Power Line Conducted Emissions Measurement


<b>Final Test Date</b>	Nov. 08, 2010	<b>Test Site No.</b>	CO04-HY
<b>Temperature</b>	24.9°C	<b>Humidity</b>	47.2%
<b>Test Engineer</b>	Jason	<b>Configuration</b>	Normal Mode

Line



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.1730540	47.68	-7.13	54.81	47.31	0.08	0.29	Average
2	0.1730540	53.18	-11.63	64.81	52.81	0.08	0.29	QP
3	0.2316380	47.76	-14.63	62.39	47.40	0.08	0.28	QP
4	0.2316380	39.96	-12.43	52.39	39.60	0.08	0.28	Average
5	0.2893470	41.89	-18.65	60.54	41.59	0.09	0.21	QP
6	0.2893470	34.39	-16.15	50.54	34.09	0.09	0.21	Average
7	1.850	35.97	-10.03	46.00	35.70	0.13	0.14	Average
8	1.850	42.37	-13.63	56.00	42.10	0.13	0.14	QP
9	4.000	37.78	-8.22	46.00	37.40	0.16	0.22	Average
10	4.000	51.48	-4.52	56.00	51.10	0.16	0.22	QP
11	5.200	41.65	-18.35	60.00	41.21	0.19	0.25	QP
12	5.200	30.75	-19.25	50.00	30.31	0.19	0.25	Average

Neutral



	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.1720450	46.27	-8.59	54.86	45.90	0.08	0.29	Average
2	0.1720450	52.14	-12.72	64.86	51.77	0.08	0.29	QP
3	0.2303960	47.66	-14.78	62.44	47.30	0.08	0.28	QP
4	0.2303960	39.96	-12.48	52.44	39.60	0.08	0.28	Average
5	0.2882840	41.39	-19.18	60.57	41.10	0.08	0.21	QP
6	0.2882840	35.99	-14.58	50.57	35.70	0.08	0.21	Average
7	2.020	36.95	-9.05	46.00	36.70	0.11	0.14	Average
8	2.020	43.55	-12.45	56.00	43.30	0.11	0.14	QP
9	3.870	38.76	-7.24	46.00	38.39	0.15	0.22	Average
10	3.870	52.46	-3.54	56.00	52.09	0.15	0.22	QP
11	5.420	37.75	-22.25	60.00	37.30	0.19	0.26	QP
12	5.420	27.95	-22.05	50.00	27.50	0.19	0.26	Average

Note:  
Level = Read Level + LISN Factor + Cable Loss.



**3.2 Peak Output Power Measurement**

**3.2.1 Limit**

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-multipoint antenna reduction operation, the limit has to be reduced by 1dB for every dB that the directional gain of the antenna exceeds 6dBi. Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted output power.

**3.2.2 Measuring Instruments and Setting**


Please refer to section 4 of equipments list in this report. The following table is the setting of the power meter.

<b>Power Meter Parameter</b>	<b>Setting</b>
Filter No.	Auto
Measurement time	0.135 s ~ 26 s
Used Peak Sensor	MA2411B

**3.2.3 Test Procedures**

1. The transmitter output (antenna port) was connected to the power meter.
2. Turn on the EUT and power meter and then record the peak power value.
3. Repeat above procedures on all channels needed to be tested.
4. When measuring maximum conducted output power within multiple antenna systems, add every result of the values by mathematic formula.

**3.2.4 Test Setup Layout**



**3.2.5 Test Deviation**

There is no deviation with the original standard.

**3.2.6 EUT Operation during Test**

The EUT was programmed to be in continuously transmitting mode.

**3.2.7 Test Result of Peak Output Power**

<b>Final Test Date</b>	Jan. 14, 2012	<b>Test Site No.</b>	TH01-HY
<b>Temperature</b>	21.4°C	<b>Humidity</b>	25%
<b>Test Engineer</b>	Shiming	<b>Configurations</b>	802.11n

**Configuration of IEEE 802.11n-5G Port 1 (20MHz)**

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	8.77	30.00	<b>Complies</b>
157	5785 MHz	8.52	30.00	<b>Complies</b>
165	5825 MHz	8.90	30.00	<b>Complies</b>

**Configuration of IEEE 802.11n-5G Port 2 (20MHz)**

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	8.60	30.00	<b>Complies</b>
157	5785 MHz	8.25	30.00	<b>Complies</b>
165	5825 MHz	8.73	30.00	<b>Complies</b>

**Configuration of IEEE 802.11n-5G Port 1+ Port 2 (20MHz)**

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	11.70	30.00	<b>Complies</b>
157	5785 MHz	11.40	30.00	<b>Complies</b>
165	5825 MHz	11.83	30.00	<b>Complies</b>

**Configuration of IEEE 802.11n-5G Port 1 (40MHz)**

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
151	5755 MHz	8.31	30.00	<b>Complies</b>
159	5795 MHz	8.46	30.00	<b>Complies</b>

**Configuration of IEEE 802.11n-5G Port 2 (40MHz)**

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
151	5755 MHz	8.46	30.00	<b>Complies</b>
159	5795 MHz	8.05	30.00	<b>Complies</b>

**Configuration of IEEE 802.11n-5G Port 1+ Port 2 (40MHz)**

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
151	5755 MHz	11.40	30.00	<b>Complies</b>
159	5795 MHz	11.27	30.00	<b>Complies</b>

**Configuration of IEEE 802.11n-2.4G Port 1 (20MHz)**

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	16.32	30.00	<b>Complies</b>
6	2437 MHz	16.68	30.00	<b>Complies</b>
11	2462 MHz	16.42	30.00	<b>Complies</b>

**Configuration of IEEE 802.11n-2.4G Port 2 (20MHz)**

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	16.15	30.00	<b>Complies</b>
6	2437 MHz	16.53	30.00	<b>Complies</b>
11	2462 MHz	16.48	30.00	<b>Complies</b>

**Configuration of IEEE 802.11n-2.4G Port 1+ Port 2 (20MHz)**

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	19.25	30.00	<b>Complies</b>
6	2437 MHz	19.62	30.00	<b>Complies</b>
11	2462 MHz	19.46	30.00	<b>Complies</b>

**Configuration of IEEE 802.11n-2.4G Port 1 (40MHz)**

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	16.11	30.00	<b>Complies</b>
6	2437 MHz	16.33	30.00	<b>Complies</b>
9	2452 MHz	15.90	30.00	<b>Complies</b>

**Configuration of IEEE 802.11n-2.4G Port 2 (40MHz)**

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	15.95	30.00	<b>Complies</b>
6	2437 MHz	16.45	30.00	<b>Complies</b>
9	2452 MHz	16.70	30.00	<b>Complies</b>

**Configuration of IEEE 802.11n-2.4G Port 1+ Port 2 (40MHz)**

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	19.04	30.00	<b>Complies</b>
6	2437 MHz	19.40	30.00	<b>Complies</b>
9	2452 MHz	19.33	30.00	<b>Complies</b>

**3.3 Power Spectral Density Measurement**

**3.3.1 Limit**

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

**3.3.2 Measuring Instruments and Setting**


Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	1.5MHz
RB	3 kHz
VB	30 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	500s

**3.3.3 Test Procedures**

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Set RBW of spectrum analyzer to 3kHz and VBW to 30kHz. Set Detector to Peak, Trace to Max Hold.
3. Mark the frequency with maximum peak power as the center of the display of the spectrum.
4. Set the span to 1.5MHz and the sweep time to 500s and record the maximum peak value.
5. Measuring multiple antennas, the connectors are required to link with Spectrum Analyzer through a combiner.

**3.3.4 Test Setup Layout**



**3.3.5 Test Deviation**

There is no deviation with the original standard.

**3.3.6 EUT Operation during Test**

The EUT was programmed to be in continuously transmitting mode.

**3.3.7 Test Result of Power Spectral Density**

<b>Final Test Date</b>	Jan. 14, 2012	<b>Test Site No.</b>	TH01-HY
<b>Temperature</b>	21.4°C	<b>Humidity</b>	25%
<b>Test Engineer</b>	Shiming	<b>Configurations</b>	802.11n

**Configuration of IEEE 802.11n-5G Port 1 (20MHz)**

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	-24.82	8.00	<b>Complies</b>
157	5785 MHz	-24.84	8.00	<b>Complies</b>
165	5825 MHz	-25.59	8.00	<b>Complies</b>

**Configuration of IEEE 802.11n-5G Port 2 (20MHz)**

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	-28.56	8.00	<b>Complies</b>
157	5785 MHz	-26.66	8.00	<b>Complies</b>
165	5825 MHz	-27.36	8.00	<b>Complies</b>

**Configuration of IEEE 802.11n-5G Port 1+ Port 2 (20MHz)**

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	-23.29	8.00	<b>Complies</b>
157	5785 MHz	-22.65	8.00	<b>Complies</b>
165	5825 MHz	-23.38	8.00	<b>Complies</b>

**Configuration of IEEE 802.11n-5G Port 1 (40MHz)**

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
151	5755 MHz	-25.30	8.00	<b>Complies</b>
159	5795 MHz	-25.52	8.00	<b>Complies</b>

**Configuration of IEEE 802.11n-5G Port 2 (40MHz)**

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
151	5755 MHz	-27.40	8.00	<b>Complies</b>
159	5795 MHz	-27.73	8.00	<b>Complies</b>

**Configuration of IEEE 802.11n-5G Port 1+ Port 2 (40MHz)**

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
151	5755 MHz	-23.21	8.00	<b>Complies</b>
159	5795 MHz	-23.48	8.00	<b>Complies</b>

**Configuration of IEEE 802.11n-2.4G Port 1 (20MHz)**

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-18.05	8.00	Complies
6	2437 MHz	-17.75	8.00	Complies
11	2462 MHz	-18.31	8.00	Complies

**Configuration of IEEE 802.11n-2.4G Port 2 (20MHz)**

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-15.17	8.00	Complies
6	2437 MHz	-15.84	8.00	Complies
11	2462 MHz	-16.14	8.00	Complies

**Configuration of IEEE 802.11n-2.4G Port 1+ Port 2 (20MHz)**

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-13.37	8.00	Complies
6	2437 MHz	-13.68	8.00	Complies
11	2462 MHz	-14.08	8.00	Complies

**Configuration of IEEE 802.11n-2.4G Port 1 (40MHz)**

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	-18.83	8.00	Complies
6	2437 MHz	-18.52	8.00	Complies
9	2452 MHz	-18.73	8.00	Complies

**Configuration of IEEE 802.11n-2.4G Port 2 (40MHz)**


Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	-15.36	8.00	Complies
6	2437 MHz	-16.11	8.00	Complies
9	2452 MHz	-15.97	8.00	Complies

**Configuration of IEEE 802.11n-2.4G Port 1+ Port 2 (40MHz)**

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	-13.75	8.00	Complies
6	2437 MHz	-14.14	8.00	Complies
9	2452 MHz	-14.12	8.00	Complies




Power Density Plot on Configuration of IEEE 802.11n-5G Port 1 (20MHz) / 5745 MHz




Date: 14.JAN.2012 09:42:55

Power Density Plot on Configuration of IEEE 802.11n-5G Port 1 (20MHz) / 5785 MHz




Date: 14.JAN.2012 09:50:25

Power Density Plot on Configuration of IEEE 802.11n-5G Port 1 (20MHz) / 5825 MHz




Date: 14.JAN.2012 10:25:15

Power Density Plot on Configuration of IEEE 802.11n-5G Port 2 (20MHz) / 5745 MHz




Date: 14.JAN.2012 09:31:45

Power Density Plot on Configuration of IEEE 802.11n-5G Port 2 (20MHz) / 5785 MHz




Date: 14.JAN.2012 10:00:32

Power Density Plot on Configuration of IEEE 802.11n-5G Port 2 (20MHz) / 5825 MHz




Date: 14.JAN.2012 10:13:19

Power Density Plot on Configuration of IEEE 802.11n-5G Port 1 (40MHz) / 5755 MHz




Date: 14. JAN. 2012 10:45:29

Power Density Plot on Configuration of IEEE 802.11n-5G Port 1 (40MHz) / 5795 MHz




Date: 14. JAN. 2012 11:17:23

Power Density Plot on Configuration of IEEE 802.11n-5G Port 2 (40MHz) / 5755 MHz




Date: 14.JAN.2012 10:55:36

Power Density Plot on Configuration of IEEE 802.11n-5G Port 2 (40MHz) / 5795 MHz




Date: 14.JAN.2012 11:08:00

Power Density Plot on Configuration of IEEE 802.11n-2.4G Port 1 (20MHz) / 2412 MHz




Date: 11.JAN.2012 10:59:09

Power Density Plot on Configuration of IEEE 802.11n-2.4G Port 1 (20MHz) / 2437 MHz



Date: 11.JAN.2012 13:46:26


Power Density Plot on Configuration of IEEE 802.11n-2.4G Port 1 (20MHz) / 2462 MHz



Date: 11.JAN.2012 14:01:31




Power Density Plot on Configuration of IEEE 802.11n-2.4G Port 2 (20MHz) / 2412 MHz




Date: 11.JAN.2012 12:56:27

Power Density Plot on Configuration of IEEE 802.11n-2.4G Port 2 (20MHz) / 2437 MHz




Date: 11.JAN.2012 13:16:50

Power Density Plot on Configuration of IEEE 802.11n-2.4G Port 2 (20MHz) / 2462 MHz




Date: 11.JAN.2012 14:14:12

Power Density Plot on Configuration of IEEE 802.11n-2.4G Port 1 (40MHz) / 2422 MHz




Date: 11. JAN. 2012 14:40:41

Power Density Plot on Configuration of IEEE 802.11n-2.4G Port 1 (40MHz) / 2437 MHz




Date: 11. JAN. 2012 14:47:32

Power Density Plot on Configuration of IEEE 802.11n-2.4G Port 1 (40MHz) / 2452 MHz




Date: 11.JAN.2012 15:23:53

Power Density Plot on Configuration of IEEE 802.11n-2.4G Port 2 (40MHz) / 2422 MHz




Date: 11. JAN. 2012 14:25:59

Power Density Plot on Configuration of IEEE 802.11n-2.4G Port 2 (40MHz) / 2437 MHz



Date: 11. JAN. 2012 14:57:18

Power Density Plot on Configuration of IEEE 802.11n-2.4G Port 2 (40MHz) / 2452 MHz



Date: 11.JAN.2012 15:07:56

**3.4 6dB Spectrum Bandwidth Measurement**

**3.4.1 Limit**

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

**3.4.2 Measuring Instruments and Setting**


Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

<b>Spectrum Parameters</b>	<b>Setting</b>
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	100 kHz
VB	300 kHz
Detector	Sample
Trace	Max Hold
Sweep Time	Auto

**3.4.3 Test Procedures**

1. The transmitter output (antenna port) was connected to the spectrum analyzer in sample hold mode.
2. The resolution bandwidth of 100 kHz and the video bandwidth of 300 kHz were used.
3. Measured the spectrum width with power higher than 6dB below carrier.
4. For 99% Occupied Bandwidth the resolution Bandwidth  $\geq 1\%$  of the selected span.

**3.4.4 Test Setup Layout**



**3.4.5 Test Deviation**

There is no deviation with the original standard.

**3.4.6 EUT Operation during Test**

The EUT was programmed to be in continuously transmitting mode.

**3.4.7 Test Result of 6dB Spectrum Bandwidth**

<b>Final Test Date</b>	Jan. 14, 2012	<b>Test Site No.</b>	TH01-HY
<b>Temperature</b>	21.4°C	<b>Humidity</b>	25%
<b>Test Engineer</b>	Shiming	<b>Configurations</b>	802.11n

**Configuration of IEEE 802.11n-5G Port 1 (20MHz)**

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	17.56	17.48	500	<b>Complies</b>
157	5785 MHz	17.56	17.48	500	<b>Complies</b>
165	5825 MHz	17.56	17.48	500	<b>Complies</b>

**Configuration of IEEE 802.11n-5G Port 2 (20MHz)**

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	17.04	17.48	500	<b>Complies</b>
157	5785 MHz	17.56	17.48	500	<b>Complies</b>
165	5825 MHz	17.32	17.48	500	<b>Complies</b>

**Configuration of IEEE 802.11n-5G Port 1 (40MHz)**

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
151	5755 MHz	36.32	36.00	500	<b>Complies</b>
159	5795 MHz	36.32	36.08	500	<b>Complies</b>

**Configuration of IEEE 802.11n-5G Port 2 (40MHz)**

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
151	5755 MHz	35.68	36.00	500	<b>Complies</b>
159	5795 MHz	36.08	36.08	500	<b>Complies</b>



**Configuration of IEEE 802.11n-2.4G Port 1 (20MHz)**

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	17.56	17.48	500	Complies
6	2437 MHz	17.52	17.48	500	Complies
11	2462 MHz	17.52	17.48	500	Complies

**Configuration of IEEE 802.11n-2.4G Port 2 (20MHz)**

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	17.52	17.44	500	Complies
6	2437 MHz	17.52	17.48	500	Complies
11	2462 MHz	17.28	17.48	500	Complies


**Configuration of IEEE 802.11n-2.4G Port 1 (40MHz)**

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
3	2422 MHz	36.08	36.00	500	Complies
6	2437 MHz	36.08	36.00	500	Complies
9	2452 MHz	36.08	36.00	500	Complies

**Configuration of IEEE 802.11n-2.4G Port 2 (40MHz)**


Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
3	2422 MHz	34.80	36.00	500	Complies
6	2437 MHz	35.12	36.00	500	Complies
9	2452 MHz	35.12	36.00	500	Complies

6 dB Bandwidth Plot on Configuration of IEEE 802.11n-5G Port 1 (20MHz) / 5745 MHz




Date: 14.JAN.2012 09:37:34

6 dB Bandwidth Plot on Configuration of IEEE 802.11n-5G Port 1 (20MHz) / 5785 MHz




Date: 14.JAN.2012 09:47:04

6 dB Bandwidth Plot on Configuration of IEEE 802.11n-5G Port 1 (20MHz) / 5825 MHz




Date: 14.JAN.2012 10:18:55

6 dB Bandwidth Plot on Configuration of IEEE 802.11n-5G Port 2 (20MHz) / 5745 MHz




Date: 14.JAN.2012 09:22:38

6 dB Bandwidth Plot on Configuration of IEEE 802.11n-5G Port 2 (20MHz) / 5785 MHz




Date: 14.JAN.2012 09:55:42

6 dB Bandwidth Plot on Configuration of IEEE 802.11n-5G Port 2 (20MHz) / 5825 MHz




Date: 14.JAN.2012 10:05:47

6 dB Bandwidth Plot on Configuration of IEEE 802.11n-5G Port 1 (40MHz) / 5755 MHz




Date: 14.JAN.2012 10:39:55

6 dB Bandwidth Plot on Configuration of IEEE 802.11n-5G Port 1 (40MHz) / 5795 MHz




Date: 14.JAN.2012 11:12:08

6 dB Bandwidth Plot on Configuration of IEEE 802.11n-5G Port 2 (40MHz) / 5755 MHz




Date: 14.JAN.2012 10:50:40

6 dB Bandwidth Plot on Configuration of IEEE 802.11n-5G Port 2 (40MHz) / 5795 MHz




Date: 14.JAN.2012 11:01:16

6 dB Bandwidth Plot on Configuration of IEEE 802.11n-2.4G Port 1 (20MHz) / 2412 MHz



Date: 11.JAN.2012 10:44:09


6 dB Bandwidth Plot on Configuration of IEEE 802.11n-2.4G Port 1 (20MHz) / 2437 MHz



Date: 11.JAN.2012 13:38:32




6 dB Bandwidth Plot on Configuration of IEEE 802.11n-2.4G Port 1 (20MHz) / 2462 MHz




Date: 11.JAN.2012 13:53:30

6 dB Bandwidth Plot on Configuration of IEEE 802.11n-2.4G Port 2 (20MHz) / 2412 MHz




Date: 11. JAN. 2012 11:05:00

6 dB Bandwidth Plot on Configuration of IEEE 802.11n-2.4G Port 2 (20MHz) / 2437 MHz




Date: 11. JAN. 2012 13:10:22

6 dB Bandwidth Plot on Configuration of IEEE 802.11n-2.4G Port 2 (20MHz) / 2462 MHz




Date: 11.JAN.2012 14:09:05

6 dB Bandwidth Plot on Configuration of IEEE 802.11n-2.4G Port 1 (40MHz) / 2422 MHz




Date: 11. JAN. 2012 14:35:05

6 dB Bandwidth Plot on Configuration of IEEE 802.11n-2.4G Port 1 (40MHz) / 2437 MHz




Date: 11. JAN. 2012 14:44:01

6 dB Bandwidth Plot on Configuration of IEEE 802.11n-2.4G Port 1 (40MHz) / 2452 MHz




Date: 11.JAN.2012 15:12:20

6 dB Bandwidth Plot on Configuration of IEEE 802.11n-2.4G Port 2 (40MHz) / 2422 MHz




Date: 11. JAN. 2012 14:20:18

6 dB Bandwidth Plot on Configuration of IEEE 802.11n-2.4G Port 2 (40MHz) / 2437 MHz




Date: 11. JAN. 2012 14:53:32

6 dB Bandwidth Plot on Configuration of IEEE 802.11n-2.4G Port 2 (40MHz) / 2452 MHz




Date: 11.JAN.2012 15:01:38

99% Occupied Bandwidth Plot on Configuration of IEEE 802.11n-5G Port 1 (20MHz) / 5745 MHz



Date: 14.JAN.2012 09:39:06


99% Occupied Bandwidth Plot on Configuration of IEEE 802.11n-5G Port 1 (20MHz) / 5785 MHz



Date: 14.JAN.2012 09:49:08




99% Occupied Bandwidth Plot on Configuration of IEEE 802.11n-5G Port 1 (20MHz) / 5825 MHz




Date: 14.JAN.2012 10:20:04

99% Occupied Bandwidth Plot on Configuration of IEEE 802.11n-5G Port 2 (20MHz) / 5745 MHz




Date: 14.JAN.2012 09:25:16

99% Occupied Bandwidth Plot on Configuration of IEEE 802.11n-5G Port 2 (20MHz) / 5785 MHz




Date: 14.JAN.2012 09:58:30

99% Occupied Bandwidth Plot on Configuration of IEEE 802.11n-5G Port 2 (20MHz) / 5825 MHz




Date: 14.JAN.2012 10:07:56

99% Occupied Bandwidth Plot on Configuration of IEEE 802.11n-5G Port 1 (40MHz) / 5755 MHz




Date: 14.JAN.2012 10:41:40

99% Occupied Bandwidth Plot on Configuration of IEEE 802.11n-5G Port 1 (40MHz) / 5795 MHz




Date: 14.JAN.2012 11:14:13

99% Occupied Bandwidth Plot on Configuration of IEEE 802.11n-5G Port 2 (40MHz) / 5755 MHz




Date: 14.JAN.2012 10:51:59

99% Occupied Bandwidth Plot on Configuration of IEEE 802.11n-5G Port 2 (40MHz) / 5795 MHz




Date: 14.JAN.2012 11:03:31

99% Occupied Bandwidth Plot on Configuration of IEEE 802.11n-2.4G Port 1 (20MHz) / 2412 MHz




Date: 11.JAN.2012 10:49:21

99% Occupied Bandwidth Plot on Configuration of IEEE 802.11n-2.4G Port 1 (20MHz) / 2437 MHz




Date: 11.JAN.2012 13:41:39

99% Occupied Bandwidth Plot on Configuration of IEEE 802.11n-2.4G Port 1 (20MHz) / 2462 MHz




Date: 11.JAN.2012 13:55:02

99% Occupied Bandwidth Plot on Configuration of IEEE 802.11n-2.4G Port 2 (20MHz) / 2412 MHz



Date: 11.JAN.2012 11:08:14


99% Occupied Bandwidth Plot on Configuration of IEEE 802.11n-2.4G Port 2 (20MHz) / 2437 MHz



Date: 11.JAN.2012 13:13:39




99% Occupied Bandwidth Plot on Configuration of IEEE 802.11n-2.4G Port 2 (20MHz) / 2462 MHz




Date: 11.JAN.2012 14:10:58

99% Occupied Bandwidth Plot on Configuration of IEEE 802.11n-2.4G Port 1 (40MHz) / 2422 MHz




Date: 11. JAN. 2012 14:36:37

99% Occupied Bandwidth Plot on Configuration of IEEE 802.11n-2.4G Port 1 (40MHz) / 2437 MHz




Date: 11. JAN. 2012 14:45:58

99% Occupied Bandwidth Plot on Configuration of IEEE 802.11n-2.4G Port 1 (40MHz) / 2452 MHz




Date: 11.JAN.2012 15:14:20

99% Occupied Bandwidth Plot on Configuration of IEEE 802.11n-2.4G Port 2 (40MHz) / 2422 MHz




Date: 11.JAN.2012 14:22:08

99% Occupied Bandwidth Plot on Configuration of IEEE 802.11n-2.4G Port 2 (40MHz) / 2437 MHz



Date: 11.JAN.2012 14:55:36

99% Occupied Bandwidth Plot on Configuration of IEEE 802.11n-2.4G Port 2 (40MHz) / 2452 MHz



Date: 11.JAN.2012 15:03:01

**3.5 Radiated Emissions Measurement**

**3.5.1 Limit**

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter measurement is based on the maximum conducted output power, the attenuation required under this paragraph shall be 30dB instead of 20dB. In addition, radiated emissions which fall in section 15.205(a) the restricted bands must also comply with the radiated emission limit specified in section 15.209(a).

<b>Frequencies (MHz)</b>	<b>Field Strength (microvolt/meter)</b>	<b>Measurement Distance (meters)</b>
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

**3.5.2 Measuring Instruments and Setting**

Please refer to section 4 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

<b>Spectrum Parameter</b>	<b>Setting</b>
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for peak


<b>Receiver Parameter</b>	<b>Setting</b>
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

**3.5.3 Test Procedures**


1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

3.5.4 Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.  
 Distance extrapolation factor =  $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$  (dB);  
 Limit line = specific limits (dBuV) + distance extrapolation factor [9.54 dB].

3.5.5 Test Deviation

There is no deviation with the original standard.

3.5.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.



**3.5.7 Results of Radiated Emissions (9kHz~30MHz)**

<b>Final Test Date</b>	Jan. 17, 2012	<b>Test Site No.</b>	03CH02-HY
<b>Temperature</b>	20°C	<b>Humidity</b>	66%
<b>Test Engineer</b>	Streak		

<b>Freq. (MHz)</b>	<b>Level (dBuV)</b>	<b>Over Limit (dB)</b>	<b>Limit Line (dBuV)</b>	<b>Remark</b>
-	-	-	-	See Note

**Note:**

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor =  $40 \log(\text{specific distance} / \text{test distance})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

3.5.8 Results of Radiated Emissions (30MHz~1GHz)


<b>Final Test Date</b>	Jan. 17, 2012	<b>Test Site No.</b>	03CH02-HY
<b>Temperature</b>	20°C	<b>Humidity</b>	66%
<b>Test Engineer</b>	Streak	<b>Configurations</b>	Normal Mode

Horizontal



	Freq	Level	Over Limit	Limit	Read	Antenna	Cable	Preamp	Remark	Ant Pos	Table Pos
	MHz	dBUV/m	dB	dBUV/m	dBuV	dB/m	dB	dB		cm	deg
1	141.550	28.30	-15.20	43.50	42.19	11.78	2.00	27.67	Peak	---	---
2	164.830	34.30	-9.20	43.50	49.38	10.34	2.14	27.56	Peak	---	---
3	230.790	31.13	-14.87	46.00	43.45	12.37	2.64	27.33	Peak	---	---
4	335.550	29.60	-16.40	46.00	39.63	14.26	3.12	27.41	Peak	---	---
5	439.340	28.13	-17.87	46.00	36.61	16.06	3.53	28.07	Peak	---	---
6	913.670	30.72	-15.28	46.00	32.57	20.37	5.33	27.55	Peak	---	---

Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	94.990	36.51	-6.99	43.50	52.42	10.34	1.60	27.85	Peak	---	---
2	141.550	36.03	-7.47	43.50	49.92	11.78	2.00	27.67	Peak	---	---
3	164.830	39.13	-4.37	43.50	54.21	10.34	2.14	27.56	Peak	---	---
4	629.460	31.19	-14.81	46.00	35.48	19.79	4.33	28.41	Peak	---	---
5	696.390	30.35	-15.65	46.00	35.22	18.89	4.53	28.29	Peak	---	---
6	749.740	31.09	-14.91	46.00	34.94	19.55	4.71	28.11	Peak	---	---

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).


Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

3.5.9 Results for Radiated Emissions (1GHz~10<sup>th</sup> Harmonic)

For Two Chains

Final Test Date	Jan. 19, 2012	Test Site No.	03CH02-HY
Temperature	20°C	Humidity	66%
Test Engineer	Streak	Configuration	5G 802.11n Ch. 149 (20MHz)


Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBUV/m	dB	dBUV/m	dBuV	dB/m	dB	dB		cm	deg
1	9320.000	52.18	-11.36	63.54	42.55	38.78	6.26	35.41	PK	---	---
2	11490.000	55.69	-7.85	63.54	43.19	40.59	6.63	34.72	PK	---	---
3	17235.000	62.92			44.79	43.56	8.55	33.98	Peak	---	---

Note: The item 3 is are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Vertical




	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	9190.000	52.16	-11.38	63.54	42.79	38.52	6.22	35.37	PK	---	---
2	11490.000	55.58	-7.96	63.54	43.08	40.59	6.63	34.72	PK	---	---
3	17235.000	62.59			44.46	43.56	8.55	33.98	Peak	---	---

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

<b>Final Test Date</b>	Jan. 20, 2012	<b>Test Site No.</b>	03CH02-HY
<b>Temperature</b>	20°C	<b>Humidity</b>	66%
<b>Test Engineer</b>	Streak	<b>Configuration</b>	5G 802.11n Ch. 157 (20MHz)


**Horizontal**



	<b>Freq</b>	<b>Level</b>	<b>Over Limit</b>	<b>Limit Line</b>	<b>ReadAntenna Level</b>	<b>Antenna Factor</b>	<b>Cable Loss</b>	<b>Preamp Factor</b>	<b>Remark</b>	<b>Ant Pos</b>	<b>Table Pos</b>
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	8780.000	53.35			44.30	38.27	6.06	35.28	Peak	---	---
2	11570.000	55.95	-7.59	63.54	43.45	40.63	6.63	34.76	PK	---	---
3	17355.000	63.18			45.17	43.49	8.50	33.98	Peak	---	---

Note: The item 1 and 3 on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Vertical




	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	8620.000	52.34			43.20	38.41	5.99	35.26	Peak	---	---
2	11570.000	55.54	-8.00	63.54	43.04	40.63	6.63	34.76	PK	---	---
3	17355.000	63.06			45.05	43.49	8.50	33.98	Peak	---	---

Note: The item 1 and 3 on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Final Test Date	Jan. 20, 2012	Test Site No.	03CH02-HY
Temperature	20°C	Humidity	66%
Test Engineer	Streak	Configuration	5G 802.11n Ch. 165 (20MHz)

Horizontal




	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	8840.000	52.16			43.13	38.23	6.09	35.29	Peak	---	---
2	11650.000	55.90	-7.64	63.54	43.41	40.66	6.64	34.81	PK	---	---
3	17475.000	62.49			44.61	43.42	8.44	33.98	Peak	---	---

Note: The item 1 and 3 on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).



Vertical




	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	8840.000	52.16	-----	-----	43.13	38.23	6.09	35.29	Peak	---	---
2	11650.000	55.90	-7.64	63.54	43.41	40.66	6.64	34.81	PK	---	---
3	17475.000	62.49			44.61	43.42	8.44	33.98	Peak	---	---

Note: The item 1 and 3 on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

<b>Final Test Date</b>	Jan. 30, 2012	<b>Test Site No.</b>	03CH02-HY
<b>Temperature</b>	20°C	<b>Humidity</b>	66%
<b>Test Engineer</b>	Streak	<b>Configuration</b>	5G 802.11n Ch. 151 (40MHz)


**Horizontal**



	<b>Freq</b>	<b>Level</b>	<b>Over Limit</b>	<b>Limit Line</b>	<b>Read Level</b>	<b>Antenna Factor</b>	<b>Cable Loss</b>	<b>Preamp Factor</b>	<b>Remark</b>	<b>Ant Pos</b>	<b>Table Pos</b>
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	9250.000	53.36			43.87	38.63	6.25	35.39	Peak	---	---
2	11510.000	55.97	-7.57	63.54	43.46	40.60	6.63	34.72	PK	---	---
3	17265.000	62.97			44.87	43.54	8.54	33.98	Peak	---	---

Note: The items 1 and 3 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Vertical




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	9321.000	54.04	-9.50	63.54	44.41	38.78	6.26	35.41	PK	---	---
2	11510.000	56.66	-6.88	63.54	44.15	40.60	6.63	34.72	PK	---	---
3	17265.000	64.37			46.27	43.54	8.54	33.98	Peak	---	---

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

<b>Final Test Date</b>	Jan. 30, 2012	<b>Test Site No.</b>	03CH02-HY
<b>Temperature</b>	20°C	<b>Humidity</b>	66%
<b>Test Engineer</b>	Streak	<b>Configuration</b>	5G 802.11n Ch. 159 (40MHz)


**Horizontal**



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBUV/m	dB	dBUV/m	dBuV	dB/m	dB	dB		cm	deg
1	8865.000	52.58			43.56	38.21	6.11	35.30	Peak	---	---
2	11590.000	56.49	-7.05	63.54	43.99	40.63	6.63	34.76	PK	---	---
3	17385.000	63.51			45.54	43.47	8.48	33.98	Peak	---	---

Note: The items 1 and 3 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Vertical




	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	8865.000	52.58			43.56	38.21	6.11	35.30	Peak	---	---
2	11590.000	56.49	-7.05	63.54	43.99	40.63	6.63	34.76	PK	---	---
3	17385.000	63.51			45.54	43.47	8.48	33.98	Peak	---	---

Note: The items 1 and 3 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

<b>Final Test Date</b>	Jan. 14, 2012	<b>Test Site No.</b>	03CH02-HY
<b>Temperature</b>	20°C	<b>Humidity</b>	66%
<b>Test Engineer</b>	Streak	<b>Configuration</b>	2.4G 802.11n Ch. 1 (20MHz)


**Horizontal**



	<b>Freq</b>	<b>Level</b>	<b>Over Limit</b>	<b>Limit Line</b>	<b>ReadAntenna Level</b>	<b>Antenna Factor</b>	<b>Cable Loss</b>	<b>Preamp Factor</b>	<b>Remark</b>	<b>Ant Pos</b>	<b>Table Pos</b>
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4824.000	49.35	-4.65	54.00	43.81	35.76	4.58	34.80	PK	---	---
2	7236.000	50.68			42.28	37.85	5.63	35.08	Peak	---	---
3	9648.000	54.50			44.24	39.39	6.34	35.47	Peak	---	---

Note: The items 2 and 3 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Vertical




Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 4824.000	48.21	-5.79	54.00	43.30	35.13	4.58	34.80	PK	---	---
2 7236.000	49.58			42.13	36.90	5.63	35.08	Peak	---	---
3 9648.000	52.82			43.36	38.59	6.34	35.47	Peak	---	---

Note: The items 2 and 3 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

<b>Final Test Date</b>	Jan. 14, 2012	<b>Test Site No.</b>	03CH02-HY
<b>Temperature</b>	20°C	<b>Humidity</b>	66%
<b>Test Engineer</b>	Streak	<b>Configuration</b>	2.4G 802.11n Ch. 6 (20MHz)

**Horizontal**




	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4874.000	48.55	-5.45	54.00	42.89	35.83	4.61	34.78	PK	---	---
2	7311.000	52.47	-21.53	74.00	44.07	37.86	5.64	35.10	Peak	---	---
3	7311.000	38.39	-15.61	54.00	29.99	37.86	5.64	35.10	Average	---	---
4	9748.000	54.39			44.00	39.51	6.36	35.48	Peak	---	---

Note: The item 4 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).



Vertical




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4874.000	48.83	-5.17	54.00	43.82	35.18	4.61	34.78	PK	---	---
2	7311.000	52.25	-21.75	74.00	44.79	36.92	5.64	35.10	Peak	---	---
3	7311.000	38.41	-15.59	54.00	30.95	36.92	5.64	35.10	Average	---	---
4	9748.000	53.32			43.73	38.71	6.36	35.48	Peak	---	---

Note: The item 4 is on an un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

<b>Final Test Date</b>	Jan. 14, 2012	<b>Test Site No.</b>	03CH02-HY
<b>Temperature</b>	20°C	<b>Humidity</b>	66%
<b>Test Engineer</b>	Streak	<b>Configuration</b>	2.4G 802.11n Ch. 11 (20MHz)


**Horizontal**



Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 4924.000	48.98	-5.02	54.00	43.17	35.90	4.68	34.77	PK	---	---
2 @ 7386.000	50.20	-3.80	54.00	41.79	37.88	5.65	35.12	PK	---	---
3 9848.000	54.47			43.97	39.61	6.38	35.49	Peak	---	---

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Vertical




Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 4924.000	49.20	-4.80	54.00	44.06	35.23	4.68	34.77	PK	---	---
2 @ 7386.000	50.26	-3.74	54.00	42.77	36.96	5.65	35.12	PK	---	---
3 9848.000	53.45			43.75	38.81	6.38	35.49	Peak	---	---

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

<b>Final Test Date</b>	Jan. 14, 2012	<b>Test Site No.</b>	03CH02-HY
<b>Temperature</b>	20°C	<b>Humidity</b>	66%
<b>Test Engineer</b>	Streak	<b>Configuration</b>	2.4G 802.11n Ch. 3 (40MHz)


**Horizontal**



	<b>Freq</b>	<b>Level</b>	<b>Over Limit</b>	<b>Limit Line</b>	<b>ReadAntenna Level</b>	<b>Antenna Factor</b>	<b>Cable Loss</b>	<b>Preamp Factor</b>	<b>Remark</b>	<b>Ant Pos</b>	<b>Table Pos</b>
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4844.000	49.42	-4.58	54.00	43.82	35.78	4.61	34.79	PK	---	---
2	7266.000	51.75	-22.25	74.00	43.35	37.86	5.63	35.09	Peak	---	---
3	7266.000	37.94	-16.06	54.00	29.54	37.86	5.63	35.09	Average	---	---
4	9688.000	54.70	-----	-----	44.40	39.43	6.35	35.48	Peak	---	---

Note: The item 4 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Vertical




Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4844.000	48.99	-5.01	54.00	44.03	35.14	4.61	34.79	PK	---	---
2	7266.000	51.44	-22.56	74.00	43.99	36.91	5.63	35.09	Peak	---	---
3	7266.000	37.31	-16.69	54.00	29.86	36.91	5.63	35.09	Average	---	---
4	9688.000	53.80			44.30	38.63	6.35	35.48	Peak	---	---

Note: The item 4 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

<b>Final Test Date</b>	Jan. 14, 2012	<b>Test Site No.</b>	03CH02-HY
<b>Temperature</b>	20°C	<b>Humidity</b>	66%
<b>Test Engineer</b>	Streak	<b>Configuration</b>	2.4G 802.11n Ch. 6 (40MHz)


**Horizontal**



	<b>Freq</b>	<b>Level</b>	<b>Over Limit</b>	<b>Limit Line</b>	<b>ReadAntenna Level</b>	<b>Antenna Factor</b>	<b>Cable Loss</b>	<b>Preamp Factor</b>	<b>Remark</b>	<b>Ant Pos</b>	<b>Table Pos</b>
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4874.000	49.31	-4.69	54.00	43.65	35.83	4.61	34.78	PK	---	---
2	7311.000	51.99	-22.01	74.00	43.59	37.86	5.64	35.10	Peak	---	---
3	7311.000	38.08	-15.92	54.00	29.68	37.86	5.64	35.10	Average	---	---
4	9748.000	54.44			44.05	39.51	6.36	35.48	Peak	---	---

Note: The item 4 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Vertical




Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 4874.000	49.01	-4.99	54.00	44.00	35.18	4.61	34.78	PK	---	---
2 @ 7311.000	50.97	-3.03	54.00	43.51	36.92	5.64	35.10	PK	---	---
3	9748.000	53.39		43.80	38.71	6.36	35.48	Peak	---	---

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Final Test Date	Jan. 14, 2012	Test Site No.	03CH02-HY
Temperature	20°C	Humidity	66%
Test Engineer	Streak	Configuration	2.4G 802.11n Ch. 9 (40MHz)

Horizontal




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4904.000	49.05	-4.95	54.00	43.31	35.88	4.64	34.78	PK	---	---
2	7356.000	51.94	-22.06	74.00	43.54	37.87	5.64	35.11	Peak	---	---
3	7356.000	38.44	-15.56	54.00	30.04	37.87	5.64	35.11	Average	---	---
4	9808.000	55.13			44.67	39.57	6.37	35.48	Peak	---	---

Note: The item 4 is on an un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).



Vertical



Item	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4904.000	47.50	-6.50	54.00	42.43	35.21	4.64	34.78	PK	---	---
2	7356.000	51.09	-22.91	74.00	43.62	36.94	5.64	35.11	Peak	---	---
3	7356.000	37.48	-16.52	54.00	30.01	36.94	5.64	35.11	Average	---	---
4	9808.000	53.24			43.58	38.77	6.37	35.48	Peak	---	---

Note: The item 4 is on an un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.6.7).

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

**3.6 Band Edge and Fundamental Emissions Measurement**

**3.6.1 Limit**

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter measurement is based on the maximum conducted output power, the attenuation required under this paragraph shall be 30dB instead of 20dB. In addition, radiated emissions which fall in section 15.205(a) the restricted bands must also comply with the radiated emission limit specified in section 15.209(a).

<b>Frequencies (MHz)</b>	<b>Field Strength (micorvolts/meter)</b>	<b>Measurement Distance (meters)</b>
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

**3.6.2 Measuring Instruments and Setting**

Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

<b>Spectrum Parameter</b>	<b>Setting</b>
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for Peak

**3.6.3 Test Procedures**

11. The test procedure is the same as section 3.5.3; only the frequency range investigated is limited to 100MHz around band edges.
12. In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

**3.6.4 Test Setup Layout**

This test setup layout is the same as that shown in section 3.5.4.

**3.6.5 Test Deviation**

There is no deviation with the original standard.

**3.6.6 EUT Operation during Test**

The EUT was programmed to be in continuously transmitting mode.

3.6.7 Test Result of Band Edge and Fundamental Emissions

For Two Chains:

<b>Final Test Date</b>	Jan. 13, 2012	<b>Test Site No.</b>	03CH02-HY
<b>Temperature</b>	20°C	<b>Humidity</b>	66%
<b>Test Engineer</b>	Streak	<b>Configuration</b>	5G 802.11n Ch. 149, 157, 165 (20MHz)

Channel 149

Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 5725.000	60.34			18.33	36.97	5.04	0.00	Average	---	---
2 @ 5743.450	101.09			59.03	36.99	5.07	0.00	Average	---	---
1 @ 5696.620	73.57			31.62	36.93	5.02	0.00	Peak	---	---
2 @ 5747.090	112.28			70.22	36.99	5.07	0.00	Peak	---	---

The item 2 is fundamental emissions and the item 1 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions.

Channel 157

Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 5716.830	60.24			18.25	36.95	5.04	0.00	Average	---	---
2 @ 5780.070	101.07			58.95	37.03	5.09	0.00	Average	---	---
3 @ 5851.470	60.05			17.83	37.11	5.11	0.00	Average	---	---
1 @ 5717.510	73.06			31.05	36.97	5.04	0.00	Peak	---	---
2 @ 5781.940	112.18			70.06	37.03	5.09	0.00	Peak	---	---
3 @ 5860.310	73.30			31.04	37.13	5.13	0.00	Peak	---	---

The item 2 is fundamental emissions and the items 1 and 3 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions.

Channel 165

Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 5822.870	100.40			58.20	37.09	5.11	0.00	Average	---	---
2 @ 5854.050	59.82			17.58	37.13	5.11	0.00	Average	---	---
1 @ 5821.990	112.00			69.80	37.09	5.11	0.00	Peak	---	---
2 @ 5853.010	73.76			31.54	37.11	5.11	0.00	Peak	---	---

The item 1 is fundamental emissions and the item 2 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

<b>Final Test Date</b>	Jan. 13, 2012	<b>Test Site No.</b>	03CH02-HY
<b>Temperature</b>	20°C	<b>Humidity</b>	66%
<b>Test Engineer</b>	Streak	<b>Configuration</b>	5G 802.11n Ch. 151, 159 (40MHz)

**Channel 151**

	<b>Freq</b>	<b>Level</b>	<b>Over Limit</b>	<b>Limit Line</b>	<b>Read Level</b>	<b>Antenna Factor</b>	<b>Cable Loss</b>	<b>Preamp Factor</b>	<b>Remark</b>	<b>Ant Pos</b>	<b>Table Pos</b>
	<b>MHz</b>	<b>dBuV/m</b>	<b>dB</b>	<b>dBuV/m</b>	<b>dBuV</b>	<b>dB/m</b>	<b>dB</b>	<b>dB</b>		<b>cm</b>	<b>deg</b>
1 @	5716.400	59.99			18.00	36.95	5.04	0.00	Average	---	---
2 @	5778.400	98.23			56.11	37.03	5.09	0.00	Average	---	---
1	5722.800	72.80			30.79	36.97	5.04	0.00	Peak	---	---
2 @	5778.500	110.23			68.11	37.03	5.09	0.00	Peak	---	---

The item 2 is fundamental emissions and the item 1 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions.

**Channel 159**

	<b>Freq</b>	<b>Level</b>	<b>Over Limit</b>	<b>Limit Line</b>	<b>Read Level</b>	<b>Antenna Factor</b>	<b>Cable Loss</b>	<b>Preamp Factor</b>	<b>Remark</b>	<b>Ant Pos</b>	<b>Table Pos</b>
	<b>MHz</b>	<b>dBuV/m</b>	<b>dB</b>	<b>dBuV/m</b>	<b>dBuV</b>	<b>dB/m</b>	<b>dB</b>	<b>dB</b>		<b>cm</b>	<b>deg</b>
1 @	5788.700	97.51			55.37	37.05	5.09	0.00	Average	---	---
2 @	5857.900	59.75			17.49	37.13	5.13	0.00	Average	---	---
1 @	5788.600	109.33			67.19	37.05	5.09	0.00	Peak	---	---
2	5865.400	72.77			30.51	37.13	5.13	0.00	Peak	---	---

The item 1 is fundamental emissions and the item 2 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

<b>Final Test Date</b>	Jan. 13, 2012	<b>Test Site No.</b>	03CH02-HY
<b>Temperature</b>	20°C	<b>Humidity</b>	66%
<b>Test Engineer</b>	Streak	<b>Configuration</b>	2.4G 802.11n Ch. 1, 6, 11(20MHz)

**Channel 1**

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @	2390.000	52.73	-1.27	54.00	17.92	31.79	3.02	0.00	Average	---	---
2 @	2413.170	102.18			67.30	31.86	3.02	0.00	Average	---	---
1 @	2390.000	68.84	-5.16	74.00	34.03	31.79	3.02	0.00	Peak	---	---
2 @	2413.930	113.86			78.98	31.86	3.02	0.00	Peak	---	---

The item 2 is Fundamental Emissions.

**Channel 6**

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @	2438.820	103.69			68.65	31.99	3.05	0.00	Average	---	---
1 @	2438.060	115.00			79.96	31.99	3.05	0.00	Peak	---	---

The item 1 is Fundamental Emissions.

**Channel 11**

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @	2460.290	102.19			67.08	32.06	3.05	0.00	Average	---	---
2 @	2483.500	52.97	-1.03	54.00	17.76	32.13	3.08	0.00	Average	---	---
1 @	2460.290	113.84			78.73	32.06	3.05	0.00	Peak	---	---
2 @	2483.850	70.82	-3.18	74.00	35.61	32.13	3.08	0.00	Peak	---	---

The item 1 is Fundamental Emissions.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

<b>Final Test Date</b>	Jan. 13, 2012	<b>Test Site No.</b>	03CH02-HY
<b>Temperature</b>	20°C	<b>Humidity</b>	66%
<b>Test Engineer</b>	Streak	<b>Configuration</b>	2.4G 802.11n Ch. 3, 6, 9 (40MHz)

**Channel 3**

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @	2390.000	52.48	-1.52	54.00	17.67	31.79	3.02	0.00	Average	---	---
2 @	2425.330	97.65			62.68	31.92	3.05	0.00	Average	---	---
1 @	2388.660	68.00	-6.00	74.00	33.19	31.79	3.02	0.00	Peak	---	---
2 @	2426.090	108.80			73.83	31.92	3.05	0.00	Peak	---	---

The item 2 is Fundamental Emissions.

**Channel 6**

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @	2439.770	99.83			64.79	31.99	3.05	0.00	Average	---	---
1 @	2440.530	111.31			76.27	31.99	3.05	0.00	Peak	---	---

The item 1 is Fundamental Emissions.

**Channel 9**

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @	2456.490	97.88			62.77	32.06	3.05	0.00	Average	---	---
2 @	2483.850	52.92	-1.08	54.00	17.71	32.13	3.08	0.00	Average	---	---
1 @	2454.780	109.13			74.02	32.06	3.05	0.00	Peak	---	---
2 @	2486.130	67.50	-6.50	74.00	32.29	32.13	3.08	0.00	Peak	---	---

The item 1 is Fundamental Emissions.

Note:


Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

For Emission not in Restricted Band


Final Test Date	Jan. 14, 2012	Test Site No.	TH01-HY
Temperature	21.4°C	Humidity	25%
Test Engineer	Shiming	Configurations	802.11n

Low Band Edge Plot on Configuration of IEEE 802.11n-5G Port 1 (20MHz) / 5745 MHz




Date: 14.JAN.2012 09:41:33

High Band Edge Plot on Configuration of IEEE 802.11n-5G Port 1 (20MHz) / 5825 MHz




Date: 14.JAN.2012 10:23:06

Low Band Edge Plot on Configuration of IEEE 802.11n-5G Port 2 (20MHz) / 5745 MHz



Date: 14.JAN.2012 09:29:46


High Band Edge Plot on Configuration of IEEE 802.11n-5G Port 2 (20MHz) / 5825 MHz



Date: 14.JAN.2012 10:10:31




Low Band Edge Plot on Configuration of IEEE 802.11n-5G Port 1 (40MHz) / 5755 MHz




Date: 14.JAN.2012 10:43:25

High Band Edge Plot on Configuration of IEEE 802.11n-5G Port 1 (40MHz) / 5795 MHz




Date: 14.JAN.2012 11:15:32

Low Band Edge Plot on Configuration of IEEE 802.11n-5G Port 2 (40MHz) / 5755 MHz




Date: 14.JAN.2012 10:53:08

High Band Edge Plot on Configuration of IEEE 802.11n-5G Port 2 (40MHz) / 5795 MHz




Date: 14.JAN.2012 11:05:48

Low Band Edge Plot on Configuration of IEEE 802.11n-2.4G Port 1 (20MHz) / 2412 MHz




Date: 11.JAN.2012 10:57:38

High Band Edge Plot on Configuration of IEEE 802.11n-2.4G Port 1 (20MHz) / 2462 MHz




Date: 11.JAN.2012 13:59:22

Low Band Edge Plot on Configuration of IEEE 802.11n-2.4G Port 2 (20MHz) / 2412 MHz




Date: 11.JAN.2012 12:53:38

High Band Edge Plot on Configuration of IEEE 802.11n-2.4G Port 2 (20MHz) / 2462 MHz




Date: 11.JAN.2012 14:12:58

Low Band Edge Plot on Configuration of IEEE 802.11n-2.4G Port 1 (40MHz) / 2422 MHz




Date: 11.JAN.2012 14:38:08

High Band Edge Plot on Configuration of IEEE 802.11n-2.4G Port 1 (40MHz) / 2452 MHz




Date: 11.JAN.2012 15:19:53

Low Band Edge Plot on Configuration of IEEE 802.11n-2.4G Port 2 (40MHz) / 2422 MHz



Date: 11.JAN.2012 14:24:27

High Band Edge Plot on Configuration of IEEE 802.11n-2.4G Port 2 (40MHz) / 2452 MHz



Date: 11.JAN.2012 15:05:40

### **3.7 Antenna Requirements**

#### **3.7.1 Limit**

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

#### **3.7.2 Antenna Connector Construction**

Please refer to section 2.2 in this test report; antenna connector complied with the requirements.

**4 LIST OF MEASURING EQUIPMENTS**

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100174	9kHz – 2.75GHz	Apr. 06, 2010	Conduction (CO04-HY)
LISN	MessTec	NNB-2/16Z	99041	9kHz – 30MHz	Mar. 23, 2010	Conduction (CO04-HY)
LISN (Support Unit)	EMCO	3810/2NM	9703-1839	9kHz – 30MHz	Apr. 29, 2010	Conduction (CO04-HY)
RF Cable-CON	UTIFLEX	3102-26886-4	CB049	9kHz – 30MHz	Apr. 20, 2010	Conduction (CO04-HY)
EMI Filter	LINDGREN	LRE-2030	2651	< 450 Hz	N/A	Conduction (CO04-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSP 40	100305	9 KHz ~ 40 GHz	Feb. 11, 2011	Conducted (TH01-HY)
DC Power Source	G.W.	GPC-6030D	C671845	DC 1V ~ 60V	Jun. 03, 2011	Conducted (TH01-HY)
Temp. and Humidity Chamber	Giant Force	GTH-225-20-S	MAB0103-001	N/A	Nov. 17, 2011	Conducted (TH01-HY)
Signal Generator	R&S	SMR40	100116	10 MHz ~ 40 GHz	Jun. 07, 2011	Conducted (TH01-HY)
Power Sensor	Anritsu	MA2411B	1027452	300 MHz ~ 40 GHz	Jun. 16, 2011	Conducted (TH01-HY)
Power Meter	Anritsu	ML2495A	1124009	300 MHz ~ 40 GHz	Jun. 20, 2011	Conducted (TH01-HY)
RF Cable-1m	Jye Bao	RG142	CB034-1m	20 MHz ~ 7 GHz	Dec. 03, 2011	Conducted (TH01-HY)
RF Cable-2m	Jye Bao	RG142	CB035-2m	20 MHz ~ 1 GHz	Dec. 03, 2011	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
AC Power Source	HPC	HPA-500W	HPA-9100024	AC 0 ~ 300V	Jun. 09, 2011*	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is two year.



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSP40	100593	9 kHz ~ 40 GHz	Aug. 08, 2011	Radiation (03CH02-HY)
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH02-HY	30 MHz ~ 1 GHz 3m	May 11, 2011	Radiation (03CH02-HY)
Amplifier	Agilent	8447D	2944A11146	100 kHz ~ 1.3 GHz	Jul. 25, 2011	Radiation (03CH02-HY)
Amplifier	Agilent	8449B	3008A02373	1 GHz ~ 26.5 GHz	Jul. 25, 2011	Radiation (03CH02-HY)
Horn Antenna	ETS-LINDGREN	3117	00091920	1 GHz ~ 18 GHz	Nov. 15, 2011	Radiation (03CH02-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30 MHz ~ 1 GHz	Nov. 11, 2011	Radiation (03CH02-HY)
RF Cable-high	SUHNER	SUCOFLEX106	03CH02-HY	1 GHz ~ 40 GHz	Mar. 07, 2011	Radiation (03CH02-HY)
Bilog Antenna	SCHAFFNER	CBL61128	2723	30 MHz ~ 2 GHz	Oct. 22, 2011	Radiation (03CH02-HY)
Turn Table	HD	DS 420	420/649/00	0 - 360 degree	N/A	Radiation (03CH02-HY)
Antenna Mast	HD	MA 240	240/559/00	1 m - 4 m	N/A	Radiation (03CH02-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz - 30 MHz	Jul. 29, 2010*	Radiation (03CH03-HY)

Note: Calibration Interval of instruments listed above is two year.

**5 TEST LOCATION**

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 <sup>nd</sup> Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

## 6 TAF CERTIFICATE OF ACCREDITATION



Certificate No. : L1190-110111

財團法人全國認證基金會  
Taiwan Accreditation Foundation

## Certificate of Accreditation

This is to certify that

**Sporton International Inc.****EMC & Wireless Communications Laboratory**

No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,  
Taiwan, R.O.C.

**is accredited in respect of laboratory**

**Accreditation Criteria** : ISO/IEC 17025:2005  
**Accreditation Number** : 1190  
**Originally Accredited** : December 15, 2003  
**Effective Period** : January 10, 2010 to January 09, 2013  
**Accredited Scope** : Testing Field, see described in the Appendix  
**Specific Accreditation Program** : Accreditation Program for Designated Testing Laboratory for Commodities Inspection  
Accreditation Program for Telecommunication Equipment Testing Laboratory  
Accreditation Program for BSMI Mutual Recognition Arrangement with Foreign Authorities

Jay-San Chen  
President, Taiwan Accreditation Foundation  
Date : January 11, 2011

P1, total 24 pages