

Modular Approval Request FCC (per DA 00-1407)

FCC ID: RYYWYSAAVDXB-E

	4	Anguar from amplicant
1.	The modular transmitter must have its own RF shielding.	Answer from applicant Yes, the modular transmitter
1.	The modular transmitter must have its own Kr shielding.	has its own RF shielding with
		metal case. Refer to the
		external photo.
2.	The modular transmitter must have buffered modulation/data inputs (if such inputs	Yes, using IC, 88W8787, has
۷.	are provided) to ensure that the module will comply with Part 15 requirements	buffered circuit.
	under conditions of excessive data rates or over-modulation.	bulleted circuit.
	under conditions of excessive data rates of over-modulation.	
3.	The modular transmitter must have its own power supply regulation.	No, this modular transmitter
		doesn't have its own power
		supply regulation. The
		modular transmitter is always
		incorporated into a specific
		host device having power
		supply regulators. We specify
		the operating voltage range
		and instruct to our host
		device manufacturer to
		ensure to use the voltage in
		the recommended range.
		Please refer to user's manual.
4.	The modular transmitter must comply with the antenna requirements of Section	Yes, this modular transmitter
	15.203 and 15.204(c). The antenna must either be permanently attached or employ	uses monopole ceramic chip
	a "unique" antenna coupler (at all connections between the module and the antenna,	antenna attached with solder.
	including the cable)	
5.	The modular transmitter must be tested in a stand-alone configuration, i.e., the	No, this modular transmitter
	module must not be inside another device during testing. This is intended to	has been performed the testing
	demonstrate that the module is capable of complying with Part 15 emission limits	in a stand-alone configuration
	regardless of the device into which it is eventually installed.	in RF aspects, but it has been
1		tested in a state of being
		installed in a specific host
		device to comply with RF
		Exposure requirements. Please
6.	The modules transmitted must be labeled with its own ECC ID number and if the	refer to SAR test reports.
0.	The modular transmitter must be labeled with its own FCC ID number, and, if the FCC ID is not visible when the module is installed inside another device, then the	Yes, the label of this modular transmitter with its own FCC
	· · · · · · · · · · · · · · · · · · ·	
	outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the	ID is put on PCB. Exterior label instruction to
	following: "Contains Transmitter Module FCC ID: XYZMODEL1" or "Contains	installer of this module is
	FCC ID: XYZMODEL1." Any similar wording that expresses the same meaning	provided in user manual.
	may be used. The Grantee may either provide such a label, an example of which	provided in user manuar.
	must be included in the application for equipment authorization, or, must provide	
	adequate instructions along with the module which explain this requirement. In the	
	latter case, a copy of these instructions must be included in the application for	
	equipment authorization.	
	1. 1	
7.	The modular transmitter must comply with any specific rule or operating	Yes, instruction for
	requirements applicable to the transmitter and the manufacturer must provide	operational requirements is
	adequate instructions along with the module to explain any such requirements. A	provided in the user manual.
	copy of these instructions must be included in the application for equipment	_
	authorization. For example, there are very strict operational and timing	
	requirements that must be met before a transmitter is authorized for operation under	
	Section 15.231. For instance, data transmission is prohibited, except for operation	
	under Section 15.231(e), in which case there are separate field strength level and	
	timing requirements. Compliance with these requirements must be assured.	



8. The modular transmitter must comply with any applicable RF exposure requirements. For example, FCC Rules in Sections 2.1091, 2.1093 and specific Sections of Part 15, including 15.319(i), 15.407(f), 15.253(f) and 15.255(g), require that Unlicensed PCS, UNII and millimeter wave devices perform routine environmental evaluation for RF Exposure to demonstrate compliance. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF Exposure compliance in accordance with Section 15.247(b)(4). Modular transmitters approved under other Sections of Part 15, when necessary, may also need to address certain RF Exposure concerns, typically by providing specific installation and operating instructions for users, installers and other interested parties to ensure compliance.

Yes, the modular transmitter complies with RF exposure requirements and the instruction for users is provided in the user manual.

Note: If compliance with one or more of the numbered requirements, listed above, cannot be demonstrated, it may be possible to obtain a "Limited Modular Approval" (LMA).

M. Satomi

Name and surname of applicant (or authorized representative): Manabu Satomi

Date: July 9, 2015 **Signature:**