

## **RF Exposure / SAR Statement**

### **No. : 10949091S-A**

<b>Applicant</b>	<b>:</b>	<b>TAIYO YUDEN CO., LTD.</b>
<b>Type of Equipment</b>	<b>:</b>	<b>CPU Embedded WLAN Module</b>
<b>Model No.</b>	<b>:</b>	<b>WYSACVLXY</b>
<b>FCC ID</b>	<b>:</b>	<b>RYYWYSACVLXY</b>

---

TAIYO YUDEN CO., LTD. declares that Model : WYSACVLXY  
complies with FCC radiation exposure requirement specified in the FCC Rules 2.1091.

### **RF Exposure Calculations:**

The following information provides the minimum separation distance for the highest gain antenna provided with the “WYSACVLXY” as calculated  
from FCC Part 1, §1.1310, TABLE 1 (B) Limits for General Population / Uncontrolled Exposure.  
This calculation is based on the highest EIRP possible from the system,  
considering maximum power and antenna gain, and considering a 1.0mW/cm<sup>2</sup> uncontrolled exposure limit. The Friis formula used was:

$$S = (P * G) / (4 * \pi * r^2)$$

**Where**

<b>P =</b>	<b>32.36 mW (Maximum average output power)</b>
<b>G =</b>	<b>0.51 Numerical Antenna gain; equal to -2.90 dBi</b>
<b>r =</b>	<b>20.0 cm</b>

**For: WYSACVLXY**

$$S = 0.00330 \text{ mW/cm}^2$$

Even taking into account the tolerance, this device can be satisfied with the limits.

---

**UL Japan, Inc.**

**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401