

FCC Part 2 section 2.1091

FCC ID: RZEDVW-632

(ii) Limits for General Population/Uncontrolled Exposure				
Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1	<30

f = frequency in MHz. * = Plane-wave equivalent power density.

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user.

$$S = \text{EIRP} / (4 R^2 \pi)$$

- Note

S= Maximum power density(mW/cm²)

EIRP= Equivalent Isotropic Radiated Power(mW)

R= Distance to the center of the radiation of the antenna(Over 20cm)

Maximum Permissible Exposure Calculation

Operation Mode	Evaluation Frequency (MHz)	MAX Output Power (dBm)	Antenna Gain (dBi)	MAX. EIRP (dBm)	MAX. EIRP (mW)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Result
2.4G WIFI	2412 ~ 2462	22.32	5.94	28.26	669.88	20	0.133	1	PASS
5G WIFI NII 1	5180 ~ 5240	15.01	6.11	21.12	129.42	20	0.026	1	PASS
5G WIFI NII 3	5745 ~ 5825	20.33	6.57	26.90	489.78	20	0.097	1	PASS
6G WIFI NII 5	5745~5825	17.11	5.48	22.59	181.55	20	0.036	1	PASS
6G WIFI NII 6	5745~5825	18.08	5.44	23.52	224.91	20	0.045	1	PASS
6G WIFI NII 7	5745~5825	16.81	6.23	23.04	201.37	20	0.040	1	PASS
6G WIFI NII 8	5745~5825	13.45	5.44	18.89	77.45	20	0.015	1	PASS

Conclusion of Simultaneous Transmitter

6G WIFI + 2.4G/5G WIFI

The formula of calculated the MPE is CPD1 / LPD 1 + CPD2 / LPD 2 + < 1

CPD = Calculation power density / LPD = Limit of power density

Result : 0.133 + 0.045 = 0.178 < 1

Conclusion

maximum calculations of above situations are less than the “1” limit.