To Whom It May Concern:

CORONIS , Inc would like to apply for Modular FCC approval. This letter is our application for such according to FCC public notice **DA 00-1407**.

9XTEND and Modular Transmitter Requirements

Modular Transmitter Requirements	Manufacturer Clarification
A - In order to be considered a transmitter module, the device must be a complete RF transmitter, i.e., it must have its own reference oscillator (e.g., VCO), antenna, etc. The only connectors to the module, if any, may be the power supply and modulation/data inputs.	The only connector of the module is: à The power supply à Data inputs/outputs
B - Compliance with FCC RF Exposure requirements may, in some instances, limit the output power of a module and/or the final applications in which the approved module may be employed.	ОК
C – While the applicant for a device into which an authorized module is installed is not required to obtain a new authorization for the module, this does not preclude the possibility that some other form of authorization or testing may be required for the device (e.g., a WLAN into which an authorized module is installed must still be authorized as a PC peripheral, subject to the appropriate equipment authorization).	OK
D – In the case of a modular transceiver, the modular approval policy only applies to the transmitter portion of such devices. Pursuant to Section 15.101(b), the receiver portion will either be subject to Verification, or it will not be subject to any authorization requirements (unless it is a Scanning Receiver, in which case it is also	OK

Modular Transmitter Requirements	Manufacturer Clarification
subject to Certification, pursuant to Section	
15.101(a)).	
E – The holder of the grant of equipment authorization (Grantee) of the module is	OK
responsible for the compliance of the	
module in its final configuration, provided	
that the OEM, integrator, and/or end user	
has complied with all of the instructions	
provided by the Grantee which indicate	
installation and/or operating conditions	
necessary for compliance.	
2.74	
1. The modular transmitter must have its	
own RF shielding. This is intended to ensure that the module does not have to	It does have its own RF shielding
rely upon the shielding provided by the	it does have its own ixi sinciding
device into which it is installed in order for	
all modular transmitter emissions to	
comply with Part 15 limits Such	
coupling may result in non-compliant	
operation.	
2. The modular transmitter must have	
buffered modulation/data inputs (if such	OK
inputs are provided) to ensure that the	
module will comply with Part 15	
requirements under conditions of excessive	
data rates or over-modulation.	
3. The modular transmitter must have its	
own power supply regulation. This is	The module has its own power
intended to ensure that the module will	regulator
comply with Part 15 requirements	
regardless of the design of the power	
supplying circuitry in the device into which	
the module is installed.	
4. The modular transmitter must comply	
with the antenna requirements of Section	Coronis apply for a "Limited Modula"
15.203 and 15.204c. The antenna must	Approval" for this Module named-
either be permanently attached or employ a	EvoModule1
"unique" antenna coupler (at all	Lyonoduici
connections between the module and the	
antenna, including the cable). Any antenna	
used with the module must be approved	
with the module; either at the time of initial	
authorization or through a Class II	

Modular Transmitter Requirements	Manufacturer Clarification
permissive change. The "professional	
installation" provision of Section 15.203	
may not be applied to modules.	
5. The modular transmitter must be tested	
in a stand-alone configuration, i.e., the	OK
module must not be inside another device	
during testing. This is intended to	
demonstrate that the module is capable of	
complying with Part 15 emission limits	
regardless of the device into which it is	
eventually installed	
6. The modular transmitter must be labeled	
with its own FCC ID number, and, if the	OK
FCC ID is not visible when the module is	
installed inside another device, then the	
outside of the device into which the module	
is installed must also display a label	
referring to the enclosed module	
7. The modular transmitter must comply	
with any specific rule or operating	OK ,
requirements applicable to the transmitter	
and the manufacturer must provide	
adequate instructions along with the	
module to explain any such requirements.	
The modular transmitter must comply	OV
with any applicable RF exposure	, OK
requirements.	

Sincerely,