

TEST REPORT

Applicant: GuangZhou Walkera Technology Co., Ltd

Address of Applicant: Taishi Industrial Park, Dongchong Town, Panyu District, Guangzhou 511475, China

Manufacturer/Factory: GuangZhou Walkera Technology Co., Ltd

Address of Manufacturer/Factory: Taishi Industrial Park, Dongchong Town, Panyu District, Guangzhou 511475, China

Equipment Under Test (EUT)

Product Name: Aircraft

Model No.: MINI SE, Velo Mini

Trade Mark:  

FCC ID: S29MINISE

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of sample receipt: July 06, 2023

Date of Test: July 07, 2023-August 15, 2023

Date of report issued: August 16, 2023

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Robinson Luo


Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	August 16, 2023	Original

Prepared By:




Date:

August 16, 2023

Project Engineer

Check By:



Reviewer

Date:

August 16, 2023

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS	3
4 TEST SUMMARY	4
5 GENERAL INFORMATION.....	5
5.1 GENERAL DESCRIPTION OF EUT	5
5.2 TEST MODE	7
5.3 DESCRIPTION OF SUPPORT UNITS	7
5.4 DEVIATION FROM STANDARDS.....	7
5.5 ABNORMALITIES FROM STANDARD CONDITIONS	7
5.6 TEST FACILITY.....	7
5.7 TEST LOCATION	7
5.8 ADDITIONAL INSTRUCTIONS.....	7
6 TEST INSTRUMENTS LIST	8
7 TEST RESULTS AND MEASUREMENT DATA.....	10
7.1 ANTENNA REQUIREMENT	10
7.2 CONDUCTED EMISSIONS	11
7.3 CONDUCTED OUTPUT POWER	14
7.4 CHANNEL BANDWIDTH	15
7.5 POWER SPECTRAL DENSITY	16
7.6 SPURIOUS EMISSION IN NON-RESTRICTED & RESTRICTED BANDS	17
7.6.1 Conducted Emission Method.....	17
7.6.2 Radiated Emission Method.....	18
8 TEST SETUP PHOTO	30
9 EUT CONSTRUCTIONAL DETAILS	30

4 Test Summary

Test Item	Section	Result
Antenna requirement	FCC part 15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	FCC part 15.207	Pass
Conducted Peak Output Power	FCC part 15.247 (b)(3)	Pass
Channel Bandwidth & 99% OCB	FCC part 15.247 (a)(2)	Pass
Power Spectral Density	FCC part 15.247 (e)	Pass
Band Edge	FCC part 15.247(d)	Pass
Spurious Emission	FCC part 15.205/15.209	Pass

Remark: Test according to ANSI C63.10:2013 and RSS-Gen

Pass: The EUT complies with the essential requirements in the standard.

Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9kHz-30MHz	3.1dB	(1)
Radiated Emission	30MHz-200MHz	3.8039dB	(1)
Radiated Emission	200MHz-1GHz	3.9679dB	(1)
Radiated Emission	1GHz-18GHz	4.29dB	(1)
Radiated Emission	18GHz-40GHz	3.30dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	3.44dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

5 General Information

5.1 General Description of EUT

Product Name:	Aircraft
Model No.:	MINI SE, Velo Mini
Test Model No.:	MINI SE
Remark: All above models are identical in the same PCB layout, interior structure and electrical circuits. The differences are appearance color, trade mark and model name for commercial purpose.	
Test sample(s) ID:	GTS2023070071-1
Sample(s) Status	Engineer sample
S/N:	01238180001
Operation Frequency:	802.11g /802.11n(HT20): 2412MHz-2462MHz
Channel numbers:	802.11g /802.11n(HT20): 11
Channel separation:	5MHz
Modulation technology:	802.11g/802.11n(H20): Orthogonal Frequency Division Multiplexing (OFDM)
Antenna Type:	PCB antenna
Antenna gain:	ANT1:2dBi ANT2:2dBi
Power supply:	Input:5V 3A/9V 2A/12V 2A Or DC 7.7V, 2250mAh 17.32Wh for Li-ion Battery

Remark:

1. Antenna gain information provided by the customer
2. The relevant information of the sample is provided by the entrusting company, and the laboratory is not responsible for its authenticity.

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz	X	

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency (MHz)
	802.11g/802.11n(HT20)
Lowest channel	2412MHz
Middle channel	2437MHz
Highest channel	2462MHz

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode
-------------------	--

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Pre-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.

Mode	802.11g	802.11n(HT20)
Data rate	6Mbps	6.5Mbps

5.3 Description of Support Units

Manufacturer	Description	Model	Serial Number
XIAOMI	USB Charger	MDY-10-EH	N/A

5.4 Deviation from Standards

None.

5.5 Abnormalities from Standard Conditions

None.

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC —Registration No.: 381383**

Designation Number: CN5029

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files.

- **ISED—Registration No.: 9079A**

CAB identifier: CN0091

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of ISED for radio equipment testing.

- **NVLAP (LAB CODE:600179-0)**

Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).

5.7 Test Location

All tests were performed at:
Global United Technology Services Co., Ltd. Address: No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102 Tel: 0755-27798480 Fax: 0755-27798960

5.8 Additional Instructions

Test Software	Special test command provided by manufacturer
Power level setup	Default

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	June 23, 2021	June 22, 2024
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	April 14, 2023	April 13, 2024
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9168	GTS640	March 19, 2023	March 18, 2025
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	April 17, 2023	April 16, 2025
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Coaxial Cable	GTS	N/A	GTS213	April 21, 2023	April 20, 2024
8	Coaxial Cable	GTS	N/A	GTS211	April 21, 2023	April 20, 2024
9	Coaxial cable	GTS	N/A	GTS210	April 21, 2023	April 20, 2024
10	Coaxial Cable	GTS	N/A	GTS212	April 21, 2023	April 20, 2024
11	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	April 14, 2023	April 13, 2024
12	Loop Antenna	ZHINAN	ZN30900A	GTS534	Nov. 29, 2022	Nov. 28, 2023
13	Broadband Preamplifier	SCHWARZBECK	BBV9718	GTS535	April 14, 2023	April 13, 2024
14	Amplifier(1GHz-26.5GHz)	HP	8449B	GTS601	April 14, 2023	April 13, 2024
15	Horn Antenna (18-26.5GHz)	/	UG-598A/U	GTS664	Oct. 30, 2022	Oct. 29, 2023
16	Horn Antenna (26.5-40GHz)	A.H Systems	SAS-573	GTS665	Oct. 30, 2022	Oct. 29, 2023
17	FSV·Signal Analyzer (10Hz-40GHz)	Keysight	FSV-40-N	GTS666	March 13, 2023	March 12, 2024
18	Amplifier	/	LNA-1000-30S	GTS650	April 14, 2023	April 13, 2024
19	CDNE M2+M3-16A	HCT	30MHz-300MHz	GTS668	Dec. 20,2022	Dec.19,2023
20	Thermo meter	JINCHUANG	GSP-8A	GTS643	April 19, 2023	April 18, 2024

Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	July 12, 2022	July 11, 2027
2	EMI Test Receiver	R&S	ESCI 7	GTS552	April 14, 2023	April 13, 2024
3	LISN	ROHDE & SCHWARZ	ENV216	GTS226	April 14, 2023	April 13, 2024
4	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
5	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
6	Thermo meter	JINCHUANG	GSP-8A	GTS642	April 19, 2023	April 18, 2024
7	Absorbing clamp	Elektronik-Feinmechanik	MDS21	GTS229	April 14, 2023	April 13, 2024
8	ISN	SCHWARZBECK	NTFM 8158	GTS565	April 14, 2023	April 13, 2024
9	High voltage probe	SCHWARZBECK	TK9420	GTS537	April 14, 2023	April 13, 2024
10	Antenna end assembly	Weinschel	1870A	GTS560	April 14, 2023	April 13, 2024

RF Conducted Test:						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	April 14, 2023	April 13, 2024
2	EMI Test Receiver	R&S	ESCI 7	GTS552	April 14, 2023	April 13, 2024
3	PSA Series Spectrum Analyzer	Agilent	E4440A	GTS536	April 14, 2023	April 13, 2024
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	April 14, 2023	April 13, 2024
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	April 14, 2023	April 13, 2024
6	USB RF Power Sensor	DARE	RPR3006W	GTS569	April 14, 2023	April 13, 2024
7	RF Switch Box	Shongyi	RFSW3003328	GTS571	April 14, 2023	April 13, 2024
8	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	April 14, 2023	April 13, 2024
9	Thermo meter	JINCHUANG	GSP-8A	GTS641	April 19, 2023	April 18, 2024


General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Barometer	KUMAO	SF132	GTS647	April 19, 2023	April 18, 2024

7 Test results and Measurement Data

7.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
<p>15.203 requirement:</p> <p>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>15.247(c) (1)(i) requirement:</p> <p>(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.</p>	
EUT Antenna:	
The antenna is PCB antenna, reference to the appendix II for details	


7.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207					
Test Method:	ANSI C63.10:2013					
Test Frequency Range:	150KHz to 30MHz					
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto					
Limit:	Frequency range (MHz)		Limit (dBuV)			
			Quasi-peak		Average	
	0.15-0.5		66 to 56*		56 to 46*	
	0.5-5		56		46	
	5-30		60		50	
* Decreases with the logarithm of the frequency.						
Test setup:	 <p>Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>					
Test procedure:	<ol style="list-style-type: none"> 1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement. 					
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	Pass					

Measurement data


Pre-scan all test modes, found worst case at 802.11g 2462MHz@Ant 1, and so only show the test result of it.

Line:



Freq	Reading level	LISN/ISN factor	Cable loss	Level	Limit level	Over limit	Remark
MHz	dBuV	dB	dB	dBuV	dBuV	dB	
0.15	20.41	10.12	0.01	30.54	65.74	-35.20	QP
0.15	6.30	10.12	0.01	16.43	55.74	-39.31	Average
0.32	15.84	9.98	0.01	25.83	59.80	-33.97	QP
0.32	5.67	9.98	0.01	15.66	49.80	-34.14	Average
0.63	6.99	9.96	0.02	16.97	56.00	-39.03	QP
0.63	1.24	9.96	0.02	11.22	46.00	-34.78	Average
1.68	5.27	9.87	0.04	15.18	56.00	-40.82	QP
1.68	-3.20	9.87	0.04	6.71	46.00	-39.29	Average
3.36	4.53	9.74	0.05	14.32	56.00	-41.68	QP
3.36	-4.00	9.74	0.05	5.79	46.00	-40.21	Average
13.55	15.80	9.52	0.15	25.47	60.00	-34.53	QP
13.55	10.26	9.52	0.15	19.93	50.00	-30.07	Average

Neutral:




Freq	Reading level	LISN/ISN factor	Cable loss	Level	Limit level	Over limit	Remark
MHz	dBuV	dB	dB	dBuV	dBuV	dB	
0.17	18.51	10.12	0.01	28.64	65.08	-36.44	QP
0.17	6.27	10.12	0.01	16.40	55.08	-38.68	Average
0.38	14.17	9.96	0.01	24.14	58.25	-34.11	QP
0.38	3.31	9.96	0.01	13.28	48.25	-34.97	Average
0.80	7.57	9.96	0.02	17.55	56.00	-38.45	QP
0.80	2.98	9.96	0.02	12.96	46.00	-33.04	Average
2.45	6.49	9.68	0.05	16.22	56.00	-39.78	QP
2.45	-1.94	9.68	0.05	7.79	46.00	-38.21	Average
8.41	12.09	9.64	0.10	21.83	60.00	-38.17	QP
8.41	5.52	9.64	0.10	15.26	50.00	-34.74	Average
15.39	18.71	9.49	0.16	28.36	60.00	-31.64	QP
15.39	12.43	9.49	0.16	22.08	50.00	-27.92	Average

Notes:


1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

7.3 Conducted Output Power

Test Requirement :	FCC Part15 C Section 15.247 (b)(3)
Test Method :	KDB558074 D01 15.247 Meas Guidance v05r02
Limit:	30dBm
Test setup:	 <p>The diagram illustrates the test setup. A Power Meter is connected to an E.U.T (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Measurement Data: The detailed test data see Appendix for WIFI 2.4G.

7.4 Channel Bandwidth

Test Requirement :	FCC Part15 C Section 15.247 (a)(2)
Test Method :	KDB558074 D01 15.247 Meas Guidance v05r02
Limit:	>500KHz
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which sits on a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data: The detailed test data see Appendix for WIFI 2.4G.


7.5 Power Spectral Density

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	KDB558074 D01 15.247 Meas Guidance v05r02
Limit:	8dBm/3kHz
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by two legs and sits on a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data: The detailed test data see Appendix for WIFI 2.4G.


7.6 Spurious Emission in Non-restricted & restricted Bands



7.6.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074 D01 15.247 Meas Guidance v05r02
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which sits on a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data: The detailed test data see Appendix for WIFI 2.4G.

7.6.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Note: For Duty cycle $\geq 98\%$, average detector set as above For Duty cycle $< 98\%$, average detector set as below: $VBW \geq 1 / T$					
Limit:	Frequency	Limit (uV/m)	Value	Measurement Distance	
	0.009MHz-0.490MHz	2400/F(KHz)	PK/QP/A V	300m	
	0.490MHz-1.705MHz	24000/F(KHz)	QP	30m	
	1.705MHz-30MHz	30	QP	30m	
	30MHz-88MHz	100	QP	3m	
	88MHz-216MHz	150	QP		
	216MHz-960MHz	200	QP		
	960MHz-1GHz	500	QP		
	Above 1GHz	500	Average		
		5000	Peak		
Test setup:	For radiated emissions from 9kHz to 30MHz				
					
For radiated emissions from 30MHz to 1GHz					

	 <p>For radiated emissions above 1GHz</p> 
<p>Test Procedure:</p>	<ol style="list-style-type: none"> 1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
<p>Test Instruments:</p>	<p>Refer to section 6.0 for details</p>

Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	DC 7.7V					
Test results:	Pass					

Remarks:

1. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.


Measurement data:

■ **9kHz~30MHz**


The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o), the test result no need to reported.

■ **Below 1GHz**

Pre-scan all test modes, found worst case at 802.11g 2462MHz@Ant 1, and so only show the test result of it.
Horizontal:



Vertical:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
68.631	42.44	10.77	0.93	30.00	24.14	40.00	-15.86	QP
104.170	36.89	10.04	1.23	30.00	18.16	43.50	-25.34	QP
150.538	36.85	12.51	1.57	30.00	20.93	43.50	-22.57	QP
227.691	38.80	10.81	2.01	30.00	21.62	46.00	-24.38	QP
300.367	42.90	12.41	2.36	30.00	27.67	46.00	-18.33	QP
560.693	34.06	18.67	3.56	30.00	26.29	46.00	-19.71	QP

- Above 1GHz
- All antennas have test, only the worst case ANT 1 report.
- Unwanted Emissions in non-restricted Frequency Bands

Test mode:	802.11g	Test channel:	lowest
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	37.62	31.24	4.63	37.68	35.81	74.00	-38.19	Vertical
7236.00	32.53	36.25	6.52	37.80	37.50	74.00	-36.50	Vertical
9648.00	31.51	37.97	7.98	37.93	39.53	74.00	-34.47	Vertical
4824.00	36.71	31.24	4.63	37.68	34.90	74.00	-39.10	Horizontal
7236.00	32.49	36.25	6.52	37.80	37.46	74.00	-36.54	Horizontal
9648.00	31.18	37.97	7.98	37.93	39.20	74.00	-34.80	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	26.91	31.24	4.63	37.68	25.10	54.00	-28.90	Vertical
7236.00	21.45	36.25	6.52	37.80	26.42	54.00	-27.58	Vertical
9648.00	21.90	37.97	7.98	37.93	29.92	54.00	-24.08	Vertical
4824.00	26.38	31.24	4.63	37.68	24.57	54.00	-29.43	Horizontal
7236.00	21.12	36.25	6.52	37.80	26.09	54.00	-27.91	Horizontal
9648.00	20.97	37.97	7.98	37.93	28.99	54.00	-25.01	Horizontal

Test mode:	802.11g	Test channel:	Middle
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	37.14	31.31	4.69	37.62	35.52	74.00	-38.48	Vertical
7311.00	32.89	36.39	6.61	37.78	38.11	74.00	-35.89	Vertical
9748.00	32.73	38.10	8.02	37.95	40.90	74.00	-33.10	Vertical
4874.00	37.96	31.31	4.69	37.62	36.34	74.00	-37.66	Horizontal
7311.00	31.71	36.39	6.61	37.78	36.93	74.00	-37.07	Horizontal
9748.00	32.70	38.10	8.02	37.95	40.87	74.00	-33.13	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	28.16	31.31	4.69	37.62	26.54	54.00	-27.46	Vertical
7311.00	21.26	36.39	6.61	37.78	26.48	54.00	-27.52	Vertical
9748.00	22.03	38.10	8.02	37.95	30.20	54.00	-23.80	Vertical
4874.00	28.19	31.31	4.69	37.62	26.57	54.00	-27.43	Horizontal
7311.00	20.83	36.39	6.61	37.78	26.05	54.00	-27.95	Horizontal
9748.00	22.45	38.10	8.02	37.95	30.62	54.00	-23.38	Horizontal

Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	41.07	31.37	4.75	37.58	39.61	74.00	-34.39	Vertical
7386.00	32.55	36.57	6.71	37.74	38.09	74.00	-35.91	Vertical
9848.00	35.31	38.20	8.07	37.58	44.00	74.00	-30.00	Vertical
4924.00	40.97	31.37	4.75	37.58	39.51	74.00	-34.49	Horizontal
7386.00	31.76	36.57	6.71	37.74	37.30	74.00	-36.70	Horizontal
9848.00	31.61	38.20	8.07	37.58	40.30	74.00	-33.70	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	32.28	31.37	4.75	37.58	30.82	54.00	-23.18	Vertical
7386.00	22.55	36.57	6.71	37.74	28.09	54.00	-25.91	Vertical
9848.00	23.88	38.20	8.07	37.58	32.57	54.00	-21.43	Vertical
4924.00	31.53	31.37	4.75	37.58	30.07	54.00	-23.93	Horizontal
7386.00	21.21	36.57	6.71	37.74	26.75	54.00	-27.25	Horizontal
9848.00	20.93	38.20	8.07	37.58	29.62	54.00	-24.38	Horizontal

Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	37.91	31.24	4.63	37.68	36.10	74.00	-37.90	Vertical
7236.00	32.71	36.25	6.52	37.80	37.68	74.00	-36.32	Vertical
9648.00	31.64	37.97	7.98	37.93	39.66	74.00	-34.34	Vertical
4824.00	36.95	31.24	4.63	37.68	35.14	74.00	-38.86	Horizontal
7236.00	32.65	36.25	6.52	37.80	37.62	74.00	-36.38	Horizontal
9648.00	31.30	37.97	7.98	37.93	39.32	74.00	-34.68	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	27.18	31.24	4.63	37.68	25.37	54.00	-28.63	Vertical
7236.00	21.63	36.25	6.52	37.80	26.60	54.00	-27.40	Vertical
9648.00	22.03	37.97	7.98	37.93	30.05	54.00	-23.95	Vertical
4824.00	26.62	31.24	4.63	37.68	24.81	54.00	-29.19	Horizontal
7236.00	21.27	36.25	6.52	37.80	26.24	54.00	-27.76	Horizontal
9648.00	21.08	37.97	7.98	37.93	29.10	54.00	-24.90	Horizontal

Test mode:	802.11n(HT20)	Test channel:	Middle
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	37.38	31.31	4.69	37.62	35.76	74.00	-38.24	Vertical
7311.00	33.04	36.39	6.61	37.78	38.26	74.00	-35.74	Vertical
9748.00	32.84	38.10	8.02	37.95	41.01	74.00	-32.99	Vertical
4874.00	38.17	31.31	4.69	37.62	36.55	74.00	-37.45	Horizontal
7311.00	31.84	36.39	6.61	37.78	37.06	74.00	-36.94	Horizontal
9748.00	32.80	38.10	8.02	37.95	40.97	74.00	-33.03	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	28.39	31.31	4.69	37.62	26.77	54.00	-27.23	Vertical
7311.00	21.40	36.39	6.61	37.78	26.62	54.00	-27.38	Vertical
9748.00	22.13	38.10	8.02	37.95	30.30	54.00	-23.70	Vertical
4874.00	28.38	31.31	4.69	37.62	26.76	54.00	-27.24	Horizontal
7311.00	20.96	36.39	6.61	37.78	26.18	54.00	-27.82	Horizontal
9748.00	22.55	38.10	8.02	37.95	30.72	54.00	-23.28	Horizontal

Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	41.49	31.37	4.75	37.58	40.03	74.00	-33.97	Vertical
7386.00	32.82	36.57	6.71	37.74	38.36	74.00	-35.64	Vertical
9848.00	35.49	38.20	8.07	37.58	44.18	74.00	-29.82	Vertical
4924.00	41.32	31.37	4.75	37.58	39.86	74.00	-34.14	Horizontal
7386.00	31.99	36.57	6.71	37.74	37.53	74.00	-36.47	Horizontal
9848.00	31.78	38.20	8.07	37.58	40.47	74.00	-33.53	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	32.67	31.37	4.75	37.58	31.21	54.00	-22.79	Vertical
7386.00	22.81	36.57	6.71	37.74	28.35	54.00	-25.65	Vertical
9848.00	24.06	38.20	8.07	37.58	32.75	54.00	-21.25	Vertical
4924.00	31.86	31.37	4.75	37.58	30.40	54.00	-23.60	Horizontal
7386.00	21.44	36.57	6.71	37.74	26.98	54.00	-27.02	Horizontal
9848.00	21.10	38.20	8.07	37.58	29.79	54.00	-24.21	Horizontal

Notes:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

■ **Unwanted Emissions in restricted Frequency Bands**

■ **ANT 1**

Test mode:	802.11g	Test channel:	Lowest
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	39.50	27.14	2.81	38.64	30.81	74.00	-43.19	Horizontal
2390.00	47.79	27.37	2.91	38.84	39.23	74.00	-34.77	Horizontal
2310.00	38.03	27.14	2.81	38.64	29.34	74.00	-44.66	Vertical
2390.00	49.01	27.37	2.91	38.84	40.45	74.00	-33.55	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	29.88	27.14	2.81	38.64	21.19	54.00	-32.81	Horizontal
2390.00	36.94	27.37	2.91	38.84	28.38	54.00	-25.62	Horizontal
2310.00	28.53	27.14	2.81	38.64	19.84	54.00	-34.16	Vertical
2390.00	38.90	27.37	2.91	38.84	30.34	54.00	-23.66	Vertical

Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	48.23	27.82	2.99	39.05	39.99	74.00	-34.01	Horizontal
2500.00	40.75	27.70	3.01	39.10	32.36	74.00	-41.64	Horizontal
2483.50	48.05	27.82	2.99	39.05	39.81	74.00	-34.19	Vertical
2500.00	41.88	27.70	3.01	39.10	33.49	74.00	-40.51	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	36.92	27.82	2.99	39.05	28.68	54.00	-25.32	Horizontal
2500.00	33.43	27.70	3.01	39.10	25.04	54.00	-28.96	Horizontal
2483.50	37.67	27.82	2.99	39.05	29.43	54.00	-24.57	Vertical
2500.00	32.23	27.70	3.01	39.10	23.84	54.00	-30.16	Vertical

Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	39.66	27.14	2.81	38.64	30.97	74.00	-43.03	Horizontal
2390.00	48.01	27.37	2.91	38.84	39.45	74.00	-34.55	Horizontal
2310.00	38.20	27.14	2.81	38.64	29.51	74.00	-44.49	Vertical
2390.00	49.27	27.37	2.91	38.84	40.71	74.00	-33.29	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	30.00	27.14	2.81	38.64	21.31	54.00	-32.69	Horizontal
2390.00	37.07	27.37	2.91	38.84	28.51	54.00	-25.49	Horizontal
2310.00	28.66	27.14	2.81	38.64	19.97	54.00	-34.03	Vertical
2390.00	39.05	27.37	2.91	38.84	30.49	54.00	-23.51	Vertical

Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	48.47	27.82	2.99	39.05	40.23	74.00	-33.77	Horizontal
2500.00	40.93	27.70	3.01	39.10	32.54	74.00	-41.46	Horizontal
2483.50	48.32	27.82	2.99	39.05	40.08	74.00	-33.92	Vertical
2500.00	42.09	27.70	3.01	39.10	33.70	74.00	-40.30	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	37.06	27.82	2.99	39.05	28.82	54.00	-25.18	Horizontal
2500.00	33.54	27.70	3.01	39.10	25.15	54.00	-28.85	Horizontal
2483.50	37.83	27.82	2.99	39.05	29.59	54.00	-24.41	Vertical
2500.00	32.34	27.70	3.01	39.10	23.95	54.00	-30.05	Vertical

■ ANT 2

Test mode:	802.11g	Test channel:	Lowest
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	39.29	27.14	2.81	38.64	30.60	74.00	-43.40	Horizontal
2390.00	47.52	27.37	2.91	38.84	38.96	74.00	-35.04	Horizontal
2310.00	37.81	27.14	2.81	38.64	29.12	74.00	-44.88	Vertical
2390.00	48.68	27.37	2.91	38.84	40.12	74.00	-33.88	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	29.73	27.14	2.81	38.64	21.04	54.00	-32.96	Horizontal
2390.00	36.77	27.37	2.91	38.84	28.21	54.00	-25.79	Horizontal
2310.00	28.37	27.14	2.81	38.64	19.68	54.00	-34.32	Vertical
2390.00	38.72	27.37	2.91	38.84	30.16	54.00	-23.84	Vertical

Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	47.94	27.82	2.99	39.05	39.70	74.00	-34.30	Horizontal
2500.00	40.52	27.70	3.01	39.10	32.13	74.00	-41.87	Horizontal
2483.50	47.72	27.82	2.99	39.05	39.48	74.00	-34.52	Vertical
2500.00	41.62	27.70	3.01	39.10	33.23	74.00	-40.77	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	36.74	27.82	2.99	39.05	28.50	54.00	-25.50	Horizontal
2500.00	33.29	27.70	3.01	39.10	24.90	54.00	-29.10	Horizontal
2483.50	37.48	27.82	2.99	39.05	29.24	54.00	-24.76	Vertical
2500.00	32.08	27.70	3.01	39.10	23.69	54.00	-30.31	Vertical

Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	39.57	27.14	2.81	38.64	30.88	74.00	-43.12	Horizontal
2390.00	47.88	27.37	2.91	38.84	39.32	74.00	-34.68	Horizontal
2310.00	38.10	27.14	2.81	38.64	29.41	74.00	-44.59	Vertical
2390.00	49.12	27.37	2.91	38.84	40.56	74.00	-33.44	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	29.93	27.14	2.81	38.64	21.24	54.00	-32.76	Horizontal
2390.00	37.00	27.37	2.91	38.84	28.44	54.00	-25.56	Horizontal
2310.00	28.58	27.14	2.81	38.64	19.89	54.00	-34.11	Vertical
2390.00	38.96	27.37	2.91	38.84	30.40	54.00	-23.60	Vertical

Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	48.33	27.82	2.99	39.05	40.09	74.00	-33.91	Horizontal
2500.00	40.82	27.70	3.01	39.10	32.43	74.00	-41.57	Horizontal
2483.50	48.16	27.82	2.99	39.05	39.92	74.00	-34.08	Vertical
2500.00	41.97	27.70	3.01	39.10	33.58	74.00	-40.42	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	36.98	27.82	2.99	39.05	28.74	54.00	-25.26	Horizontal
2500.00	33.48	27.70	3.01	39.10	25.09	54.00	-28.91	Horizontal
2483.50	37.74	27.82	2.99	39.05	29.50	54.00	-24.50	Vertical
2500.00	32.28	27.70	3.01	39.10	23.89	54.00	-30.11	Vertical

Remarks:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor*
2. *The emission levels of other frequencies are very lower than the limit and not show in test report.*

8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

-----End-----