

# FCC RF Test Report

APPLICANT : Kilpatrick LLC  
EQUIPMENT : Tablet PC  
MODEL NAME : C6R7NC  
FCC ID : S2F-5830  
STANDARD : FCC Part 15 Subpart C §15.247  
CLASSIFICATION : (DTS) Digital Transmission System


The product was received on Sep. 17, 2014 and testing was completed on Sep. 24, 2014. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



---

Reviewed by: Joseph Lin / Supervisor



---

Approved by: Jones Tsai / Manager



**SPORTON INTERNATIONAL INC.**

**No. 52, Hwa Ya 1<sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.**

# TABLE OF CONTENTS

<b>REVISION HISTORY.....</b>	<b>3</b>
<b>SUMMARY OF TEST RESULT .....</b>	<b>4</b>
<b>1 GENERAL DESCRIPTION.....</b>	<b>5</b>
1.1 Applicant.....	5
1.2 Product Feature of Equipment Under Test.....	5
1.3 Product Specification subjective to this standard .....	5
1.4 Modification of EUT .....	6
1.5 Testing Location .....	6
1.6 Applicable Standards.....	6
<b>2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....</b>	<b>7</b>
2.1 Descriptions of Test Mode.....	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system .....	10
2.5 EUT Operation Test Setup .....	10
2.6 Measurement Results Explanation Example.....	10
<b>3 TEST RESULT .....</b>	<b>11</b>
3.1 6dB Bandwidth Measurement .....	11
3.2 Peak Output Power Measurement .....	14
3.3 Power Spectral Density Measurement .....	16
3.4 Conducted Band Edges and Spurious Emission Measurement .....	22
3.5 Radiated Band Edges and Spurious Emission Measurement .....	31
3.6 AC Conducted Emission Measurement.....	35
3.7 Antenna Requirements.....	41
<b>4 LIST OF MEASURING EQUIPMENT.....</b>	<b>42</b>
<b>5 UNCERTAINTY OF EVALUATION.....</b>	<b>43</b>
<b>APPENDIX A. RADIATED SPURIOUS EMISSION</b>	

## REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR332726-14	Rev. 01	Initial issue of report	Sep. 25, 2014

## SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.2	15.247(b)(1)	Peak Output Power	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	$\leq 20\text{dBc}$	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 6.26 dB at 2487.920 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 9.10 dB at 0.486 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-

# 1 General Description

## 1.1 Applicant

Kilpatrick LLC  
102 S. Tejon Street  
Suite 1100  
Colorado Springs, Colorado 80903

## 1.2 Product Feature of Equipment Under Test

Product Feature	
Equipment	Tablet PC
Model Name	C6R7NC
FCC ID	S2F-5830
EUT supports Radios application	GSM/EGPRS/WCDMA/HSPA/LTE WLAN 11b/g/n HT20 WLAN 11a/n HT20/HT40 Bluetooth v4.0 EDR/LE

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 1.3 Product Specification subjective to this standard

Product Specification subjective to this standard	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	40
Carrier Frequency of Each Channel	40 Channel(37 hopping + 3 advertising channel)
Maximum Output Power to Antenna	5.54 dBm (0.0036 W)
Antenna Type	Fixed internal Antenna type with gain 4.10 dBi
Type of Modulation	Bluetooth LE : GFSK

## 1.4 Modification of EUT

No modifications are made to the EUT during all test items.

## 1.5 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

<b>Test Site</b>	SPORTON INTERNATIONAL INC.		
<b>Test Site Location</b>	No. 52, Hwa Ya 1 <sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-3273456 / FAX: +886-3-3284978		
<b>Test Site No.</b>	<b>Sporton Site No.</b>		
	TH02-HY	CO05-HY	03CH06-HY

## 1.6 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02
- ANSI C63.4-2003

**Remark:** All test items were verified and recorded according to the standards and without any deviation during the test.

## 2 Test Configuration of Equipment Under Test

### 2.1 Descriptions of Test Mode

The RF output power was recorded in the following table:

Channel	Frequency	Bluetooth 4.0 – LE RF Output Power
		Data Rate / Modulation
		GFSK
		1Mbps
Ch00	2402MHz	4.16 dBm
Ch19	2440MHz	<b>5.54 dBm</b>
Ch39	2480MHz	4.65 dBm

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). Pre-scanned tests, X, Y, Z in three orthogonal panels to determine the final configuration (Y plane as worst plane) from all possible combinations.
  
- b. AC power line Conducted Emission was tested under maximum output power.

## 2.2 Test Mode


The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth 4.0 – LE / GFSK
Conducted TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
Radiated TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
AC Conducted Emission	Mode 1: Bluetooth Tx + Earphone + USB Cable (Charging from Adapter) + Camera




## 2.3 Connection Diagram of Test System

### <Bluetooth 4.0 – LE Tx Mode>



### <AC Conducted Emission Mode>



## 2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	iPod Earphone	Apple	N/A	Verification	Unshielded, 1.0 m	N/A
2.	Adapter	Foxlink	PE98ED	Verification	N/A	N/A

## 2.5 EUT Operation Test Setup

For Bluetooth function, programmed RF utility, "ADB" installed in the notebook make the EUT provides functions like channel selection and power level for continuous transmitting and receiving signals.

## 2.6 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$

## 3 Test Result

### 3.1 6dB Bandwidth Measurement

#### 3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


#### 3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

#### 3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. Measure and record the results in the test report.

#### 3.1.4 Test Setup




### 3.1.5 Test Result of 6dB Bandwidth

Test Mode :	Bluetooth 4.0 - LE	Temperature :	22~25°C
Test Engineer :	Stuart Lin	Relative Humidity :	51~55%


Channel	Frequency (MHz)	6dB Bandwidth (MHz)	6dB Bandwidth Min. Limit (MHz)	Pass/Fail
00	2402	0.66	0.5	Pass
19	2440	0.65	0.5	Pass
39	2480	0.66	0.5	Pass

6 dB Bandwidth Plot on Channel 00




Date: 23.SEP.2014 16:31:15

### 6 dB Bandwidth Plot on Channel 19



Date: 23.SEP.2014 16:35:09

### 6 dB Bandwidth Plot on Channel 39



Date: 23.SEP.2014 16:39:02

## 3.2 Peak Output Power Measurement

### 3.2.1 Limit of Peak Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


### 3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

### 3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r02.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

### 3.2.4 Test Setup



### 3.2.5 Test Result of Peak Output Power

<b>Test Mode :</b>	Bluetooth 4.0 - LE	<b>Temperature :</b>	22~25°C
<b>Test Engineer :</b>	Stuart Lin	<b>Relative Humidity :</b>	51~55%

Channel	Frequency (MHz)	RF Power (dBm)		
		GFSK	Max. Limits (dBm)	Pass/Fail
		1 Mbps		
00	2402	4.16	30.00	Pass
19	2440	5.54	30.00	Pass
39	2480	4.65	30.00	Pass

## 3.3 Power Spectral Density Measurement

### 3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


### 3.3.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

### 3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

### 3.3.4 Test Setup





### 3.3.5 Test Result of Power Spectral Density

Test Mode :	Bluetooth 4.0 - LE	Temperature :	22~25°C
Test Engineer :	Stuart Lin	Relative Humidity :	51~55%


Channel	Frequency (MHz)	Power Density		Max. Limits (dBm/3kHz)	Pass/Fail
		PSD/100kHz (dBm)	PSD/3kHz (dBm)		
00	2402	3.16	-11.68	8	Pass
19	2440	4.87	-10.01	8	Pass
39	2480	3.36	-11.50	8	Pass

**Note:**

1. Measured power density (dBm) has offset with cable loss.
2. The Measured power density (dBm)/ 100kHz is reference level and used as 20dBc down for Conducted Band Edges and Conducted Spurious Emission limit line.


### 3.3.6 Test Result of Power Spectral Density Plots (100kHz)

#### PSD 100kHz Plot on Channel 00




Date: 23.SEP.2014 16:32:16

#### PSD 100kHz Plot on Channel 19



Date: 23.SEP.2014 16:36:16


### PSD 100kHz Plot on Channel 39



Date: 23.SEP.2014 16:39:48


### 3.3.7 Test Result of Power Spectral Density Plots (3kHz)

PSD 3kHz Plot on Channel 00




Date: 23.SEP.2014 16:31:49

PSD 3kHz Plot on Channel 19



Date: 23.SEP.2014 16:35:53

### PSD 3kHz Plot on Channel 39



Date: 23.SEP.2014 16:39:26

## 3.4 Conducted Band Edges and Spurious Emission Measurement

### 3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


### 3.4.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

### 3.4.3 Test Procedure

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


### 3.4.4 Test Setup



### 3.4.5 Test Result of Conducted Band Edges


Test Mode :	Bluetooth 4.0 - LE	Temperature :	22~25°C
Test Channel :	00 and 39	Relative Humidity :	51~55%
		Test Engineer :	Stuart Lin

Low Band Edge Plot on Channel 00



Date: 23.SEP.2014 16:32:34

## High Band Edge Plot on Channel 39




Date: 23.SEP.2014 16:40:15



### 3.4.6 Test Result of Conducted Spurious Emission


Test Mode :	Bluetooth 4.0 - LE	Temperature :	22~25°C
Test Channel :	00	Relative Humidity :	51~55%
		Test Engineer :	Stuart Lin

#### Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00



Date: 23.SEP.2014 16:45:05


## Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00



Date: 23.SEP.2014 16:33:20


Test Mode :	Bluetooth 4.0 - LE	Temperature :	22~25°C
Test Channel :	19	Relative Humidity :	51~55%
		Test Engineer :	Stuart Lin

**Conducted Spurious Emission Plot on Bluetooth LE 1Mbps  
GFSK Channel 19**



Date: 23.SEP.2014 16:37:26


## Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19



Date: 23.SEP.2014 16:37:44

Test Mode :	Bluetooth 4.0 - LE	Temperature :	22~25°C
Test Channel :	39	Relative Humidity :	51~55%
		Test Engineer :	Stuart Lin

**Conducted Spurious Emission Plot on Bluetooth LE 1Mbps  
GFSK Channel 39**



Date: 23.SEP.2014 16:43:58



### 3.5 Radiated Band Edges and Spurious Emission Measurement

#### 3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.5.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

### 3.5.3 Test Procedures


1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1$  GHz;  $VBW \geq RBW$ ; Sweep = auto; Detector function = peak; Trace = max hold;
  - (3) Set RBW = 1 MHz, VBW= 3MHz for  $f \geq 1$  GHz for peak measurement.  
 For average measurement:
    - $VBW = 10$  Hz, when duty cycle is no less than 98 percent.
    - $VBW \geq 1/T$ , when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

Band	Duty Cycle(%)	T( $\mu$ s)	1/T(kHz)	VBW Setting
Bluetooth 4.0 - LE	64.97	408	2.45	3kHz




### 3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



### 3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

### 3.5.6 Test Result of Radiated Spurious Emission (30MHz ~ 10<sup>th</sup> Harmonic)

Please refer Appendix A.

## 3.6 AC Conducted Emission Measurement

### 3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


### 3.6.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

### 3.6.3 Test Procedures


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

### 3.6.4 Test Setup



### 3.6.5 Test Result of AC Conducted Emission


Test Mode :	Mode 1	Temperature :	20~22°C
Test Engineer :	Kai-Chun Chu	Relative Humidity :	46~48%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	Bluetooth Tx + Earphone + USB Cable (Charging from Adapter) + Camera		



#### Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	47.9	Off	L1	19.4	18.1	66.0
0.206000	47.8	Off	L1	19.4	15.6	63.4
0.390000	46.2	Off	L1	19.5	11.9	58.1
0.414000	45.9	Off	L1	19.5	11.7	57.6
0.486000	46.0	Off	L1	19.5	10.2	56.2
0.534000	42.4	Off	L1	19.5	13.6	56.0
0.598000	41.7	Off	L1	19.5	14.3	56.0
1.006000	38.3	Off	L1	19.5	17.7	56.0
1.534000	37.9	Off	L1	19.5	18.1	56.0
2.518000	37.1	Off	L1	19.6	18.9	56.0
4.038000	36.8	Off	L1	19.6	19.2	56.0
4.822000	36.9	Off	L1	19.6	19.1	56.0


Test Mode :	Mode 1	Temperature :	20~22°C
Test Engineer :	Kai-Chun Chu	Relative Humidity :	46~48%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	Bluetooth Tx + Earphone + USB Cable (Charging from Adapter) + Camera		



**Final Result : Average**

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	33.5	Off	L1	19.4	22.5	56.0
0.206000	34.6	Off	L1	19.4	18.8	53.4
0.390000	33.9	Off	L1	19.5	14.2	48.1
0.414000	33.1	Off	L1	19.5	14.5	47.6
0.486000	34.3	Off	L1	19.5	11.9	46.2
0.534000	31.5	Off	L1	19.5	14.5	46.0
0.598000	31.1	Off	L1	19.5	14.9	46.0
1.006000	25.2	Off	L1	19.5	20.8	46.0
1.534000	26.2	Off	L1	19.5	19.8	46.0
2.518000	25.8	Off	L1	19.6	20.2	46.0
4.038000	27.6	Off	L1	19.6	18.4	46.0
4.822000	27.0	Off	L1	19.6	19.0	46.0


Test Mode :	Mode 1	Temperature :	20~22°C
Test Engineer :	Kai-Chun Chu	Relative Humidity :	46~48%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	Bluetooth Tx + Earphone + USB Cable (Charging from Adapter) + Camera		



#### Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.158000	45.6	Off	N	19.4	20.0	65.6
0.182000	44.9	Off	N	19.4	19.5	64.4
0.206000	47.8	Off	N	19.4	15.6	63.4
0.414000	46.6	Off	N	19.5	11.0	57.6
0.486000	47.1	Off	N	19.6	9.1	56.2
0.526000	44.2	Off	N	19.5	11.8	56.0
0.614000	41.6	Off	N	19.5	14.4	56.0
0.926000	40.9	Off	N	19.5	15.1	56.0
1.006000	40.2	Off	N	19.6	15.8	56.0
1.078000	39.1	Off	N	19.5	16.9	56.0
1.270000	38.5	Off	N	19.5	17.5	56.0
1.438000	38.7	Off	N	19.6	17.3	56.0
1.526000	39.6	Off	N	19.5	16.4	56.0
1.638000	35.5	Off	N	19.6	20.5	56.0
2.518000	38.6	Off	N	19.6	17.4	56.0
2.678000	36.1	Off	N	19.6	19.9	56.0
3.558000	38.0	Off	N	19.6	18.0	56.0
3.998000	38.2	Off	N	19.6	17.8	56.0
4.414000	37.1	Off	N	19.6	18.9	56.0
4.854000	37.9	Off	N	19.6	18.1	56.0

Test Mode :	Mode 1	Temperature :	20~22°C
Test Engineer :	Kai-Chun Chu	Relative Humidity :	46~48%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	Bluetooth Tx + Earphone + USB Cable (Charging from Adapter) + Camera		



**Final Result : Average**

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.158000	32.0	Off	N	19.4	23.6	55.6
0.182000	31.4	Off	N	19.4	23.0	54.4
0.206000	34.9	Off	N	19.4	18.5	53.4
0.414000	34.2	Off	N	19.5	13.4	47.6
0.486000	32.3	Off	N	19.6	13.9	46.2
0.526000	30.7	Off	N	19.5	15.3	46.0
0.614000	31.5	Off	N	19.5	14.5	46.0
0.926000	28.4	Off	N	19.5	17.6	46.0
1.006000	27.6	Off	N	19.6	18.4	46.0
1.078000	27.3	Off	N	19.5	18.7	46.0
1.270000	27.2	Off	N	19.5	18.8	46.0
1.438000	28.0	Off	N	19.6	18.0	46.0
1.526000	28.6	Off	N	19.5	17.4	46.0
1.638000	25.5	Off	N	19.6	20.5	46.0
2.518000	27.7	Off	N	19.6	18.3	46.0
2.678000	25.6	Off	N	19.6	20.4	46.0
3.558000	29.2	Off	N	19.6	16.8	46.0
3.998000	28.8	Off	N	19.6	17.2	46.0
4.414000	27.5	Off	N	19.6	18.5	46.0
4.854000	28.4	Off	N	19.6	17.6	46.0



## **3.7 Antenna Requirements**

### **3.7.1 Standard Applicable**

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

### **3.7.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.7.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz~40GHz	Jun. 09, 2014	Sep. 23, 2014	Jun. 08, 2015	Conducted (TH02-HY)
Power Meter	Agilent	E4416A	GB412923 44	300MHz~40GHz	Jan. 28, 2014	Sep. 23, 2014	Jan. 27, 2015	Conducted (TH02-HY)
Power Sensor	Agilent	E9327A	US404415 48	300MHz~40GHz	Jan. 28, 2014	Sep. 23, 2014	Jan. 27, 2015	Conducted (TH02-HY)
Spectrum Analyzer	R&S	FSP30	101067	9kHz ~ 30GHz	Nov. 20, 2013	Sep. 24, 2014	Nov. 19, 2014	Radiation (03CH06-HY)
Spectrum Analyzer	Agilent	E4408B	MY442110 30	9kHz ~ 26.5GHz	Dec. 02, 2013	Sep. 24, 2014	Dec. 01, 2014	Radiation (03CH06-HY)
EMI Test Receiver	R&S	ESVS10	834468/00 03	20MHz ~ 1000MHz	May 06, 2014	Sep. 24, 2014	May 05, 2015	Radiation (03CH06-HY)
Bilog Antenna	Schaffner	CBL6112B	2885	30MHz ~ 2GHz	Oct. 10, 2013	Sep. 24, 2014	Oct. 09, 2014	Radiation (03CH06-HY)
Double Ridge Horn Antenna	EMCO	3117	00066583	1GHz ~ 18GHz	Jul. 24, 2014	Sep. 24, 2014	Jul. 23, 2015	Radiation (03CH06-HY)
Amplifier	SONOMA	310N	186713	9kHz ~ 1GHz	Apr. 16, 2014	Sep. 24, 2014	Apr. 15, 2015	Radiation (03CH06-HY)
Preamplifier	EMCI	EMC051845	SN980048	1GHz ~ 18GHz	Jul. 17, 2014	Sep. 24, 2014	Jul. 16, 2015	Radiation (03CH06-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170 251	15GHz ~ 40GHz	Oct. 03, 2013	Sep. 24, 2014	Oct. 02, 2014	Radiation (03CH06-HY)
Preamplifier	Agilent	8449B	3008A019 17	1GHz ~ 26.5GHz	Apr. 10, 2014	Sep. 24, 2014	Apr. 09, 2015	Radiation (03CH06-HY)
Turn Table	INN-CO	DS2000	420/650/00	0 ~ 360 degree	N/A	Sep. 24, 2014	N/A	Radiation (03CH06-HY)
Antenna Mast	MF	MF-7802	MF780208 212	1 m ~ 4 m	N/A	Sep. 24, 2014	N/A	Radiation (03CH06-HY)
EMI Test Receiver	Rohde & Schwarz	ESCS 30	100356	9kHz ~ 2.75GHz	Nov. 15, 2013	Sep. 23, 2014	Nov. 14, 2014	Conduction (CO05-HY)
LISN (for auxiliary equipment)	Rohde & Schwarz	ENV216	100081	9kHz ~ 30MHz	Dec. 12, 2013	Sep. 23, 2014	Dec. 11, 2014	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz ~ 30MHz	Dec. 04, 2013	Sep. 23, 2014	Dec. 03, 2014	Conduction (CO05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Sep. 23, 2014	N/A	Conduction (CO05-HY)

## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.26
---	------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.50
---	------

# Appendix A. Radiated Spurious Emission

Test Engineer :	Donny Pang		
Temperature :	22~25°C	Relative Humidity :	42~45%

## 15C 2.4GHz 2400~2483.5MHz

### BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.	
		( MHz )	( dBμV/m )	( dB )	Limit	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
					Line	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )	
BLE CH 00 2402MHz		2365.35	51.36	-22.64	74	47.92	31.92	6.17	34.65	131	54	P	H	
		2313.96	40.33	-13.67	54	36.99	31.89	6.1	34.65	131	54	A	H	
	*	2402.171	104.07	-	-	100.56	31.94	6.21	34.64	131	54	P	H	
	*	2402.004	103.13	-	-	99.62	31.94	6.21	34.64	131	54	A	H	
													H	
														H
			2370.84	51.52	-22.48	74	48.07	31.93	6.17	34.65	137	78	P	V
			2355.36	40.25	-13.75	54	36.84	31.92	6.14	34.65	137	78	A	V
	*		2402.171	104.35	-	-	100.84	31.94	6.21	34.64	137	78	P	V
	*		2402.004	103.41	-	-	99.9	31.94	6.21	34.64	137	78	A	V
														V
														V
BLE CH 19 2440MHz		2321.07	51.75	-22.25	74	48.4	31.9	6.1	34.65	102	129	P	H	
		2363.64	40.4	-13.6	54	36.99	31.92	6.14	34.65	102	129	A	H	
	*	2439.746	106.38	-	-	102.81	31.97	6.24	34.64	102	129	P	H	
	*	2439.997	105.41	-	-	101.84	31.97	6.24	34.64	102	129	A	H	
			2488.32	53.87	-20.13	74	50.2	32	6.3	34.63	102	129	P	H
			2487.92	47.74	-6.26	54	44.07	32	6.3	34.63	102	129	A	H
			2331.42	51.69	-22.31	74	48.34	31.9	6.1	34.65	109	56	P	V
			2353.29	40.38	-13.62	54	36.97	31.92	6.14	34.65	109	56	A	V
	*		2439.746	104.85	-	-	101.28	31.97	6.24	34.64	109	56	P	V
	*		2439.997	103.82	-	-	100.25	31.97	6.24	34.64	109	56	A	V
			2487.88	53.22	-20.78	74	49.55	32	6.3	34.63	109	56	P	V
			2487.92	46.29	-7.71	54	42.62	32	6.3	34.63	109	56	A	V

<b>BLE CH 39 2480MHz</b>	*	2479.826	101.14	-	-	97.48	31.99	6.3	34.63	131	294	P	H
	*	2480.076	100.15	-	-	96.49	31.99	6.3	34.63	131	294	A	H
		2498.24	52.14	-21.86	74	48.43	32	6.34	34.63	131	294	P	H
		2483.72	40.57	-13.43	54	36.91	31.99	6.3	34.63	131	294	A	H
													H
													H
	*	2479.826	102.6	-	-	98.94	31.99	6.3	34.63	100	263	P	V
	*	2480.076	101.59	-	-	97.93	31.99	6.3	34.63	100	263	A	V
		2483.52	51.82	-22.18	74	48.16	31.99	6.3	34.63	100	263	P	V
		2484.28	41.44	-12.56	54	37.78	31.99	6.3	34.63	100	263	A	V
													V
													V
<b>Remark</b>	<ol style="list-style-type: none"> <li>1. No other spurious found.</li> <li>2. All results are PASS against Peak and Average limit line.</li> </ol>												

**15C 2.4GHz 2400~2483.5MHz**  
**BLE (Harmonic @ 3m)**

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
		( MHz )	( dB $\mu$ V/m )	( dB )	( dB $\mu$ V/m )	( dB $\mu$ V )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
BLE CH 00 2402MHz		4803	40.82	-13.18	54	58.81	34.35	8.52	60.86	100	0	P	H
													H
													H
													H
		4803	39.59	-14.41	54	57.58	34.35	8.52	60.86	100	0	P	V
													V
													V
													V
BLE CH 19 2440MHz		4881	40.84	-13.16	54	58.36	34.4	8.77	60.69	100	0	P	H
		7320	43.59	-10.41	54	56.44	35.73	11.95	60.53	100	0	P	H
													H
													H
		4881	40.55	-13.45	54	58.07	34.4	8.77	60.69	100	0	P	V
		7320	43.38	-10.62	54	56.23	35.73	11.95	60.53	100	0	P	V
													V
													V
BLE CH 39 2480MHz		4959	40.01	-13.99	54	57	34.47	9.02	60.48	100	0	P	H
		7440	44	-10	54	56.86	35.71	12.01	60.58	100	0	P	H
													H
													H
		4959	40.39	-13.61	54	57.38	34.47	9.02	60.48	100	0	P	V
		7440	43.26	-10.74	54	56.12	35.71	12.01	60.58	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

**15C Emission below 1GHz**

**2.4GHz BLE (LF @ 3m)**

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.	
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )	
2.4GHz BLE LF		82.65	18.3	-21.7	40	41.68	7.38	1	31.76			P	H	
		183.9	30.43	-13.07	43.5	51.66	9.06	1.46	31.75	177	102	P	H	
		211.44	28.15	-15.35	43.5	49.21	9.11	1.58	31.75			P	H	
		545	21.56	-24.44	46	31.71	19.3	2.54	31.99			P	H	
		802.6	23.75	-22.25	46	32.58	20.04	3.07	31.94			P	H	
		972	25.49	-28.51	54	31.66	21.34	3.35	30.86			P	H	
														H
														H
														H
														H
														H
														H
			52.14	27.02	-12.98	40	50.32	7.66	0.82	31.78	189	349	P	V
			167.16	24.15	-19.35	43.5	44.46	9.86	1.58	31.75			P	V
			291.9	26.92	-19.08	46	43.73	13.04	1.87	31.72			P	V
			343.4	29.57	-16.43	46	45.16	14.15	2.02	31.76			P	V
			536.6	26.95	-19.05	46	37.59	18.81	2.53	31.98			P	V
			874	29.02	-16.98	46	36.46	20.9	3.3	31.64			P	V
														V
														V
													V	
													V	
													V	
													V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.													

### Note symbol

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency per 15.209(c).
!	Test result is <b>over limit</b> line.
P/A	<b>P</b> eak or <b>A</b> verage
H/V	<b>H</b> orizontal or <b>V</b> ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H
2412MHz													

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

**For Peak Limit @ 2390MHz:**

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

**For Average Limit @ 2390MHz:**

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

**Both peak and average measured complies with the limit line, so test result is “PASS”.**