



Nemko

Nemko Test Report: 2087RUS1

Applicant: Crane Co WMS
1820 Preston Park Blvd Suite 2800
Plano, TX 75093
USA

Equipment Under Test: LG2400
(E.U.T.)


In Accordance With: **FCC Part 15, Subpart C, 15.247**
Digital Transmission System Transmitter

Tested By: Nemko USA, Inc.
802 N. Kealy
Lewisville, Texas 75057-3136

TESTED BY: 

David Light, senior Wireless Engineer

DATE: 17 January 2007

APPROVED BY: 

Kevin Rose Wireless Engineer

DATE: 17 January 2007

Number of Pages: 38

Table of Contents

SECTION 1. SUMMARY OF TEST RESULTS	3
SECTION 2. EQUIPMENT UNDER TEST (E.U.T.)	5
SECTION 3. POWERLINE CONDUCTED EMISSIONS	7
SECTION 4. OCCUPIED BANDWIDTH	10
SECTION 5. MAXIMUM PEAK OUTPUT POWER	13
SECTION 6. SPURIOUS EMISSIONS AT ANTENNA TERMINALS	16
SECTION 7. RADIATED EMISSIONS	19
SECTION 8. PEAK POWER SPECTRAL DENSITY	24
SECTION 9. TEST EQUIPMENT LIST	27
ANNEX A - TEST DETAILS	28
ANNEX B - TEST DIAGRAMS	36

Section 1. Summary of Test Results

Manufacturer: Crane Co WMS

Model No.: LG2400

Serial No.: 2006112100011

General: **All measurements are traceable to national standards.**

These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 15, Subpart C, Paragraph 15.247 for Digital Transmission Systems. Radiated tests were conducted in accordance with ANSI C63.4-2003. Radiated emissions are made on an open area test site. A description of the test facility is on file with the FCC.



New Submission



Production Unit



Class II Permissive Change



Pre-Production Unit

THIS TEST REPORT RELATES ONLY TO THE ITEM(S) TESTED.**THE FOLLOWING DEVIATIONS FROM, ADDITIONS TO, OR EXCLUSIONS FROM THE TEST SPECIFICATIONS HAVE BEEN MADE.**

See "Summary of Test Data".



Nemko USA Inc. authorizes the above named company to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko USA Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report. This report applies only to the items tested.

Nemko USA, Inc.

EQUIPMENT: LG2400

FCC PART 15, SUBPART C
Digital Transmission Systems
Test Report No.: 2087RUS1

Summary Of Test Data

NAME OF TEST	PARA. NO.	RESULT
Powerline Conducted Emissions	15.207(a)	Complies
Minimum 6 dB Bandwidth	15.247(a)(2)	Complies
Maximum Peak Power Output	15.247(b)(3)	Complies
Spurious Emissions (Antenna Conducted)	15.247(d)	Complies
Spurious Emissions (Restricted Bands)	15.247(d)/15.209(a)	Complies
Peak Power Spectral Density	15.247(e)	Complies

Footnotes:

Section 2. Equipment Under Test (E.U.T.)**General Equipment Information**

Frequency Band (MHz):	902-928	2400-2483.5	5725-5850
	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>

Operating Frequency of Test Sample: 2405 to 2475 MHz

Channel Spacing: 5 MHz

User Frequency Adjustment: Software controlled

Nominal Voltage: 8-30 Vdc


Antenna Type(s): 5.5 dBi Omni or 13 dBi Directional

Antenna Connector: Reverse polarity SMA

Description of EUT

Gateway for a wireless ZigBee network

System Diagram



Nemko USA, Inc.

EQUIPMENT: LG2400

FCC PART 15, SUBPART C
Digital Transmission Systems
Test Report No.: 2087RUS1

Section 3. Powerline Conducted Emissions

NAME OF TEST: Powerline Conducted Emissions	PARA. NO.: 15.207(a)
TESTED BY: David Light	DATE: 17 January 2007

Test Results: Complies.

Measurement Data: See attached plots.

Measurement Uncertainty: +/- 1.7 dB


Test Equipment Used: 1663-1652-704-1188-674

Test Conditions 23°C
42% RH

Power adapter: Phihong PSA15-120P


Test Data – Powerline Conducted Emissions

L1 Peak



Date: 18.JAN.2007 09:14:03


L1 Peak



Date: 18.JAN.2007 09:15:12

Test Data – Powerline Conducted Emissions

L2 Peak



Date: 18.JAN.2007 09:23:35

L2 Peak



Date: 18.JAN.2007 09:18:14

Nemko USA, Inc.

EQUIPMENT: LG2400

FCC PART 15, SUBPART C
Digital Transmission Systems
Test Report No.: 2087RUS1

Section 4. Occupied Bandwidth

NAME OF TEST: Occupied Bandwidth	PARA. NO.: 15.247(a)(2)
TESTED BY: David Light	DATE: 14 January 2007

Test Results: Complies.

Measurement Data: See 6 dB BW plot

Measured 6 dB bandwidth:

1.57 MHZ MAXIMUM



Channel Separation:

5 MHz

Test Conditions: 24 %RH
32 °C

Measurement Uncertainty: $\pm 1 \times 10^{-7}$ ppm

Test Equipment Used: 1464-1082-1472


Test Data – Occupied Bandwidth

Nemko USA, Inc.

EQUIPMENT: LG2400

FCC PART 15, SUBPART C
Digital Transmission Systems
Test Report No.: 2087RUS1

Test Data – Occupied Bandwidth



Section 5. Maximum Peak Output Power

NAME OF TEST: Maximum Peak Output power	PARA. NO.: 15.247(b)(3)
TESTED BY: David Light	DATE: 14 January 2007

Test Results: Complies. Highest peak power measured was 21.6 dBm or 144.5 mW



Measurement Data: Refer to attached data

Test Conditions: 24 %RH
32 °C

Measurement Uncertainty: +/-1.7 dB

Test Equipment Used: 1464-1082-1472

- This device was tested at +/- 15% input power per 15.31(e), with no variation in output power.
- For battery powered equipment, the device was tested with a fresh battery per 15.31(e).
- The device was tested on three channels per 15.31(l).
- This test was performed radiated.


Test Data – Peak Power

Nemko USA, Inc.

EQUIPMENT: LG2400

FCC PART 15, SUBPART C
Digital Transmission Systems
Test Report No.: 2087RUS1

Test Data – Peak Power



Nemko USA, Inc.

EQUIPMENT: LG2400

FCC PART 15, SUBPART C
Digital Transmission Systems
Test Report No.: 2087RUS1

Section 6 Spurious Emissions at Antenna Terminals

NAME OF TEST: Spurious Emissions at Antenna Terminals	PARA. NO.: 15.247 (d)
TESTED BY: David Light	DATE: 14 January 2007



Test Results: Complies.



Measurement Data: See attached plots.

Test Conditions: 24 %RH
 32 °C

Measurement Uncertainty: +/-1.7 dB

Test Equipment Used: 1464-1082-1472

Test Data – Spurious Emissions at Antenna Terminals**Lower Band Edge****Low Channel**

Test Data – Spurious Emissions at Antenna Terminals**Mid Channel****High Channel**

Section 7. Radiated Emissions

NAME OF TEST: Radiated Emissions	PARA. NO.: 15.247 (d)
TESTED BY: David Light	DATE: 14 January 2007

Test Results: Complies.**Measurement Data:** See attached table.**Test Conditions:** 24 %RH
32 °C**Measurement Uncertainty:** +/-1.7 dB**Test Equipment Used:** 1464-1484-1485-1016-759-1195-791**Notes:**

- For handheld devices, the EUT was tested on three orthogonal axis'
- The device was tested from 30 MHz to the tenth harmonic of the highest fundamental frequency per 15.33
- The device was tested on three channels per 15.31(l).
- No emissions were detected within 20 dB of the specification limit therefore none are reported per 15.31(o). Band edge data is presented below.
- All emissions within 20 dB of the specification limit are reported.

RBW=VBW=100 kHz below 1000 MHz

RBW=VBW=1 MHz above 1000 MHz (Peak)

RBW= 1 MHz VBW=1 MHz (Average)

All measurements made using PEAK detector function

Radiated Emissions

High Gain Antenna

Frequency (MHz)	Reading (dB μ V)	Cable 1 (dB)	Cable 2 (dB)	Pre-Amp (dB)	Antenna (dB)	Duty Cycle Margin	Corrected (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Polarity
4810.0	50.0	1.0	3.2	32.5	33.1	0.0	54.8	74.0	-19.2	V
4810.0	50.0	1.0	3.2	32.5	33.1	26.1	28.7	54.0	-25.3	V
7215.0	51.5	1.2	3.9	32.1	35.8	0.0	60.3	74.0	-13.7	V
7215.0	51.5	1.2	3.9	32.1	35.8	26.1	34.2	54.0	-19.8	V
4810.0	46.2	1.0	3.2	32.5	33.1	0.0	51.0	74.0	-23.0	H
4810.0	46.2	1.0	3.2	32.5	33.1	26.1	24.9	54.0	-29.1	H
7215.0	45.7	1.2	3.9	32.1	35.8	0.0	54.5	74.0	-19.5	H
7215.0	45.7	1.2	3.9	32.1	35.8	26.1	28.4	54.0	-25.6	H
Lowest Channel										
4880.0	50.3	1.0	3.2	32.5	33.1	0.0	55.1	74.0	-18.9	V
4880.0	50.3	1.0	3.2	32.5	33.1	26.1	29.0	54.0	-25.0	V
7320.0	52.2	1.2	3.9	32.1	35.8	0.0	61.0	74.0	-13.0	V
7320.0	52.2	1.2	3.9	32.1	35.8	26.1	34.9	54.0	-19.1	V
4880.0	47.8	1.0	3.2	32.5	33.1	0.0	52.6	74.0	-21.4	H
4880.0	47.8	1.0	3.2	32.5	33.1	26.1	26.5	54.0	-27.5	H
7320.0	50.3	1.2	3.9	32.1	35.8	0.0	59.1	74.0	-14.9	H
7320.0	50.3	1.2	3.9	32.1	35.8	26.1	33.0	54.0	-21.0	H
Mid Channel										
2483.5	72.8	0.8	2.3	32.8	29.0	0.0	72.1	74.0	-1.9	V
2483.5	72.8	0.8	2.3	32.8	29.0	26.1	46.0	54.0	-8.0	V
4950.0	52.3	1.0	3.2	32.5	33.1	0.0	57.1	74.0	-16.9	V
4950.0	52.3	1.0	3.2	32.5	33.1	26.1	31.0	54.0	-23.0	V
7425.0	52.7	1.2	3.9	32.1	35.8	0.0	61.5	74.0	-12.5	V
7425.0	52.7	1.2	3.9	32.1	35.8	26.1	35.4	54.0	-18.6	V
2483.5	65.0	0.8	2.3	32.8	29.0	0.0	64.3	74.0	-9.7	H
2483.5	65.0	0.8	2.3	32.8	29.0	26.1	38.2	54.0	-15.8	H
4950.0	45.5	1.0	3.2	32.5	33.1	0.0	50.3	74.0	-23.7	H
4950.0	45.5	1.0	3.2	32.5	33.1	26.1	24.2	54.0	-29.8	H
7425.0	51.7	1.2	3.9	32.1	35.8	0.0	60.5	74.0	-13.5	H
7425.0	51.7	1.2	3.9	32.1	35.8	26.1	34.4	54.0	-19.6	H
Highest Channel										



Radiated Emissions

Omni Antenna

Frequency (MHz)	Reading (dB μ V)	Cable 1 (dB)	Cable 2 (dB)	Pre-Amp (dB)	Antenna (dB)	Duty Cycle Margin	Corrected (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Polarity
4810.0	52.2	1.0	3.2	32.5	33.1	0.0	57.0	74.0	-17.0	V
4810.0	52.2	1.0	3.2	32.5	33.1	26.1	30.9	54.0	-23.1	V
7215.0	48.2	1.2	3.9	32.1	35.8	0.0	57.0	74.0	-17.0	V
7215.0	48.2	1.2	3.9	32.1	35.8	26.1	30.9	54.0	-23.1	V
4810.0	47.3	1.0	3.2	32.5	33.1	0.0	52.1	74.0	-21.9	H
4810.0	47.3	1.0	3.2	32.5	33.1	26.1	26.0	54.0	-28.0	H
7215.0	43.2	1.2	3.9	32.1	35.8	0.0	52.0	74.0	-22.0	H
7215.0	43.2	1.2	3.9	32.1	35.8	26.1	25.9	54.0	-28.1	H
Lowest Channel										
4880.0	51.5	1.0	3.2	32.5	33.1	0.0	56.3	74.0	-17.7	V
4880.0	51.5	1.0	3.2	32.5	33.1	26.1	30.2	54.0	-23.8	V
7320.0	50.0	1.2	3.9	32.1	35.8	0.0	58.8	74.0	-15.2	V
7320.0	50.0	1.2	3.9	32.1	35.8	26.1	32.7	54.0	-21.3	V
4880.0	46.3	1.0	3.2	32.5	33.1	0.0	51.1	74.0	-22.9	H
4880.0	46.3	1.0	3.2	32.5	33.1	26.1	25.0	54.0	-29.0	H
7320.0	49.5	1.2	3.9	32.1	35.8	0.0	58.3	74.0	-15.7	H
7320.0	49.5	1.2	3.9	32.1	35.8	26.1	32.2	54.0	-21.8	H
Mid Channel										
2483.5	70.0	0.8	2.3	32.8	29.0	0.0	69.3	74.0	-4.7	V
2483.5	70.0	0.8	2.3	32.8	29.0	26.1	43.2	54.0	-10.8	V
4950.0	50.2	1.0	3.2	32.5	33.1	0.0	55.0	74.0	-19.0	V
4950.0	50.2	1.0	3.2	32.5	33.1	26.1	28.9	54.0	-25.1	V
7425.0	53.7	1.2	3.9	32.1	35.8	0.0	62.5	74.0	-11.5	V
7425.0	53.7	1.2	3.9	32.1	35.8	26.1	36.4	54.0	-17.6	V
2483.5	65.0	0.8	2.3	32.8	29.0	0.0	64.3	74.0	-9.7	H
2483.5	65.0	0.8	2.3	32.8	29.0	26.1	38.2	54.0	-15.8	H
4950.0	45.2	1.0	3.2	32.5	33.1	0.0	50.0	74.0	-24.0	H
4950.0	45.2	1.0	3.2	32.5	33.1	26.1	23.9	54.0	-30.1	H
7425.0	49.0	1.2	3.9	32.1	35.8	0.0	57.8	74.0	-16.2	H
7425.0	49.0	1.2	3.9	32.1	35.8	26.1	31.7	54.0	-22.3	H
Highest Channel										


Radiated Emissions

Duty Cycle



Radiated Emissions

Duty Cycle



4.96 mS Occupancy within 100 mS

Duty cycle = $20 \log (4.96/100) = -26.1 \text{ dB}$

Nemko USA, Inc.

EQUIPMENT: LG2400

FCC PART 15, SUBPART C
Digital Transmission Systems
Test Report No.: 2087RUS1

Section 8. Peak Power Spectral Density

NAME OF TEST: Peak Power Spectral Density	PARA. NO.: 15.247(e)
TESTED BY: David Light	DATE: 14 January 2007



Test Results: Complies.

Measurement Data: See attached data..

Test Conditions: 24 %RH
45 °C

Measurement Uncertainty: +/-1.7 dB

Test Equipment Used: 1464-1082-1472


Peak Power Spectral Density

Nemko USA, Inc.

EQUIPMENT: LG2400

FCC PART 15, SUBPART C
Digital Transmission Systems
Test Report No.: 2087RUS1

Peak Power Spectral Density



Section 9. Test Equipment List

Nemko ID	Description	Manufacturer Model Number	Serial Number	Calibration Date	Calibration Due
1464	Spectrum analyzer	Hewlett Packard 8563E	3551A04428	01/24/07	01/24/09
1082	CABLE 2m	Astrolab 32027-2-29094-72TC	N/A	CBU	N/A
1472	20db Attenuator DC 18 Ghz	Omni Spectra 20600-20db	NONE	CBU	N/A
1484	Cable	Storm PR90-010-072	N/A	10/02/06	10/02/07
1485	Cable	Storm PR90-010-216	N/A	10/02/06	10/02/07
1016	Pre-Amp	HEWLETT PACKARD 8449A	2749A00159	04/20/06	04/20/07
993	Horn antenna	A.H. Systems SAS-200/571	XXX	08/01/05	08/02/07
791	PREAMP, 25dB	Nemko USA, Inc. LNA25	398	04/20/06	04/20/07
759	ANTENNA, LOG PERIODIC	A.H. SYSTEMS SAS-200/510	556	02/13/06	02/13/07
1195	ANTENNA,BICONICAL	A.H. SYSTEMS SAS-200/542	235	02/10/06	02/10/07
1663	Spectrum Analyzer	Rhode & Schwarz FSP	973351	05/18/06	05/18/07
1652	CABLE	Nemko USA, Inc. RG223	NA	03/09/06	03/09/07
704	FILTER, HIGH PASS, 5 KHz	SOLAR 7930-5.0	933126	04/20/06	04/20/07
1188	LISN	EMCO 3825/2	1214	04/19/06	04/19/07
674	LIMITER	HP 11947A	3107A02200	04/19/06	04/19/07

Nemko USA, Inc.

EQUIPMENT: LG2400

FCC PART 15, SUBPART C
Digital Transmission Systems
Test Report No.: 2087RUS1

ANNEX A - TEST DETAILS

NAME OF TEST: Powerline Conducted Emissions	PARA. NO.: 15.207(a)
---	----------------------

Minimum Standard: §15.207 Conducted limits.

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 mH/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of Conducted Emission (MHz)	Limit (dBmV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:

(1) For carrier current systems containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 mV within the frequency band 535-1705 kHz, as measured using a 50 mH/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits as provided in §15.205 and §§15.209, 15.221, 15.223, 15.225 or 15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provision for, the use of battery chargers which permit operating while charging, AC adaptors or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

Nemko USA, Inc.

EQUIPMENT: LG2400

FCC PART 15, SUBPART C
Digital Transmission Systems
Test Report No.: 2087RUS1

NAME OF TEST: Occupied Bandwidth

PARA. NO.: 15.247(a)(2)

Minimum Standard: The minimum 6 dB bandwidth shall be at least 500 kHz

NAME OF TEST: Maximum Peak Output Power**PARA. NO.:** 15.247(b)(3)**Minimum Standard:** The maximum peak output power shall not exceed 1 watt.

If transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Systems operating in the 2400-2483.5 MHz band that are used exclusively for fixed, point to point operation may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum peak output power is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceed 6 dBi.

Systems operating in the 5725 – 5850 MHz band that are used exclusively for fixed, point-to-point operation may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter peak output power.

Direct Measurement Method For Detachable Antennas:

If the antenna is detachable, a peak power meter is used to measure the power output with the transmitter operating into a 50 ohm load. The dBi gain of the antenna(s) employed shall be reported.

Substitution Antenna Method for Integral Antennas:

The peak field strength of the carrier is measured in a worst-case configuration with a RBW > 5 times the occupied bandwidth of the transmitted waveform. For cases where the RBW of the test instrument is not sufficient, the power is measured using a peak power meter instead of the spectrum analyzer.

The RBW of the spectrum analyzer shall be set to a value greater than the measured 6 dB occupied bandwidth of the E.U.T.

Number of channels tested:

Tuning range	Number of channels tested	Channel location in band
1 MHz or less	1	middle
1 to 10 MHz	2	top and bottom
more than 10 MHz	3	top, middle, bottom

NAME OF TEST: Occupied Bandwidth

PARA. NO.: 15.247(a)(2)

Minimum Standard: Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Method Of Measurement:

The spectrum analyzer is set as follows:

RBW = VBW = 100 kHz.

Span: Sufficient to display 6 dB bandwidth

LOG dB/div.: 10 dB

Sweep: Auto

Number of channels tested:

Tuning range	Number of channels tested	Channel location in band
1 MHz or less	1	middle
1 to 10 MHz	2	top and bottom
more than 10 MHz	3	top, middle, bottom

NAME OF TEST: Spurious Emissions(conducted)	PARA. NO.: 15.247(d)
---	----------------------

Minimum Standard: In any 100kHz bandwidth outside the frequency band in which the transmitter is operating, emissions shall be at least 20 dB below the fundamental emission or shall not exceed the following field strength limits. Emissions falling in the restricted bands of 15.205 shall not exceed the following field strength limits:

Frequency (MHz)	Field Strength (μ V/m @ 3m)	Field Strength (dB @ 3m)
30 - 88	100	40.0
88 - 216	150	43.5
216 - 960	200	46.0
Above 960	500	54.0

THE SPECTRUM IS SEARCHED TO THE 10th HARMONIC OF THE HIGHEST FREQUENCY GENERATED IN THE EUT.

Method Of Measurement:30 MHz - 10th harmonic plot

RBW: 100 kHz

VBW: 300 kHz

Sweep: Auto

Display line: -20 dBc

Lower Band Edge

RBW: At least 1% of span/div.

VBW: >RBW

Span: As necessary to display any spurious at band edge.

Sweep: Auto

Center Frequency: 902 MHz, 2400 MHz, or 5725 MHz

Marker: Peak of fundamental emission

Marker Δ: Peak of highest spurious level below center frequency.

Upper Band Edge

RBW: At least 1% of span/div.

VBW: >RBW

Span: As necessary to display any spurious at band edge.

Sweep: Auto

Center Frequency: 928 MHz, 2483.5 MHz, or 5850 MHz

Marker: Peak of fundamental emission

Marker Δ: Peak of highest spurious level above center frequency.

Number of channels tested:

Tuning range	Number of channels tested	Channel location in band
1 MHz or less	1	middle
1 to 10 MHz	2	top and bottom
more than 10 MHz	3	top, middle, bottom

NAME OF TEST: Radiated Spurious Emissions**PARA. NO.:** 15.247(c)

Minimum Standard: In any 100kHz bandwidth outside the frequency band in which the transmitter is operating, emissions shall be at least 20 dB below the fundamental emission or shall not exceed the following field strength limits:

Emissions falling in the restricted bands of 15.205 shall not exceed the following field strength limits:

Frequency (MHz)	Field Strength (μ V/m @ 3m)	Field Strength (dB @ 3m)
30 - 88	100	40.0
88 - 216	150	43.5
216 - 960	200	46.0
Above 960	500	54.0

THE SPECTRUM WAS SEARCHED TO THE 10th HARMONIC

15.205 Restricted Bands

MHz	MHz	MHz	GHz
0.09-0.11	16.42-16.423	399.9-410	4.5-5.25
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.125-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2655-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41	1718		

Number of channels tested:

Tuning range	Number of channels tested	Channel location in band
1 MHz or less	1	middle
1 to 10 MHz	2	top and bottom
more than 10 MHz	3	top, middle, bottom

NAME OF TEST: Transmitter Power Density**PARA. NO.:** 15.247(d)

Minimum Standard: The transmitted power density averaged over any 1 second interval shall not be greater than +8 dBm in any 3 kHz bandwidth.

Method Of Measurement: The spectrum analyzer is set as follows:

RBW: 3 kHz
VBW: >3 kHz
Span: => measured 6 dB bandwidth
Sweep: Span(kHz)/3 (i.e. for a span of 1.5 MHz the sweep rate is 1500/3 = 500 sec.
LOG dB/div.: 2 dB

Note: For devices with spectrum line spacing =< 3 kHz, the RBW of the analyzer is reduced until the spectral lines are resolved. The measurement data is normalized to 3 kHz by summing the power of all the individual spectral lines within a 3 kHz band in linear power units.

For Devices With Integral Antenna:

For devices with non-detachable antennas, the received field strength is peaked and the spectrum analyzer is set as above. The peak emission level is then measured and converted to a field strength by adding the appropriate antenna factor and cable loss. This field strength is then converted to an equivalent isotropic radiated power using the same method as described for Peak Power output.

Number of channels tested:



Tuning Range	Number Of Channels Tested	Channel Location In Band
1 MHz or Less	1	Middle
1 to 10 MHz	2	Top And Bottom
More Than 10 MHz	3	Top, Middle, Bottom


Nemko USA, Inc.

EQUIPMENT: LG2400

FCC PART 15, SUBPART C
Digital Transmission Systems
Test Report No.: 2087RUS1

ANNEX B - TEST DIAGRAMS

Test Site For Radiated Emissions**Conducted Emissions**

Peak Power At Antenna Terminals

Note: A spectrum analyzer may be substituted for Peak Power Meter given that the measurement bandwidth is sufficient to capture the 60 dB bandwidth of the transmitter.

**Minimum 6 dB Bandwidth
Peak Power Spectral Density
Spurious Emissions (conducted)**