



400 W. Cesar Chavez
Austin
TX 78701
USA

29th of April 2016

Analysis for FCC portable use

Standalone SAR test exclusion considerations are defined in KDB 447498D01 (v06) Chapter 4.3.1 where the 1-g head or body and 10-g extremity SAR exclusion threshold is defined by the following formula:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

For the S4GEM358X module the maximum conducted output power is 9.0 dBm (7.94mW)


Applying the above data using the given KDB 447498 D01 formula, and minimum separation distance of 5mm, the following results:

$$(7.94 \text{ mW} / 5 \text{ mm}) \times \sqrt{2.43 \text{ GHz}} = 2.48$$

(i.e.: ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR)

Conclusion

This demonstrates the S4GEM358X module meets the criteria for 1-g head/ body and 10-g extremity SAR test exemption.

Signature:  Date: 29. April 2016