

APPENDIX 2: Data of DFS test

Parameter Data for Radar Type 5

Trial Number	Burst	Number of Pulses	Pulse Width (usec)	Chirp Width (MHz)	Pulse 1-to-2 Spacing (usec)	Pulse 2-to-3 Spacing (usec)	Starting Location Within Interval (usec)
1	1	3	60	10	1763	1600	198588
1	2	1	85	14			939907
1	3	2	73	16	1526		159373
1	4	3	57	13	1589	1695	485730
1	5	1	58	9			286346
1	6	1	97	18			834461
1	7	3	76	18	1289	1949	706862
1	8	1	76	11			911400
1	9	2	84	15	1543		57309
1	10	3	92	14	1401	1440	898873

APPENDIX 3:Test instruments

EMI Test Equipment

Control No.	Instrument	Manufacturer	Model No	Test Item	Calibration Date * Interval(month)
MOS-14	Thermo-Hygrometer	Custom	CTH-180	DFS	2006/01/19 * 24
MSG-05	Signal Generator	Agilent	E4438C	DFS	2007/06/20 * 12
MSA-10	Spectrum Analyzer	Agilent	E4448A	DFS	2007/07/04 * 12
MPSC-02	Power Splitters/Combiners	Mini-Circuit	ZFSC-2-10G	DFS	2006/09/25 * 12
MPSC-04	Power Splitters/Combiners	Mini-Circuit	ZFSC-2-10G	DFS	2007/01/17 * 12
MPD-01	PowerDivider DC to 26.5GHz	Agilent	11636B	DFS	2007/03/16 * 12
MCC-65	Microwave Cable 1G-40GHz	Schner	SUCOFLEX102	DFS	2007/04/03 * 12
MCC-66	Microwave Cable 1G-40GHz	Schner	SUCOFLEX102	DFS	2007/04/03 * 12
MCC-36	Microwave Cable	Hirose Electric	U.FL-2LP-066-A-(200)	DFS	2006/11/13 * 12
MCC-37	Microwave Cable	Hirose Electric	U.FL-2LP-066-A-(200)	DFS	2006/11/13 * 12
MAT-22	Attenuator(10dB) DC-18GHz	Orient Microwave	BX10-0476-00	DFS	2007/03/07 * 12
MAT-23	Attenuator(10dB) DC-18GHz	Orient Microwave	BX10-0476-00	DFS	2007/03/07 * 12
MAT-37	Attenuator(10dB)1-40GHz	Weinschel	54A-10	DFS	2006/12/12 * 12
MAT-38	Attenuator(10dB)1-40GHz	Weinschel	54A-10	DFS	2006/12/12 * 12
MAT-39	Attenuator(20dB)1-40GHz	Weinschel	54A-20	DFS	2006/12/12 * 12
MAT-40	Attenuator(20dB)1-40GHz	Weinschel	54A-20	DFS	2006/12/12 * 12
MTA-24	Terminator	Weinschel	M1459A	DFS	2006/12/13 * 12
MTA-25	Terminator	Weinschel	M1459A	DFS	2006/12/13 * 12
MSTW-30	Signal Studio Software for DFS	Agilent	N7620A-101	DFS	-
MSTW-31	Radar Generating Software for DFS	Agilent	-	DFS	-

The expiration date of the calibration is the end of the expired month.

All equipment is calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

Test Item:

DFS: Dynamic Frequency Selection

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124