

RF Exposure Report

Report No.: SABURR-WTW-P21040075

FCC ID: S4L4FIC1

Contains module FCC ID: QIPELS61-US

Test Model: 4FIC1

Series Model: 4FIC0

Received Date: May 26, 2021

Test Date: Jun. 01 ~ Jun. 03, 2021

Issued Date: Jun. 16, 2021

Applicant: TomTom International B.V.

Address: De Ruijterkade 154, 1011 AC Amsterdam The Netherlands

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location (1): No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, TAIWAN

Test Location (2): B2F., No.215, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231,
Taiwan

FCC Registration / 788550 / TW0003
Designation Number (1):

FCC Registration / 427177 / TW0011
Designation Number (2):



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

| | |
|--|----------|
| Release Control Record | 3 |
| 1 Certificate of Conformity | 4 |
| 2 RF Exposure | 5 |
| 2.1 Limits for Maximum Permissible Exposure (MPE)..... | 5 |
| 2.2 MPE Calculation Formula | 5 |
| 2.3 Classification | 5 |
| 3 Calculation Result of Maximum Conducted Power | 6 |

Release Control Record

| Issue No. | Description | Date Issued |
|----------------------|------------------|---------------|
| SABURR-WTW-P21040075 | Original release | Jun. 16, 2021 |

1 Certificate of Conformity

Product: TomTom BRIDGE Hub

Brand: TOMTOM

Test Model: 4FIC1

Series Model: 4FIC0

Sample Status: Pre-MFB build sample

Applicant: TomTom International B.V.

Test Date: Jun. 01 ~ Jun. 03, 2021

Standards: FCC Part 2 (Section 2.1091)

References Test Guidance: KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Celine Chou , **Date:** Jun. 16, 2021
Celine Chou / Senior Specialist

Approved by : Bruce Chen , **Date:** Jun. 16, 2021
Bruce Chen / Senior Project Engineer

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Average Time (minutes) |
|---|-------------------------------|-------------------------------|-------------------------------------|------------------------|
| Limits For General Population / Uncontrolled Exposure | | | | |
| 300-1500 | ... | ... | F/1500 | 30 |
| 1500-100,000 | ... | ... | 1.0 | 30 |

F = Frequency in MHz

2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

3 Calculation Result of Maximum Conducted Power

For WLAN, BT and BT LE:

| Function | Frequency Band (MHz) | Max AV Power (dBm) | Antenna Gain (dBi) | Distance (cm) | Power Density (mW/cm ²) | Limit (mW/cm ²) |
|----------|----------------------|--------------------|--------------------|---------------|-------------------------------------|-----------------------------|
| WLAN | 2412-2462 | 14.82 | 1.69 | 20 | 0.0089 | 1 |
| | 5180-5240 | 12.90 | 3.11 | 20 | 0.0079 | 1 |
| | 5260-5320 | 12.91 | 3.11 | 20 | 0.0080 | 1 |
| | 5500-5700 | 12.92 | 3.11 | 20 | 0.0080 | 1 |
| | 5745-5825 | 12.88 | 3.11 | 20 | 0.0079 | 1 |
| BT EDR | 2402-2480 | 2.14 | 1.69 | 20 | 0.0005 | 1 |
| BT LE | 2402-2480 | 0.14 | 1.69 | 20 | 0.0003 | 1 |

Note:

1. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
2. The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

For WWAN: (Base on WWAN module report (model no.: ELS61-US, brand name: GEMALTO, FCC ID: QIPELS61-US))

| Function | Frequency Band (MHz) | Max Power (dBm) | Antenna Gain (dBi) | Distance (cm) | Power Density (mW/cm ²) | Limit (mW/cm ²) |
|--------------|----------------------|-----------------|--------------------|---------------|-------------------------------------|-----------------------------|
| WCDMA Band 2 | 1850-1910 | 21.53 | -5.00 | 20 | 0.0089 | 1 |
| WCDMA Band 4 | 1710-1755 | 21.48 | -5.00 | 20 | 0.0088 | 1 |
| WCDMA Band 5 | 824-849 | 23.93 | -5.00 | 20 | 0.0155 | 0.549 |
| LTE Band 2 | 1850-1910 | 20.95 | -5.00 | 20 | 0.0078 | 1 |
| LTE Band 4 | 1710-1755 | 20.96 | -5.00 | 20 | 0.0078 | 1 |
| LTE Band 5 | 824-849 | 23.12 | -5.00 | 20 | 0.0129 | 0.549 |
| LTE Band 12 | 698-716 | 23.26 | -5.00 | 20 | 0.0133 | 0.465 |

Note:

1. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
2. The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

Conclusion:

WLAN (2.4GHz or 5GHz), BT (BT EDR or BT LE) and WWAN technology can transmit simultaneously.

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

$WLAN\ 2.4GHz + BT + WWAN = 0.0089 / 1 + 0.0005 / 1 + 0.0133 / 0.465 = 0.038$

Therefore the maximum calculations of above situations are less than the "1" limit.

---END---