

Maximum Permissible Exposure (MPE)

Evaluation Report

Product : GPS Navigation System

Model Number : DUB1

According : FCC Guidelines for Human Exposure IEEE C95.1

Applicant : TomTom International BV.

Address : Rembrandtplein 35 1017 CT Amsterdam The Netherlands

Issued By : Interocean EMC Technology Corp.

LAB Location : 244 No.5-2, Lin 1, Tin-Fu Tsun, Lin-Kou Hsiang, Taipei
County, Taiwan, R.O.C.

The test report consists of **5** pages in total. It shall not be reproduced except in full, without the written approval of IETC. This document may be altered or revised by IETC only, and shall be noted in the revision section of the document. The test results in the report only to the tested sample.

Report Issued : 2008/11/19

Project Engineer : Anya Lee
Anya Lee

Approved :

Jerry Liu
Jerry Liu

Table of Contents

| | | |
|----------|--------------------------------|----------|
| 1 | Introduction | 4 |
| 2 | Classification | 4 |
| 3 | RF Exposure Limit | 4 |
| 4 | Friis Formula | 5 |
| 5 | EUT Operating condition | 5 |
| 6 | Test Results | 5 |

Summary of Tests

GPS Navigation System DUB1

| Test | Reference | Results |
|----------------|--|---------|
| MPE Evaluation | FCC Guidelines for Human Exposure IEEE C95.1 | Pass |

RF Exposure Measurement (Fixed use Device)

1 Introduction

2.4GHz frequency band is regarded specially as a dangerous band for its heating harmfulness to the human body. That's why microwave oven is operating in this frequency band. The manufacturer whose product is working in this frequency band is obligatory to prove the harmfulness of his product.

In this document, we try to prove the safety of radiation harmfulness to the human body for our product. The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The Gain of the antenna used in this product is measured in a Fully Anechoic Chamber (FAC), and the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

2 Classification

The antenna of the product, under normal use condition, is at least 20cm away from the body of the user. Warning statement for keeping 20cm separation distance and the prohibition of operating next to a person has been printed on the user's manual. So, this product is classified as the Fixed use Device

3 RF Exposure Limit

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b).

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Average Time (minutes) |
|--|-------------------------------|-------------------------------|-------------------------------------|------------------------|
| (A) Limits For Occupational / Control Exposures | | | | |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1500 | ... | ... | F/300 | 6 |
| 1500-100,000 | ... | ... | 5 | 6 |
| (B) Limits For General Population / Uncontrolled Exposure | | | | |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | ... | ... | F/500 | 30 |
| 1500-100,000 | ... | ... | 1.0 | 30 |

F = Frequency in MHz

4 Friis Formula

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

$\pi = 3.1416$

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum Gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

5 EUT Operating condition

The software provided by Manufacturer enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

6 Test Results

| Frequency (MHz) | Maximum Antenna gain (numeric) | Output power To antenna (mW) | Power density (mW/cm ²) | Limit of Power density (mW/cm ²) |
|------------------|--------------------------------|------------------------------|-------------------------------------|--|
| 2402 to 2480 MHz | 1.58 | 0.9226 | 0.000290 | 1.0 |

The minimum allowable distance is very close to the enclosure of the antenna. So, the user has no need to worry about the harmfulness of radiation. But it is recommended to always keep, at least, 20cm separation distance with the antenna.