



FCC 47 CFR PART 15 SUBPART C

TEST REPORT

For

GPS Tracking System

Model: TomTom ONE New Edition

Trade Name: tomtom

Prepared for

TomTom BV

Rembrandtplein 35, 1017 CT Amsterdam, The Netherlands

Issued by

COMPLIANCE CERTIFICATION SERVICES (KUNSHAN) INC.

10#Weiye Rd, Innovation Park Eco. & Tec. Development Zone

Kunshan city JiangSu, (215300) CHINA



Lab. Code: 200581-0

TEL: 86-512-57355888

FAX: 86-512-57370818

Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document.



TABLE OF CONTENTS

1. TEST RESULT CERTIFICATION.....	3
2. EUT DESCRIPTION	4
3. TEST METHODOLOGY	5
3.1 EUT CONFIGURATION	5
3.2 EUT EXERCISE.....	5
3.3 GENERAL TEST PROCEDURES.....	5
3.4 MODIFICATION	5
3.5 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS.....	6
3.6 DESCRIPTION OF TEST MODES	6
4. INSTRUMENT CALIBRATION.....	7
5. FACILITIES AND ACCREDITATIONS	8
5.1 FACILITIES8	
5.2 EQUIPMENT.....	8
5.3 LABORATORY ACCREDITATIONS AND LISTING.....	8
TABLE OF ACCREDITATIONS AND LISTINGS	9
6. SETUP OF EQUIPMENT UNDER TEST	10
6.1 SETUP CONFIGURATION OF EUT.....	10
6.2 SUPPORT EQUIPMENT	10
7. FCC PART 15.247 REQUIREMENTS.....	11
7.1 PEAK POWER.....	11
7.2 BAND EDGES MEASUREMENT	12
7.3 PEAK POWER SPECTRAL DENSITY	18
7.4 FREQUENCY SEPARATION.....	21
7.5 NUMBER OF HOPPING FREQUENCY.....	23
7.6 TIME OF OCCUPANCY (DWELL TIME)	25
7.7 RADIO FREQUENCY EXPOSURE	32
7.8 SPURIOUS EMISSIONS.....	33
7.9 POWERLINE CONDUCTED EMISSIONS.....	44
APPENDIX 1 PHOTOGRAPHS OF TEST SETUP	48



1. TEST RESULT CERTIFICATION

Applicant: TomTom BV
Rembrandtplein 35, 1017 CT Amsterdam, The Netherlands

Equipment Under Test: GPS Tracking System

Trade Name: tomtom

Model: TomTom ONE New Edition

Date of Test: From August 2, 2006 to August 11, 2006

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 15 Subpart C	No non-compliance noted


We here by certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

Approved by:

Reviewed by:



Tony Houn
General Manager of Kunshan Laboratory
Compliance Certification Services Inc.



Miro Chueh
Section Manager of Kunshan Laboratory
Compliance Certification Services Inc.



2. EUT DESCRIPTION

Product	GPS Tracking System
Trade Name	tomtom
Model Number	TomTom ONE New Edition
Model Discrepancy	All the above models are identical except the model designation.
Wireless LAN module Model Number	BC41B143A
Wireless LAN module Brand name	CSR
Power Supply	Trade Name : PHIHONG Model Number: PSB05R-050Q Input: AC 100-240V, 0.2A, 50-60Hz DC 5V, 1.0A
Frequency Range	2402 ~ 2480 MHz
Transmit Power	0.82 dBm
Modulation Technique	FHSS
Transmit Data Rate	1Mbps
Number of Channels	79 Channels
Antenna Specification	Chip Antenna / Gain: 0.77 dBi

Remark: This submittal(s) (test report) is intended for FCC ID: S4LONE-ED filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.



3. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4 and FCC CFR 47 2.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055, 2.1057, 15.207, 15.209 and 15.247.

3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

3.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

3.3 GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4.

3.4 MODIFICATION

N/A

3.5 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

- (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	(²)
13.36 - 13.41	322 - 335.4		

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

- (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

3.6 DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition.

Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz, which worst case was in normal link mode only.

Channel Low (2402MHz) 、 Mid (2441MHz) and High (2480MHz) were chosen for full testing.



4. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.



5. FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at CCS China Kunshan Lab at 10#Weiye Rd, Innovation Park Eco. & Tec. Development Zone Kunshan city JiangSu, (215300), CHINA.

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5.3 LABORATORY ACCREDITATIONS AND LISTING

The test facilities used to perform radiated and conducted emissions tests are accredited by National Voluntary Laboratory Accreditation Program for the specific scope of accreditation under Lab Code: 200581-0 to perform Electromagnetic Interference tests according to FCC PART 15 AND CISPR 22 requirements. No part of this report may be used to claim or imply product endorsement by NVLAP or any agency of the US Government. In addition, the test facilities are listed with Federal Communications Commission (Registration no: 93105 and 90471).

**TABLE OF ACCREDITATIONS AND LISTINGS**

Country	Agency	Scope of Accreditation	Logo
USA	NVLAP	EN 55022, EN 61000-3-2, EN 61000-3-3, EN550024, EN 61000-4-2, EN 61000-4-3, EN61000-4-4, EN 61000-4-5, EN 61000-4-6, IEC 61000-4-8, EN 61000-4-11 ANSI C63.4, CISPR16-1, IEC61000-3-2, IEC61000-3-3, IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, IEC 61000-4-8, IEC 61000-4-11	 Lab. Code: 200581-0
USA	FCC	3/10 meter Sites to perform FCC Part 15/18 measurements	 93105, 90471
Japan	VCCI	3/10 meter Sites and conducted test sites to perform radiated/conducted measurements	VCCI R-1600 C-1707
Norway	NEMKO	EN61000-6-1/2/3/4, EN 50082-1/2, IEC 61000-6-1/2/3/4, EN 50091-2, EN 55011, EN 55022, EN 55024, EN 61000-3-2/3, EN 61000-11, IEC 61000-4-2/3/4/5/6/8/11, CISPR16-1/2/3/4	 ELA 105

** No part of this report may be used to claim or imply product endorsement by NVLAP or any agency of the US Government.*



6. SETUP OF EQUIPMENT UNDER TEST

6.1 SETUP CONFIGURATION OF EUT

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

6.2 SUPPORT EQUIPMENT

No	Equipment	Model	Serial No.	FCC ID	Trade Name	Data Cable	Power Cord
1	SD card	128MB	N/A	DoC	Kingston	N/A	N/A

Remark:

- 1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.*
- 2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.*



7. FCC PART 15.247 REQUIREMENTS

7.1 PEAK POWER

LIMIT

The maximum peak output power of the intentional radiator shall not exceed the following:


1. For systems using digital modulation in the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz: 1 watt.
2. Except as shown in paragraphs (b)(3) (i), (ii) and (iii) of this section, if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	11/16/2006
Peak and Avg Power Sensor	Agilent	E9327A	US40441788	07/29/2007
EPM-P Series Power Meter	Agilent	E4416A	QB41292714	07/29/2007

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

The transmitter output is connected to the Power Meter.

TEST RESULTS

No non-compliance noted

Test Data

Channel	Frequency (MHz)	Reading Power (dBm)	Factor (dB)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2402	-1.86	1.50	-0.36	0.00092	1	PASS
Mid	2441	-0.68	1.50	0.82	0.00121		PASS
High	2480	-1.15	1.50	0.35	0.00108		PASS

7.2 BAND EDGES MEASUREMENT

LIMIT


According to §15.247(c), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

MEASUREMENT EQUIPMENT USED

977 Chamber (3m)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	11/16/2006
Pre-Amplifier	Miteq	NSP4000-NF	870731	01/21/2007
Horn Antenna	Austriah	BBHA9120D	D267	02/03/2007
Turn Table	CT	CT123	4162	N.C.R
Antenna Tower	CT	CTERG23	3253	N.C.R
Controller	CT	CT100	95635	N.C.R
Coax Switch	Anitsu	MP 598	M 80094	N/A
Site NSA	CCS Lab.	N/A	N/A	02/15/2007

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8m above the ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out



the highest emission.

4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
 - (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.

TEST RESULTS

CH LOW

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Peak Margin (dB)	AV Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)				
2390.00	V	41.79	30.49	4.80	46.59	35.29	74	54	-27.41	-18.71
	V									
2390.00	H	40.20	30.44	4.80	45.00	35.24	74	54	-29.00	-18.76
	H									

CH HIGH

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Peak Margin (dB)	AV Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)				
2483.50	V	41.00	30.12	4.80	45.80	34.92	74	54	-28.20	-19.08
	V									
2483.50	H	42.29	30.71	4.80	47.09	35.51	74	54	-26.91	-18.49
	H									

Refer to attach spectrum analyzer data chart.




Band Edges (CH Low)

Detector mode: Peak

Polarity: Vertical


Agilent 15:29:53 Aug 5, 2006



Detector mode: Average

Polarity: Vertical

Agilent 15:40:21 Aug 5, 2006






Detector mode: Peak

Polarity: Horizontal


Agilent 15:42:53 Aug 5, 2006



Detector mode: Average


Polarity: Horizontal

Agilent 15:43:38 Aug 5, 2006




**Band Edges (CH High)****Detector mode: Peak****Polarity: Vertical**

Agilent 15:55:13 Aug 5, 2006

**Detector mode: Average****Polarity: Vertical**

Agilent 15:55:39 Aug 5, 2006






Detector mode: Peak

Polarity: Horizontal

Agilent 15:52:02 Aug 5, 2006




Marker			
Select Marker			
<u>1</u>	2	3	4
Normal			
Delta			
Delta Pair (Tracking Ref)			
Ref	▲		
Span Pair			
Span	<u>Center</u>		
Off			
More 1 of 2			

File Operation Status, A:\SCREN092.GIF file saved

Detector mode: Average

Polarity: Horizontal

Agilent 15:52:29 Aug 5, 2006



Marker			
Select Marker			
<u>1</u>	2	3	4
Normal			
Delta			
Delta Pair (Tracking Ref)			
Ref	▲		
Span Pair			
Span	<u>Center</u>		
Off			
More 1 of 2			

File Operation Status, A:\SCREN093.GIF file saved



7.3 PEAK POWER SPECTRAL DENSITY

LIMIT


1. For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.
2. The direct sequence operating of the hybrid system, with the frequency hopping operation turned off, shall comply with the power density requirements of paragraph (d) of this section.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	11/16/2006

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW = 3kHz, VBW = 10kHz, Span = 300kHz, Sweep=100s
4. Record the max. reading.
5. Repeat the above procedure until the measurements for all frequencies are completed.

TEST RESULTS


No non-compliance noted

Test Data


Channel	Frequency	Reading (dBm)	Factor (dB)	PPSD (dBm)	Limit (dBm)	Result
Low	2402	-7.26	1.50	-5.76	8.00	PASS
Mid	2441	-5.68	1.50	-4.18		PASS
High	2480	-6.10	1.50	-4.60		PASS

**Test Plot****PPSD (CH Low)**

Agilent 14:56:40 Aug 3, 2006

**PPSD (CH Mid)**


Agilent 14:58:33 Aug 3, 2006





PPSD (CH High)

Agilent 15:00:11 Aug 3, 2006





7.4 FREQUENCY SEPARATION

LIMIT


According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	11/16/2006

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = middle of hopping channel.
4. Set the spectrum analyzer as RBW = 30kHz, VBW = 100kHz, Span = 3MHz, Sweep = auto.
5. Max hold, mark 2 peaks of hopping channel and record the 2 peaks frequency.

TEST RESULTS

No non-compliance noted

Test Data


Channel Separation (MHz)	20dB Bandwidth (kHz)	Limit (kHz)	Result
1.015	1080	>25	Pass



Test Plot

Measurement of Channel Separation


* Agilent 15:20:07 Aug 3, 2006



Copyright 2000-2003 Agilent Technologies

Measurement of 20dB Bandwidth

* Agilent 13:27:48 Aug 5, 2006



Unable to save file



7.5 NUMBER OF HOPPING FREQUENCY

LIMIT


According to §15.247(a)(1)(ii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands shall use at least 75 hopping frequencies.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	11/16/2006

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set spectrum analyzer Start=2400MHz, Stop = 2441.5MHz, Sweep = auto and Start=2441.5MHz, Stop = 2483.5MHz, Sweep = auto.
4. Set the spectrum analyzer as RBW, VBW=100kHz.
5. Max hold, view and count how many channel in the band.

TEST RESULTS


No non-compliance noted

Test Data


Result (No. of CH)	Limit (No. of CH)	Result
79	>75	PASS

**Test Plot****Channel Number****2.4 GHz – 2.4415 GHz**

Agilent 20:23:51 Aug 5, 2006

**2.4415 GHz – 2.4835 GHz**

Agilent 20:28:56 Aug 5, 2006





7.6 TIME OF OCCUPANCY (DWELL TIME)

LIMIT


According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands. The average time of occupancy on any channels shall not greater than 0.4 s within a period 0.4 s multiplied by the number of hopping channels employed.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	11/16/2006

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = operating frequency.
4. Set the spectrum analyzer as RBW, VBW=1MHz, Span = 0Hz, Sweep = auto.
5. Repeat above procedures until all frequency measured were complete.



TEST RESULTS

No non-compliance noted

Test Data

DH 1

CH Low: $0.40 * (1600/2)/79 * 31.6 = 128.00$ (ms)

CH Mid: $0.43 * (1600/2)/79 * 31.6 = 137.00$ (ms)

CH High: $0.43 * (1600/2)/79 * 31.6 = 137.60$ (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Low	0.40	128.00	31.60	400.00	PASS
Mid	0.43	137.00	31.60		PASS
High	0.43	137.60	31.60		PASS

DH 3

CH Low: $1.70 * (1600/4)/79 * 31.6 = 272.00$ (ms)

CH Mid: $1.70 * (1600/4)/79 * 31.6 = 272.00$ (ms)

CH High: $1.67 * (1600/4)/79 * 31.6 = 267.20$ (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Low	1.70	272.00	31.60	400.00	PASS
Mid	1.70	272.00	31.60		PASS
High	1.67	267.20	31.60		PASS

DH 5

CH Low: $2.93 * (1600/6)/79 * 31.6 = 312.53$ (ms)


CH Mid: $2.93 * (1600/6)/79 * 31.6 = 312.53$ (ms)

CH High: $2.93 * (1600/6)/79 * 31.6 = 312.53$ (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Low	2.93	312.53	31.60	400.00	PASS
Mid	2.93	312.53	31.60		PASS
High	2.93	312.53	31.60		PASS

**Test Plot****DH 1****(CH Low)**


* Agilent 16:03:36 Aug 3, 2006



Copyright 2000-2003 Agilent Technologies

(CH Mid)


* Agilent 16:05:16 Aug 3, 2006



Copyright 2000-2003 Agilent Technologies

**(CH High)**

* Agilent 16:07:35 Aug 3, 2006




Marker			
Select Marker			
1	2	3	4
Normal			
Delta			
Delta Pair (Tracking Ref)			
Ref	▲		
Span Pair			
Span	Center		
Off			
More 1 of 2			

Copyright 2000-2003 Agilent Technologies

DH 3**(CH Low)**

* Agilent 16:13:47 Aug 3, 2006




Marker			
Select Marker			
1	2	3	4
Normal			
Delta			
Delta Pair (Tracking Ref)			
Ref	▲		
Span Pair			
Span	Center		
Off			
More 1 of 2			

Copyright 2000-2003 Agilent Technologies

**(CH Mid)**


* Agilent 16:12:06 Aug 3, 2006



Copyright 2000-2003 Agilent Technologies

(CH High)


* Agilent 16:10:05 Aug 3, 2006




File Operation Status, A:\SCREN050.GIF file saved

**DH 5****(CH Low)**

* Agilent 16:14:51 Aug 3, 2006

**(CH Mid)**


* Agilent 16:17:08 Aug 3, 2006





(CH High)

Agilent 16:18:14 Aug 3, 2006



Marker			
Select Marker			
1	2	3	4
Normal			
Delta			
Delta Pair (Tracking Ref)			
Ref	Δ		
Span Pair			
Span	Center		
Off			
More 1 of 2			

Copyright 2000-2003 Agilent Technologies



7.7 RADIO FREQUENCY EXPOSURE

LIMIT

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See §15.247(b)(4) and §1.1307(b)(1) of this chapter.

EUT Specification

EUT	GPS Tracking System
Frequency band (Operating)	☐ WLAN: 2.412GHz ~ 2.462GHz ☐ WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz ☐ WLAN: 5.745GHz ~ 5.825GHz ☒ Others: <u>Bluetooth: 2.402GHz ~ 2.480GHz</u>
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation) ☐ Others
Exposure classification	☐ Occupational/Controlled exposure ($S = 5mW/cm^2$) ☒ General Population/Uncontrolled exposure ($S=1mW/cm^2$)
Antenna diversity	☒ Single antenna ☐ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Max. output power	0.82dBm (1.208mW)
Antenna gain (Max)	0.77 dBi (Numeric gain: 1.194mW)
Evaluation applied	☐ MPE Evaluation ☐ SAR Evaluation ☒ N/A

Remark:

1. The maximum output power is 0.82dBm (1.208mW) at 2441MHz (with 1.194 numeric antenna gain.)
2. DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance.
3. For mobile or fixed location transmitters, no SAR consideration applied. The minimum separation generally be used is at least 20 cm, even if the calculations indicate that the MPE distance would be lesser.

TEST RESULTS

Non-compliance.



7.8 SPURIOUS EMISSIONS

7.8.1 Conducted Measurement

LIMIT


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	11/16/2006

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 KHz. The video bandwidth is set to 100 KHz.


Measurements are made over the 30MHz to 26GHz range with the transmitter set to the lowest, middle, and highest channels.

TEST RESULTS

No non-compliance noted

**Test Plot****CH Low****30MHz ~ 2.9GHz**

* Agilent 14:15:28 Aug 5, 2006




Marker			
Select Marker			
1	2	3	4
Normal			
Delta			
Delta Pair (Tracking Ref)			
Ref Δ			
Span Pair			
Span Center			
Off			
More 1 of 2			

Copyright 2000-2003 Agilent Technologies

2.9GHz ~ 26.5GHz

* Agilent 14:19:42 Aug 5, 2006




Marker			
Select Marker			
1	2	3	4
Normal			
Delta			
Delta Pair (Tracking Ref)			
Ref Δ			
Span Pair			
Span Center			
Off			
More 1 of 2			


Copyright 2000-2003 Agilent Technologies

**CH Mid****30MHz ~ 2.9GHz**

* Agilent 14:23:36 Aug 5, 2006


**2.9GHz ~ 26.5GHz**

* Agilent 14:26:37 Aug 5, 2006



**CH High****30MHz ~ 2.9GHz**

Agilent 14:28:36 Aug 5, 2006




Display
Full Screen
Display Line 86.91 dB μ V On Off
Limits
Active Fctn Position Top
Title
Preferences

Copyright 2000-2003 Agilent Technologies

2.9GHz ~ 26.5GHz

Agilent 14:32:03 Aug 5, 2006



Marker
Select Marker 1 2 3 4
Normal
Delta
Delta Pair (Tracking Ref) Ref Δ
Span Pair Span Center
Off
More 1 of 2

Copyright 2000-2003 Agilent Technologies



7.8.2 Radiated Emissions

LIMIT

1. Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (mV/m)	Measurement Distance (m)
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3

Remark: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

2. In the above emission table, the tighter limit applies at the band edges.

Frequency (Hz)	Field Strength (μ V/m at 3-meter)	Field Strength (dB μ V/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54


MEASUREMENT EQUIPMENT USED

977 Chamber (3m)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	11/16/2006
ESPI3 EMI RECEIVER	R&S	ESPI3	101026	11/10/2006
Pre-Amplifier	MINI	ZFL-1000VH2	d041703	12/12/2006
Pre-Amplifier	Miteq	NSP4000-NF	870731	01/21/2007
Bi-log Antenna	Sunol Sciences	JB1	A110204-2	11/09/2006
Horn Antenna	Austriah	BBHA9120D	D267	09/20/2006
Turn Table	CT	CT123	4162	N.C.R
Antenna Tower	CT	CTERG23	3253	N.C.R
Controller	CT	CT100	95635	N.C.R
Coax Switch	Anitsu	MP 598	M 80094	N/A
Site NSA	CCS Lab.	N/A	N/A	02/15/2007


Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration

Below 1 GHz



Above 1 GHz



TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Set the spectrum analyzer in the following setting as:

Below 1GHz:

RBW=100kHz / VBW=300kHz / Sweep=AUTO

Above 1GHz:

(a) PEAK: RBW=VBW=1MHz / Sweep=AUTO

(b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO

7. Repeat above procedures until the measurements for all frequencies are complete.



TEST RESULTS

Below 1 GHz

Operation Mode: Normal Link**Test Date:** August 10, 2006**Temperature:** 25°C**Tested by:** lin**Humidity:** 45 % RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit 3m (dBuV/m)	Safe Margin (dB)
138.01	V	Peak	42.17	-1.36	40.81	43.5	-2.69
147.45	V	QP	42.77	-1.97	40.8	43.5	-2.7
156.91	V	QP	43.12	-2.24	40.88	43.5	-2.62
270.75	V	Peak	41.85	-0.54	41.31	46.0	-4.69
532.16	V	Peak	31.13	5.67	36.8	46.0	-9.2
946.33	V	Peak	28.32	11.7	40.02	46.0	-5.98
157.15	H	Peak	43.3	-2.24	41.06	43.5	-2.44
166.89	H	QP	44.64	-2.7	41.94	43.5	-1.56
195.03	H	QP	45.44	-2.59	42.85	43.5	-0.65
204.76	H	QP	45.49	-2.53	42.96	43.5	-0.54
290.81	H	QP	42.58	-0.22	42.36	46.0	-3.64
917.23	H	Peak	27.97	11.27	39.24	46.0	-6.76

Notes:

1. Measuring frequencies from 30 MHz to the 1GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak detector mode.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. The IF bandwidth of SPA between 30MHz to 1GHz was 100kHz.

**Above 1 GHz****Operation Mode:** TX/ CH Low**Test Date:** August 10, 2006**Temperature:** 25°C**Tested by:** lin**Humidity:** 48 % RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
4808.33	V	38.51	32.23	10.13	48.64	42.36	74	54	-11.64	Avg
7208.33	V	39.83	31.75	15.21	55.04	46.96	74	54	-7.04	Avg
4808.33	H	38.77	32.5	10.13	48.9	42.63	74	54	-11.37	Avg
7208.33	H	39.82	30.44	15.21	55.03	45.65	74	54	-8.35	Avg

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 1MHz, Sweep time = Auto.
 - b. AV Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 10Hz, Sweep time = Auto.

Operation Mode: TX/ CH Mid

Test Date: August 10, 2006

Temperature: 24°C

Tested by: lin

Humidity: 46 % RH

Polarity: Ver. / Hor.

[illegible]

Remark:

1. *Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.*
2. *Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.*
3. *Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.*
4. *Spectrum setting:*
 - a. *Peak Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 1MHz, Sweep time = Auto.*
 - b. *AV Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 10Hz, Sweep time = Auto.*



Operation Mode: TX/ CH High

Test Date: August 10, 2006

Temperature: 25°C

Tested by: lin

Humidity: 46 % RH

Polarity: Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
4958.33	V	39.65	33.61	10.99	50.64	44.6	74	54	-9.4	Avg
7441.67	V	39.89	33.87	16.19	56.08	50.06	74	54	-3.94	Avg
4957.63	H	38.75	32.72	10.99	49.74	43.71	74	54	-10.29	Avg
7439.99	H	40.5	34.46	16.19	56.69	50.65	74	54	-3.35	Avg

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 1MHz, Sweep time = Auto.
 - b. AV Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 10Hz, Sweep time = Auto.



7.9 POWERLINE CONDUCTED EMISSIONS

LIMIT

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50


Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

MEASUREMENT EQUIPMENT USED

Conducted Emission Test Site A (10m chamber)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESI26	100068	02/11/2007
EMC Analyzer	Agilent	E7402A	US41160329	02/11/2007
LISN	FCC	FCC-LISN-50-50-2-M	01067	02/11/2007
LISN (EUT)	FCC	FCC-LISN-50-50-2-M	01068	02/11/2007
TRANSIENT LIMITER	SCHAFFNER	CFL9206	1710	03/15/2007
EMI Monitor control box	FCC	0-SVDC	N/A	N/A

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

TEST PROCEDURE

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

**TEST RESULTS**

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

Test Data**Model:** TomTom ONE New Edition**Test Mode:** Normal Link**Temperature:** 24°C**Humidity:** 49% RH**Tested by:** lin**Test Results:** Pass

Freq. (MHz)	PEAK Amptd (dBuV)	Q.P. Amptd (dBuV)	AVG Amptd (dBuV)	Q.P. Limit (dBuV)	AVG Limit (dBuV)	Q.P. Margi n (dB)	AVG Margi n (dB)	Factor (dB)	Remark
0.165	56.07	37.35	38.53	65.57	55.57	-28.22	-17.04	10.37	Line
0.240	49.46	30.99	31.25	63.43	53.43	-32.44	-22.18	10.38	Line
0.515	41.07	27.59	27.52	56.00	46.00	-28.41	-18.48	10.40	Line
1.575	37.81	22.23	24.40	56.00	46.00	-33.77	-21.60	10.48	Line
2.100	38.69	26.18	24.38	56.00	46.00	-29.82	-21.62	10.52	Line
2.460	37.92	22.97	23.65	56.00	46.00	-33.03	-22.35	10.54	Line
0.165	54.77	38.42	39.22	65.57	55.57	-27.15	-16.35	10.41	Neutral
0.535	42.75	30.90	30.35	56.00	46.00	-25.10	-15.65	10.39	Neutral
1.560	36.09	23.88	21.99	56.00	46.00	-32.12	-24.01	10.46	Neutral
2.085	37.92	21.68	22.06	56.00	46.00	-34.32	-23.94	10.51	Neutral
4.420	34.55	20.78	20.94	56.00	46.00	-35.22	-25.06	10.70	Neutral
12.115	33.55	18.78	19.63	60.00	50.00	-41.22	-30.37	11.60	Neutral

Remark:

1. The measuring frequencies range between 0.15 MHz and 30 MHz.
2. The emissions measured in the frequency range between 0.15 MHz and 30MHz were made with an instrument using Quasi-peak detector and Average detector.
3. "---" denotes the emission level was or more than 2dB below the Average limit, and no re-check was made.
4. The IF bandwidth of SPA between 0.15MHz and 30MHz was 10KHz. The IF bandwidth of Test Receiver between 0.15MHz and 30MHz was 9kHz.

Note:

Freq. = Emission frequency in KHz

Factor (dB) = cable loss + Insertion loss of LISN+ Insertion loss of TRANSIENT LIMITER (The TRANSIENT LIMITER included 10 dB ATTENUATION)



$$\text{Amptd dBuV} = \text{Uncorrected Analyzer/Receiver reading} + \text{cable loss} + \text{Insertion loss of LISN} + \text{Insertion loss of TRANSIENT LIMITER, if it} > 0.5 \text{ dB}$$

$$\text{Limit dBuV} = \text{Limit stated in standard}$$


$$\text{Margin dB} = \text{Reading in reference to limit}$$

Calculation Formula

$$\text{Margin (dB)} = \text{Amptd (dBuV)} - \text{Limit (dBuV)}$$


Test Plot

Conducted emissions (Line 1)



Test Plot

Conducted emissions (Line 2)




APPENDIX 1 PHOTOGRAPHS OF TEST SETUP

Radiated Emission Set up Photos

Front of view



Back of view



Conducted Emission Set Up Photos

