4 FCC §1.1310 & §2.1091 - RF Exposure Information

4.1 Applicable Standards

According to §1.1310 and §2.1091 (Mobile Devices) RF exposure is calculated.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m) Limits for Genera	Magnetic Field Strength (A/m) l Population/Uncontrolled	Power Density (mW/cm²)	Averaging Time (minute)
0.2.1.24			-	20
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	$*(180/f^2)$	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

Note: f = frequency in MHz

4.2 MPE Prediction

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

 $S = PG/4\pi R^2$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

 $R = \mbox{distance}$ to the center of radiation of the antenna

Cellular Band

Uplink:

<u>21.35</u>
<u>136.46</u>
<u>20</u>
<u>836.5</u>
<u>7.14</u>
<u>5.176</u>
<u>0.141</u>
0.558

^{* =} Plane-wave equivalent power density

1.0

PCS Band

Uplink:

Maximum peak output power at antenna input terminal (dBm):21.31Maximum peak output power at antenna input terminal (mW):135.21Prediction distance (cm):20Prediction frequency (MHz):1864Maximum Antenna Net Gain (dBi):7.14Maximum Antenna Net Gain (numeric):5.176Power density at predication frequency and distance (mW/cm²):0.139

4.3 Test Result

The device complies with the MPE requirements by providing a safe separation distance of 20 cm between the antenna, including any radiating structure, and any persons when normally operated based on the maximum antenna gain of 7.14. The proposed RF exposure safety information has been included in the User's Manual.

MPE limit for uncontrolled exposure at predication frequency (mW/cm²):