4 FCC §1.1310 & §2.1091 - RF Exposure Information

4.1 Applicable Standards

According to §1.1310 and §2.1091 (Mobile Devices) RF exposure is calculated.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m) Limits for Genera	Magnetic Field Strength (A/m) l Population/Uncontrolled	Power Density (mW/cm²)	Averaging Time (minute)
0.2.1.24			-	20
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	$*(180/f^2)$	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

Note: f = frequency in MHz

4.2 MPE Prediction

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

 $S = PG/4\pi R^2$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Cellular Band

Uplink:

Maximum peak output power at antenna input terminal (dBm):	<u>20.92</u>	
Maximum peak output power at antenna input terminal (mW):		
Prediction distance (cm):	<u>20</u>	
Prediction frequency (MHz):	<u>837</u>	
Maximum Antenna Net Gain (dBi):	<u>7.14</u>	
Maximum Antenna Net Gain (numeric):	<u>5.176</u>	
Power density at predication frequency and distance (mW/cm ²):	<u>0.127</u>	
MPE limit for uncontrolled exposure at predication frequency (mW/cm²):		

^{* =} Plane-wave equivalent power density

PCS Band

Uplink:

Maximum peak output power at antenna input terminal (dBm): 20.29

Maximum peak output power at antenna input terminal (mW): 106.91

Prediction distance (cm): 20

Prediction frequency (MHz): 1865.4

Maximum Antenna Net Gain (dBi): 7.14

Maximum Antenna Net Gain (numeric): 5.176

Power density at predication frequency and distance (mW/cm²): <u>0.110</u>

MPE limit for uncontrolled exposure at predication frequency (mW/cm^2): $\underline{1.0}$

4.3 Test Result

The device complies with the MPE requirements by providing a safe separation distance of 20 cm between the antenna, including any radiating structure, and any persons when normally operated based on the maximum antenna gain of 7.14. The proposed RF exposure safety information has been included in the User's Manual.