

RF Exposure MPE Exhibit

FCC ID: S52-1-09-01-00-1

IC: 8076A-10901001

This device operates at frequencies in the 1900 MHz PCS Band. Maximum permissible exposure in this band is specified under per FCC Part 1, Section 1.1310, Table 1, as 1 mW/cm². FCC Part 1, Section 1.1307 states that Part 24E (Broadband PCS) devices are excluded from routine environmental evaluation when operating at power levels less than 3280 Watts EIRP.

EIRP (Effective Isotropic Radiated Power) is the amount of power that a theoretical isotropic antenna (that evenly distributes power in all directions) would emit to produce the peak power density observed in the direction of maximum antenna gain. EIRP can take into account the losses in transmission line and connectors and includes the gain of the antenna.

Where *EIRP* and P_t (power of transmitter) are in dBm, cable losses (L_c) is in dB, and antenna gain (G_a) is expressed in dBi, relative to a (theoretical) isotropic reference antenna. No antenna is supplied with this unit. Therefore, based on measured RF output power of 10.54 Watts at 1988.75 MHz and assumption of cable loss is zero, the maximum antenna gain that will allow the EIRP to remain under the environmental evaluation exclusion limit of 3280 Watts is 24.9 dB.

MPE is determined by the following relationship:

$$\text{Power Density } P_d (\text{mW/cm}^2) = \text{EIRP}/4\pi d^2$$

Where d = distance.

$$3280 \text{ Watts} = 3.28 \times 10^6 \text{ mW}$$

Therefore:

$$\begin{aligned} d &= (\text{EIRP}/4\pi P_d)^{1/2} \\ &= (3.28 \times 10^6 \text{ mW} / 4\pi (1 \text{ mW/cm}^2))^{1/2} \\ &= 510.89 = 5.1 \text{ m} \end{aligned}$$

The minimum safe distance from a radiating structure exhibiting a maximum gain of 24.9 dB connected to the BTS when installed and transmitting at full output power is 5.1 m.

The antenna(s) used for this transmitter must be fixed-mounted on permanent outdoor structures. RF exposure compliance is addressed at the time of licensing, as required by the responsible FCC Bureau(s), including antenna co-location requirements of Section 1.1037(b)(3).

Date: May 17, 2012

Revision #: 0

