



FDAP31 Gen3 Anchor

Honeywell FIELD DEVICE ACCES POINT GEN3, ANCHOR
Fort Washington, PA 19034, USA
ASSEMBLED IN MEXICO
Model: FDAP31
Part No.: 51156751-006
Ser. No.:
Input: 12V - 28VDC, 1.0W
Temp: -40 °C TO +70 °C
IP66/67

CE Ⓢ



 Ex ia, Cl. I, Div.1 Gp.CD;T4
Cl. I, Zn 0, Ex ia IIB; T4 Gc
US TYPE 4

Installation per Dwg 50165525

This device complies with Part 15 of FCC Rules and Regulations. Operation is subject to the following conditions: (1) This device may not cause harmful interference and (2) This Device must accept any interference received, including interference that may cause undesired operation.


FCC ID : S5751308987
Contains FCC ID : XPNINAB1
Ethernet MAC: 00-40-84-xx-xx-xx-xx


IC: 573W-51308987
Contains IC: 8595A-NINAB1 Model NINA-B1
BLE MAC: xx-xx-xx-xx-xx-xx


FDAP32 Gen3 Anchor

Honeywell FIELD DEVICE ACCES POINT GEN3, ANCHOR
Fort Washington, PA 19034, USA
ASSEMBLED IN MEXICO
Model: FDAP32
Part No.: 51156751-006
Ser. No.:
Input: 12 - 28VDC , 3.05W
POE 37 - 57VDC 3.24W
Temp: -40 °C TO +70 °C
IP66/67

CE Ⓢ



 CSANe 21ATEX3127X
IIG Ex ec [ic] IIC T4 Gc
IECEX CSA 21.0025X
Ex ec [ic] IIC T4 Gc

 Cl. I, Div. 2 Gp. ABCD; T4
Nonincendive Field Wiring (NIFW)
connection to external antenna
as per the installation drawing.
US TYPE 4

Installation per Dwg 50165525

This device complies with Part 15 of FCC Rules and Regulations. Operation is subject to the following conditions: (1) This device may not cause harmful interference and (2) This Device must accept any interference received, including interference that may cause undesired operation.

FCC ID : S5751308987
Contains FCC ID : XPNINAB1
Ethernet MAC: 00-40-84-xx-xx-xx-xx

IC: 573W-51308987
Contains IC: 8595A-NINAB1 Model NINA-B1
BLE MAC: xx-xx-xx-xx-xx-xx

FDAP3P Gen3 Anchor

Honeywell FIELD DEVICE ACCESS POINT GEN3 PLUS, ANCHOR

Fort Washington, PA 19034, USA

ASSEMBLED IN MEXICO

Model: FDAP3P

Part No.: 51156751-004

Ser. No.:

Input: POE 37 - 57VDC 3.24W

Temp.: -40 °C TO +70 °C

IP66/67

CE Ⓢ

CSA

Ex

CSANe 2IATEX3127X
IIG Ex ec [ic] IIC T4 Gc
IECEX CSA 21.0025X
Ex ec [ic] IIC T4 Gc

CL I, Div. 2 Gp. ABCD; T4
Nonincendive Field Wiring (NIFW)
connection to external antenna
as per the installation drawing.

CS

C US TYPE 4

Installation per Dwg 50165525

This device complies with Part 15 of FCC Rules and Regulations. Operation is subject to the following conditions: (1) This device may not cause harmful interference and (2) This Device must accept any interference received, including interference that may cause undesired operation.

FCC ID : 5751308987 IC: 573W-51308987
Contains FCC ID : XPYNINAB1 Contains IC: 8595A-NINAB1 Model NINA-B1
Ethernet MAC: 00-40-84-xx-xx-xx-xx BLE MAC: xx-xx-xx-xx-xx-xx



Label Placement

On front surface