



FDAP31 Anchor2

Honeywell FIELD DEVICE ACCESS POINT GEN3 ANCHOR2
 Fort Washington, PA 19034, USA
 ASSEMBLED IN MEXICO
 Model: FDAP31
 Part No.: 51156751-009
 Ser. No.:
 Input: 12V - 28VDC, 1.0W

Temp.: -40 °C TO +70 °C
 IP66/67
 MFD.: MM/YYYY

Ex ia, Cl I, Div.1 Gp.CD;T4
 Cl I, Zn 0, Ex ia IIB; T4 Gc
 US TYPE 4



Installation per Dwg 50185525

This device complies with Part 15 of FCC Rules and Regulations. Operation is subject to the following conditions: (1) This device may not cause harmful interference and (2) This Device must accept any interference received, including interference that may cause undesired operation.

FCC ID : S5751460094 IC: 573W-51460094
 Contains FCC ID : XPYNINAB1 Contains IC: 8595A-NINAB1 Model NINA-B1
 Ethernet MAC: 00-40-84-xx-xx-xx-xx BLE MAC: xx-xx-xx-xx-xx-xx

FDAP32 Anchor2

Honeywell FIELD DEVICE ACCESS POINT GEN3 ANCHOR2
 Fort Washington, PA 19034, USA
 ASSEMBLED IN MEXICO
 Model: FDAP32
 Part No.: 51156751-008
 Ser. No.:
 Input: 12V - 28VDC, 2.4W
 POE 37V - 57VDC, 2.51W
 Temp.: -40 °C TO +70 °C
 IP66/67
 MFD.: MM/YYYY

CSA# 21ATEX3127X
 I3G Ex ec [ic] IIC T4 Gc
 IECEx CSA 210025X
 Ex ec [ic] IIC T4 Gc

Cl I, Div. 2 Gp. ABCD; T4
 Nonincendive Field Wiring (NIFW)
 connection to external antenna
 as per the installation drawing.
 US TYPE 4

Installation per Dwg 50185525

This device complies with Part 15 of FCC Rules and Regulations. Operation is subject to the following conditions: (1) This device may not cause harmful interference and (2) This Device must accept any interference received, including interference that may cause undesired operation.

FCC ID : S5751460094 IC: 573W-51460094
 Contains FCC ID : XPYNINAB1 Contains IC: 8595A-NINAB1 Model NINA-B1
 Ethernet MAC: 00-40-84-xx-xx-xx-xx BLE MAC: xx-xx-xx-xx-xx-xx

FDAP3P Anchor2

Honeywell FIELD DEVICE ACCESS POINT GEN3 PLUS ANCHOR2
Fort Washington, PA 19034, USA
ASSEMBLED IN MEXICO
Model: FDAP3P
Part No.: 51156751-007
Ser. No.:
Input: POE 37V - 57VDC, 2.5W

CE Ⓢ

Ex CSANe 21ATEX3127X
IIG Ex ec [ic] IIC T4 Gc
IECEX CSA 210025X
Ex ec [ic] IIC T4 Gc

Temp.: -40 °C TO +70 °C
IP66/67
MFD: MM/YYYY

SP Cl. I, Div. 2 Gp. ABCD; T4
Nonincendive Field Wiring (NIFW)
connection to external antenna
as per the installation drawing.
US TYPE 4

Installation per Dwg 50185525

This device complies with Part 15 of FCC Rules and Regulations. Operation is subject to the following conditions: (1) This device may not cause harmful interference and (2) This Device must accept any interference received, including interference that may cause undesired operation.

FCC ID : S5751460094
Contains FCC ID : XPYNINAB1
Ethernet MAC: 00-40-84-xx-xx-xx-xx

IC: 573W-51460094
Contains IC: 8595A-NINAB1 Model NINA-B1
BLE MAC: xx-xx-xx-xx-xx-xx

