



Test Report No.: Prüfbericht-Nr.:	US21127L.001 Rev.: 01	Order No.: Auftrags-Nr.:	P00233769 234173418	Page 1 of 78 Seite 1 von 78
Client Reference No.: Kunden-Referenz-Nr.:	2229228	Order date: Auftragsdatum:	3/26/2021	
Client: Auftraggeber:	Satellite Tracking of People, LLC 5353 W Sam Houston Parkway N, Suite 190 Houston, Texas, 77041			
Test item: Prüfgegenstand:	BLUband			
Identification/ Type No.: Bezeichnung / Typ-Nr.	BLUband V3			
Order content: Auftrags-Inhalt:	Radio Compliance Test Report			
Test specification: Prüfgrundlage:	FCC 47 CFR Part 15.247:2021, RSS-247:2020			
Date of sample receipt: Wareneingangsdatum:	6/10/2021	See Test Setup Exhibit for Photos		
Test sample No.: Prüfmuster-Nr.:	17-000005, 17-000006			
Testing period: Prüfzeitraum:	6/11/2021- 6/18/2021			
Testing laboratory: Prüflaboratorium:	TUV Rheinland of North America 710 Resende Road, Building 199 Webster, NY 14580			
Test result*: Prüfergebnis*:	Pass			
tested by: geprüft von:		authorized by: / genehmigt von:		
Date: 7/6/2021 Datum:		Issue Date: 7/6/2021 Ausstellungsdatum:		
Position / Stellung:	Expert	Position / Stellung:	Expert	
Others / Sonstiges:				
Condition of the test item at delivery: Zustand des Prüfgegenstandes bei Anlieferung:	Test sample complete and undamaged			
* Legend:	P(ass) = passed a.m. test specification(s)	F(ail) = failed a.m. test specification(s)	N/A = not applicable	N/T = not tested
* Legende:	P(ass) = entspricht o.g. Prüfgrundlage(n)	F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	N/A = nicht anwendbar	N/T = nicht getestet
<p>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</p> <p><i>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</i></p>				

Test report no.: US21127L.001 Rev.:01

Page 2 of 78
Seite 2 von 78

Prüfbericht-Nr.:

Remarks
Anmerkungen

1	<p>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</p> <p><i>Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden.</i></p>
2	<p>As contractually agreed, this document has been signed digitally only. TÜV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TÜV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged.</p> <p><i>Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben.</i></p>
3	<p>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report. Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</p> <p><i>Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt.</i></p>
4	<p>The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA.</p>
5	<p>Radio Compliance Test Report. The above product was found to be Compliant to the above test standard(s).</p>

Test report no .: US21127L.001 Rev.:01	Page 3 of 78 Seite 3 von 78
<i>Prüfbericht-Nr.:</i>	
Product description <i>Produktbeschreibung</i>	

1	Product details: <i>Produktdetails:</i>	BLUband records and reports the date and time an enrollee enters of leaves a designated location
2	Dimensions / Weight: <i>Maße / Gewicht:</i>	3.75 in x 1.80 in x 1.00 in / 0.29 lbs
3	Operating elements: <i>Bedienelemente:</i>	Battery Powered (3.6 VDC), Transmit band 902-928 MHz
4	Equipment / Accessories: <i>Ausstattung / Zubehör:</i>	None.
5	Used materials: <i>Verwendete Materialien:</i>	None.
6	Other: <i>Sonstiges:</i>	Test sample(s), as well sample information, description, product details and intended usage was provided by customer.
7	Test sample obtaining: <i>Prüfmusterbereitstellung:</i>	<input checked="" type="checkbox"/> Sending by customer <input type="checkbox"/> Sampling by TÜV Rheinland Group <input type="checkbox"/> others:

Test report no.: US21127L.001 Rev.:01

Page 4 of 78
Seite 4 von 78

Prüfbericht-Nr.:

Revisions

Date mm/dd/yy	Name	Page Number of Change	Describe Change
07/06/2021	Rev.:01	N/A	Original Document

TABLE OF CONTENTS

1	General Information	7
1.1	Scope	7
1.2	Purpose.....	7
1.3	Summary of Test Results.....	8
2	Laboratory Information	9
2.1	Accreditations & Endorsements	9
2.2	Test Software	9
2.3	Measurement Uncertainty	10
2.4	Calibration Traceability	11
2.5	Measurement Equipment Identification	12
3	Product Information	13
3.1	Test Plan	13
4	Transmitter Requirements	14
4.1	Antenna Requirements	14
4.2	Transmitter Output Power	15
4.3	Occupied Bandwidth	20
4.4	Power Spectral Density	28
4.5	Out of Band Emissions	33
4.6	Transmitter Spurious Emissions	40
	Appendix A	74
5	Test Plan	74
5.1	General Information.....	74
5.2	Model(s) Name	74
5.3	Type of Product	74
5.4	Equipment Under Test (EUT) Description.....	75
5.5	Wireless Information	75
5.6	Testing Preparation	75
5.7	General Product Information	75
5.8	Modifications.....	76
5.9	EUT Electrical Power Information.....	76
5.10	EUT Modes of Operation during Testing.....	76
5.11	EUT Clock/Oscillator Frequencies	76
5.12	Electrical Support Equipment	76
5.13	Non - Electrical Support Equipment	77
5.14	EUT Equipment/Cabling Information.....	77

Test report no.: US21127L.001 Rev.:01

Page 6 of 78
Seite 6 von 78

Prüfbericht-Nr.:

5.15	EUT Configuration	77
5.16	Block Diagram	77

1 General Information

1.1 Scope

This report is intended to document the status of conformance based on the results of testing performed on the BLUband, Model Number: BLUband V3, manufactured by Satellite Tracking of People, LLC. This report only applies to the specific samples tested under the stated test conditions. It is the responsibility of the manufacturer to assure that additional production units of this model are manufactured with identical or EMI equivalent electrical and mechanical components.

1.2 Purpose

Testing was performed to evaluate the Radio performance of the EUT (Equipment Under Test) in accordance with the applicable requirements, procedures, and criteria defined in the application of regulations and application of standards listed in this report.

Test report no.: US21127L.001 Rev.:01

Page 8 of 78
Seite 8 von 78

Prüfbericht-Nr.:

1.3 Summary of Test Results

Applicant:	Satellite Tracking of People, LLC 5353 W Sam Houston Parkway N, Suite 190 Houston, Texas, 77041	Tel:	713-354-9393	Contact:	Mark Kirincic
		Fax:	--	e-mail:	mkirincic@securustechnologies.com
Description:	BLUband	Test Voltage/Freq.:		3.6 VDC	
Model Number:	BLUband V3	Test Engineer:		Alexander Sowinski	
Serial Number:	17-000005, 17-000006				
Standards	Description	Severity Level or Limit		Criteria	Test Result
FCC 47 CFR Part 15.247:2021, RSS-247:2020 Radio Standard	Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.	See Basic Sections Below		See Below	Complies
FCC 47 CFR Part 15.203, RSS-Gen (6.8)	Antenna Requirements	Per Standards		Report	Complies
FCC 47 CFR Part 15.247 (b.3), RSS-247 (5.4)	Transmitter Output Power	EIRP < 1 Watt (30 dBm)		Limit	Complies
FCC 47 CFR Part 15.247 (a.2), RSS-247 (5.2)	Occupied Bandwidth	6dB OBW > 500 kHz		Limit	Complies
FCC 47 CFR Part 15.247 (e), RSS-247 (5.2)	Power Spectral Density	PSD < 8dBm / 3kHz band		Limit	Complies
FCC 47 CFR Part 15.247 (d), RSS-247 (5.5)	Out of Band Emissions	< 20 dB / 100kHz band		Limit	Complies
FCC CFR 15.209, RSS-Gen (8.9)	Transmitter Spurious Emissions	Class B, 30 - 1000 MHz Class B, 1000 - 18000 MHz		Limit	Complies

2 Laboratory Information

2.1 Accreditations & Endorsements

TUV Rheinland of North America located at, 710 Resende Road Webster, NY 14580 is accredited by the commission for performing testing services for the general public on a fee basis. This laboratory test facilities have been fully described in reports submitted to and accepted by the FCC (Registration No 5253). The laboratory scope of accreditation includes: Title 47 CFR Part 15, and 18. The accreditation is updated every 3 years.

2.1.1 ILAC/A2LA

This is a program which is administered under the auspices of A2LA accredited. The laboratory has been assessed and accredited in accordance with ISO Standard 17025:2017 (Certificate Number: 3331.08). The scope of laboratory accreditation includes emission and immunity testing. The accreditation is updated annually.

2.1.2 VCCI

VCCI Accredited test lab. Registration numbers A-0329.

2.1.3 Industry Canada

(Registration No.: 482B-1) The 10 meter Semi-Anechoic chamber has been accepted by Industry Canada to perform testing to 3 and to 10m, based on the test procedures described in ANSI C63.4-2014.

2.1.4 BSMI

Registration No.: SL2-IN-E-1159R. The BSMI accreditation was obtained by NIST MRA with the BSMI.

2.1.5 Korea

(Designation No.: US0192). Recognized by National Radio Research Agency (RRA) as an accredited Conformity Assessment Body (CAB) under the terms for Korea Phase I of the APEC TEL.

2.2 Test Software

- 1) CIGUI 32 Version 1.4 for California Instruments AC power source
- 2) TILE version 4.1.B
- 3) TILE 7 version 7.1.3.24
- 4) Voltech PM 6000 Firmware 1.22.07RC6, Software IEC61000-3 for PM6000 Release 1.24.12
- 5) California Instruments AC power source MXHCL
- 6) Rohde & Schwarz EMI Measurement software EMC32 version 8.54.0
- 7) TEMA 3000 version 4.1.2
- 8) TILE version 3.4.k.28

2.3 Measurement Uncertainty

Two types of measurement uncertainty are expressed in this report, per *ISO Guide To The Expression Of Uncertainty In Measurement*, 1st Edition, 1995.

The Combined Standard Uncertainty is the standard uncertainty of the result of a measurement when that result is obtained from the values of a number of other quantities, equal to the positive square root of a sum of terms, the terms being the variances or co-variances of these other quantities weighted according to how the measurement result varies with changes in these quantities. The term standard uncertainty is the result of a measurement expressed as a standard deviation.

The Expanded Uncertainty defines an interval about the result of a measurement that may be expected to encompass a large fraction of the distribution of values that could reasonably be attributed to the measurand. The fraction may be viewed as the coverage probability or level of confidence of the interval.

2.3.1 Sample Calculation – radiated & conducted emissions

The field strength is calculated by subtracting the Amplifier Gain and adding the Cable Loss and Antenna Correction Factor to the measured reading. The basic equation is as follows:

$$\text{Field Strength (dB}\mu\text{V/m)} = \text{RAW} - \text{AMP} + \text{CBL} + \text{ACF}$$

Where: RAW = Measured level before correction (dBμV)

AMP = Amplifier Gain (dB)

CBL = Cable Loss (dB)

ACF = Antenna Correction Factor (dB/m)

$$\mu\text{V/m} = 10^{\frac{\text{dB}\mu\text{V/m}}{20}}$$

Sample radiated emissions calculation @ 30 MHz

Measurement +Antenna Factor–Amplifier Gain+Cable loss=Radiated Emissions (dBuV/m)

$$25 \text{ dBuV/m} + 17.5 \text{ dB} - 20 \text{ dB} + 1.0 \text{ dB} = 23.5 \text{ dBuV/m}$$

2.3.2 Measurement Uncertainty Emissions

Per CISPR 16-4-2	Ulab	Ucisp
Radiated Disturbance @ 10m		
30 MHz – 1,000 MHz	4.57 dB	5.2 dB
Radiated Disturbance @ 3m		
1.0 GHz – 6.0 GHz	5.18 dB	5.2 dB
6.0 GHz – 18.0 GHz	5.48 dB	5.5 dB
18.0 GHz – 26.5 GHz	5.21 dB	
26.5 GHz – 40.0 GHz	4.99 dB	
Conducted Disturbance @ Mains Terminals		
150 kHz – 30 MHz	2.62 dB	3.6 dB
Disturbance Power		
30 MHz – 300 MHz	3.88 dB	4.5 dB

Test report no.: US21127L.001 Rev.:01

Page 11 of 78
Seite 11 von 78

Prüfbericht-Nr.:

Measurement Uncertainty Emissions

The estimated combined standard uncertainty for radiated emissions measurements is ± 4.57 dB	Per CISPR16-4-2 Method
The estimated combined standard uncertainty for radiated emissions measurements from 1 GHz to 6 GHz is ± 5.18 dB	Per CISPR16-4-2 Method
The estimated combined standard uncertainty for radiated emissions measurements from 6 GHz to 18 GHz is ± 5.48 dB	Per CISPR16-4-2 Method
The estimated combined standard uncertainty for conducted emissions measurements is ± 2.62 dB.	Per CISPR16-4-2 Method

Expanded measurement uncertainty numbers are shown in the tables above. Compliance criteria are not based on measurement uncertainty.

2.4 Calibration Traceability

All measurement instrumentation is traceable to the National Institute of Standards and Technology (NIST). Measurement method complies with ANSI/NCSL Z540-1-1994 and ISO Standard ISO IEC 17025:2017. Equipment calibration records are kept on file at the test facility.

Test report no.: US21127L.001 Rev.:01

Page 12 of 78
 Seite 12 von 78

Prüfbericht-Nr.:

2.5 Measurement Equipment Identification

Equip.	Description	Model	Manufacturer	Page 1 of 1	
				Last Date MM/DD/YYYY	Due Date MM/DD/YYYY
G1701077	SunAR JB6 Antenna	JB6	SunAR	04/30/2020	04/30/2022
G1701081	Fluke Multimeter 87 V 39760226	87 V	Fluke	04/09/2021	04/09/2022
G1701082	Temperature/Humidity/Barometer	68000-49	Control Company	02/12/2021	06/12/2023
G1701089	R&S EMI Receiver ESW44 101880	ESW44	Rohde & Schwarz	04/02/2021	04/02/2022
G1701233	EMCO Horn Antenna 3115 9812-5635	3115	EMCO	02/28/2020	03/28/2022
G1701365	EMCO Horn 3160-10 1180	3160-10	EMCO	08/11/2020	08/11/2022
G1701367	EMCO Horn 3160-09 6707	3160-09	EMCO	08/11/2020	08/11/2022
G1701385	R&S EMI Receiver ESU40 100274	ESU40	Rohde & Schwarz	02/09/2021	02/09/2022
G1701452	RF Path 30-1000MHz	RF Cable Path		05/12/2021	02/12/2023
G1701526	Tunable Notch Filter	240NFM	EAGLE	No Cal	No Cal

Test report no.: US21127L.001 Rev.:01

Prüfbericht-Nr.:

Page 13 of 78
Seite 13 von 78

3 Product Information

3.1 Test Plan

The EUT product information, test configuration, mode of operation, test types, test procedures, test levels, pass/failure criteria, in this report were carried out per the product test plan located in appendix A of this report.

Test report no.: US21127L.001 Rev.:01

Page 14 of 78
Seite 14 von 78

Prüfbericht-Nr.:

4 Transmitter Requirements

4.1 Antenna Requirements

Per the requirements of FCC 47 CFR 15.203: 2021, the antenna of an intentional transmitter shall:
... be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

The BLUband contains a stamp metal embedded SMT antenna with a maximum gain of 1.0 dBi. The antenna is contained fully within the BLUband and is not accessible to the end user.

Test report no.: US21127L.001 Rev.:01

Page 15 of 78
 Seite 15 von 78

Prüfbericht-Nr.:

4.2 Transmitter Output Power

This test measures conducted output power of the transmitter

4.2.1 Over View of Test

Results	Complies (as tested per this report)					Date	06/10/2021
Standard	FCC 47 CFR Part 15.247 (b.3), RSS-247 (5.4)						
Product Model	BLUband V3			Serial#	17-000005		
Configuration	See test plan for details.						
Test Set-up	Tested in shielded room, EUT placed on table. See test plans for details.						
EUT Powered By	3.6 VDC	Temp	22°C	Humidity	46%	Pressure	1004 mbar
Channel Frequencies	Low Channel: 903 MHz Mid Channel: 915 MHz High Channel: 927 MHz			Power Setting @ Channel	14 dBm		
Perf. Criteria	ERP < 1 Watt (30 dBm)			Perf. Verification	Readings Under Limit		
Mod. to EUT	None			Test Performed By	Alexander Sowinski		

4.2.2 Test Procedure

Antenna port conducted emission tests were performed using the procedures of FCC 47 CFR Part 15.247 (b.3), RSS-247 (5.4) and/or ANSI C63.10 including methods for signal maximizations and EUT configuration. The EUT was placed in the test chamber and connected directly to the spectrum analyzer via temporary SMA connection. Peak measurements were taken with RBW = 1 MHz on each of the low, mid, and high channels utilizing both the LoRa and FSK transmission schemes of the EUT.

4.2.3 Deviations

There were no deviations from the test methodology listed in the test plan for the conducted emission test.

4.2.4 Final Test

All final conducted emissions measurements were below (in compliance) the limits.

Test report no.: US21127L.001 Rev.:01

Page 16 of 78
Seite 16 von 78


Prüfbericht-Nr.:

4.2.5 Final Data

Table 1: Output Power, EUT power setting @ 14 dBm


Type	Frequency	Conducted Power	Antenna Gain	EIRP	ERP	Limit	Margin
	MHz	dBm	dBi	dBm	dBm	dBm	dB
LoRa	903.00	14.81	1.00	15.81	13.66	30.0	-16.34
LoRa	915.00	14.85	1.00	15.85	13.70	30.0	-16.30
LoRa	927.00	14.87	1.00	15.87	13.72	30.0	-16.28
FSK	903.00	14.80	1.00	15.80	13.65	30.0	-16.35
FSK	915.00	14.84	1.00	15.84	13.69	30.0	-16.31
FSK	927.00	14.85	1.00	15.85	13.70	30.0	-16.30

4.2.6 Final Plots




Date: 24.JUN.2021 04:03:29

Figure 1 – Low Channel Output Power (LoRa)




Date: 24.JUN.2021 04:01:32

Figure 2 – Mid Channel Output Power (LoRa)




Date: 24.JUN.2021 04:00:42

Figure 3 – High Channel Output Power (LoRa)




Date: 24.JUN.2021 04:02:54

Figure 4 – Low Channel Output Power (FSK)



Date: 24.JUN.2021 04:02:15

Figure 5 – Mid Channel Output Power (FSK)



Date: 24.JUN.2021 03:59:55

Figure 6 – High Channel Output Power (FSK)

Test report no.: US21127L.001 Rev.:01

Page 20 of 78
 Seite 20 von 78

Prüfbericht-Nr.:

4.3 Occupied Bandwidth

This test measures the 6 dB and 99% bandwidth of the EUT.

4.3.1 Test Over View

Results	Complies (as tested per this report)				Date	06/10/2021	
Standard	FCC 47 CFR Part 15.247 (a.2), RSS-247 (5.2)						
Product Model	BLUband V3			Serial#	17-000005		
Configuration	See test plan for details.						
Test Set-up	Tested in shielded room, EUT placed on table. See test plan for details.						
EUT Powered By	3.6 VDC	Temp	22°C	Humidity	46%	Pressure	1004 mbar
Channel Frequencies	Low Channel: 903 MHz Mid Channel: 915 MHz High Channel: 927 MHz			Power Setting @ Channel	14 dBm		
Perf. Criteria	6 dB OBW > 500 kHz			Perf. Verification	Readings above Minimum		
Mod to EUT	None			Test Performed By	Alexander Sowinski		

4.3.2 Test Procedure

Antenna port conducted emission tests were performed using the procedures of FCC 47 CFR Part 15.247 (a.2), RSS-247 (5.2) and/or ANSI C63.10 including methods for signal maximizations and EUT configuration. The EUT was placed in the test chamber and connected directly to the spectrum analyzer via temporary SMA connection. Peak measurements were taken with RBW = 100 kHz on each of the low, mid, and high channels utilizing both the LoRa and FSK transmission schemes of the EUT.

4.3.3 Deviations

There were no deviations from the test methodology listed in the test plan for the occupied bandwidth test.

4.3.4 Final Test

The occupied bandwidth of the EUT were above the minimum levels specified by the standard

Test report no.: US21127L.001 Rev.:01

Page 21 of 78
Seite 21 von 78


Prüfbericht-Nr.:

4.3.5 Final Data

Table 2: Occupied Bandwidth, EUT power setting @ 14 dBm


Type	Frequency MHz	Flow MHz	Fhigh MHz	6dB OBW kHz	99% OBW kHz	6dB OBW Minimum kHz	Result
LoRa	903.00	902.62340	903.24840	625.00000	673.07690	500.00000	PASS
LoRa	915.00	914.62339	915.24840	625.01000	665.06410	500.00000	PASS
LoRa	927.00	926.62340	927.24840	625.00000	681.08974	500.00000	PASS
FSK	903.00	902.66346	903.19231	528.84600	600.96154	500.00000	PASS
FSK	915.00	914.66346	915.20032	536.86000	600.96154	500.00000	PASS
FSK	927.00	926.66346	927.19231	528.84700	592.94872	500.00000	PASS

4.3.6 Final Plots



Date: 24.JUN.2021 03:42:53

Figure 7 – Low Channel 6 dB Occupied Bandwidth (LoRa)




Date: 24.JUN.2021 03:51:22

Figure 8 – Mid Channel 6 dB Occupied Bandwidth (LoRa)

Test report no.: US21127L.001 Rev.:01


Page 23 of 78
 Seite 23 von 78

Prüfbericht-Nr.:



Date: 24.JUN.2021 03:55:44

Figure 9 – High Channel 6 dB Occupied Bandwidth (LoRa)




Date: 24.JUN.2021 03:46:26

Figure 10 – Low Channel 6 dB Occupied Bandwidth (FSK)

Test report no.: US21127L.001 Rev.:01


Page 24 of 78
 Seite 24 von 78

Prüfbericht-Nr.:




Date: 24.JUN.2021 03:52:38

Figure 11 – Mid Channel 6 dB Occupied Bandwidth (FSK)




Date: 24.JUN.2021 03:57:11

Figure 12 – High Channel 6 dB Occupied Bandwidth (FSK)




Date: 24.JUN.2021 03:44:40

Figure 13 – Low Channel 99% Occupied Bandwidth (LoRa)




Date: 24.JUN.2021 03:50:05

Figure 14 – Mid Channel 99% Occupied Bandwidth (LoRa)



Date: 24.JUN.2021 03:54:45

Figure 15 – High Channel 99% Occupied Bandwidth (LoRa)




Date: 24.JUN.2021 03:48:06

Figure 16 – Low Channel 99% Occupied Bandwidth (FSK)

Test report no.: US21127L.001 Rev.:01


Page 27 of 78
 Seite 27 von 78

Prüfbericht-Nr.:



Date: 24.JUN.2021 03:53:31

Figure 17 – Mid Channel 99% Occupied Bandwidth (FSK)



Date: 24.JUN.2021 03:58:31

Figure 18 – High Channel 99% Occupied Bandwidth (FSK)

Test report no.: US21127L.001 Rev.:01

Page 28 of 78
 Seite 28 von 78

Prüfbericht-Nr.:

4.4 Power Spectral Density

This test measures the power spectral density of the EUT.

4.4.1 Test Over View

Results	Complies (as tested per this report)				Date	06/10/2021	
Standard	FCC 47 CFR Part 15.247 (e), RSS-247 (5.2)						
Product Model	BLUband V3			Serial#	17-000005		
Configuration	See test plan for details.						
Test Set-up	Tested in shielded room, EUT placed on table. See test plan for details						
EUT Powered By	3.6 VDC	Temp	22°C	Humidity	46%	Pressure	1004 mbar
Channel Frequencies	Low Channel: 903 MHz Mid Channel: 915 MHz High Channel: 927 MHz		Power Setting @ Channel		14 dBm		
Perf. Criteria	PSD < 8dBm / 3kHz		Perf. Verification		Readings under Limit		
Mod to EUT	None		Test Performed By		Alexander Sowinski		

4.4.2 Test Procedure

Antenna port conducted emission tests were performed using the procedures of FCC 47 CFR Part 15.247 (e), RSS-247 (5.2) and/or ANSI C63.10 including methods for signal maximizations and EUT configuration. The EUT was placed in the test chamber and connected directly to the spectrum analyzer via temporary SMA connection. Peak measurements were taken with RBW = 3 kHz on each of the low, mid, and high channels utilizing both the LoRa and FSK transmission schemes of the EUT.

4.4.3 Deviations

There were no deviations from the test methodology listed in the test plan for the power spectral density test.

4.4.4 Final Test

The power spectral density measurements were below the limits specified by the standard

Test report no.: US21127L.001 Rev.:01

Page 29 of 78
Seite 29 von 78


Prüfbericht-Nr.:

4.4.5 Final Data

Table 3: Power Spectral Density, EUT power setting @ 14 dBm.


Type	Frequency	PSD	Limit	Margin
	MHz	dBm/3kHz	dBm	dB
LoRa	903.00	-2.46	8.0	-10.46
LoRa	915.00	-2.47	8.0	-10.47
LoRa	927.00	-2.27	8.0	-10.27
FSK	903.00	7.73	8.0	-0.27
FSK	915.00	7.82	8.0	-0.18
FSK	927.00	7.74	8.0	-0.26

4.4.6 Final Plots



Date: 24.JUN.2021 04:06:17

Figure 19 – Low Channel Power Spectral Density (LoRa)




Date: 24.JUN.2021 04:09:02

Figure 20 – Mid Channel Power Spectral Density (LoRa)

Test report no.: US21127L.001 Rev.:01


Page 31 of 78
Seite 31 von 78

Prüfbericht-Nr.:



Date: 24.JUN.2021 04:09:42

Figure 21 – High Channel Power Spectral Density (LoRa)




Date: 24.JUN.2021 04:07:38

Figure 22 – Low Channel Power Spectral Density (FSK)

Test report no.: US21127L.001 Rev.:01


Page 32 of 78
Seite 32 von 78

Prüfbericht-Nr.:



Date: 24.JUN.2021 04:08:31

Figure 23 – Mid Channel Power Spectral Density (FSK)



Date: 24.JUN.2021 04:10:30

Figure 24 – High Channel Power Spectral Density (FSK)

Test report no.: US21127L.001 Rev.:01

Page 33 of 78
Seite 33 von 78

Prüfbericht-Nr.:

4.5 Out of Band Emissions

This test checks for any spurious emissions outside of the transmit band.

4.5.1 Test Over View

Results	Complies (as tested per this report)			Date	06/10/2021		
Standard	FCC 47 CFR Part 15.247 (d), RSS-247 (5.5)						
Product Model	BLUband V3			Serial#	17-000005		
Configuration	See test plan for details.						
Test Set-up	Tested in shielded room, EUT placed on table. See test plan for details						
EUT Powered By	3.6 VDC	Temp	22°C	Humidity	46%	Pressure	1004 mbar
Channel Frequencies	Low Channel: 903 MHz Mid Channel: 915 MHz High Channel: 927 MHz			Power Setting @ Channel	14 dBm		
Perf. Criteria	< 20 dBr / 100 kHz band			Perf. Verification	Readings Below Limit		
Mod to EUT	None			Test Performed By	Alexander Sowinski		

4.5.2 Test Procedure

Antenna port conducted emission tests were performed using the procedures of FCC 47 CFR Part 15.247 (d), RSS-247 (5.5) and/or ANSI C63.10 including methods for signal maximizations and EUT configuration. The EUT was placed in the test chamber and connected directly to the spectrum analyzer via temporary SMA connection. Peak measurements were taken with RBW = 100 kHz on each of the low, mid, and high channels utilizing both the LoRa and FSK transmission schemes of the EUT.

4.5.3 Deviations

There were no deviations from the test methodology listed in the test plan for the out of band emissions test.

4.5.4 Final Test

The reading from the EUT were below the limits specified by the relevant standard.

Test report no.: US21127L.001 Rev.:01

Page 34 of 78
 Seite 34 von 78


Prüfbericht-Nr.:

4.5.5 Final Data

Table 4: Conducted Out of Band Emissions – EUT power setting @ 14 dBm


Type	Freq MHz	Level dBm	Limit dBm	Margin dB			Type	Freq MHz	Level dBm	Limit dBm	Margin dB
LoRa	903.00	15.27	N/A	N/A			FSK	903.00	15.25	N/A	N/A
	2708.22	-42.73	-4.73	-38.00				2708.22	-43.40	-4.75	-38.65
	7229.52	-41.78	-4.73	-37.05				5184.86	-41.32	-4.75	-36.57
LoRa	915.00	15.35	N/A	N/A			FSK	915.00	15.18	N/A	N/A
	7315.91	-40.79	-4.65	-36.14				2737.02	-43.89	-4.82	-39.07
								7315.91	-42.48	-4.82	-37.66
LoRa	927.00	15.36	N/A	N/A			FSK	927.00	15.21	N/A	N/A
	7402.31	-40.93	-4.64	-36.29				7402.31	-39.11	-4.79	-34.32

4.5.6 Final Plots



Date: 24.JUN.2021 04:15:58

Figure 25 – Low Channel Conducted Spurious Emissions (LoRa)



Date: 24.JUN.2021 04:27:31

Figure 26 – Mid Channel Conducted Spurious Emissions (LoRa)