

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan
District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM130100014501
Page: 1 of 19

FCC REPORT

Application No.:	SZEM1301000145RF(GZEM1301000090RF)
Applicant:	Guangzhou Wong Da Hardware & Knitwear co., Ltd.
Manufacturer:	Guangzhou Wong Da Hardware & Knitwear co., Ltd.
Factory:	Guangzhou Wong Da Hardware & Knitwear co., Ltd.
Buyer:	RMD Technologies, LLC
Product Name:	D-Mometer 232T
Model No.(EUT):	D-Mometer 232T
FCC ID:	S5S232T
Standards:	47 CFR Part 15, Subpart C (2011)
Date of Receipt:	2013-01-10
Date of Test:	2013-02-01 to 2013-02-06
Date of Issue:	2013-03-22
Test Result:	PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

2 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203	ANSI C63.10(2009)	PASS
Field Strength of the Fundamental Signal	47 CFR Part 15, Subpart C Section 15.231 (e)	ANSI C63.10(2009)	PASS
Spurious Emissions	47 CFR Part 15, Subpart C Section 15.231 (e)/15.209	ANSI C63.10(2009)	PASS
20Db Bandwidth	47 CFR Part 15, Subpart C Section 15.231 ©	ANSI C63.10(2009)	PASS
Dwell Time	47 CFR Part 15, Subpart C Section 15.231 (e)	ANSI C63.10(2009)	PASS

3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	2
3 CONTENTS	3
4 GENERAL INFORMATION	4
4.1 CLIENT INFORMATION	4
4.2 GENERAL DESCRIPTION OF EUT	4
4.3 TEST ENVIRONMENT AND MODE	5
4.4 DESCRIPTION OF SUPPORT UNITS	5
4.5 TEST LOCATION	5
4.6 TEST FACILITY	6
4.7 DEVIATION FROM STANDARDS	6
4.8 ABNORMALITIES FROM STANDARD CONDITIONS	6
4.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
4.10 EQUIPMENT LIST	7
5 TEST RESULTS AND MEASUREMENT DATA	9
5.1 ANTENNA REQUIREMENT	9
5.2 SPURIOUS EMISSIONS	10
5.2.1 Field Strength Of The Fundamental Signal	12
5.2.2 Spurious Emissions	13
5.3 20dB BANDWIDTH	16
5.4 DWELL TIME	18-19



4 General Information

4.1 Client Information

Applicant:	Guangzhou Wong Da Hardware & Knitwear co., Ltd.
Address of Applicant:	SHA ZHUANG STREET ZENGCHENG CITY GUANGDONG PROVINCE CHINA
Manufacturer:	Guangzhou Wong Da Hardware & Knitwear co., Ltd.
Address of Manufacturer:	SHA ZHUANG STREET ZENGCHENG CITY GUANGDONG PROVINCE CHINA
Factory:	Guangzhou Wong Da Hardware & Knitwear co., Ltd.
Address of Factory:	SHA ZHUANG STREET ZENGCHENG CITY GUANGDONG PROVINCE CHINA
Buyer:	RMD Technologies, LLC
Address of Buyer:	635 West Michigan street, 32805 Orlando, Florida

4.2 General Description of EUT

Name:	D-Mometer 232T
Model No.:	D-Mometer 232T
Sample Type:	Portable production
Operation Frequency:	433MHz
Channel Numbers:	1
Modulation Type:	GFSK
Antenna Type:	Integral
Antenna Gain:	2.15dBi
Power Supply:	6.0V DC (1.5V x 4 "AA" Size Batteries)
Test Voltage:	6.0V DC

4.3 Test Environment and Mode

Operating Environment:	
Temperature:	25.0 °C
Humidity:	50 % RH
Atmospheric Pressure:	1015 mbar
Test mode:	
TX mode:	EUT transmitted the continuous modulation signal at the specific channel

4.4 Description of Support Units

The EUT has been tested as an independent unit.

4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,
No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**
CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.
- **VCCI**
The 3m Semi-anechoic chamber, Full-anechoic Chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2197, G-416, T-1153 and C-2383 respectively.
- **FCC – Registration No.: 556682**
SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.
- **Industry Canada (IC)**
The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1.

4.7 Deviation from Standards

None.

4.8 Abnormalities from Standard Conditions

None.

4.9 Other Information Requested by the Customer

None.

4.10 Equipment List

RE in Chamber					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	2013-06-10
2	EMI Test Receiver	Rohde & Schwarz	ESIB26	SEL0023	2013-05-17
3	EMI Test software	AUDIX	E3	SEL0050	N/A
4	Coaxial cable	SGS	N/A	SEL0027	2013-05-29
5	Coaxial cable	SGS	N/A	SEL0189	2013-05-29
6	Coaxial cable	SGS	N/A	SEL0121	2013-05-29
7	Coaxial cable	SGS	N/A	SEL0178	2013-05-29
8	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0015	2013-10-24
9	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0006	2013-10-24
10	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	2013-05-17
11	Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEL0168	2013-10-24
12	Barometer	ChangChun	DYM3	SEL0088	2013-05-24
13	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2013-10-24
14	Humidity/ Temperature Indicator	Shanghai Qixiang	ZJ1-2B	SEL0103	2013-10-24
15	Signal Generator	Rohde & Schwarz	SMY01	SEL0155	2013-10-24
16	Signal Generator (10M-27GHz)	Rohde & Schwarz	SMR27	SEL0067	2013-05-17
17	Loop Antenna	Beijing Daze	ZN30401	SEL0203	2013-06-04




RF connected test					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2013-10-24
2	Humidity/ Temperature Indicator	HYGRO	ZJ1-2B	SEL0033	2013-10-24
3	Spectrum Analyzer	Rohde & Schwarz	FSP	SEL0154	2013-10-24
4	Coaxial cable	SGS	N/A	SEL0178	2013-05-29
5	Coaxial cable	SGS	N/A	SEL0179	2013-05-29
6	Barometer	ChangChun	DYM3	SEL0088	2013-05-24
7	Signal Generator	Rohde & Schwarz	SML03	SEL0068	2013-05-17
8	Band filter	amideon	82346	SEL0094	2013-05-17
9	POWER METER	R & S	NRVS	SEL0144	2013-10-24
10	Attenuator	Beijin feihang taida	TST-2-6dB	SEL0205	2013-05-17
11	Power Divider(splitter)	Agilent Technologies	11636B	SEL0130	2013-10-24

Note: The calibration interval is one year, all the instruments are valid.

5 Test results and Measurement Data

5.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203
15.203 Requirement:	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.
EUT Antenna:	The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 2.15dBi.
	

5.2 Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.231(e) and 15.209				
Test Method:	ANSI C63.10: 2009				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit: (Spurious Emissions)	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance(m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.					
Limit: (Field strength of the fundamental signal)	Frequency	Limit (dBuV/m @3m)		Remark	
	433MHz	72.83		Average Value	
		92.83		Peak Value	

Test Procedure:	<ol style="list-style-type: none"> a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report.
Test Setup:	




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test mode:	Tx mode
Instruments Used:	Refer to section 4.10 for details
Test Results:	Pass

Measurement Data

5.2.1 Field Strength Of The Fundamental Signal

Peak value:								
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Average Limit Line (dBuV/m)	Over Limit (dB)	Polarization
433.000	2.35	11.97	27.33	70.57	57.55	72.83	-15.28	Horizontal
433.000	2.35	11.97	27.33	82.93	69.91	72.83	-2.92	Vertical

Remark:


As shown in this section, the peak field strength of any emission shall not exceed the maximum permitted average limits, So only the peak measurements were shown in the report.

5.2.2 Spurious Emissions

Below 1GHz

QP value:

Horizontal



Condition : FCC 15.231E 3m 3142C NEW HORIZONTAL


Job NO. : 0145RF

model: : TX

Freq	Cable		Antenna	Preamp	Read	Limit	Over	
	Loss	Factor	Factor	Level	Level			
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	60.070	0.80	5.06	27.27	37.34	15.94	40.00	-24.06
2	126.030	1.27	7.98	27.03	34.79	17.01	43.50	-26.49
3	191.990	1.39	6.93	26.73	29.89	11.49	43.50	-32.01
4	256.980	1.71	8.90	26.51	32.45	16.54	46.00	-29.46
5	334.580	2.02	10.39	26.66	30.14	15.88	46.00	-30.12
6	433.000	2.35	11.97	27.33	70.57	57.55	72.83	-15.28
7	866.000	3.48	19.40	26.96	38.44	34.36	52.83	-18.47



Vertical



Condition : FCC 15.231E 3m 3142C NEW VERTICAL
 Job NO. : 0145RF
 model : TX

Freq	Cable		Antenna	Preamp	Read	Limit	Over	
	MHz	dB	Loss Factor	Factor	Level			
1	60.070	0.80	5.06	27.27	43.54	22.13	40.00	-17.87
2	126.030	1.27	7.98	27.03	40.60	22.81	43.50	-20.69
3	159.980	1.34	9.50	26.86	34.57	18.55	43.50	-24.95
4	191.020	1.39	6.84	26.73	32.98	14.47	43.50	-29.03
5	433.000	2.35	11.97	27.33	82.93	69.91	72.83	-2.92
6	641.100	2.78	15.80	27.49	32.67	23.77	46.00	-22.23
7	866.000	3.48	19.40	26.96	41.15	37.07	52.83	-15.76

Above 1GHz


Peak value:

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2157.069	2.90	32.08	39.68	46.91	42.21	74	-31.79	Vertical
3120.061	3.41	33.35	40.40	48.39	44.75	74	-29.25	Vertical
4490.048	4.48	35.15	41.40	48.68	46.91	74	-27.09	Vertical
5631.725	5.00	35.09	41.24	48.98	47.83	74	-26.17	Vertical
7338.621	5.94	35.94	39.75	48.82	50.95	74	-23.05	Vertical
8527.851	6.18	36.23	38.73	47.89	51.57	74	-22.43	Vertical
2162.567	2.90	32.08	39.68	53.00	48.30	74	-25.70	Horizontal
2468.631	3.02	32.64	39.91	54.23	49.98	74	-24.02	Horizontal
3776.385	3.98	33.53	40.87	48.88	45.52	74	-28.48	Horizontal
5674.896	5.01	35.18	41.20	48.99	47.98	74	-26.02	Horizontal
7172.406	5.73	35.87	39.90	48.98	50.68	74	-23.32	Horizontal
9346.262	6.06	37.01	38.03	46.34	51.38	74	-22.62	Horizontal

Remark:


- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 2) The disturbance above 10GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.
- 3) As shown in this section, the peak field strength of any emission shall not exceed the maximum permitted average limits, So only the peak measurements were shown in the report.

5.3 20dB Bandwidth


Test Requirement:	47 CFR Part 15C Section 15.231 (c)
Test Method:	ANSI C63.10:2009
Test Setup:	
Limit:	The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.
Test Mode:	Tx mode
Instruments Used:	Refer to section 4.10 for details
Test Results:	Pass

Measurement Data

20dB bandwidth (MHz)	Limit (MHz)	Results
0.548	1.0825	Pass

Test plot as follows:


5.4 Dwell Time

Test Requirement:	47 CFR Part 15C Section 15.231(e)
Test Method:	ANSI C63.10:2009
Test Setup:	
Limit:	Not more than 5 seconds
Test Mode:	Tx mode
Instruments Used:	Refer to section 4.10 for details
Test Results:	Pass

Measurement Data

Test item	Limit (MHz)	Results
Silent period	<10s	Pass

Remark:

There is only one automatically transmitting mode for this EUT of every 20minutes.

Test plot as follows:
