

TEST REPORT

Product : 8" Tablet PC
Trade mark : Dragon Touch, KINGPAD,
KINGSLIM, AKASO
Model/Type reference : i8 Pro, i8, i8X, i8D, i8X Pro,
i88, i80, i80X, i8 Plus, i8X Plus,
i8 hybrid
Serial Number : N/A
Report Number : EED32H00215003
FCC ID : S5V-D080W1
Date of Issue : Dec. 22, 2015
Test Standards : 47 CFR Part 15 Subpart C (2014)
Test result : PASS

Prepared for:

Proexpress Distributor LLC

11011 GREENWOOD AVE. N APT5, SEATTLE, WA 98103.

Prepared by:

Centre Testing International Group Co., Ltd.

Hongwei Industrial Zone, Bao'an 70 District,

Shenzhen, Guangdong, China

TEL: +86-755-3368 3668

FAX: +86-755-3368 3385

Compiled by:

Kevin Tang

Reviewed by:

Fanon-Li

Approved by:

Sheek, Luo

Date:

Dec. 22, 2015



Sheek Luo
Lab supervisor

Check No.: 2212834822

2 Version

Version No.	Date	Description
00	Dec. 22, 2015	Original

3 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10-2013	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10-2013	PASS
Conducted (Average) Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(3)	ANSI C63.10-2013	PASS
6dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(2)	ANSI C63.10-2013	PASS
Power Spectral Density	47 CFR Part 15, Subpart C Section 15.247 (e)	ANSI C63.10-2013	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10-2013	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10-2013	PASS
Radiated Spurious Emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10-2013	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10-2013	PASS

Remark:

Test according to ANSI C63.4-2014 & ANSI C63.10-2013.

The tested sample(s) and the sample information are provided by the client.

Model No.: i8 Pro, i8, i8X, i8D, i8X Pro, i88, i80, i80X, i8 Plus, i8X Plus, i8 hybrid

Only the Model i8 Pro was tested, since the electrical circuit design, layout, components used and internal wiring were identical for all above models. Only different on agent and marketing purposes.


4 Content

1 COVER PAGE	1
2 VERSION	2
3 TEST SUMMARY	3
4 CONTENT	4
5 TEST REQUIREMENT	5
5.1 TEST SETUP.....	5
5.1.1 For Conducted test setup.....	5
5.1.2 For Radiated Emissions test setup.....	5
5.1.3 For Conducted Emissions test setup.....	6
5.2 TEST ENVIRONMENT.....	6
5.3 TEST CONDITION.....	6
6 GENERAL INFORMATION	7
6.1 CLIENT INFORMATION.....	7
6.2 GENERAL DESCRIPTION OF EUT.....	7
6.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD.....	7
6.4 DESCRIPTION OF SUPPORT UNITS.....	8
6.5 TEST LOCATION.....	8
6.6 TEST FACILITY.....	8
6.7 DEVIATION FROM STANDARDS.....	9
6.8 ABNORMALITIES FROM STANDARD CONDITIONS.....	9
6.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	9
6.10 MEASUREMENT UNCERTAINTY(95% CONFIDENCE LEVELS, K=2).....	9
7 EQUIPMENT LIST	10
8 RADIO TECHNICAL REQUIREMENTS SPECIFICATION	12
Appendix A) Conducted (Average) Output Power.....	13
Appendix B) 6dB Occupied Bandwidth.....	18
Appendix C) Band-edge for RF Conducted Emissions.....	23
Appendix D) RF Conducted Spurious Emissions.....	27
Appendix E) Power Spectral Density.....	36
Appendix F) Antenna Requirement.....	41
Appendix G) AC Power Line Conducted Emission.....	42
Appendix H) Restricted bands around fundamental frequency (Radiated).....	45
Appendix I) Radiated Spurious Emissions.....	47
PHOTOGRAPHS OF TEST SETUP	56
PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	58

5 Test Requirement

5.1 Test setup

5.1.1 For Conducted test setup



5.1.2 For Radiated Emissions test setup

Radiated Emissions setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz





Figure 3. Above 1GHz

5.1.3 For Conducted Emissions test setup Conducted Emissions setup



5.2 Test Environment

Operating Environment:	
Temperature:	24 °C
Humidity:	50 % RH
Atmospheric Pressure:	1010mbar

5.3 Test Condition

Test channel:

Test Mode	Tx/Rx	RF Channel		
		Low(L)	Middle(M)	High(H)
802.11b/g/n(HT20)	2412MHz ~2462 MHz	Channel 1	Channel 6	Channel11
		2412MHz	2437MHz	2462MHz
802.11n(HT40)	2422MHz ~2452 MHz	Channel 1	Channel 4	Channel7
		2422MHz	2437MHz	2452MHz
Transmitting mode:	The EUT transmitted the continuous modulation test signal at the specific channel(s).			

Test mode:

Pre-scan under all rate at lowest channel 1

Mode	802.11b				X								
	1Mbps	2Mbps	5.5Mbps	11Mbps									
Power(dBm)	8.04	8.38	8.52	8.64									
Mode	802.11g												
Data Rate	6Mbps	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps					
Power(dBm)	8.06	8.01	7.96	7.81	7.73	7.65	7.48	7.41					
Mode	802.11n (HT20)												
Data Rate	6.5Mbps	13Mbps	19.5Mbps	26Mbps	39Mbps	52Mbps	58.5Mbps	65Mbps					
Power(dBm)	7.43	7.41	7.38	7.22	7.20	7.19	7.15	7.09					
Mode	802.11n (HT40)												
Data Rate	13.5Mbps	27Mbps	40.5Mbps	54Mbps	81Mbps	108Mbps	121.5Mbps	135Mbps					
Power(dBm)	6.51	6.50	6.48	6.42	6.33	6.01	6.00	5.98					

Through Pre-scan, 11Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n (HT20); 13.5Mbps of rate is the worst case of 802.11n (HT40).

6 General Information

6.1 Client Information

Applicant:	Proexpress Distributor LLC
Address of Applicant:	11011 GREENWOOD AVE. N APT5, SEATTLE, WA 98103.
Manufacturer:	Proexpress Distributor LLC
Address of Manufacturer:	11011 GREENWOOD AVE. N APT5, SEATTLE, WA 98103.

6.2 General Description of EUT

Product Name:	8" Tablet PC	
Model No.:	i8 Pro, i8, i8X, i8D, i8X Pro, i88, i80, i80X, i8 Plus, i8X Plus, i8 hybrid	
Test Model No.:	i8 Pro	
Trade mark:	Dragon Touch, KINGPAD, KINGSLIM, AKASO	
EUT Supports Radios application:	Wlan 2.4GHz 802.11b/g/n(HT20&HT40)	
Power Supply:	Adapter:	AC 100-240V, 50/60Hz Output: DC 5.0V, 2000mA
	Battery:	DC 3.7V, 4000mA
AC Adapter line:	120cm(Unshielded)	
Sample Received Date:	Nov. 11, 2015	
Sample tested Date:	Nov. 11, 2015 to Dec. 07, 2015	

6.3 Product Specification subjective to this standard

Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422MHz to 2452MHz
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels IEEE 802.11n HT40: 7 Channels
Channel Separation:	5MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK, DQPSK, DBPSK) IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20 and HT40) : OFDM (64QAM, 16QAM, QPSK, BPSK)
Sample Type:	Portable production
Test Power Grade:	802.11b: 36, 802.11g: 43, 802.11n(HT20): 42, 802.11n(HT40): 42 (manufacturer declare)
Test Software of EUT:	REALTEK 11n 8723BS SDIO WLAN NIC Massproduction kit (manufacturer declare)
Antenna Type and Gain:	Type: Internal antenna Gain:2.2dBi
Test Voltage:	

Operation Frequency each of channel(802.11b/g/n HT20)

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Operation Frequency each of channel(802.11n HT40)					
Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2422MHz	4	2437MHz	7	2452MHz
2	2427MHz	5	2442MHz		
3	2432MHz	6	2447MHz		

6.4 Description of Support Units

The EUT has been tested with associated equipment below.

Description	Manufacturer	Model No.	Certification	Supplied by
Mobile Phone	SAMSUNG	GT-I9082i	FCC DOC	CTI
Router	TP-Link	TL-WR340G+	FCC DOC	CTI

6.5 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd.

Hongwei Industrial Zone, Bao'an 70 District, Shenzhen, Guangdong, China518101

Telephone: +86 (0) 755 3368 3668 Fax:+86 (0) 755 3368 3385

No tests were sub-contracted.

6.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L1910

Centre Testing International Group Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories..

A2LA-Lab Cert. No. 3061.01

Centre Testing International Group Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 565659

Centre Testing International Group Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 565659.

IC-Registration No.: 7408A

The 3m Alternate Test Site of Centre Testing International Group Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 7408A .

IC-Registration No.: 7408B

The 10m Alternate Test Site of Centre Testing International Group Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 7408B.

NEMKO-Aut. No.: ELA503

Centre Testing International Group Co., Ltd. has been assessed the quality assurance system, the testing facilities, qualifications and testing practices of the relevant parts of the organization. The quality assurance system of the Laboratory has been validated against ISO/IEC 17025 or equivalent. The laboratory also fulfills the conditions described in Nemko Document NLA-10.

VCCI

The Radiation 3 & 10 meters site of Centre Testing International Group Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-4096.

Main Ports Conducted Interference Measurement of Centre Testing International Group Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: C-4563.

Telecommunication Ports Conducted Disturbance Measurement of Centre Testing International Group Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: T-2146.

The Radiation 3 meters site of Centre Testing International Group Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-758

6.7 Deviation from Standards

None.

6.8 Abnormalities from Standard Conditions

None.

6.9 Other Information Requested by the Customer

None.

6.10 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.9×10^{-8}
2	RF power, conducted	0.31dB (30MHz-1GHz)
		0.57dB (1GHz-18GHz)
3	Radiated Spurious emission test	4.5dB (30MHz-1GHz)
		4.8dB (1GHz-12.75GHz)
4	Conduction emission	3.6dB (9kHz to 150kHz)
		3.2dB (150kHz to 30MHz)
5	Temperature test	0.64°C
6	Humidity test	2.8%
7	DC power voltages	0.025%

7 Equipment List

RF test system					
Equipment	Manufacturer	Mode No.	Serial Number	Cal. Date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Signal Generator	Keysight	E8257D	MY53401106	04-14-2015	04-13-2016
Communication test set test set	Agilent	N4010A	MY47230124	04-02-2015	04-01-2016
Spectrum Analyzer	Keysight	N9010A	MY54510339	04-01-2015	03-31-2016
Attenuator	HuaXiang	SHX370	15040701	04-01-2015	03-31-2016
Signal Generator	Keysight	N5182B	MY53051549	03-31-2015	03-30-2016
High-pass filter(3-18GHz)	Sinoscite	FL3CX03WG18 NM12-0398-002	---	01-13-2015	01-12-2016
High-pass filter(5-18GHz)	MICRO-TRONICS	SPA-F-63029-4	---	01-13-2015	01-12-2016
band rejection filter (GSM900)	Sinoscite	FL5CX01CA09C L12-0395-001	---	01-13-2015	01-12-2016
band rejection filter (GSM850)	Sinoscite	FL5CX01CA08C L12-0393-001	---	01-13-2015	01-12-2016
band rejection filter (GSM1800)	Sinoscite	FL5CX02CA04C L12-0396-002	---	01-13-2015	01-12-2016
band rejection filter (GSM1900)	Sinoscite	FL5CX02CA03C L12-0394-001	---	01-13-2015	01-12-2016
DC Power	Keysight	E3642A	MY54436035	03-31-2015	03-30-2016
PC-1	Lenovo	R4960d	---	04-01-2015	03-31-2016
BT&WI-FI Automatic control	R&S	OSPB157	101374	04-01-2015	03-31-2016
RF control unit	JS Tonscend	JS0806-2	2015860006	04-01-2015	03-31-2016
BT&WI-FI Automatic test software	JS Tonscend	JSTS1120-2	---	04-01-2015	03-31-2016

Conducted disturbance Test					
Equipment	Manufacturer	Mode No.	Serial Number	Cal. date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Receiver	R&S	ESCI	100435	06-30-2015	06-28-2016
Receiver	R&S	ESCI	100009	06-30-2015	06-28-2016
Temperature/ Humidity Indicator	Belida	TT-512	101	07-09-2015	07-07-2016
Communication test set	Agilent	E5515C	GB47050533	01-13-2015	01-12-2016
Communication test set	R&S	CMW500	152394	04-19-2015	04-18-2016
LISN	R&S	ENV216	100098	06-30-2015	06-28-2016
LISN	schwarzbeck	NNLK8121	8121-529	06-30-2015	06-28-2016
Voltage Probe	R&S	ESH2-Z3	100042	07-09-2014	07-08-2017
Current Probe	R&S	EZ17	100106	07-09-2014	07-08-2017
ISN	TESEQ GmbH	ISN T800	30297	01-29-2015	01-27-2017

3M Semi/full-anechoic Chamber					
Equipment	Manufacturer	Mode No.	Serial Number	Cal. date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
3M Chamber	TDK	SAC-3	---	06-02-2013	06-01-2016
TRILOG Broadband Antenna	schwarzbeck	VULB9163	9163-617	07-31-2015	07-29-2016
Microwave Pre-amplifier	Agilent	8449B	3008A02425	02-05-2015	02-04-2016
Horn Antenna	ETS-LINDGREN	3117	00057410	06-30-2015	06-28-2018
Loop Antenna	ETS	6502	00071730	07-30-2015	07-28-2017
Spectrum Analyzer	R&S	FSP40	100416	06-30-2015	06-28-2016
Receiver	R&S	ESCI	100435	06-30-2015	06-28-2016
Multi device Controller	maturio	NCD/070/10711112	---	01-13-2015	01-12-2016
LISN	schwarzbeck	NNBM8125	81251547	06-30-2015	06-28-2016
LISN	schwarzbeck	NNBM8125	81251548	06-30-2015	06-28-2016
Signal Generator	Agilent	E4438C	MY45095744	04-19-2015	04-18-2016
Signal Generator	Keysight	E8257D	MY53401106	04-14-2015	04-13-2016
Temperature/Humidity Indicator	TAYLOR	1451	1905	07-08-2015	07-06-2016
Communication test set	Agilent	E5515C	GB47050533	01-13-2015	01-12-2016
Cable line	Fulai(7M)	SF106	5219/6A	01-13-2015	01-12-2016
Cable line	Fulai(6M)	SF106	5220/6A	01-13-2015	01-12-2016
Cable line	Fulai(3M)	SF106	5216/6A	01-13-2015	01-12-2016
Cable line	Fulai(3M)	SF106	5217/6A	01-13-2015	01-12-2016
Communication test set	R&S	CMW500	152394	04-19-2015	04-18-2016
High-pass filter(3-18GHz)	Sinoscite	FL3CX03WG18NM 12-0398-002	---	01-13-2015	01-12-2016
High-pass filter(5-18GHz)	MICRO-TRONICS	SPA-F-63029-4	---	01-13-2015	01-12-2016
band rejection filter	Sinoscite	FL5CX01CA09CL1 2-0395-001	---	01-13-2015	01-12-2016
band rejection filter	Sinoscite	FL5CX01CA08CL1 2-0393-001	---	01-13-2015	01-12-2016
band rejection filter	Sinoscite	FL5CX02CA04CL1 2-0396-002	---	01-13-2015	01-12-2016
band rejection filter	Sinoscite	FL5CX02CA03CL1 2-0394-001	---	01-13-2015	01-12-2016

8 Radio Technical Requirements Specification

Reference documents for testing:

No.	Identity	Document Title
1	FCC Part15C (2014)	Subpart C-Intentional Radiators
2	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices

Test Results List:


Test Requirement	Test method	Test item	Verdict	Note
Part15C Section 15.247 (b)(3)	ANSI C63.10	Conducted (Average) Output Power	PASS	Appendix A)
Part15C Section 15.247 (a)(2)	ANSI C63.10	6dB Occupied Bandwidth	PASS	Appendix B)
Part15C Section 15.247(d)	ANSI C63.10	Band-edge for RF Conducted Emissions	PASS	Appendix C)
Part15C Section 15.247(d)	ANSI C63.10	RF Conducted Spurious Emissions	PASS	Appendix D)
Part15C Section 15.247 (e)	ANSI C63.10	Power Spectral Density	PASS	Appendix E)
Part15C Section 15.203/15.247 (c)	ANSI C63.10	Antenna Requirement	PASS	Appendix F)
Part15C Section 15.207	ANSI C63.10	AC Power Line Conducted Emission	PASS	Appendix G)
Part15C Section 15.205/15.209	ANSI C63.10	Restricted bands around fundamental frequency (Radiated Emission)	PASS	Appendix H)
Part15C Section 15.205/15.209	ANSI C63.10	Radiated Spurious Emissions	PASS	Appendix I)




Appendix A) Conducted (Average) Output Power




Result Table




Mode	Channel	Conducted Average Output Power [dBm]	Verdict	Remark
11B	LCH	8.25	PASS	RMS detector
11B	MCH	8.63	PASS	
11B	HCH	8.64	PASS	
11G	LCH	8.06	PASS	
11G	MCH	7.77	PASS	
11G	HCH	7.77	PASS	
11N20SISO	LCH	7	PASS	
11N20SISO	MCH	7.23	PASS	
11N20SISO	HCH	7.43	PASS	
11N40SISO	LCH	6.13	PASS	
11N40SISO	MCH	6.36	PASS	
11N40SISO	HCH	6.51	PASS	

Test Graph



<p>11B/MCH</p>	 <p>Keyight Spectrum Analyzer - Channel Power</p> <p>Center Freq: 2.437000000 GHz</p> <p>Channel Power: 8.63 dBm / 20 MHz</p> <p>Power Spectral Density: -64.38 dBm / Hz</p>
<p>11B/HCH</p>	 <p>Keyight Spectrum Analyzer - Channel Power</p> <p>Center Freq: 2.462000000 GHz</p> <p>Channel Power: 8.64 dBm / 20 MHz</p> <p>Power Spectral Density: -64.37 dBm / Hz</p>
<p>11G/LCH</p>	 <p>Keyight Spectrum Analyzer - Channel Power</p> <p>Center Freq: 2.412000000 GHz</p> <p>Channel Power: 8.06 dBm / 20 MHz</p> <p>Power Spectral Density: -64.95 dBm / Hz</p>

<p>11G/MCH</p>	 <p>Keyight Spectrum Analyzer - Channel Power</p> <p>Center Freq: 2.437000000 GHz</p> <p>Channel Power: 7.77 dBm / 20 MHz</p> <p>Power Spectral Density: -65.24 dBm / Hz</p>
<p>11G/HCH</p>	 <p>Keyight Spectrum Analyzer - Channel Power</p> <p>Center Freq: 2.462000000 GHz</p> <p>Channel Power: 7.77 dBm / 20 MHz</p> <p>Power Spectral Density: -65.24 dBm / Hz</p>
<p>11N20SISO/LCH</p>	 <p>Keyight Spectrum Analyzer - Channel Power</p> <p>Center Freq: 2.412000000 GHz</p> <p>Channel Power: 7.00 dBm / 20 MHz</p> <p>Power Spectral Density: -66.01 dBm / Hz</p>

<p>11N20SISO/MCH</p>	 <p>Keysight Spectrum Analyzer - Channel Power</p> <p>Center Freq: 2.437000000 GHz</p> <p>Ref Offset: 23.76 dB Ref: 30.00 dBm</p> <p>Channel Power: 7.23 dBm / 20 MHz</p> <p>Power Spectral Density: -65.78 dBm / Hz</p>
<p>11N20SISO/HCH</p>	 <p>Keysight Spectrum Analyzer - Channel Power</p> <p>Center Freq: 2.462000000 GHz</p> <p>Ref Offset: 23.76 dB Ref: 30.00 dBm</p> <p>Channel Power: 7.43 dBm / 20 MHz</p> <p>Power Spectral Density: -65.58 dBm / Hz</p>
<p>11N40SISO/LCH</p>	 <p>Keysight Spectrum Analyzer - Channel Power</p> <p>Center Freq: 2.422000000 GHz</p> <p>Ref Offset: 23.76 dB Ref: 30.00 dBm</p> <p>Channel Power: 6.13 dBm / 40 MHz</p> <p>Power Spectral Density: -69.90 dBm / Hz</p>




Appendix B) 6dB Occupied Bandwidth

Result Table

Mode	Channel	6dB Bandwidth [MHz]	99% OBW [MHz]	Verdict	Remark
11B	LCH	10.05	15.294	PASS	Peak detector
11B	MCH	9.098	15.199	PASS	
11B	HCH	10.01	15.227	PASS	
11G	LCH	16.34	17.017	PASS	
11G	MCH	16.35	17.066	PASS	
11G	HCH	16.36	17.037	PASS	
11N20SISO	LCH	17.57	18.202	PASS	
11N20SISO	MCH	16.49	16.870	PASS	
11N20SISO	HCH	16.44	16.736	PASS	
11N40SISO	LCH	35.28	53.326	PASS	
11N40SISO	MCH	35.40	52.147	PASS	
11N40SISO	HCH	35.70	51.345	PASS	

Test Graph



<p>11B/MCH</p>	<p>KeySight Spectrum Analyzer - Occupied BW</p> <p>Center Freq: 2.437000000 GHz</p> <p>Ref Offset: 23.76 dB Ref: 30.00 dBm</p> <p>Center Freq: 2.437000000 GHz</p> <p>Span: 40 MHz Sweep: 4.267 ms</p> <p>Occupied Bandwidth: 15.199 MHz</p> <p>Total Power: 12.3 dBm</p> <p>Transmit Freq Error: 40.079 kHz</p> <p>OBW Power: 99.00 %</p> <p>x dB Bandwidth: 9.098 MHz</p> <p>x dB: -6.00 dB</p>
<p>11B/HCH</p>	<p>KeySight Spectrum Analyzer - Occupied BW</p> <p>Center Freq: 2.462000000 GHz</p> <p>Ref Offset: 23.76 dB Ref: 30.00 dBm</p> <p>Center Freq: 2.462000000 GHz</p> <p>Span: 40 MHz Sweep: 4.267 ms</p> <p>Occupied Bandwidth: 15.227 MHz</p> <p>Total Power: 12.4 dBm</p> <p>Transmit Freq Error: 9.656 kHz</p> <p>OBW Power: 99.00 %</p> <p>x dB Bandwidth: 10.01 MHz</p> <p>x dB: -6.00 dB</p>
<p>11G/LCH</p>	<p>KeySight Spectrum Analyzer - Occupied BW</p> <p>Center Freq: 2.412000000 GHz</p> <p>Ref Offset: 23.76 dB Ref: 30.00 dBm</p> <p>Center Freq: 2.412000000 GHz</p> <p>Span: 40 MHz Sweep: 4.267 ms</p> <p>Occupied Bandwidth: 17.017 MHz</p> <p>Total Power: 6.19 dBm</p> <p>Transmit Freq Error: -9.630 kHz</p> <p>OBW Power: 99.00 %</p> <p>x dB Bandwidth: 16.34 MHz</p> <p>x dB: -6.00 dB</p>

<p>11G/MCH</p>	<p>Keyight Spectrum Analyzer - Occupied BW</p> <p>Center Freq: 2.437000000 GHz</p> <p>Ref Offset: 23.76 dB Ref: 30.00 dBm</p> <p>Center: 2.437 GHz #Res BW: 100 kHz</p> <p>Span: 40 MHz Sweep: 4.267 ms</p> <p>#VBW: 300 kHz</p> <p>Occupied Bandwidth: 17.066 MHz</p> <p>Total Power: 6.22 dBm</p> <p>Transmit Freq Error: 11.891 kHz</p> <p>x dB Bandwidth: 16.35 MHz</p> <p>OBW Power: 99.00 %</p> <p>x dB: -6.00 dB</p>
<p>11G/HCH</p>	<p>Keyight Spectrum Analyzer - Occupied BW</p> <p>Center Freq: 2.462000000 GHz</p> <p>Ref Offset: 23.76 dB Ref: 30.00 dBm</p> <p>Center: 2.462 GHz #Res BW: 100 kHz</p> <p>Span: 40 MHz Sweep: 4.267 ms</p> <p>#VBW: 300 kHz</p> <p>Occupied Bandwidth: 17.037 MHz</p> <p>Total Power: 6.35 dBm</p> <p>Transmit Freq Error: -8.210 kHz</p> <p>x dB Bandwidth: 16.36 MHz</p> <p>OBW Power: 99.00 %</p> <p>x dB: -6.00 dB</p>
<p>11N20SISO/LCH</p>	<p>Keyight Spectrum Analyzer - Occupied BW</p> <p>Center Freq: 2.412000000 GHz</p> <p>Ref Offset: 23.76 dB Ref: 30.00 dBm</p> <p>Center: 2.412 GHz #Res BW: 100 kHz</p> <p>Span: 40 MHz Sweep: 4.267 ms</p> <p>#VBW: 300 kHz</p> <p>Occupied Bandwidth: 18.202 MHz</p> <p>Total Power: 5.49 dBm</p> <p>Transmit Freq Error: 21.325 kHz</p> <p>x dB Bandwidth: 17.57 MHz</p> <p>OBW Power: 99.00 %</p> <p>x dB: -6.00 dB</p>

<p>11N20SISO/MCH</p>	<p>KeySight Spectrum Analyzer - Occupied BW</p> <p>Center Freq 2.437000000 GHz</p> <p>Center Freq: 2.437000000 GHz</p> <p>Ref Offset 23.76 dB Ref 30.00 dBm</p> <p>Center 2.437 GHz</p> <p>#Res BW 100 kHz</p> <p>#VBW 300 kHz</p> <p>Span 40 MHz</p> <p>Sweep 4.267 ms</p> <p>Occupied Bandwidth 16.870 MHz</p> <p>Total Power 5.63 dBm</p> <p>Transmit Freq Error 50.435 kHz</p> <p>OBW Power 99.00 %</p> <p>x dB Bandwidth 16.49 MHz</p> <p>x dB -6.00 dB</p>
<p>11N20SISO/HCH</p>	<p>KeySight Spectrum Analyzer - Occupied BW</p> <p>Center Freq 2.462000000 GHz</p> <p>Center Freq: 2.462000000 GHz</p> <p>Ref Offset 23.76 dB Ref 30.00 dBm</p> <p>Center 2.462 GHz</p> <p>#Res BW 100 kHz</p> <p>#VBW 300 kHz</p> <p>Span 40 MHz</p> <p>Sweep 4.267 ms</p> <p>Occupied Bandwidth 16.736 MHz</p> <p>Total Power 6.15 dBm</p> <p>Transmit Freq Error 917 Hz</p> <p>OBW Power 99.00 %</p> <p>x dB Bandwidth 16.44 MHz</p> <p>x dB -6.00 dB</p>
<p>11N40SISO/LCH</p>	<p>KeySight Spectrum Analyzer - Occupied BW</p> <p>Center Freq 2.422000000 GHz</p> <p>Center Freq: 2.422000000 GHz</p> <p>Ref Offset 23.76 dB Ref 30.00 dBm</p> <p>Center 2.422 GHz</p> <p>#Res BW 100 kHz</p> <p>#VBW 300 kHz</p> <p>Span 80 MHz</p> <p>Sweep 8 ms</p> <p>Occupied Bandwidth 53.326 MHz</p> <p>Total Power 4.42 dBm</p> <p>Transmit Freq Error 354.57 kHz</p> <p>OBW Power 99.00 %</p> <p>x dB Bandwidth 35.28 MHz</p> <p>x dB -6.00 dB</p>







Appendix C) Band-edge for RF Conducted Emissions


Result Table


Mode	Channel	Carrier Power[dBm]	Max.Spurious Level [dBm]	Limit [dBm]	Verdict
11B	LCH	3.203	-46.734	-26.8	PASS
11B	HCH	3.731	-45.901	-26.27	PASS
11G	LCH	0.429	-45.990	-29.57	PASS
11G	HCH	1.686	-44.937	-28.31	PASS
11N20SISO	LCH	-0.808	-45.865	-30.81	PASS
11N20SISO	HCH	0.636	-45.076	-29.36	PASS
11N40SISO	LCH	-4.069	-45.355	-34.07	PASS
11N40SISO	HCH	-3.729	-44.195	-33.73	PASS

Test Graph



<p>11B/HCH</p>		<p>Frequency</p> <p>Auto Tune</p> <p>Center Freq 2.475000000 GHz</p> <p>Start Freq 2.450000000 GHz</p> <p>Stop Freq 2.500000000 GHz</p> <p>CF Step 5.000000 MHz</p> <p>Freq Offset 0 Hz</p>
<p>11G/LCH</p>		<p>Frequency</p> <p>Auto Tune</p> <p>Center Freq 2.387500000 GHz</p> <p>Start Freq 2.355000000 GHz</p> <p>Stop Freq 2.420000000 GHz</p> <p>CF Step 6.500000 MHz</p> <p>Freq Offset 0 Hz</p>
<p>11G/HCH</p>		<p>Frequency</p> <p>Auto Tune</p> <p>Center Freq 2.475000000 GHz</p> <p>Start Freq 2.450000000 GHz</p> <p>Stop Freq 2.500000000 GHz</p> <p>CF Step 5.000000 MHz</p> <p>Freq Offset 0 Hz</p>








Appendix D) RF Conducted Spurious Emissions

Result Table



Mode	Channel	Pref [dBm]	Puw[dBm]	Verdict
11B	LCH	-4.111	<Limit	PASS
11B	MCH	-3.645	<Limit	PASS
11B	HCH	-3.525	<Limit	PASS
11G	LCH	-3.459	<Limit	PASS
11G	MCH	-2.52	<Limit	PASS
11G	HCH	-2.484	<Limit	PASS
11N20SISO	LCH	-3.437	<Limit	PASS
11N20SISO	MCH	-2.721	<Limit	PASS
11N20SISO	HCH	-2.953	<Limit	PASS
11N40SISO	LCH	-7.329	<Limit	PASS
11N40SISO	MCH	-6.572	<Limit	PASS
11N40SISO	HCH	-6.607	<Limit	PASS

Test Graph









11B_HCH_Graphs





11G_LCH_Graphs













11N20SISO_HCH_Graphs



11N40SISO_LCH_Graphs











Appendix E) Power Spectral Density Result Table




Mode	Channel	Power Spectral Density [dBm]	Verdict
11B	LCH	-17.141	PASS
11B	MCH	-17.402	PASS
11B	HCH	-17.451	PASS
11G	LCH	-25.990	PASS
11G	MCH	-25.071	PASS
11G	HCH	-24.949	PASS
11N20SISO	LCH	-26.708	PASS
11N20SISO	MCH	-25.696	PASS
11N20SISO	HCH	-26.362	PASS
11N40SISO	LCH	-30.675	PASS
11N40SISO	MCH	-29.949	PASS
11N40SISO	HCH	-30.524	PASS


Test Graph



<p>11B/MCH</p>	<p>KeySight Spectrum Analyzer - Sweep SA Center Freq 2.43700000 GHz Ref Offset 23.76 dB Ref 10.00 dBm Mkr1 2.438 965 GHz -17.402 dBm 10 dB/div Log Center 2.437000 GHz #Res BW 3.0 kHz #VBW 10 kHz Sweep 1.439 s (1001 pts) Span 13.65 MHz</p>
<p>11B/HCH</p>	<p>KeySight Spectrum Analyzer - Sweep SA Center Freq 2.46200000 GHz Ref Offset 23.76 dB Ref 10.00 dBm Mkr1 2.462 811 GHz -17.451 dBm 10 dB/div Log Center 2.462000 GHz #Res BW 3.0 kHz #VBW 10 kHz Sweep 1.583 s (1001 pts) Span 15.02 MHz</p>
<p>11G/LCH</p>	<p>KeySight Spectrum Analyzer - Sweep SA Center Freq 2.41200000 GHz Ref Offset 23.76 dB Ref 10.00 dBm Mkr1 2.413 201 GHz -25.990 dBm 10 dB/div Log Center 2.412000 GHz #Res BW 3.0 kHz #VBW 10 kHz Sweep 2.584 s (1001 pts) Span 24.31 MHz</p>

<p>11G/MCH</p>	
<p>11G/HCH</p>	
<p>11N20SISO/LCH</p>	

<p>11N20SISO/MCH</p>	
<p>11N20SISO/HCH</p>	
<p>11N40SISO/LCH</p>	



Appendix F) Antenna Requirement

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 2.2dBi.



Appendix G) AC Power Line Conducted Emission

<p>Test Procedure:</p>	<p>Test frequency range :150KHz-30MHz</p> <ol style="list-style-type: none"> 1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement. 																
<p>Limit:</p>	<table border="1" data-bbox="499 1151 1366 1373"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBμV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table> <p>* The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.</p> <p>NOTE : The lower limit is applicable at the transition frequency</p>			Frequency range (MHz)	Limit (dB μ V)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dB μ V)																
	Quasi-peak	Average															
0.15-0.5	66 to 56*	56 to 46*															
0.5-5	56	46															
5-30	60	50															


Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.


Live line:

80.0 dBuV



No.	Freq. MHz	Reading_Level (dBuV)			Correct Factor dB	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1860	44.29	41.00	20.69	9.80	54.09	50.80	30.49	64.21	54.21	-13.41	-23.72	P	
2	0.4020	39.92	36.90	18.57	9.90	49.82	46.80	28.47	57.81	47.81	-11.01	-19.34	P	
3	0.5780	38.06	35.20	13.49	9.90	47.96	45.10	23.39	56.00	46.00	-10.90	-22.61	P	
4	1.0580	36.79	33.00	14.22	10.00	46.79	43.00	24.22	56.00	46.00	-13.00	-21.78	P	
5	2.2700	34.11	31.04	14.85	10.00	44.11	41.04	24.85	56.00	46.00	-14.96	-21.15	P	
6	6.6300	37.70	34.00	16.51	10.00	47.70	44.00	26.51	60.00	50.00	-16.00	-23.49	P	

Neutral line:
80.0 dBuV



No.	Freq. MHz	Reading_Level (dBuV)			Correct Factor dB	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1940	45.26	41.20	26.86	9.80	55.06	51.00	36.66	63.86	53.86	-12.86	-17.20	P	
2	0.5860	42.35	38.62	17.63	9.90	52.25	48.52	27.53	56.00	46.00	-7.48	-18.47	P	
3	1.2660	41.64	37.30	21.17	10.00	51.64	47.30	31.17	56.00	46.00	-8.70	-14.83	P	
4	2.3660	42.73	38.37	19.60	10.00	52.73	48.37	29.60	56.00	46.00	-7.63	-16.40	P	
5	6.0020	41.63	37.60	20.96	10.00	51.63	47.60	30.96	60.00	50.00	-12.40	-19.04	P	
6	26.3260	36.52	33.20	19.94	10.37	46.89	43.57	30.31	60.00	50.00	-16.43	-19.69	P	

Notes:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.

Appendix H) Restricted bands around fundamental frequency (Radiated)

Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
Peak		1MHz	10Hz	Average	
Test Procedure:	<p>Below 1GHz test procedure as below:</p> <ol style="list-style-type: none"> The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel <p>Above 1GHz test procedure as below:</p> <ol style="list-style-type: none"> Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre). Test the EUT in the lowest channel , the Highest channel The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is worse case. Repeat above procedures until all frequencies measured was complete. 				
Limit:	Frequency	Limit (dB μ V/m @3m)	Remark		
	30MHz-88MHz	40.0	Quasi-peak Value		
	88MHz-216MHz	43.5	Quasi-peak Value		
	216MHz-960MHz	46.0	Quasi-peak Value		
	960MHz-1GHz	54.0	Quasi-peak Value		
	Above 1GHz	54.0	Average Value		
		74.0	Peak Value		

Test plot as follows:

Worse case mode:		802.11b (11Mbps)								
Frequency (MHz)	Read Level (dBμV)	Level (dBμV/m)	Antenna Factor (dB/m)	Cable Loss (dB)	Premap Factor (dB)	Limit (dBμV/m)	Over Limit (dB)	Antenna Polaxis	Remark	Test channel
2390.00	44.94	44.54	32.53	4.28	37.21	74	-29.46	H	PK	Lowest
2390.00	44.15	43.75	32.53	4.28	37.21	74	-30.25	V	PK	Lowest
2483.50	44.87	44.90	32.71	4.51	37.19	74	-29.10	H	PK	Highest
2483.50	44.72	44.75	32.71	4.51	37.19	74	-29.25	V	PK	Highest

Worse case mode:		802.11g (6Mbps)								
Frequency (MHz)	Read Level (dBμV)	Level (dBμV/m)	Antenna Factor (dB/m)	Cable Loss (dB)	Premap Factor (dB)	Limit (dBμV/m)	Over Limit (dB)	Antenna Polaxis	Remark	Test channel
2390.00	45.64	45.24	32.53	4.28	37.21	74	-28.76	H	PK	Lowest
2390.00	45.64	45.24	32.53	4.28	37.21	74	-28.76	V	PK	Lowest
2483.50	48.68	48.71	32.71	4.51	37.19	74	-25.29	H	PK	Highest
2483.50	45.64	45.67	32.71	4.51	37.19	74	-28.33	V	PK	Highest

Worse case mode:		802.11n(HT20) (6.5Mbps)								
Frequency (MHz)	Read Level (dBμV)	Level (dBμV/m)	Antenna Factor (dB/m)	Cable Loss (dB)	Premap Factor (dB)	Limit (dBμV/m)	Over Limit (dB)	Antenna Polaxis	Remark	Test channel
2390.00	46.92	46.52	32.53	4.28	37.21	74	-27.48	H	PK	Lowest
2390.00	45.83	45.43	32.53	4.28	37.21	74	-28.57	V	PK	Lowest
2483.50	51.27	51.30	32.71	4.51	37.19	74	-22.70	H	PK	Highest
2483.50	48.52	48.55	32.71	4.51	37.19	74	-25.45	V	PK	Highest

Worse case mode:		802.11n(HT40) (13.5Mbps)								
Frequency (MHz)	Read Level (dBμV)	Level (dBμV/m)	Antenna Factor (dB/m)	Cable Loss (dB)	Premap Factor (dB)	Limit (dBμV/m)	Over Limit (dB)	Antenna Polaxis	Remark	Test channel
2390.00	44.44	44.04	32.53	4.28	37.21	74	-29.96	H	PK	Lowest
2390.00	43.78	43.38	32.53	4.28	37.21	74	-30.62	V	PK	Lowest
2483.50	48.50	48.53	32.71	4.51	37.19	74	-25.47	H	PK	Highest
2483.50	45.67	45.70	32.71	4.51	37.19	74	-28.30	V	PK	Highest

Remark:

1) Through Pre-scan transmitting mode with all kind of modulation and data rate, find the 11Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20) ; 13.5Mbps of rate is the worst case of 802.11n(HT40),and then Only the worst case is recorded in the report.

2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Pre-amplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading - Correct Factor


Correct Factor = Pre-amplifier Factor- Antenna Factor-Cable Factor

Appendix I) Radiated Spurious Emissions


Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	120 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
Peak		1MHz	10Hz	Average	
Test Procedure:					
Below 1GHz test procedure as below:					
<p>a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</p> <p>c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</p> <p>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</p>					
Above 1GHz test procedure as below:					
<p>g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre)..</p> <p>h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel</p> <p>i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is worse case.</p> <p>j. Repeat above procedures until all frequencies measured was complete.</p>					
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBµV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
<p>Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.</p>					

Radiated Spurious Emissions test Data:
Radiated Emission below 1GHz

30MHz~1GHz (QP)



	Ant Freq	Ant Factor	Cable Loss	Read Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dB/m	dB	dBuV	dBuV/m	dB		
1	105.27	12.76	1.57	9.63	23.96	43.50	-19.54	Horizontal
2	138.87	10.37	1.58	9.89	21.84	43.50	-21.66	Horizontal
3	208.58	11.75	2.24	10.36	24.35	43.50	-19.15	Horizontal
4	264.75	12.75	2.36	10.11	25.22	46.00	-20.78	Horizontal
5	290.02	13.30	2.37	9.58	25.25	46.00	-20.75	Horizontal
6 pp	377.26	15.64	2.76	9.95	28.35	46.00	-17.65	Horizontal



	Ant Freq	Ant Factor	Cable Loss	Read Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	100.93	13.12	1.57	8.78	23.47	43.50	-20.03	Vertical
2	128.11	11.06	1.58	10.67	23.31	43.50	-20.19	Vertical
3	180.02	10.90	1.98	9.86	22.74	43.50	-20.76	Vertical
4	216.02	11.88	2.26	10.13	24.27	46.00	-21.73	Vertical
5	282.99	13.15	2.37	10.07	25.59	46.00	-20.41	Vertical
6 pp	350.48	14.82	2.71	9.96	27.49	46.00	-18.51	Vertical

Transmitter Emission above 1GHz

Test mode:		802.11b		Test Frequency:		2412MHz		
Frequency (MHz)	Antenna Factor (dB/m)	Preamp Gain (dB)	Cable Loss (dB)	Read Level (dBμV)	Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Antenna Polaxis
1472.440	30.82	38.01	2.80	45.48	41.09	74	-32.91	H
1642.761	31.13	37.75	2.95	45.22	41.55	74	-32.45	H
3225.037	33.40	37.05	5.57	46.11	48.03	74	-25.97	H
4824.000	34.73	36.82	5.10	43.23	46.24	74	-27.76	H
7236.000	36.42	37.45	6.69	43.50	49.16	74	-24.84	H
9648.000	37.93	37.83	7.70	43.60	51.40	74	-22.60	H
1668.044	31.18	37.72	2.98	45.32	41.76	74	-32.24	V
1889.633	31.54	37.43	3.15	45.08	42.34	74	-31.66	V
3634.910	33.07	36.97	5.50	46.20	47.80	74	-26.20	V
4824.000	34.73	36.82	5.10	44.58	47.59	74	-26.41	V
7236.000	36.42	37.45	6.69	42.47	48.13	74	-25.87	V
9648.000	37.93	37.83	7.70	44.21	52.01	74	-21.99	V

Test mode:		802.11b		Test Frequency:		2437MHz		
Frequency (MHz)	Antenna Factor (dB/m)	Preamp Gain (dB)	Cable Loss (dB)	Read Level (dBμV)	Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Antenna Polaxis
1597.401	31.05	37.82	2.92	45.90	42.05	74	-31.95	H
1865.735	31.50	37.46	3.13	45.48	42.65	74	-31.35	H
3719.146	33.00	36.95	5.49	45.47	47.01	74	-26.99	H
4874.000	34.84	36.81	5.09	45.34	48.46	74	-25.54	H
7311.000	36.43	37.43	6.76	43.17	48.93	74	-25.07	H
9748.000	38.03	37.85	7.61	44.38	52.17	74	-21.83	H
1630.264	31.11	37.77	2.94	45.37	41.65	74	-32.35	V
3192.366	33.43	37.06	5.58	45.73	47.68	74	-26.32	V
3709.691	33.01	36.95	5.49	45.16	46.71	74	-27.29	V
4874.000	34.84	36.81	5.09	44.81	47.93	74	-26.07	V
7311.000	36.43	37.43	6.76	43.80	49.56	74	-24.44	V
9748.000	38.03	37.85	7.61	43.71	51.50	74	-22.50	V

Test mode:		802.11b		Test Frequency:		2462MHz		
Frequency (MHz)	Antenna Factor (dB/m)	Preamp Gain (dB)	Cable Loss (dB)	Read Level (dBμV)	Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Antenna Polaxis
1655.354	31.15	37.74	2.97	45.70	42.08	74	-31.92	H
2029.233	31.77	37.29	3.32	44.99	42.79	74	-31.21	H
3766.785	32.97	36.94	5.48	45.17	46.68	74	-27.32	H
4924.000	34.94	36.81	5.07	42.55	45.75	74	-28.25	H
7386.000	36.44	37.42	6.83	43.76	49.61	74	-24.39	H
9848.000	38.14	37.87	7.53	43.64	51.44	74	-22.56	H
1689.410	31.21	37.69	2.99	46.19	42.70	74	-31.30	V
1904.119	31.56	37.41	3.16	45.35	42.66	74	-31.34	V
3747.656	32.98	36.95	5.48	45.62	47.13	74	-26.87	V
4924.000	34.94	36.81	5.07	45.41	48.61	74	-25.39	V
7386.000	36.44	37.42	6.83	44.00	49.85	74	-24.15	V
9848.000	38.14	37.87	7.53	44.87	52.67	74	-21.33	V

Test mode:		802.11g		Test Frequency:		2412MHz		
Frequency (MHz)	Antenna Factor (dB/m)	Preamp Gain (dB)	Cable Loss (dB)	Read Level (dBμV)	Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Antenna Polaxis
1476.193	30.82	38.00	2.81	45.84	41.47	74	-32.53	H
1782.177	31.37	37.57	3.07	45.64	42.51	74	-31.49	H
3776.385	32.96	36.94	5.48	45.57	47.07	74	-26.93	H
4824.000	34.73	36.82	5.10	45.84	48.85	74	-25.15	H
7236.000	36.42	37.45	6.69	43.81	49.47	74	-24.53	H
9648.000	37.93	37.83	7.70	44.07	51.87	74	-22.13	H
1597.401	31.05	37.82	2.92	46.18	42.33	74	-31.67	V
1851.542	31.48	37.48	3.12	45.14	42.26	74	-31.74	V
3625.669	33.07	36.97	5.50	44.82	46.42	74	-27.58	V
4824.000	34.73	36.82	5.10	42.03	45.04	74	-28.96	V
7236.000	36.42	37.45	6.69	43.14	48.80	74	-25.20	V
9648.000	37.93	37.83	7.70	43.26	51.06	74	-22.94	V

Test mode:		802.11g		Test Frequency:		2437MHz		
Frequency (MHz)	Antenna Factor (dB/m)	Preamp Gain (dB)	Cable Loss (dB)	Read Level (dBμV)	Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Antenna Polaxis
1597.401	31.05	37.82	2.92	46.40	42.55	74	-31.45	H
2013.795	31.73	37.30	3.27	45.08	42.78	74	-31.22	H
3233.257	33.39	37.05	5.57	45.88	47.79	74	-26.21	H
4874.000	34.84	36.81	5.09	42.14	45.26	74	-28.74	H
7311.000	36.43	37.43	6.76	43.55	49.31	74	-24.69	H
9748.000	38.03	37.85	7.61	43.92	51.71	74	-22.29	H
1439.090	30.75	38.06	2.77	46.13	41.59	74	-32.41	V
1889.633	31.54	37.43	3.15	44.90	42.16	74	-31.84	V
3283.018	33.35	37.04	5.56	45.98	47.85	74	-26.15	V
4874.000	34.84	36.81	5.09	42.26	45.38	74	-28.62	V
7311.000	36.43	37.43	6.76	43.45	49.21	74	-24.79	V
9748.000	38.03	37.85	7.61	43.95	51.74	74	-22.26	V

Test mode:		802.11g		Test Frequency:		2462MHz		
Frequency (MHz)	Antenna Factor (dB/m)	Preamp Gain (dB)	Cable Loss (dB)	Read Level (dBμV)	Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Antenna Polaxis
1597.401	31.05	37.82	2.92	46.41	42.56	74	-31.44	H
1973.201	31.66	37.33	3.21	45.54	43.08	74	-30.92	H
3128.013	33.48	37.07	5.59	45.95	47.95	74	-26.05	H
4924.000	34.94	36.81	5.07	44.20	47.40	74	-26.60	H
7386.000	36.44	37.42	6.83	44.30	50.15	74	-23.85	H
9848.000	38.14	37.87	7.53	44.30	52.10	74	-21.9	H
1597.401	31.05	37.82	2.92	46.41	42.56	74	-31.44	V
1958.189	31.64	37.35	3.20	45.69	43.18	74	-30.82	V
3308.185	33.33	37.03	5.56	46.88	48.74	74	-25.26	V
4924.000	34.94	36.81	5.07	44.40	47.60	74	-26.40	V
7386.000	36.44	37.42	6.83	44.30	50.15	74	-23.85	V
9848.000	38.14	37.87	7.53	44.86	52.66	74	-21.34	V

Test mode:		802.11n(HT20)		Test Frequency:		2412MHz		
Frequency (MHz)	Antenna Factor (dB/m)	Preamp Gain (dB)	Cable Loss (dB)	Read Level (dB μ V)	Level (dB μ V/m)	Limit Line (dB μ V/m)	Over Limit (dB)	Antenna Polaxis
1420.890	30.71	38.09	2.75	46.20	41.57	74	-32.43	H
1672.296	31.18	37.71	2.98	46.12	42.57	74	-31.43	H
3208.660	33.41	37.05	5.58	46.53	48.47	74	-25.53	H
4824.000	34.73	36.82	5.10	43.10	46.11	74	-27.89	H
7236.000	36.42	37.45	6.69	43.18	48.84	74	-25.16	H
9648.000	37.93	37.83	7.70	44.24	52.04	74	-21.96	H
1439.090	30.75	38.06	2.77	44.98	40.44	74	-33.56	V
1597.401	31.05	37.82	2.92	44.32	40.47	74	-33.53	V
3757.208	32.97	36.94	5.48	44.05	45.56	74	-28.44	V
4824.000	34.73	36.82	5.10	42.27	45.28	74	-28.72	V
7236.000	36.42	37.45	6.69	41.95	47.61	74	-26.39	V
9648.000	37.93	37.83	7.70	42.53	50.33	74	-23.67	V

Test mode:		802.11n(HT20)		Test Frequency:		2437MHz		
Frequency (MHz)	Antenna Factor (dB/m)	Preamp Gain (dB)	Cable Loss (dB)	Read Level (dB μ V)	Level (dB μ V/m)	Limit Line (dB μ V/m)	Over Limit (dB)	Antenna Polaxis
1378.143	30.63	38.16	2.71	46.34	41.52	74	-32.48	H
1689.410	31.21	37.69	2.99	45.19	41.70	74	-32.30	H
3728.625	33.00	36.95	5.48	45.22	46.75	74	-27.25	H
4874.000	34.84	36.81	5.09	42.29	45.41	74	-28.59	H
7311.000	36.43	37.43	6.76	44.15	49.91	74	-24.09	H
9748.000	38.03	37.85	7.61	43.64	51.43	74	-22.57	H
1439.090	30.75	38.06	2.77	45.75	41.21	74	-32.79	V
1828.125	31.44	37.51	3.10	44.86	41.89	74	-32.11	V
3662.775	33.04	36.96	5.50	45.41	46.99	74	-27.01	V
4874.000	34.84	36.81	5.09	42.23	45.35	74	-28.65	V
7311.000	36.43	37.43	6.76	43.17	48.93	74	-25.07	V
9748.000	38.03	37.85	7.61	44.05	51.84	74	-22.16	V

Test mode:		802.11n(HT20)		Test Frequency:		2462MHz		
Frequency (MHz)	Antenna Factor (dB/m)	Preamp Gain (dB)	Cable Loss (dB)	Read Level (dB μ V)	Level (dB μ V/m)	Limit Line (dB μ V/m)	Over Limit (dB)	Antenna Polaxis
1371.145	30.61	38.17	2.70	46.53	41.67	74	-32.33	H
1728.561	31.28	37.64	3.03	45.80	42.47	74	-31.53	H
3786.010	32.95	36.94	5.47	45.26	46.74	74	-27.26	H
4924.000	34.94	36.81	5.07	42.55	45.75	74	-28.25	H
7386.000	36.44	37.42	6.83	43.51	49.36	74	-24.64	H
9848.000	38.14	37.87	7.53	44.52	52.32	74	-21.68	H
1597.401	31.05	37.82	2.92	45.18	41.33	74	-32.67	V
1889.633	31.54	37.43	3.15	44.75	42.01	74	-31.99	V
3241.498	33.38	37.05	5.57	46.60	48.50	74	-25.50	V
4924.000	34.94	36.81	5.07	41.27	44.47	74	-29.53	V
7386.000	36.44	37.42	6.83	44.12	49.97	74	-24.03	V
9848.000	38.14	37.87	7.53	43.35	51.15	74	-22.85	V

Test mode:		802.11n(HT40)		Test Frequency:		2422MHz		
Frequency (MHz)	Antenna Factor (dB/m)	Preamp Gain (dB)	Cable Loss (dB)	Read Level (dB μ V)	Level (dB μ V/m)	Limit Line (dB μ V/m)	Over Limit (dB)	Antenna Polaxis
1693.716	31.22	37.68	3.00	45.62	42.16	74	-31.84	H
3653.463	33.05	36.96	5.50	44.69	46.28	74	-27.72	H
4191.816	33.28	36.88	5.36	45.01	46.77	74	-27.23	H
4844.000	34.77	36.81	5.10	41.85	44.91	74	-29.09	H
7266.000	36.43	37.44	6.72	43.01	48.72	74	-25.28	H
9688.000	37.97	37.84	7.66	43.56	51.35	74	-22.65	H
1693.716	31.22	37.68	3.00	45.62	42.16	74	-31.84	V
3653.463	33.05	36.96	5.50	44.69	46.28	74	-27.72	V
4191.816	33.28	36.88	5.36	45.01	46.77	74	-27.23	V
4844.000	34.77	36.81	5.10	41.85	44.91	74	-29.09	V
7266.000	36.43	37.44	6.72	42.44	48.15	74	-25.85	V
9688.000	37.97	37.84	7.66	43.36	51.15	74	-22.85	V

Test mode:		802.11n(HT40)		Test Frequency:		2437MHz		
Frequency (MHz)	Antenna Factor (dB/m)	Preamp Gain (dB)	Cable Loss (dB)	Read Level (dBμV)	Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Antenna Polaxis
1453.818	30.78	38.04	2.78	45.45	40.97	74	-33.03	H
1846.834	31.47	37.48	3.12	45.94	43.05	74	-30.95	H
3747.656	32.98	36.95	5.48	44.70	46.21	74	-27.79	H
4874.000	34.84	36.81	5.09	41.02	44.14	74	-29.86	H
7311.000	36.43	37.43	6.76	43.60	49.36	74	-24.64	H
9748.000	38.03	37.85	7.61	44.36	52.15	74	-21.85	H
1846.834	31.47	37.48	3.12	45.31	42.42	74	-31.58	V
3625.669	33.07	36.97	5.50	45.21	46.81	74	-27.19	V
4524.468	34.07	36.84	5.22	43.50	45.95	74	-28.05	V
4874.000	34.84	36.81	5.09	42.07	45.19	74	-28.81	V
7311.000	36.43	37.43	6.76	43.64	49.40	74	-24.60	V
9748.000	38.03	37.85	7.61	44.00	51.79	74	-22.21	V

Test mode:		802.11n(HT40)		Test Frequency:		2452MHz		
Frequency (MHz)	Antenna Factor (dB/m)	Preamp Gain (dB)	Cable Loss (dB)	Read Level (dBμV)	Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Antenna Polaxis
1472.440	30.82	38.01	2.80	46.05	41.66	74	-32.34	H
1597.401	31.05	37.82	2.92	45.43	41.58	74	-32.42	H
3653.463	33.05	36.96	5.50	45.60	47.19	74	-26.81	H
4904.000	34.90	36.81	5.07	41.87	45.03	74	-28.97	H
7356.000	36.44	37.43	6.80	43.36	49.17	74	-24.83	H
9808.000	38.10	37.86	7.56	42.95	50.75	74	-23.25	H
1439.090	30.75	38.06	2.77	45.58	41.04	74	-32.96	V
1715.411	31.26	37.65	3.02	44.63	41.26	74	-32.74	V
3316.617	33.32	37.03	5.56	46.70	48.55	74	-25.45	V
4904.000	34.90	36.81	5.07	41.67	44.83	74	-29.17	V
7356.000	36.44	37.43	6.80	42.73	48.54	74	-25.46	V
9808.000	38.10	37.86	7.56	43.49	51.29	74	-22.71	V

Note:

1) Through Pre-scan transmitting mode with all kind of modulation and data rate, find the 11Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20) ; 13.5Mbps of rate is the worst case of 802.11n(HT40),and then Only the worst case is recorded in the report.

2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Pre-amplifier. The basic equation with a sample calculation is as follows:


Final Test Level =Receiver Reading - Correct Factor

Correct Factor = Pre-amplifier Factor- Antenna Factor-Cable Factor


3) Scan from 9kHz to 25GHz, the disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

PHOTOGRAPHS OF TEST SETUP

Test mode No.: i8 Pro



Radiated spurious emission Test Setup-1(Below 1GHz)



Radiated spurious emission Test Setup-2(Above 1GHz)



Conducted emission Test Setup

PHOTOGRAPHS OF EUT Constructional Details

Test mode No.: i8 Pro



View of product-1



View of product-2



View of product-3



View of product-4



View of product-5



View of product-6




View of product-7




View of product-8




View of product-9




View of product-10



View of product-11




View of product-12



View of product-13



View of product-14



View of product-15




View of product-16




View of product-17



View of product-18



View of product-19



View of product-20

*** End of Report ***

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.