

# FCC ID: S5V-D101V3

## Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})]^*$

$[\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

$f(\text{GHz})$  is the RF channel transmit frequency in GHz;

Power and distance are rounded to the nearest mW and mm before calculation;

The result is rounded to one decimal place for comparison;

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm

and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test

separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

We use 5mm as separation distance to calculated.

Bluetooth DSS:

Transmit Frequency (GHz)	Mode	Measured Power (dBm)	Tune-up power (dBm)	Max tune-up power(dBm)	Result calculation	1g SAR
2.402	GFSK	3.34	4±1	5	0.9802	3
2.441		4.32	4±1	5	0.9881	3
2.48		4.62	4±1	5	0.9960	3
2.402	$\pi/4$ -DQPSK	4.44	5±1	6	1.2340	3
2.441		5.37	5±1	6	1.2440	3
2.48		5.69	5±1	6	1.2539	3
2.402	8DPSK	4.68	5±1	6	1.2340	3
2.441		5.64	5±1	6	1.2440	3
2.48		5.95	5±1	6	1.2539	3

WIFI DTS:

Transmit Frequency (GHz)	Mode	Measured Power (dBm)	Tune-up power (dBm)	Max tune-up power(dBm)	Result calculation	1g SAR
2.412	802.11b	9.2	8.5±1	9.5	2.7683	3
2.437		9.3	8.5±1	9.5	2.7826	3
2.462		9.3	8.5±1	9.5	2.7969	3
2.412	802.11g	9.0	8.5±1	9.5	2.7683	3
2.437		9.2	8.5±1	9.5	2.7826	3
2.462		9.2	8.5±1	9.5	2.7969	3
2.412	802.11n HT20	8.9	8.5±1	9.5	2.7683	3
2.437		9.0	8.5±1	9.5	2.7826	3
2.462		9.2	8.5±1	9.5	2.7969	3
2.422	802.11n HT40	8.9	8.5±1	9.5	2.7741	3
2.437		9.0	8.5±1	9.5	2.7826	3
2.452		9.1	8.5±1	9.5	2.7912	3

**Conclusion:**

For the max result : 2.7969 ≤ 3.0 for 1g SAR, No SAR is required.

*Jason chen*

**Signature:**

**Date:** 2018-1-15

**NAME AND TITLE** (Please print or type): Jason Chen /Manager

**COMPANY** (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.